

# Elicitation and explanation for voting rules

**Beatrice Napolitano**

Supervisors: Remzi Sanver, Olivier Cailloux

Pré-soutenance de thèse

06 July 2021

**LAMSADE**

**UMR CNRS 7243**

laboratoire d'analyse et modélisation de systèmes pour l'aide à la décision

# Outline

- 1 Notation
- 2 Compromising as an equal loss principle
- 3 Simultaneous Elicitation of Scoring Rule and Agent Preferences for Robust Winner Determination
- 4 Setting
- 5 Preference Elicitation under Majority Judgment

# Outline

- 1 Notation
- 2 Compromising as an equal loss principle
- 3 Simultaneous Elicitation of Scoring Rule and Agent Preferences for Robust Winner Determination
- 4 Setting
- 5 Preference Elicitation under Majority Judgment

# Context

$\mathcal{A}$  alternatives,  $|\mathcal{A}| = m$

$N$  voters,  $|N| = n$

$\mathcal{L}(\mathcal{A}), \succ_i \in \mathcal{L}(\mathcal{A})$  a linear order over  $\mathcal{A}$

$P \in \mathcal{L}(\mathcal{A})^N$  a profile

$\mathcal{P}^*(\mathcal{A})$  the possible winners (the non-empty subsets of  $\mathcal{A}$ )

$f : \mathcal{L}(\mathcal{A})^N \rightarrow \mathcal{P}^*(\mathcal{A})$  a SCR

# Outline

- 1 Notation
- 2 **Compromising as an equal loss principle**
- 3 Simultaneous Elicitation of Scoring Rule and Agent Preferences for Robust Winner Determination
- 4 Setting
- 5 Preference Elicitation under Majority Judgment

# Context

## Introducing the problem

**Setting:** Several voters express their preferences over a set of alternatives

# Context

## Introducing the problem

**Setting:** Several voters express their preferences over a set of alternatives

**Goal:** Find a procedure determining a collective choice that promotes a notion of compromise

# Context

## Related Works

- **Plurality:** selects the alternatives considered as best by the highest number of voters



# Context

## Related Works

- **Plurality**: selects the alternatives considered as best by the highest number of voters
- **Median Voting Rule**: picks all alternatives receiving a majority of support at the highest possible quality

# Context

## Related Works

- **Plurality:** selects the alternatives considered as best by the highest number of voters
- **Median Voting Rule:** picks all alternatives receiving a majority of support at the highest possible quality
- **Majoritarian Compromise:** MVR and ties are broken according to the quantity of support these receive

# Context

## Related Works

- **Plurality:** selects the alternatives considered as best by the highest number of voters
- **Median Voting Rule:** picks all alternatives receiving a majority of support at the highest possible quality
- **Majoritarian Compromise:** MVR and ties are broken according to the quantity of support these receive
- **Fallback Bargaining:** bargainers fall back to less and less preferred alternatives until they reach a unanimous agreement

# Context

## Related Works

- **Plurality:** selects the alternatives considered as best by the highest number of voters
- **Median Voting Rule:** picks all alternatives receiving a majority of support at the highest possible quality
- **Majoritarian Compromise:** MVR and ties are broken according to the quantity of support these receive
- **Fallback Bargaining:** bargainers fall back to less and less preferred alternatives until they reach a unanimous agreement
- **q-approval FB:** picks the alternatives which receive the support of  $q$  voters at the highest possible quality, breaking ties according to the quantity of support

# Context

## Motivation: A simple example

$$n = 100, \mathcal{A} = \{a, b, c\}$$

51	<i>a</i>	<i>b</i>	<i>c</i>
49	<i>c</i>	<i>b</i>	<i>a</i>

# Context

## Motivation: A simple example

$$n = 100, \mathcal{A} = \{a, b, c\}$$

51	<i>a</i>	<i>b</i>	<i>c</i>
49	<i>c</i>	<i>b</i>	<i>a</i>

- Plurality:  $\{a\}$

# Context

## Motivation: A simple example

$$n = 100, \mathcal{A} = \{a, b, c\}$$

51	<i>a</i>	<i>b</i>	<i>c</i>
49	<i>c</i>	<i>b</i>	<i>a</i>

- Plurality:  $\{a\}$
- MVR:  $\{a\}$

# Context

## Motivation: A simple example

$$n = 100, \mathcal{A} = \{a, b, c\}$$

51	<i>a</i>	<i>b</i>	<i>c</i>
49	<i>c</i>	<i>b</i>	<i>a</i>

- Plurality:  $\{a\}$
- MVR:  $\{a\}$
- MC:  $\{a\}$



# Context

## Motivation: A simple example

$$n = 100, \mathcal{A} = \{a, b, c\}$$

51	<i>a</i>	<i>b</i>	<i>c</i>
49	<i>c</i>	<i>b</i>	<i>a</i>

- Plurality:  $\{a\}$
- MVR:  $\{a\}$
- MC:  $\{a\}$
- FB:  $\{b\}$

# Context

## Motivation: A simple example

$$n = 100, \mathcal{A} = \{a, b, c\}$$

51	<i>a</i>	<i>b</i>	<i>c</i>
49	<i>c</i>	<i>b</i>	<i>a</i>

- Plurality:  $\{a\}$
- MVR:  $\{a\}$
- MC:  $\{a\}$
- FB:  $\{b\}$
- q-approval FB  $q \in \{1, \dots, \frac{n}{2} + 1\}$ :  $\{a\}$

# Context

## Motivation: A simple example

$$n = 100, \mathcal{A} = \{a, b, c\}$$

51	<i>a</i>	<i>b</i>	<i>c</i>
49	<i>c</i>	<i>b</i>	<i>a</i>

- Plurality:  $\{a\}$
- MVR:  $\{a\}$
- MC:  $\{a\}$
- FB:  $\{b\}$
- $q$ -approval FB  $q \in \{1, \dots, \frac{n}{2} + 1\}$ :  $\{a\}$

Does  $b$  seem a better compromise?

# Notation

$\lambda_P : \mathcal{A} \rightarrow \llbracket 0, m-1 \rrbracket^N$  a loss vector

# Notation

## Losses

$P$	$\lambda_P$
$v_1 : a \succ b \succ c$	$a : (0, 2)$
$v_2 : c \succ b \succ a$	$b : (1, 1)$
	$c : (2, 0)$

Given  $P = (\succ_i)_{i \in N}$ :

- $\lambda_{\succ_i}(x) = |\{y \in \mathcal{A} \mid y \succ_i x\}| \in \llbracket 0, m-1 \rrbracket$  the loss of  $i$  when choosing  $x \in \mathcal{A}$  instead of her favorite alternative
- $\lambda_P(x)$  associates to each voter her loss when choosing  $x$

# Notation

$\lambda_P : \mathcal{A} \rightarrow \llbracket 0, m-1 \rrbracket^N$  a loss vector

# Notation

$\lambda_P : \mathcal{A} \rightarrow \llbracket 0, m-1 \rrbracket^N$  a loss vector

$\sigma : \llbracket 0, m-1 \rrbracket^N \rightarrow \mathbb{R}^+$  a spread measure

# Notation

$\lambda_P : \mathcal{A} \rightarrow \llbracket 0, m-1 \rrbracket^N$  a loss vector

$\sigma : \llbracket 0, m-1 \rrbracket^N \rightarrow \mathbb{R}^+$  a spread measure

$\Sigma$  is the set of spread measures  $\sigma$  such that

$$\sigma(l) = 0 \iff l_i = l_j, \forall i, j \in N, \quad \forall l \in \llbracket 0, m-1 \rrbracket^N$$

.



# Outline

- 1 Notation
- 2 Compromising as an equal loss principle
- 3 Simultaneous Elicitation of Scoring Rule and Agent Preferences for Robust Winner Determination**
- 4 Setting
- 5 Preference Elicitation under Majority Judgment

# Classical Scenario

**Setting:** Voters specify preferences over alternatives and a committee defines the social choice rule to aggregate them

(Head of the)

**Committee**



$$w = (w_1, w_2, w_3)$$

$$= (2, 1, 0)$$

**Voters**

Mickey Donald Goofy



Borda  
rule



# Classical Scenario

**Setting:** Voters specify preferences over alternatives and a committee defines the social choice rule to aggregate them

(Head of the)

**Committee**



$$w = (w_1, w_2, w_3)$$

$$= (2, 1, 0)$$

**Voters**

Mickey Donald Goofy



Borda  
rule



**Goal:** Find a consensus choice

# Outline

- 1 Notation
- 2 Compromising as an equal loss principle
- 3 Simultaneous Elicitation of Scoring Rule and Agent Preferences for Robust Winner Determination
- 4 Setting**
- 5 Preference Elicitation under Majority Judgment

# Classical Scenario

**Setting:** Voters specify preferences over alternatives and a committee defines the social choice rule to aggregate them

(Head of the)

**Committee**



$$w = (w_1, w_2, w_3)$$

$$= (2, 1, 0)$$

**Voters**

Mickey Donald Goofy



Borda  
rule



# Classical Scenario

**Setting:** Voters specify preferences over alternatives and a committee defines the social choice rule to aggregate them

(Head of the)

**Committee**



$$w = (w_1, w_2, w_3) \\ = (2, 1, 0)$$

**Voters**

Mickey Donald Goofy



Borda  
rule



**Goal:** Find a consensus choice

# Our Scenario

**Setting:** Incompletely specified preferences and social choice rule


(Head of the)  
**Committee**



$$w_1 \geq 2 w_2$$

**Voters**

Mickey Donald Goofy



positional  
scoring  
rule



# Our Scenario

**Setting:** Incompletely specified preferences and social choice rule

(Head of the)  
**Committee**



$$w_1 \geq 2 w_2$$

**Voters**

Mickey Donald Goofy



positional  
scoring  
rule



**Goal:** Develop an incremental elicitation strategy to acquire the most relevant information



# Motivation and approach

## Who?

- Imagine to be an *external observer* helping with the voting procedure

# Motivation and approach

## Who?

- Imagine to be an *external observer* helping with the voting procedure

## Why?

- Voters: difficult or costly to order *all* alternatives
- Committee: difficult to *specify* a voting rule precisely and abstractly

# Motivation and approach

## Who?

- Imagine to be an *external observer* helping with the voting procedure

## Why?

- Voters: difficult or costly to order *all* alternatives
- Committee: difficult to *specify* a voting rule precisely and abstractly

## What?

- We want to reduce uncertainty, inferring (*eliciting*) the true preferences of voters and committee, in order to quickly converge to an optimal or a near-optimal alternative

# Motivation and approach

## Approach

- Develop query strategies that interleave questions to the committee and questions to the voters
- Use *Minimax regret* to measure the quality of those strategies

# Motivation and approach

## Approach

- Develop query strategies that interleave questions to the committee and questions to the voters
- Use *Minimax regret* to measure the quality of those strategies

## Assumptions

- We consider *positional scoring rules*, which attach weights to positions according to a scoring vector  $w$
- We assume  $w$  to be *convex*

$$w_r - w_{r+1} \geq w_{r+1} - w_{r+2} \quad \forall r$$

and that  $w_1 = 1$  and  $w_m = 0$

# Related Works

## Incomplete profile

- and known weights: Minimax regret to produce a robust winner approximation (*Lu and Boutilier 2011*, [2]; *Boutilier et al. 2006*, [1])

## Uncertain weights

- and complete profile: dominance relations derived to eliminate alternatives always less preferred than others (*Stein et al. 1994*, [3])
- in positional scoring rules (*Viappiani 2018*, [4])

# Context

$A$  alternatives,  $|A| = m$

$N$  voters

$P = (\succsim_j, j \in N), P \in \mathcal{P}$  complete preferences profile

$W = (\mathbf{w}_r, 1 \leq r \leq m), W \in \mathcal{W}$  (convex) scoring vector that the committee has in mind

# Context

$A$  alternatives,  $|A| = m$

$N$  voters

$P = (\succ_j, j \in N)$ ,  $P \in \mathcal{P}$  complete preferences profile

$W = (\mathbf{w}_r, 1 \leq r \leq m)$ ,  $W \in \mathcal{W}$  (convex) scoring vector that the committee has in mind

$W$  defines a Positional Scoring Rule  $f_W(P) \subseteq A$  using scores  $s^{W,P}(a)$ ,  $\forall a \in A$



# Context

$A$  alternatives,  $|A| = m$

$N$  voters

$P = (\succ_j, j \in N)$ ,  $P \in \mathcal{P}$  complete preferences profile

$W = (\mathbf{w}_r, 1 \leq r \leq m)$ ,  $W \in \mathcal{W}$  (convex) scoring vector that the committee has in mind

$W$  defines a Positional Scoring Rule  $f_W(P) \subseteq A$  using scores  $s^{W,P}(a)$ ,  $\forall a \in A$

$P$  and  $W$  exist in the minds of voters and committee but unknown to us

# Questions

# Questions

## Questions to the voters

Comparison queries that ask a particular voter to compare two alternatives  $a, b \in A$

$$a \succ_j b \quad ?$$

# Questions

## Questions to the voters

Comparison queries that ask a particular voter to compare two alternatives  $a, b \in A$

$$a \succ_j b \quad ?$$

## Questions to the committee

Queries relating the difference between the importance of consecutive ranks from  $r$  to  $r + 2$

$$w_r - w_{r+1} \geq \lambda(w_{r+1} - w_{r+2}) \quad ?$$

# Our Knowledge

The answers to these questions define  $C_P$  and  $C_W$  that is our knowledge about  $P$  and  $W$

# Our Knowledge

The answers to these questions define  $C_P$  and  $C_W$  that is our knowledge about  $P$  and  $W$

- $C_P \subseteq \mathcal{P}$  constraints on the profile given by the voters

# Our Knowledge

The answers to these questions define  $C_P$  and  $C_W$  that is our knowledge about  $P$  and  $W$

- $C_P \subseteq \mathcal{P}$  constraints on the profile given by the voters
- $C_W \subseteq \mathcal{W}$  constraints on the voting rule given by the committee

# Minimax Regret

Given  $C_P \subseteq \mathcal{P}$  and  $C_W \subseteq \mathcal{W}$ :

$$\text{PMR}^{C_P, C_W}(a, b) = \max_{P \in C_P, W \in C_W} s^{P, W}(b) - s^{P, W}(a)$$

is the maximum difference of score between  $a$  and  $b$  under all possible realizations of the full profile *and* weights



# Minimax Regret

Given  $C_P \subseteq \mathcal{P}$  and  $C_W \subseteq \mathcal{W}$ :

$$\text{PMR}^{C_P, C_W}(a, b) = \max_{P \in C_P, W \in C_W} s^{P, W}(b) - s^{P, W}(a)$$

is the maximum difference of score between  $a$  and  $b$  under all possible realizations of the full profile *and* weights

We care about the worst case loss: *maximal regret* between a chosen alternative  $a$  and best real alternative  $b$

$$\text{MR}^{C_P, C_W}(a) = \max_{b \in A} \text{PMR}^{C_P, C_W}(a, b)$$

# Minimax Regret

Given  $C_P \subseteq \mathcal{P}$  and  $C_W \subseteq \mathcal{W}$ :

$$\text{PMR}^{C_P, C_W}(a, b) = \max_{P \in C_P, W \in C_W} s^{P, W}(b) - s^{P, W}(a)$$

is the maximum difference of score between  $a$  and  $b$  under all possible realizations of the full profile *and* weights

We care about the worst case loss: *maximal regret* between a chosen alternative  $a$  and best real alternative  $b$

$$\text{MR}^{C_P, C_W}(a) = \max_{b \in A} \text{PMR}^{C_P, C_W}(a, b)$$

**We select the alternative which minimizes the maximal regret**

$$\text{MMR}^{C_P, C_W} = \min_{a \in A} \text{MR}^{C_P, C_W}(a)$$

# Pairwise Max Regret Computation


The computation of  $\text{PMR}^{C_P, C_W}(\text{broccoli}, \text{eggplant})$  can be seen as a game in which an adversary both:

# Pairwise Max Regret Computation

The computation of  $\text{PMR}^{C_P, C_W}(\text{broccoli}, \text{eggplant})$  can be seen as a game in which an adversary both:

- chooses a complete profile  $P \in \mathcal{P}$

Mickey Donald Goofy



Mickey Donald Goofy




# Pairwise Max Regret Computation

The computation of  $\text{PMR}^{C_P, C_W}(\text{broccoli}, \text{eggplant})$  can be seen as a game in which an adversary both:

- chooses a complete profile  $P \in \mathcal{P}$

Mickey Donald Goofy



Mickey Donald Goofy



- chooses a feasible weight vector  $W \in \mathcal{W}$


$$(1, ?, 0) \longrightarrow (1, 0, 0)$$

in order to maximize the difference of scores

# Computing Minimax Regret: Example

## Profile completion

Consider the following partial profile



# Computing Minimax Regret: Example

## Weight selection

Consider the following constraint on the scoring vector given by the committee

$$w_1 \geq 2 \cdot w_2$$

and the convex assumption

$$w_1 - w_2 \geq w_2 - w_3$$

# Computing Minimax Regret: Example

## Minimax computing

$$\text{MR}(\text{carrot}) = \max \left\{ \begin{array}{l} \text{PMR}(\text{carrot}, \text{broccoli}) \xrightarrow{v = \textcircled{3} \quad w = \{1,0,0\}} = 2 \\ \text{PMR}(\text{carrot}, \text{eggplant}) \xrightarrow{v = \textcircled{2} \quad w = \{1,0,0\}} = 1 \end{array} \right.$$

$$\text{MR}(\text{broccoli}) = \boxed{0}$$

$$\text{MR}(\text{eggplant}) = 2$$

$$\boxed{\text{MMR}} = 0 \quad \rightarrow \quad \text{winner} \quad \text{broccoli}$$



# Elicitation strategies

At each step, the strategy selects a question to ask either to one of the voters about her preferences or to the committee about the voting rule

# Elicitation strategies

At each step, the strategy selects a question to ask either to one of the voters about her preferences or to the committee about the voting rule

The termination condition could be:

# Elicitation strategies

At each step, the strategy selects a question to ask either to one of the voters about her preferences or to the committee about the voting rule

The termination condition could be:

- when the minimax regret is lower than a threshold

# Elicitation strategies

At each step, the strategy selects a question to ask either to one of the voters about her preferences or to the committee about the voting rule

The termination condition could be:

- when the minimax regret is lower than a threshold
- when the minimax regret is zero

# Elicitation strategies

## Random Strategy

# Elicitation strategies

## Random Strategy

Decides with a probability of  $\frac{1}{2}$  each whether to ask a question about

# Elicitation strategies

## Random Strategy

Decides with a probability of  $\frac{1}{2}$  each whether to ask a question about

- **weights:** it draws a rank  $2 \leq r \leq m - 2$  equiprobably, takes  $\lambda$  as the middle of the interval of values we are still uncertain about, and asks whether  $w_r - w_{r+1} \geq \lambda(w_{r+1} - w_{r+2})$

# Elicitation strategies

## Random Strategy

Decides with a probability of  $\frac{1}{2}$  each whether to ask a question about

- **weights:** it draws a rank  $2 \leq r \leq m - 2$  equiprobably, takes  $\lambda$  as the middle of the interval of values we are still uncertain about, and asks whether  $w_r - w_{r+1} \geq \lambda(w_{r+1} - w_{r+2})$
- **a preference ordering:** it draws equiprobably a voter whose preference is not known entirely and two alternatives that are incomparable in our current knowledge



# Elicitation strategies

## **Pessimistic Strategy**

# Elicitation strategies

## Pessimistic Strategy

Assume that a question leads to the possible new knowledge states  $(C_P^1, C_W^1)$  and  $(C_P^2, C_W^2)$  depending on the answer, then the badness of the question in the worst case is:

$$\max_{i=1,2} \text{MMR}(C_P^i, C_W^i)$$

# Elicitation strategies

## Pessimistic Strategy

Assume that a question leads to the possible new knowledge states  $(C_P^1, C_W^1)$  and  $(C_P^2, C_W^2)$  depending on the answer, then the badness of the question in the worst case is:

$$\max_{i=1,2} \text{MMR}(C_P^i, C_W^i)$$

The pessimistic strategy selects the question that leads to minimal regret in the worst case

# Elicitation strategies

## Pessimistic Strategy

Assume that a question leads to the possible new knowledge states  $(C_P^1, C_W^1)$  and  $(C_P^2, C_W^2)$  depending on the answer, then the badness of the question in the worst case is:

$$\max_{i=1,2} \text{MMR}(C_P^i, C_W^i)$$

The pessimistic strategy selects the question that leads to minimal regret in the worst case

### Note:

if the maximal MMR of two questions are equal, then prefers the one with the lowest MMR values associated to the opposite answer

# Elicitation strategies

## Two Phase Strategy

# Elicitation strategies

## Two Phase Strategy

- **phase one:** asks a predefined sequence of  $m - 2$  questions to the committee in order to gather informations about the weights (one per rank except the extremes)

# Elicitation strategies

## Two Phase Strategy

- **phase one:** asks a predefined sequence of  $m - 2$  questions to the committee in order to gather informations about the weights (one per rank except the extremes)
- **phase two:** asks only questions to the voters, using the mechanism defined in the Pessimistic strategy

# Elicitation strategies

## Extreme Completions Strategy



# Elicitation strategies

## Extreme Completions Strategy

Let  $a^*$  be the minimax regret optimal alternative, and  $\bar{b}$ ,  $\bar{P}$  and  $\bar{W}$  the instantiations that maximize the regret when  $a^*$  is chosen.

# Elicitation strategies

## Extreme Completions Strategy

Let  $a^*$  be the minimax regret optimal alternative, and  $\bar{b}$ ,  $\bar{P}$  and  $\bar{W}$  the instantiations that maximize the regret when  $a^*$  is chosen. Define:

$$\tau_W = \min_{W \in C_W} s^{\bar{P}, W}(\bar{b}) - s^{\bar{P}, W}(a^*)$$

$$\tau_{P_i} = \min_{\hat{P}_i \in C_P} s^{\hat{P}_i, \bar{W}}(\bar{b}) - s^{\hat{P}_i, \bar{W}}(a^*)$$

where  $\hat{P}_i$  is defined as  $\bar{P}$  except for  $i$

# Elicitation strategies

## Extreme Completions Strategy

Let  $a^*$  be the minimax regret optimal alternative, and  $\bar{b}$ ,  $\bar{P}$  and  $\bar{W}$  the instantiations that maximize the regret when  $a^*$  is chosen. Define:

$$\tau_W = \min_{W \in C_W} s^{\bar{P}, W}(\bar{b}) - s^{\bar{P}, W}(a^*)$$

$$\tau_{P_i} = \min_{\hat{P}_i \in C_P} s^{\hat{P}_i, \bar{W}}(\bar{b}) - s^{\hat{P}_i, \bar{W}}(a^*)$$

where  $\hat{P}_i$  is defined as  $\bar{P}$  except for  $i$

$\text{MMR} - \tau_W$  estimates the contribution to the regret of our uncertainty about the weights;  $\text{MMR} - \tau_{P_i}$  estimates the uncertainty about the profile

# Elicitation strategies

## Extreme Completions Strategy

Let  $a^*$  be the minimax regret optimal alternative, and  $\bar{b}$ ,  $\bar{P}$  and  $\bar{W}$  the instantiations that maximize the regret when  $a^*$  is chosen. Define:

$$\tau_W = \min_{W \in C_W} s^{\bar{P}, W}(\bar{b}) - s^{\bar{P}, W}(a^*)$$

$$\tau_{P_i} = \min_{\hat{P}_i \in C_P} s^{\hat{P}_i, \bar{W}}(\bar{b}) - s^{\hat{P}_i, \bar{W}}(a^*)$$

where  $\hat{P}_i$  is defined as  $\bar{P}$  except for  $i$

$\text{MMR} - \tau_W$  estimates the contribution to the regret of our uncertainty about the weights;  $\text{MMR} - \tau_{P_i}$  estimates the uncertainty about the profile

The extreme completions strategy asks a question to whoever minimizes  $\tau$

# Results

k	Rnd $\pm$ sd	T. ph. $\pm$ sd	Pes. $\pm$ sd
0	5.0 $\pm$ 0	5.0 $\pm$ 0	5.0 $\pm$ 0
5	4.9 $\pm$ 0.2	5.0 $\pm$ 0.0	4.2 $\pm$ 0.3
10	4.8 $\pm$ 0.2	4.4 $\pm$ 0.3	3.4 $\pm$ 0.5
15	4.3 $\pm$ 0.6	3.7 $\pm$ 0.3	2.7 $\pm$ 0.5
20	3.9 $\pm$ 0.3	2.7 $\pm$ 0.5	1.6 $\pm$ 0.8
25	3.5 $\pm$ 0.8	2.2 $\pm$ 0.7	0.8 $\pm$ 0.6
30	3.0 $\pm$ 0.8	1.5 $\pm$ 1.1	0.5 $\pm$ 0.7

**Table:** Minimax regret in problems of size (5,5) after  $k$  questions.

# Outline

- 1 Notation
- 2 Compromising as an equal loss principle
- 3 Simultaneous Elicitation of Scoring Rule and Agent Preferences for Robust Winner Determination
- 4 Setting
- 5 Preference Elicitation under Majority Judgment

Thank You!



C. Boutilier, R. Patrascu, P. Poupart, and D. Schuurmans.  
Constraint-based Optimization and Utility Elicitation using the  
Minimax Decision Criterion.  
*Artificial Intelligence*, 170(8–9):686–713, 2006.



Tyler Lu and Craig Boutilier.  
Robust approximation and incremental elicitation in voting protocols.  
In *Proceedings of IJCAI 2011*, pages 287–293, 2011.



William E. Stein, Philip J. Mizzi, and Roger C. Pfaffenberger.  
A stochastic dominance analysis of ranked voting systems with  
scoring.  
*European Journal of Operational Research*, 74(1):78 – 85, 1994.



Paolo Viappiani.  
Positional scoring rules with uncertain weights.  
In *Scalable Uncertainty Management - 12th International Conference, SUM 2018, Milan, Italy, October 3-5, 2018, Proceedings*, pages 306–320, 2018.