

a <A female cyborg> style dog



a <Marc\_Allante> style dog



# Python编程与人工智能实践

应用篇：AI绘图

**私炉模式** (textual inversion, 文本反演)

于泓


鲁东大学

信息与电气工程学院

2022.10.30

# 私炉模式

利用3-5张风格图像进行训练，将风格转换为一个词向量



训练过程较慢



<https://cyberes.github.io/stable-diffusion-textual-inversion-models/>

一些训练好的 词向量

### 3d-female-cyborgs

[Download 3d-female-cyborgs.pt](#)

[View Repository](#)



a **<A female cyborg>** style dog



" **<852style-girl>** style dog"




[Download 852style-girl.pt](#)

[View Repository](#)



2022/10/31

Download 852style-girl.pt [View Repository](#)



main 852style-girl

MoososCap Upload concept

concept\_images

.gitattributes

README.md

learned\_embeds.bin

token\_identifier.txt

type\_of\_concept.txt

/home/sdo/aidraw/stable\_diffusion\_openvino/embedding/

Name	Size (KB)	La
852style-girl.pt	3	20
3d-female-cyborgs.pt	3	20
001glitch-core.pt	3	20

</> raw history blame

```
1 <852style-girl>
```

```
def load_learned_embed_in_clip(learned_embeds_path, text_encoder, tokenizer, token=None):
    loaded_learned_embeds = torch.load(learned_embeds_path, map_location="cpu")

    # separate token and the embeds
    trained_token = list(loaded_learned_embeds.keys())[0]

    embeds = loaded_learned_embeds[trained_token]

    # cast to dtype of text_encode
    dtype = text_encoder.get_input_embeddings().weight.dtype
    # embeds.to(dtype)

    # add the token in tokenizer
    token = token if token is not None else trained_token
    num_added_tokens = tokenizer.add_tokens(token)


    i = 1
    while(num_added_tokens == 0):
        print(f"The tokenizer already contains the token {token}.")
        token = f"{token[:-1]}-{i}>"
        print(f"Attempting to add the token {token}.")
        num_added_tokens = tokenizer.add_tokens(token)
        i+=1
    # resize the token embeddings
    text_encoder.resize_token_embeddings(len(tokenizer))

    # get the id for the token and assign the embeds
    token_id=tokenizer.convert_tokens_to_ids(token)
    text_encoder.get_input_embeddings().weight.data[token_id]=embeds
    return token
```

2022/10/31



```
def load_learned_embed_in_clip(learned_embeds_path, text_encoder, tokenizer, token=None):
```



# 多风格组合

```
engine = StableDiffusionEngine(  
    model = path_model,  
    file_embedding = ["embedding/Aflac-duck.pt", "embedding/852style-girl.pt", "embedding/3d-female-cyborgs.pt",  
    scheduler = scheduler  
)
```

# 加载学习的风格文件

```
if not file_embedding is None:  
    for file in file_embedding:  
        str_token = load_learned_embed_in_clip(file, self.text_encoder_torch, self.tokenizer)  
        print(str_token)
```

```
prompt = " a <852style-girl> style <bonzi>"
```

Download 852style-girl.pt

[View Repository](#)



bonzi-monkey

Download bonzi-monkey.pt

[View Repository](#)






Download 852style-girl.pt

[View Repository](#)



## 私炉特征组合

"a <852style-girl> style <aflac duck>"



Aflac-duck

Download Aflac-duck.pt

[View Repository](#)

