Supplement: Candidate-Bound Evidence for RTL-to-GDS Signoff

Rithwik Vallabhan TV, Sreejeesh SG, Jayaraj U Kidav, and Nanditha N Varma

NIELIT Calicut, India

1 Source and Execution Ledger

The primary manuscript uses frozen implementation `af31b39f6782` for fourteen design runs, twenty separate recorded-proposal executions, eighteen fault-consistency executions, and a replayed spacing-repair episode. The latter submits the recorded padding delta through a scripted proposal adapter and makes zero new model calls. It encounters native spacing failure, authorizes the recorded change, reruns the affected stages, and certifies. It supplies the post-repair artifact used by the new swap fixture.

The twenty recorded proposals originate from live Claude Sonnet 5 runs (Anthropic; identifier `claude-sonnet-5`) on snapshot `18d948815ac6`. The primary replay counts those proposal states, with six frozen certifications and fourteen native failures. It is separate from the original nine live episodes, which produced seven certifications and two escalations on that earlier code. Source snapshots, complete typed configurations, and commands identify both phases. Current source is `af31b39f6782`; Git commits modifying the manuscript and drivers do not introduce a third implementation snapshot.

The 2x2x2 padding ablation retains four source interventions derived from the frozen source. Their changes remove only the CTS and/or routing padding calls. Worker count is the other declared factor. The mapped netlist and placed DEF match across the CTS intervention, while CTS and downstream artifacts differ. The main frozen renderer retains both padding calls.

2 Original Live Repair Episodes

Three episodes per fixture type were declared before execution. Spacing and PDN each certify in 3/3 episodes; timing certifies in 1/3. The original twenty model responses record 174306 input tokens and 50164 output tokens. Table 1 retains every episode. These observations belong to `18d948815ac6`. They are descriptive outcomes for repeated fixtures, with no population repair-rate estimate.

The original timing sequence at unchanged 3 ns is shown in Figure 1. The successful configuration repeats three times at $+1.586$ ps under its archived source and three times at -0.654 ps under the frozen implementation. The current-source failure is retained; the primary factorial experiment measures the effect of CTS padding rather than attributing the result to uncontrolled noise.

Table 1. All nine original live repair episodes on source 18d948815ac6. These archived outcomes are separate from frozen replay and larger episodes.

Episode	Initial failure	Final evidence	Calls	Outcome
Spacing 1	1 marker	Full signoff	1	Verified
Spacing 2	1 marker	Full signoff	1	Verified
Spacing 3	1 marker	Full signoff	1	Verified
PDN 1	PDN-0185	Full signoff	1	Verified
PDN 2	PDN-0185	Full signoff	1	Verified
PDN 3	PDN-0185	Full signoff	1	Verified
Setup 1	-0.326192 ns	0.001586 ns	2	Verified
Setup 2	-0.326192 ns	Not certified	3	Escalated
Setup 3	-0.326192 ns	Not certified	9	Escalated




Fig. 1. Archived native routed timing checks at 3 ns on source 18d948815ac6. Lines end at the last completed check, including escalated episodes.

The archived class replay gives spacing 0/3 failed states, PDN 0/3, and timing 11/14, with two additional timing states lacking a completed target check. Every confirmed failure in the earlier 11/20 headline is therefore from the timing fixture. Fresh native execution establishes outcomes for all twenty states on the frozen source: spacing 0/3 failures, PDN 0/3, and timing 14/14. No unavailable target is silently counted as a confirmed archived failure.

3 Complete-State Replay Reconstruction

Reconstruction starts with the archived IR defaults and applies the logged characterization seed, initial overrides, curated numerical changes, and all accepted model deltas in temporal order. The archived renderer used the native one-worker default; the current replay declares that effective count explicitly. The reconstructed final IR matches every archived successful episode before any new native execution. Fresh runs disable further repair.

An initial reconstruction pilot omitted the curated PDN changes preceding the model call: strap offset 50 to 21.42 μm and utilization 0.35 to 0.29. Its three PDN configurations did not represent the recorded promoted states. The complete pilot and original launcher remain in the archive and are excluded from the final twenty-state result. The corrected cohort was declared and executed separately, with the full-state equality checks described above. This exclusion corrects configuration reconstruction rather than selecting favorable native outcomes.

4 Native Checker Invocation Controls

The pinned OpenLane wrapper and public source bytes match. The installed modern PDK deck expects runtime rule flags that this wrapper does not forward. The previous pairing declares zero categories and zero markers for both known violating and clean synthetic geometry. It is an inactive configuration observation and is excluded as an active-DRC baseline.

Table 2 reports active paired controls. The legacy native deck reports 166 categories and metal/off-grid violations; its tested poly category is absent. The modern PDK options and explicit adapter each report 220 categories, with metal/poly/off-grid markers 3/1/4 and paired clean counts 0/0/0. These control counts are raw inventories for those configurations, not the primary controller's 211 normalized-category contract. Violating stage calls return zero despite markers, so marker reporting and native exit rejection are distinguished. The adapter is a recorded sidecar change, not an unmodified stock full-flow run.

The selected PDK options enable FEOL, BEOL, off-grid and seal checks and disable floating metal. The direct modern command passes `feol=1`, `beol=1`, `offgrid=1`, `seal=1`, and `floating_met=0`. Exact argument vectors are retained in `runs/openlane_invocation_audit/controls_v1/executions/*/command.json`; `rtl2gdsagi_paper/evidence/openlane_invocation_audit.json` binds their inputs and reports. The retained formal controls use EQY revision `v0.68-2-g4a72eb9`. Comprehensive rule coverage, default Magic checking, and

Table 2. Paired synthetic DRC controls. Marker columns list metal/poly/off-grid fixtures. Modern controls use the PDK runtime options; the adapter is an explicit sidecar change. The inactive prior wrapper is a configuration diagnostic, excluded from this active-checker table.

Executed configuration	Categories	Violating markers	Clean markers
Legacy native deck	166	3/0/4	0/0/0
Modern deck, PDK options	220	3/1/4	0/0/0
Modern wrapper adapter	220	3/1/4	0/0/0

a full OpenLane-flow comparison remain unassessed. Native supply checks from the separate retained study detect disconnected vias with paired untouched DEFs. Optional reference XOR detects geometry differences when supplied a reference. The retained KLayout no-compare database is incompatible with the Netgen report interface and is not a semantic detection control. The stock source and PDK configuration provide public invocation evidence; no personal maintainer endorsement is asserted.

5 Larger Episodes and Stopping Proposals

The 1,995-cell `accum_bank32` contains thirty-two eight-bit accumulator lanes and a read-selection multiplexer. Two spacing and two antenna episodes were declared on `af31b39f6782`. Table 3 retains all four: none completes certification, two stop on previously failed fingerprints, and two remain incomplete. The latter outcomes stay unknown; their saved candidate states are not certified or labeled eventual algorithmic repair failures. Twenty-three valid model responses are retained across this separate cohort. It is not pooled with the original nine episodes.

Table 3. All four recorded 1,995-cell accumulator episodes on source af31b39f6782. Responses are valid recorded model returns. No episode completes certification. Incomplete episodes have unknown eventual repair outcomes and are not classified as algorithmic failures.

Case	Responses	Last failed native stage	Recorded outcome
Antenna 1	3	routing	Controller stop
Antenna 2	3	routing	Incomplete
Spacing 1	10	placement	Incomplete
Spacing 2	7	drc	Controller stop

The spacing-stop episode's last proposal raises padding from four to six sites. A previous six-site attempt at the same density already failed placement with DPL-0036. The sequence cycles through padding two, four and six; the recorded

earlier DRC counts are one and four markers before the six-site placement failure. The controller rejects revisiting that failed placement fingerprint after 7/24 diagnosis attempts.

The antenna-stop episode first increases repair iterations to ten and the prediction margin to 40%, then changes maximum routing layer to six and the detailed-router iteration limit to 64. Layer six causes GRT-0005. The final proposal restores maximum layer five. The resulting antenna-stage inputs revisit the prior failed signature, which had three violating nets/pins, and the controller stops after 3/24 diagnosis attempts. These are revisited failed states rather than global-budget exhaustion or an unchanged literal final delta.

Earlier spacing, antenna and diode-legalization probes of the accumulator, ALU banks, and other scale candidates remain in the native archive. They are excluded from the seven clean primary designs. Exact mapped-cell counts, failed stages, and intermediate observations are preserved in the JSON catalog.

6 Earlier Retained Observations

Table 4 preserves earlier observations under their own protocols. They do not enlarge the prospective nine-episode denominator or the twenty-state frozen replay. Full logs record the actual terminal state; unavailable intermediate prompt/response or artifact files are not invented.

Table 4. Earlier retained observations. Protocols and source snapshots differ; these records remain separate from the prospective nine-episode cohort. The JSON catalog provides the exact run paths and raw observations.

Case	First requested stage	Responses	Native certification
H1	drc	1	Verified
H2	drc	0	Not certified
H3	drc	1	Verified
H4	drc	1	Verified
H5	sta_signoff	0	Not certified
H6	sta_signoff	0	Not certified
H7	sta_signoff	1	Not certified
H8	sta_signoff	0	Not certified
H9	lint	0	Not certified
H10	lint	1	Not certified

7 Artifact Verification

The Overleaf ZIP compiles `main.tex` and `supplement.tex` independently with Springer LNCS. Cached generated inputs need no EDA tools. The experiment

archive includes a file-hash index and portable verifier. Re-execution needs the pinned tools, recorded PDK revision, and Python dependencies; raw paths retain their original workspace locations. Each manuscript/input/PDF and internal review is bound by exact hashes. The public release receipt is a separate availability check, not a scholarly review or venue acceptance.