




Introduction

Lecture 1



Welcome

to the *Microprocessor Architecture* engineering class

You will learn


- how hardware works
- how to actually build your own hardware device
- the Rust programming Language

We expect

- to come to class
- ask a lot of questions



Team




Our team

Lectures

- Alexandru Radovici

Labs

- Alexandru Radovici
- Teodor Dicu (Hardware)
- Genan Omer (Software)



Outline

Lectures

- 12 lectures
- 1 Q&A lecture for the project


Labs

- 7 labs

Project


- Build a hardware device running software written in Rust
- Presented at PM Fair during the last week of the semester






Grading

Part	Description	Points
<u>Lecture tests</u>	You will have a test at every class with subjects from the previous class.	1p
<u>Final Lecture test</u>	You will have a test during one of the lectures in January.	4p
<u>Lab</u>	Your work at every lab will be graded.	1p
<u>Project</u>	You will have to design and implement a hardware device. Grading will be done for the documentation, hardware design and software development.	3p
Final Test	You will have to take an exam during the last week of the semester.	2p
Total	<i>You will need at least 4.5 points to pass the subject.</i>	11p




Subjects




Theory

- How a microprocessor works
- How the ARM Cortex-M processor works
- Using digital signals to control devices
- Using analog signals to read data from sensors
- How interrupts work
- How asynchronous programming works (async/await)
- How embedded operating systems work




Practical

- How to use the STM32 Nucleo-U545RE-Q
 - Affordable
 - Powerful processor
 - Good documentation
- How to program in Rust
 - Memory Safe
 - *Java-like features, without Java's penalties*
 - Defines an embedded standard interface *embedded-hal*




Apollo Guidance Computer



We choose to go to the moon

John F. Kennedy, Rice University, 1961

*in this decade and do the other things, **not because they are easy, but because they are hard**, because **that goal will serve to organize and measure the best of our energies and skills**, because that challenge is one that we are willing to accept, one we are unwilling to postpone, and one which we intend to win, and the others, too.*




AGC

August 1966

Frequency	2.048 MHz
World Length	15 + 1 bit
RAM	4096 B
Storage	72 KB
Software API	AGC Assembly Language


This landed the *moon eagle*.






DSKY


Display and keyboards



Simulator




What is a microprocessor?



Microcontroller (MCU)

Integrated in embedded systems for certain tasks


- low operating frequency (MHz)
- a lot of I/O ports
- controls hardware
- does not require an Operating System
- costs \$0.1 - \$25
- annual demand is billions



Microprocessor (CPU)

General purpose, for PC & workstations


- high operating frequency (GHz)
- limited number of I/O ports
- usually requires an Operating System
- costs \$75 - \$500
- annual demand is tens of millions





How a microprocessor works


This is a simple processor






8 bit processor


a simple 8 bit processor with a text display





Programming


in Rust



```
1 use eight_bit_processor::print;
2
3 static hello: &str = "Hello World!";
4
5 #[start]
6 fn start() {
7     print(hello);
8 }
```

Assembly


```
1     JMP start
2     hello: DB "Hello World!" ; Variable
3           DB 0 ; String terminator
4     start:
5         MOV C, hello ; Point to var
6         MOV D, 232 ; Point to output
7         CALL print
8         HLT ; Stop execution
9     print: ; print(C:*from, D:*to)
10        PUSH A
11        PUSH B
12        MOV B, 0
13    .loop:
14        MOV A, [C] ; Get char from var
15        MOV [D], A ; Write to output
16        INC C
17        INC D
18        CMP B, [C] ; Check if end
19        JNZ .loop ; jump if not
20
21        POP B
22        POP A
23        RET
```



Demo

a working example for the previous code

Start



Real World Microcontrollers

Intel / AVR / PIC / TriCore / ARM Cortex-M / RISC-V rv32i(a)mc



Bibliography

for this section

Joseph Yiu, *The Definitive Guide to ARM® Cortex®-M0 and Cortex-M0+ Processors, 2nd Edition*

- Chapter 1 - *Introduction*
- Chapter 2 - *Technical Overview*



Vendor	Intel
ISA	8051, 8051
Word	8 bit
Frequency	a few MHz
Storage	?
Variants	<i>8048, 8051</i>







AVR


probably *Alf and Vegard's RISC processor*

Authors	Alf-Egil Bogen and Vegard Wollan
Vendor	Microchip (<i>Atmel</i>)
ISA	AVR
Word	8 bit
Frequency	1 - 20 MHz
Storage	4 - 256 KB
Variants	<i>ATmega</i> , <i>ATtiny</i>



Board






PIC

Peripheral Interface Controller / Programmable Intelligent Computer

Vendor	Microchip
ISA	PIC
Word	8 - 32
Frequency	1 - 20 MHz
Storage	256 B - 64 KB
Variants	<i>PIC10, PIC12, PIC16, PIC18, PIC24, PIC32</i>






TriCore



Vendor	Infineon
ISA	AURIX32
Word	32 bit
Frequency	hundreds of MHz
Storage	a few MB
Variants	<i>TC2xx, TC3xx, TC4xx</i>



ARM Cortex-M

Advanced RISC Machine


arm


Vendor	Qualcomm, NXP, Nordic Semiconductor, Broadcom, Raspberry Pi
ISA	ARMv6-M (Thumb and some Thumb-2) ARMv7-M (Thumb and Thumb-2) ARMv8-M (Thumb and Thumb-2)
Word	32
Frequency	1 - 900 MHz
Storage	up to a few MB
Variants	<i>M0, M0+, M3, M4, M7, M23, M33</i>



Fun Facts

- M0/M0+ has no `div`
- M0 - M3 have no floating point
- M23 and M33 have security extensions






RISC-V rv32i(a)mc

Fifth generation of RISC ISA




Authors	University of California, Berkeley
Vendor	Espressif System
ISA	rv32i(a)mc
Word	32 bit
Frequency	1 - 200 MHz
Storage	4 - 256 KB
Variants	<i>rv32imc, rv32iamc</i>



RP2040

ARM Cortex-M0+, built by Raspberry Pi



Bibliography

for this section

Raspberry Pi Ltd, *RP2040 Datasheet*

- Chapter 1 - *Introduction*
- Chapter 2 - *System Description*
 - Section 2.1 - *Bus Fabric*



RP2040


the MCU

Vendor	Raspberry Pi
Variant	ARM Cortex-M0+
ISA	ARMv6-M (Thumb and some Thumb-2)
Cores	2
Word	32 bit
Frequency	up to 133 MHz
RAM	264 KB


Boards


that use RP2040

Raspberry Pi Pico (W)




Arduino Nano RP2040 Connect





The Chip



GPIO: General Purpose Input/Output

SWD: Debug Protocol

DMA: Direct Memory Access

Peripherals

SIO Single Cycle I/O (implements GPIO)

PWM Pulse Width Modulation

ADC Analog to Digital Converter

(Q)SPI (Quad) Serial Peripheral Interface

UART Universal Async. Receiver/Transmitter


RTC Real Time Clock

I2C Inter-Integrated Circuit

PIO Programmable Input/Output

Pins


have multiple functions






The Bus

that interconnects the cores with the peripherals





STM32U545RE

ARM Cortex-M33, built by STMicroelectronics



Bibliography

for this section

STMicroelectronics, STM32U5 Reference Manual

- Chapter 2 - *Memory and bus architecture*
 - Section 2.1 - *System architecture*

STMicroelectronics, STM32U5 Datasheet

- Chapter 2 - *"Description"*
- Chapter 4 - *"Pinout, pin description, and alternate function"*



STM32U545RE


the MCU

Board

that use STM32U545RE

Nucleo U545RE-Q

Vendor	STMicroelectronics
Variant	ARM Cortex-M33
ISA	ARMv8-M
Cores	1
Word	32 bit
Frequency	up to 160 MHz
RAM	272 KB





Parallel interface

FSMC 8-/16-bit
(TFT-LCD, SRAM,
NOR, NAND)

Timers

19 timers including:
2 x 16-bit advanced
motor control timers
4 x ULP timers
5 x 16-bit timers
4 x 32-bit timers

I/Os

Touch-sensing controller
Camera Interface

Connectivity

USB Host/Device
1 x SD/SDIO/MMC, 3 x SPI,
4 x I²C, CAN FD,
1 x Octo-SPI,
4 x USART + 1 x LPUART

Digital

AES (256-bit),
SHA-1, SHA-256,
TRNG, PKA, 1 x SAI,
1 x MDF, 2 x ADF

Analog

1x 14-bit ADC 2 MSPS,
1x 12-bit ADC 2 MSPS,
2 x DAC, 2 x comparators,
1 x op amps
1 x temperature sensor


Datasheet STM32U545RE



Pins

have multiple functions

GPIO	F0	F1	F2	F3	F4	F5	F6	F7	F8	F9	F10	F11
0		SPI0 RX	UART0 TX	I2C0 SDA	PWM0 A	SIO	PI00	PI01	PI02	QMI CS1n	USB OVCUR DET	
1		SPI0 CSn	UART0 RX	I2C0 SCL	PWM0 B	SIO	PI00	PI01	PI02	TRACECLK	USB VBUS DET	
2		SPI0 SCK	UART0 CTS	I2C1 SDA	PWM1 A	SIO	PI00	PI01	PI02	TRACEDATA0	USB VBUS EN	UART0 TX
3		SPI0 TX	UART0 RTS	I2C1 SCL	PWM1 B	SIO	PI00	PI01	PI02	TRACEDATA1	USB OVCUR DET	UART0 RX
4		SPI0 RX	UART1 TX	I2C0 SDA	PWM2 A	SIO	PI00	PI01	PI02	TRACEDATA2	USB VBUS DET	
5		SPI0 CSn	UART1 RX	I2C0 SCL	PWM2 B	SIO	PI00	PI01	PI02	TRACEDATA3	USB VBUS EN	
6		SPI0 SCK	UART1 CTS	I2C1 SDA	PWM3 A	SIO	PI00	PI01	PI02		USB OVCUR DET	UART1 TX
7		SPI0 TX	UART1 RTS	I2C1 SCL	PWM3 B	SIO	PI00	PI01	PI02		USB VBUS DET	UART1 RX
8		SPI1 RX	UART1 TX	I2C0 SDA	PWM4 A	SIO	PI00	PI01	PI02	QMI CS1n	USB VBUS EN	
9		SPI1 CSn	UART1 RX	I2C0 SCL	PWM4 B	SIO	PI00	PI01	PI02		USB OVCUR DET	
10		SPI1 SCK	UART1 CTS	I2C1 SDA	PWM5 A	SIO	PI00	PI01	PI02		USB VBUS DET	UART1 TX
11		SPI1 TX	UART1 RTS	I2C1 SCL	PWM5 B	SIO	PI00	PI01	PI02		USB VBUS EN	UART1 RX
12	HSTX	SPI1 RX	UART0 TX	I2C0 SDA	PWM6 A	SIO	PI00	PI01	PI02	CLOCK GPIN0	USB OVCUR DET	
13	HSTX	SPI1 CSn	UART0 RX	I2C0 SCL	PWM6 B	SIO	PI00	PI01	PI02	CLOCK GP0UT0	USB VBUS DET	
14	HSTX	SPI1 SCK	UART0 CTS	I2C1 SDA	PWM7 A	SIO	PI00	PI01	PI02	CLOCK GPIN1	USB VBUS EN	UART0 TX
15	HSTX	SPI1 TX	UART0 RTS	I2C1 SCL	PWM7 B	SIO	PI00	PI01	PI02	CLOCK GP0UT1	USB OVCUR DET	UART0 RX
16	HSTX	SPI0 RX	UART0 TX	I2C0 SDA	PWM0 A	SIO	PI00	PI01	PI02		USB VBUS DET	
17	HSTX	SPI0 CSn	UART0 RX	I2C0 SCL	PWM0 B	SIO	PI00	PI01	PI02		USB VBUS EN	
18	HSTX	SPI0 SCK	UART0 CTS	I2C1 SDA	PWM1 A	SIO	PI00	PI01	PI02		USB OVCUR DET	UART0 TX
19	HSTX	SPI0 TX	UART0 RTS	I2C1 SCL	PWM1 B	SIO	PI00	PI01	PI02	QMI CS1n	USB VBUS DET	UART0 RX
20		SPI0 RX	UART1 TX	I2C0 SDA	PWM2 A	SIO	PI00	PI01	PI02	CLOCK GPIN0	USB VBUS EN	
21		SPI0 CSn	UART1 RX	I2C0 SCL	PWM2 B	SIO	PI00	PI01	PI02	CLOCK GP0UT0	USB OVCUR DET	
22		SPI0 SCK	UART1 CTS	I2C1 SDA	PWM3 A	SIO	PI00	PI01	PI02	CLOCK GPIN1	USB VBUS DET	UART1 TX



The Bus


that interconnects the core with the peripherals

...



Lab Board


- Nucleo U545RE-Q Slot / Board
- 4 buttons
- 5 LEDs
- potentiometer
- buzzer
- photoresistor
- I2C EEPROM
- MPU-6500 accelerometer & Gyro
- BMP 390 Pressure sensor
- SPI LCD Display
- SD Card Reader
- servo connectors
- stepper motor






- the hardware should not cost more than 150 RON
- STM32 Nucleo F446RE or Nucleo U545RE-Q board (include debuggers)
- Raspberry Pi Pico with a debugger


Raspberry Pi Pico 2W + Raspberry Pi Pico 1





Bitwise Ops

How to set and clear bits




Set bit

set the 1 on position bit of register

```
1 fn set_bit(register: usize, bit: u8) -> usize {
2     // assume register is 0b1000, bit is 2
3     // 1 << 2 is 0b0100
4     // 0b1000 | 0b0100 is 0b1100
5     register | 1 << bit
6 }
```

Set multiple bits

```
1 fn set_bits(register: usize, bits: usize) -> usize {
2     // assume register is 0b1000, bits is 0b0111
3     // 0b1000 | 0b0111 is 0b1111
4     register | bits
5 }
```




Clear bit

Set the 0 on position bit of register

```
1 fn clear_bit(register: usize, bit: u8) -> usize {
2     // assume register is 0b1100, bit is 2
3     // 1 << 2 is 0b0100
4     // !(1 << 2) is 0b1011
5     // 0b1100 & 0b1011 is 0b1000
6     register & !(1 << bit)
7 }
```

Clear multiple bits

```
1 fn clear_bits(register: usize, bits: usize) -> usize {
2     // assume register is 0b1111, bits is 0b0111
3     // !bits = 0b1000
4     // 0b1111 & 0b1000 is 0b1000
5     register & !bits
6 }
```



Flip bit

Flip the bit on position `bit` of `register`

```
1 fn flip_bit(register: usize, bit: u8) -> usize {
2     // assume register is 0b1100, bit is 2
3     // 1 << 2 is 0b0100
4     // 0b1100 ^ 0b0100 is 0b1000
5     register ^ 1 << bit
6 }
```

Flip multiple bits


```
1 fn flip_bits(register: usize, bits: usize) -> usize {
2     // assume register is 0b1000, bits is 0b0111
3     // 0b1000 ^ 0b0111 is 0b1111
4     register ^ bits
5 }
```



Let's see a combined operation for value extraction


- We presume an 32 bits ID = `0b1100_1010_1111_1100_0000_1111_0110_1101`
- And want to extract a portion `0b1100_1010_1111_1100_0000_1111_0110_1101`

```
1  const MASK: u32 = 0b0000_0000_0000_0000_0000_1111_1111_1111;
2
3  fn print_binary(label: &str, num: u32) {
4      println!("{}", num);
5  }
6
7  fn main() {
8      let large_id: u32 = 0b1100_1010_1111_1100_0000_1111_0110_1101;
9      let extracted_bits = (large_id >> 20) & MASK;
10
11     // Print values in binary
12     print_binary("Original_", large_id);
13     print_binary("Mask_____", MASK);
14     print_binary("Extracted", extracted_bits);
15 }
16 /* RESULT
17 Original_: 11001010111111000000111101101101
18 Mask_____: 00000000000000000000111111111111
19 Extracted: 00000000000000000000110010101111 */
```



With nice formatting

```
1  const MASK: u32 = 0b0000_0000_0000_0000_1111_1111_1111;
2  fn format_binary(num: u32) -> String {
3      (0..32).rev()
4          .map(|i| {
5              if i != 0 && i % 4 == 0 {
6                  format!("{}", _, (num >> i) & 1)
7              } else {
8                  format!("{}", (num >> i) & 1)
9              }
10         })
11         .collect::
```



Conclusion

we talked about

- How a processor functions
- Microcontrollers (MCU) / Microprocessors (CPU)
- Microcontroller architectures
- ARM Cortex-M
- RP2040 and STM32U545RE