

Branch: master ▾

Find file

Copy path

[python_speech_features](#) / [python_speech_features](#) / [sigproc.py](#) / Jump to ▾

 **hshteingart** add documentation line to explain the flag

9f244cf on 13 Aug 2017

4 contributors    

Raw Blame History



140 lines (109 sloc) 5.98 KB

Code navigation is available!

Navigate your code with ease. Click on function and method calls to jump to their definitions or references in the same repository. [Learn more](#)



● You're using code navigation to jump to definitions or references.

[Learn more](#) or [give us feedback](#)

```
1 # This file includes routines for basic signal processing including framing and computing power spectra.
2 # Author: James Lyons 2012
3 import decimal
4
5 import numpy
6 import math
7 import logging
8
9
10 def round_half_up(number):
11     return int(decimal.Decimal(number).quantize(decimal.Decimal('1'), rounding=decimal.ROUND_HALF_UP))
12
13
14 def rolling_window(a, window, step=1):
15     # http://ellisvalentiner.com/post/2017-03-21-np-strides-trick
16     shape = a.shape[:-1] + (a.shape[-1] - window + 1, window)
17     strides = a.strides + (a.strides[-1],)
18     return numpy.lib.stride_tricks.as_strided(a, shape=shape, strides=strides)[::step]
19
20
21 def framesig(sig, frame_len, frame_step, winfunc=lambda x: numpy.ones((x,)), stride_trick=True):
22     """Frame a signal into overlapping frames.
23
24     :param sig: the audio signal to frame.
25     :param frame_len: length of each frame measured in samples.
26     :param frame_step: number of samples after the start of the previous frame that the next frame should begin.
27     :param winfunc: the analysis window to apply to each frame. By default no window is applied.
28     :param stride_trick: use stride trick to compute the rolling window and window multiplication faster
29     :returns: an array of frames. Size is NUMFRAMES by frame_len.
30     """
31     slen = len(sig)
32     frame_len = int(round_half_up(frame_len))
33     frame_step = int(round_half_up(frame_step))
34     if slen <= frame_len:
35         numframes = 1
36     else:
37         numframes = 1 + int(math.ceil((1.0 * slen - frame_len) / frame_step))
38
39     padlen = int((numframes - 1) * frame_step + frame_len)
40
41     zeros = numpy.zeros((padlen - slen,))
42     padsignal = numpy.concatenate((sig, zeros))
43     if stride_trick:
44         win = winfunc(frame_len)
45         frames = rolling_window(padsignal, window=frame_len, step=frame_step)
46     else:
47         indices = numpy.tile(numpy.arange(0, frame_len), (numframes, 1)) + numpy.tile(
48             numpy.arange(0, numframes * frame_step, frame_step), (frame_len, 1)).T
49         indices = numpy.array(indices, dtype=numpy.int32)
```

```

50     frames = padsignal[indices]
51     win = numpy.tile(winfunc(frame_len), (numframes, 1))
52
53     return frames * win
54
55
56 def deframesig(frames, siglen, frame_len, frame_step, winfunc=lambda x: numpy.ones((x,))):
57     """Does overlap-add procedure to undo the action of framesig.
58
59     :param frames: the array of frames.
60     :param siglen: the length of the desired signal, use 0 if unknown. Output will be truncated to siglen samples.
61     :param frame_len: length of each frame measured in samples.
62     :param frame_step: number of samples after the start of the previous frame that the next frame should begin.
63     :param winfunc: the analysis window to apply to each frame. By default no window is applied.
64     :returns: a 1-D signal.
65     """
66     frame_len = round_half_up(frame_len)
67     frame_step = round_half_up(frame_step)
68     numframes = numpy.shape(frames)[0]
69     assert numpy.shape(frames)[1] == frame_len, "frames" matrix is wrong size, 2nd dim is not equal to frame_len'
70
71     indices = numpy.tile(numpy.arange(0, frame_len), (numframes, 1)) + numpy.tile(
72         numpy.arange(0, numframes * frame_step, frame_step), (frame_len, 1)).T
73     indices = numpy.array(indices, dtype=numpy.int32)
74     padlen = (numframes - 1) * frame_step + frame_len
75
76     if siglen <= 0: siglen = padlen
77
78     rec_signal = numpy.zeros((padlen,))
79     window_correction = numpy.zeros((padlen,))
80     win = winfunc(frame_len)
81
82     for i in range(0, numframes):
83         window_correction[indices[i, :]] = window_correction[
84             indices[i, :] + win + 1e-15 # add a little bit so it is never zero
85         rec_signal[indices[i, :]] = rec_signal[indices[i, :]] + frames[i, :]
86
87     rec_signal = rec_signal / window_correction
88     return rec_signal[0:siglen]
89
90
91 def magspec(frames, NFFT):
92     """Compute the magnitude spectrum of each frame in frames. If frames is an NxN matrix, output will be Nx(NFFT/2+1).
93
94     :param frames: the array of frames. Each row is a frame.
95     :param NFFT: the FFT length to use. If NFFT > frame_len, the frames are zero-padded.
96     :returns: If frames is an NxN matrix, output will be Nx(NFFT/2+1). Each row will be the magnitude spectrum of the corresponding frame.
97     """
98     if numpy.shape(frames)[1] > NFFT:
99         logging.warn(
100             'frame length (%d) is greater than FFT size (%d), frame will be truncated. Increase NFFT to avoid.',
101             numpy.shape(frames)[1], NFFT)
102     complex_spec = numpy.fft.rfft(frames, NFFT)
103     return numpy.absolute(complex_spec)
104
105
106 def powspec(frames, NFFT):
107     """Compute the power spectrum of each frame in frames. If frames is an NxN matrix, output will be Nx(NFFT/2+1).
108
109     :param frames: the array of frames. Each row is a frame.
110     :param NFFT: the FFT length to use. If NFFT > frame_len, the frames are zero-padded.
111     :returns: If frames is an NxN matrix, output will be Nx(NFFT/2+1). Each row will be the power spectrum of the corresponding frame.
112     """
113     return 1.0 / NFFT * numpy.square(magspec(frames, NFFT))
114
115
116 def logpowspec(frames, NFFT, norm=1):
117     """Compute the log power spectrum of each frame in frames. If frames is an NxN matrix, output will be Nx(NFFT/2+1).
118
119     :param frames: the array of frames. Each row is a frame.
120     :param NFFT: the FFT length to use. If NFFT > frame_len, the frames are zero-padded.
121     :param norm: If norm=1, the log power spectrum is normalised so that the max value (across all frames) is 0.
122     :returns: If frames is an NxN matrix, output will be Nx(NFFT/2+1). Each row will be the log power spectrum of the corresponding frame.

```

```

123     """
124     ps = powspec(frames, NFFT);
125     ps[ps <= 1e-30] = 1e-30
126     lps = 10 * numpy.log10(ps)
127     if norm:
128         return lps - numpy.max(lps)
129     else:
130         return lps
131
132
133 def preemphasis(signal, coeff=0.95):
134     """perform preemphasis on the input signal.
135
136     :param signal: The signal to filter.
137     :param coeff: The preemphasis coefficient. 0 is no filter, default is 0.95.
138     :returns: the filtered signal.
139     """
140     return numpy.append(signal[0], signal[1:] - coeff * signal[:-1])

```