


Image Augmentation for Deep Learning



Deep networks need large amount of training data to achieve good performance. To build a powerful image classifier using very little training data, image augmentation is usually required to boost the performance of deep networks. **Image** augmentation artificially creates training images through different ways of processing or combination of multiple processing, such as random rotation, shifts, shear and flips, etc.

Image Data Generator

An augmented image generator can be easily created using ImageDataGenerator generates batches of image data with real-time data augmentation. The most basic codes to create and configure ImageDataGenerator and train deep neural network with augmented images are as follows.


```
datagen = ImageDataGenerator()
datagen.fit(train)
X_batch, y_batch = datagen.flow(X_train, y_train,
batch_size=batch_size)
model.fit_generator(datagen, samples_per_epoch=len(train),
epochs=epochs)
```

We can experiment with the following code to create augmented images with the desired properties. In our case, the following data generator generates a batch of 9

augmented images with rotation by 30 degrees and horizontal shift by 0.5.

```
datagen = ImageDataGenerator(rotation_range=30, horizontal_flip=0.5)
datagen.fit(img)
i=0
for img_batch in datagen.flow(img, batch_size=9):
    for img in img_batch:
        plt.subplot(330 + 1 + i)
        plt.imshow(img)
        i=i+1
    if i >= batch_size:
        break
```





Original Image and Augmented Images

Histogram Equalization

Apart from the standard techniques of data augmentation provided by the ImageDataGenerator class in Keras, we can use custom functions to generate augmented images. For example, you may want to adjust the contrast of images using contrast stretching. Contrast stretching is a simple image processing technique that enhances the contrast by rescaling ("stretching") the range of intensity values of an image to a desired range of values.

Histogram equalization is another image processing technique to increase global contrast of an image using the image intensity histogram. The equalized image has a linear cumulative distribution function. This method needs no parameter, but it sometimes results an unnatural looking image.


An alternative is **adaptive histogram equalization** (AHE) which improves local contrast of an image by computing several histograms corresponding to different sections of an image (differs from ordinary histogram equalization which uses only one histogram to adjust global contrast), and uses them for local contrast adjustment. However, AHE has a tendency to over-amplify noise in relatively homogeneous regions of an image.

Contrast limited adaptive histogram equalization (CLAHE) was developed to prevent the over-amplification of noise resulted from AHE. In gist, it limits the contrast enhancement of AHE by clipping the histogram at a predefined value before computing the cumulative distribution function.

To implement custom preprocessing function for augmentation in Keras, we first define our custom function and pass it to ImageDataGenerator as an argument. For instance, we can implement AHE using the following code.

```
def AHE(img):
    img_adapteq = exposure.equalize_adapthist(img, clip_limit=0.03)
    return img_adapteq

datagen = ImageDataGenerator(rotation_range=30, horizontal_flip=0.5,
preprocessing_function=AHE)
```



Augmented Images using Contrast Stretching (left), Histogram Equalization (middle) and Adaptive Histogram Equalization (right)

Source code

References

- <u>Image Augmentation for Deep Learning With Keras</u>
- Building powerful image classification models using very little data

Machine Learning

Data Science

Deep Learning

Image Processing

Neural Networks





Written by Suki Lau

355 Followers · Writer for Towards Data Science

always a student

More from Suki Lau and Towards Data Science





Learning Rate Schedules and Adaptive Learning Rate Methods for Deep Learning

When training deep neural networks, it is often useful to reduce learning rate as the training progresses. This can be done by using...

6 min read · Jul 29, 2017











🧥 Tim Sumner in Towards Data Science

A New Coefficient of Correlation

What if you were told there exists a new way to measure the relationship between two variables just like correlation except possibly...

10 min read · Mar 31, 2024





 Γ



On Youness Mansar in Towards Data Science

Meet the NiceGUI: Your Soon-to-be Favorite Python UI Library

Build custom web apps easily and quickly

8 min read · Apr 17, 2024





Suki Lau in Towards Data Science

A Walkthrough of Convolutional Neural Network — Hyperparameter Tuning

Among the diverse deep learning architecture, convolutional neural network (convnets for short) stands out for its unprecedented...


4 min read · Jul 11, 2017



See all from Suki Lau

See all from Towards Data Science

Recommended from Medium



Sandaruwan Herath in Data Science and Machine Learning

EfficientNetB0 architecture—Stem Layer

EfficientNet's layers are based on a compound scaling method that uniformly scales the depth, width, and resolution of the network, with...

11 min read · Jan 14, 2024













Ultimate Guide to Fine-Tuning in PyTorch: Part 3 - Deep Dive to PyTorch **Data Transforms**

Explore PyTorch's Transforms Functions: Geometric, Photometric, Conversion, and Composition Transforms for Robust Model Training. Dive in!




21 min read · Nov 6, 2023







Lists



Predictive Modeling w/ Python

20 stories · 1153 saves



Practical Guides to Machine Learning

10 stories · 1391 saves



Natural Language Processing

1429 stories · 924 saves



data science and Al

40 stories · 146 saves





Vrunda Bhattbhatt in The Deep Hub

Learning Rate and Its Strategies in Neural Network Training

Introduction to Learning Rate in Neural Networks

7 min read · Jan 24, 2024













Juan David Otálora

Automated Data Augmentation


Machine learning models need huge amounts of data to be trained. Normally, there are databases that have hundreds of datapoints, but if the...

3 min read · Nov 26, 2023









Leonie Monigatti in Towards Data Science

A Visual Guide to Learning Rate Schedulers in PyTorch

LR decay and annealing strategies for Deep Learning in Python

· 9 min read · Dec 7, 2022

₹¹ 1.2K



 \Box [†]





Yegor Voronyansky

Digital Image Processing | Histogram Calculation, Equalization and **Normalization**

This article continues the basics of the digital image processing series. In this article, I will talk about histogram calculation and...

4 min read · Dec 9, 2023









See more recommendations