

## 标题语法：

---

Setext 形式

# A First Level Header

---

## A Second Level Header

---

atx 形式

# Header 1

---

## Header 2

---

### Header 3

#### Header 4

##### Header 5

## 区块语法：

---

This is a blockquote.

This is the second paragraph in the blockquote.

这是嵌套

## This is an H2 in a block quote

---

这是一个普通段落：

```
这是一个代码区块。  
#include <stdio.h>
```

## 分割线语法：

---

---

---

---

---

---

## 标记语法：

---

Some of these words *are emphasized*. Some of these words *are emphasized also*. Use two asterisks for **strong emphasis**. Or, if you prefer, **use two underscores instead**.

I strongly recommend against using any `<blink>` tags.

There is a literalbacktick (``) here.

I wish SmartyPants used named entities like `&mdash;` instead of decimal-encoded entites like `&#8212;` .

If you want your page to validate under XHTML 1.0 Strict, you've got to put paragraph tags in your blockquotes:

For example.

## 列表语法：

---

- Candy.
- Gum.
- Booze.
- Candy.
- Gum.
- Booze.
- Candy.
- Gum.
- Booze.
- Red
- Green
- Blue
- Lorem ipsum dolor sit amet, consectetuer adipiscing elit. Aliquam hendrerit mi posuere lectus. Vestibulum enim wisi, viverra nec, fringilla in, laoreet vitae, risus.
- Donec sit amet nisl. Aliquam semper ipsum sit amet velit. Suspendisse id sem consectetuer libero luctus adipiscing.
- 一列表项包含一个列表区块：

```
<代码写在这>  
#include <stdio.h>
```

1986. What a great season.

## 链接语法：

---

This is an [example link](#).

This is an [example link](#).

This is [an example](#) reference-style link.

[百度](#)

I get 10 times more traffic from [Google](#) than from [Yahoo](#) or [MSN](#).

## 图片语法：

---



