

I have hard coded the servers ip address as 10.234.136.55

The Server has to be placed in in-csci-rrpc02.cs.iupui.edu
10.234.136.55

Server Side

To Compile and run the server

Current directory must be /Thalluri_A2/SourceCode/server/

give the following command

```
make -f Makefile.selec
```

this compiles the code

give the following command to run the code

```
./makeselec_server.sh
```

Client Side

The client can be deployed onto any of the machines provided in the list:

```
in-csci-rrpc02.cs.iupui.edu 10.234.136.56  
in-csci-rrpc03.cs.iupui.edu 10.234.136.57  
in-csci-rrpc04.cs.iupui.edu 10.234.136.58  
in-csci-rrpc05.cs.iupui.edu 10.234.136.59  
in-csci-rrpc06.cs.iupui.edu 10.234.136.60
```

To Compile and run the server

Current directory must be /Thalluri_A2/SourceCode/client/

give the following command

```
make -f Makefile.selec
```

this compiles the code

give the following command to run the code

```
./makeselec_client.sh
```

The file required to be deleted by the client has to be present in the directory

/Thalluri_A2/SourceCode/server/

Please give sufficient access privileges to both the client files and the server files by using

In the client Folder

please run

```
chmod 777 *.*  
chmod 777 *
```

In the server Folder

please run

```
chmod 777 *.*  
chmod 777 *
```