

Condensatoare ceramice 50 V



Tip condensator	ceramic
Tensiune de lucru	50V
Temperatura de lucru	-25...85°C

Simbol	Toleranță [%]	Producător	Cap. [F]	Raster [mm]	Toleranță [pF]
CC-4.7	±10		4,7p	2,54	-
CC-6.8	±10		6,8p	2,54	±0,25
CC-8.2	±10		8,2p	2,54	-
CC-10	±10		10p	2,54	-
CC-15	±10		15p	2,54	-
CC-22	±10		22p	2,54	-
CC-27	±10		27p	2,54	-
CC-33	±10		33p	2,54	-
CC-47	±10		47p	2,54	-
CC-82	±10		82p	2,54	-
CC-100	±10		100p	2,54	-
CC-120	±10		120p	2,54	-
CC-220	±10		220p	2,54	-
CC-330	±10		330p	2,54	-
CC-470	±10		470p	2,54	-
CC-680	±10		680p	2,54	-
CC-820	±10		820p	2,54	-
CC-1N	±10		1n	2,54	-
CC-1.5N	±10		1,5n	2,54	-
CC-2.2N	±10		2,2n	2,54	-
CC-4.7N	±10		4,7n	2,54	-
CC-10N	-20...80		10n	2,54	-
CC-15N	-20...80		15n	2,54	-
CC-22N	-20...80		22n	2,54	-
CC-33N	±10		33n	2,54	-
CC-47N	±10		47n	2,54	-
CC-100N	±10		100n	2,54	-
CC-2.2U	±10	KEMET	2,2μ	5	-
CC-68N-Z	-20...80		68n	2,54	-