```
aces-mbp-22:git-testing2 acetip$ cd desktop
-bash: cd: desktop: No such file or directory
aces-mbp-22:git-testing2 acetip$ cd ..
aces-mbp-22:desktop acetip$ git clone https://github.com/xshirl/git-
testing.git
fatal: destination path 'git-testing' already exists and is not an
empty directory.
aces-mbp-22:desktop acetip$ git clone https://github.com/xshirl/git-
testing.git
Cloning into 'git-testing'...
warning: You appear to have cloned an empty repository.
aces-mbp-22:desktop acetip$ cd git-testing
aces-mbp-22:git-testing acetip$ touch index.html
aces-mbp-22:git-testing acetip$ git add .
aces-mbp-22:git-testing acetip$ git commit -m "first commit"
[master (root-commit) f15d8a1] first commit
 Committer: ACE <acetip@aces-mbp-22.acelab.lagcc>
Your name and email address were configured automatically based
on your username and hostname. Please check that they are accurate.
You can suppress this message by setting them explicitly:

    git config --global user.name "Your Name"
    git config --global user.email you@example.com

After doing this, you may fix the identity used for this commit with:

    git commit --amend --reset-author

 1 file changed, 1 insertion(+)
 create mode 100644 index.html
aces-mbp-22:git-testing acetip$ git push
Counting objects: 3, done.
Writing objects: 100% (3/3), 233 bytes | 233.00 KiB/s, done.
Total 3 (delta 0), reused 0 (delta 0)
To https://github.com/xshirl/git-testing.git
 * [new branch]      master -> master
aces-mbp-22:git-testing acetip$ git branch gh-pages
aces-mbp-22:git-testing acetip$ git push origin gh-pages
Total 0 (delta 0), reused 0 (delta 0)
To https://github.com/xshirl/git-testing.git
 * [new branch]      gh-pages -> gh-pages
aces-mbp-22:git-testing acetip$ git add .
aces-mbp-22:git-testing acetip$ git commit -m "second commit"
[master aed395c] second commit
 Committer: ACE <acetip@aces-mbp-22.acelab.lagcc>
Your name and email address were configured automatically based
on your username and hostname. Please check that they are accurate.
You can suppress this message by setting them explicitly:
```

```
    git config --global user.name "Your Name"
    git config --global user.email you@example.com

After doing this, you may fix the identity used for this commit with:

    git commit --amend --reset-author


 1 file changed, 3 insertions(+), 1 deletion(-)
aces-mbp-22:git-testing acetip$ git push
Counting objects: 3, done.
Writing objects: 100% (3/3), 280 bytes | 280.00 KiB/s, done.
Total 3 (delta 0), reused 0 (delta 0)
git checkTo https://github.com/xshirl/git-testing.git
   f15d8a1..aed395c  master -> master
aces-mbp-22:git-testing acetip$ git checkout gh-pages
Switched to branch 'gh-pages'
aces-mbp-22:git-testing acetip$ git rebase master
First, rewinding head to replay your work on top of it...
Fast-forwarded gh-pages to master.
aces-mbp-22:git-testing acetip$ git push origin gh-pages
Total 0 (delta 0), reused 0 (delta 0)
To https://github.com/xshirl/git-testing.git
   f15d8a1..aed395c  gh-pages -> gh-pages
aces-mbp-22:git-testing acetip$ git checkout master
Switched to branch 'master'
Your branch is up to date with 'origin/master'.
aces-mbp-22:git-testing acetip$ cd ..
aces-mbp-22:desktop acetip$ git clone https://github.com/xshirl/git-
testing2.git
Cloning into 'git-testing2'...
warning: You appear to have cloned an empty repository.
aces-mbp-22:desktop acetip$ cd git-testing2
aces-mbp-22:git-testing2 acetip$ touch index.html
aces-mbp-22:git-testing2 acetip$ open index.html
aces-mbp-22:git-testing2 acetip$ git add .
aces-mbp-22:git-testing2 acetip$ git commit -m "first commit"
[master (root-commit) e91b2d3] first commit
 Committer: ACE <acetip@aces-mbp-22.acelab.lagcc>
Your name and email address were configured automatically based
on your username and hostname. Please check that they are accurate.
You can suppress this message by setting them explicitly:

    git config --global user.name "Your Name"
    git config --global user.email you@example.com

After doing this, you may fix the identity used for this commit with:

    git commit --amend --reset-author
```

```
 1 file changed, 2 insertions(+)
 create mode 100644 index.html
aces-mbp-22:git-testing2 acetip$ git push
Counting objects: 3, done.
Writing objects: 100% (3/3), 246 bytes | 246.00 KiB/s, done.
Total 3 (delta 0), reused 0 (delta 0)
To https://github.com/xshirl/git-testing2.git
 * [new branch]      master -> master
aces-mbp-22:git-testing2 acetip$ git branch gh-pages
aces-mbp-22:git-testing2 acetip$ git push origin gh-pages
Total 0 (delta 0), reused 0 (delta 0)
To https://github.com/xshirl/git-testing2.git
 * [new branch]      gh-pages -> gh-pages
aces-mbp-22:git-testing2 acetip$ git checkout gh-pages
M    index.html
Switched to branch 'gh-pages'
aces-mbp-22:git-testing2 acetip$ git rebase master
Cannot rebase: You have unstaged changes.
Please commit or stash them.
aces-mbp-22:git-testing2 acetip$ git checkout master
M    index.html
Switched to branch 'master'
Your branch is up to date with 'origin/master'.
aces-mbp-22:git-testing2 acetip$ git add .
aces-mbp-22:git-testing2 acetip$ git commit -m "second commit"
[master 932162a] second commit
 Committer: ACE <acetip@aces-mbp-22.acelab.lagcc>
Your name and email address were configured automatically based
on your username and hostname. Please check that they are accurate.
You can suppress this message by setting them explicitly:

    git config --global user.name "Your Name"
    git config --global user.email you@example.com

After doing this, you may fix the identity used for this commit with:

    git commit --amend --reset-author

 1 file changed, 1 insertion(+)
aces-mbp-22:git-testing2 acetip$ git push
Counting objects: 3, done.
Delta compression using up to 4 threads.
Compressing objects: 100% (2/2), done.
Writing objects: 100% (3/3), 296 bytes | 296.00 KiB/s, done.
Total 3 (delta 0), reused 0 (delta 0)
To https://github.com/xshirl/git-testing2.git
   e91b2d3..932162a  master -> master
aces-mbp-22:git-testing2 acetip$ git checkout gh-pages
Switched to branch 'gh-pages'
```

```
aces-mbp-22:git-testing2 acetip$ git rebase master
First, rewinding head to replay your work on top of it...
Fast-forwarded gh-pages to master.
aces-mbp-22:git-testing2 acetip$ git push origin gh-pages
Total 0 (delta 0), reused 0 (delta 0)
To https://github.com/xshirl/git-testing2.git
   e91b2d3..932162a  gh-pages -> gh-pages
aces-mbp-22:git-testing2 acetip$
```