

Synchronization

Synchronization Motivation

- When threads concurrently read/write shared memory, program behavior is undefined
 - Two threads write to the same variable; which one should win?
- Thread schedule is non-deterministic
 - Behavior changes when re-run program
- Compiler/hardware instruction reordering
- Multi-word operations are not atomic

Question: Can this panic?

Thread 1

```
p = someComputation();  
pInialized = true;
```

Thread 2

```
while (!pInialized)  
    ;  
q = someFunction(p);  
if (q != someFunction(p))  
    panic
```

Why Reordering?

- Why do compilers reorder instructions?
 - Efficient code generation requires analyzing control/data dependency
 - If variables can spontaneously change, most compiler optimizations become impossible
- Why do CPUs reorder instructions?
 - Write buffering: allow next instruction to execute while write is being completed

Fix: **memory barrier**

- Instruction to compiler/CPU
- All ops before barrier complete before barrier returns
- No op after barrier starts until barrier returns

Too Much Milk Example

	Person A	Person B
12:30	Look in fridge. Out of milk.	
12:35	Leave for store.	
12:40	Arrive at store.	Look in fridge. Out of milk.
12:45	Buy milk.	Leave for store.
12:50	Arrive home, put milk away.	Arrive at store.
12:55		Buy milk.
1:00		Arrive home, put milk away. Oh no!

race → lock → crit → mutual exclusion → lock

Definitions

→ มีงานที่ต้องทำพร้อมกัน

Race condition: output of a concurrent program depends on the order of operations between threads

→ ใช้งานร่วมกัน

Mutual exclusion: only one thread does a particular thing at a time

↓ สภาวะ → ที่อนุญาตให้ thread เดียวกันทำงานร่วมกัน → ใช้งาน lock

- **Critical section:** piece of code that only one thread can execute at once

↓ ส่วนของ code ที่อนุญาตให้ thread เดียวกันทำงานร่วมกัน 1 thread / unit t.

Lock: prevent someone from doing something

↓ avoid share resource

- Lock before entering critical section, before accessing shared data

↓ ใช้งานร่วมกัน

- Unlock when leaving, after done accessing shared data

↓ avoid shared res

- Wait if locked (all synchronization involves waiting!)

↓ ใช้งานร่วมกัน

↓ avoid critical section

↓ avoid shared resource

Too Much Milk, Try #1

- Correctness property
 - Someone buys if needed (liveness)
 - At most one person buys (safety)
- Try #1: leave a note

```
if (!note)
    if (!milk) {
        leave note
        buy milk
        remove note
    }
```

Too Much Milk, Try #2

Thread A

```
leave note A
if (!note B) {
    if (!milk)
        buy milk
}
remove note A
```

Thread B

```
leave note B
if (!noteA) {
    if (!milk)
        buy milk
}
remove note B
```


Too Much Milk, Try #3

Thread A

```
leave note A
while (note B) // X
    do nothing;
if (!milk)
    buy milk;
remove note A
```

Thread B

```
leave note B
if (!noteA) { // Y
    if (!milk)
        buy milk
}
remove note B
```

Can guarantee at X and Y that either:

- (i) Safe for me to buy
- (ii) Other will buy, ok to quit

Lessons

- Solution is complicated
 - “obvious” code often has bugs
- Modern compilers/architectures reorder instructions
 - Making reasoning even more difficult
- Generalizing to many threads/processors
 - Even more complex: see Peterson’s algorithm

Roadmap

Concurrent Applications

Shared Objects

Bounded Buffer

Barrier

Synchronization Variables

Semaphores

Locks

Condition Variables

Atomic Instructions

Interrupt Disable

Test-and-Set

Hardware

Multiple Processors

Hardware Interrupts

Locks

- Lock::acquire
 - wait until lock is free, then take it
 - Lock::release
 - release lock, waking up anyone waiting for it
1. At most one lock holder at a time (safety)
 2. If no one holding, acquire gets lock (progress)
 3. If all lock holders finish and no higher priority waiters, waiter eventually gets lock (progress)

Question: Why only Acquire/Release

- Suppose we add a method to a lock, to ask if the lock is free. Suppose it returns true. Is the lock:
 - Free?
 - Busy?
 - Don't know?

Too Much Milk, #4

Locks allow concurrent code to be much simpler:

```
lock.acquire();
```

```
if (!milk)
```

```
    buy milk
```

```
lock.release();
```

Lock Example: Malloc/Free

```
char *malloc (n) {  
    heaplock.acquire();  
    p = allocate memory  
    heaplock.release();  
    return p;  
}
```

```
void free(char *p) {  
    heaplock.acquire();  
    put p back on free list  
    heaplock.release();  
}
```

Rules for Using Locks

- Lock is initially free
- Always acquire before accessing shared data structure
 - Beginning of procedure!
- Always release after finishing with shared data
 - End of procedure!
 - Only the lock holder can release
 - DO NOT throw lock for someone else to release
- Never access shared data without lock
 - Danger!

Will this code work?

```
if (p == NULL) {  
    lock.acquire();  
    if (p == NULL) {  
        p = newP();  
    }  
    lock.release();  
}  
use p->field1
```

```
newP() {  
    p = malloc(sizeof(p));  
    p->field1 = ...  
    p->field2 = ...  
    return p;  
}
```

Example: Bounded Buffer

```
tryget() {  
    item = NULL;  
    lock.acquire();  
    if (front < tail) {  
        item = buf[front % MAX];  
        front++;  
    }  
    lock.release();  
    return item;  
}
```

```
tryput(item) {  
    lock.acquire();  
    if ((tail - front) < size) {  
        buf[tail % MAX] = item;  
        tail++;  
    }  
    lock.release();  
}
```

Initially: front = tail = 0; lock = FREE; MAX is buffer capacity

Question

- If tryget returns NULL, do we know the buffer is empty?
- If we poll tryget in a loop, what happens to a thread calling tryput?

Condition Variables

- Waiting inside a critical section
 - Called only when holding a lock

- Wait: atomically release lock and relinquish processor
 - Reacquire the lock when wakened
- Signal: wake up a waiter, if any
- Broadcast: wake up all waiters, if any

→ 011010101 Monitor • wait
• pulse

↳ 2 operation → wait

↳ thread release running → wait stage

↓
waiters waiting

↓
2 threads lock obj runs sequentially

Condition Variable Design Pattern

```
methodThatWaits() {  
    lock.acquire();  
    // Read/write shared state  
  
    while (!testSharedState()) {  
        cv.wait(&lock);  
    }  
  
    // Read/write shared state  
    lock.release();  
}
```

```
methodThatSignals() {  
    lock.acquire();  
    // Read/write shared state  
  
    // If testSharedState is now true  
    cv.signal(&lock);  
  
    // Read/write shared state  
    lock.release();  
}
```

Example: Bounded Buffer

```
get() {  
    lock.acquire();  
    while (front == tail) {  
        empty.wait(lock);  
    }  
    item = buf[front % MAX];  
    front++;  
    full.signal(lock);  
    lock.release();  
    return item;  
}
```

```
put(item) {  
    lock.acquire();  
    while ((tail - front) == MAX) {  
        full.wait(lock);  
    }  
    buf[tail % MAX] = item;  
    tail++;  
    empty.signal(lock);  
    lock.release();  
}
```

Initially: front = tail = 0; MAX is buffer capacity
empty/full are condition variables

Pre/Post Conditions

เงื่อนไขก่อนและหลังการดำเนินการ condition variable

- What is state of the bounded buffer at lock acquire?
 - $\text{front} \leq \text{tail}$
 - $\text{front} + \text{MAX} \geq \text{tail}$
- These are also true on return from wait
- And at lock release
- Allows for proof of correctness

Pre/Post Conditions

```
methodThatWaits() {
    lock.acquire(); acquires lock
    // Pre-condition: State is consistent
```

```
// Read/write shared state
```

```
while (!testSharedState()) {
    cv.wait(&lock);
}
```

Handwritten notes in red:

- ← (ខ្ញុំបង្អស់នឹងត្រូវបានដាក់)
- ចាំបាច់ឱ្យមានការរង់ចាំ
- វាជាការរង់ចាំដើម្បីឱ្យមានការប្រើប្រាស់ស្ថានភាព

```
// WARNING: shared state may
// have changed! But
// testSharedState is TRUE
// and pre-condition is true
```

```
// Read/write shared state
lock.release();
```

}

```
methodThatSignals() {
    lock.acquire();
    // Pre-condition: State is consistent
```

```
// Read/write shared state
```

```
// If testSharedState is now true
cv.signal(&lock);
```

```
// NO WARNING: signal keeps lock
```

```
// Read/write shared state
lock.release();
```

↓ ការបោះឆ្នោតនៅក្នុងតំបន់ប្រជាជន
រស់នៅ → ទំនាក់ទំនងជាមួយ

if วนซ้ำ = วนซ้ำแบบธรรมดา ↓
while loop ขึ้นเรื่อย ๆ ตัวแปรจนมัน
ทำงานไม่ได้

ลักษณะการทำงานของ while loop ขึ้นอยู่

Condition Variables

↓
เกิด context switch
ไปอื่นก่อนไปรอ

→ ปล่อย lock หมด

- ALWAYS hold lock when calling wait, signal, broadcast

- Condition variable is sync FOR shared state
- ALWAYS hold lock when accessing shared state

- Condition variable is memoryless → ไร้อุปกรณ์เก็บค่า signal

- If signal when no one is waiting, no op
- If wait before signal, waiter wakes up

- Wait atomically releases lock

- What if wait, then release?
- What if release, then wait?

ปลง

↓
ไปถือธงแล้ว

↓
ถ้าในเงื่อนไขแล้ว หรือ sig

↓
ไร้อุปกรณ์เก็บค่า → ไร้อุปกรณ์
sig 1, 2, 3.

↓
ไร้อุปกรณ์เก็บค่า

↓
ปลด lock ไว้ก่อนแล้วค่อย wait

↓
ไปรับ lock กันเอง

Condition Variables, cont'd

- When a thread is ~~woken~~ up from wait, it may not run immediately
อาจไม่ได้รันทันที
wait → ready → schedules → running
 - Signal/broadcast put thread on ready list
 - When lock is released, anyone might acquire it
- Wait MUST be in a loop

```
while (needToWait()) {  
    condition.Wait(lock);  
}
```

↓ อยากรันขอ lock → เมื่อได้ขอ lock running
↓ อยากรัน ready รอขอ lock
↓ เมื่อได้ lock แล้ว
↓ ไม่ลืมนั่ง waitstate
↓ loop
- Simplifies implementation
 - Of condition variables and locks
 - Of code that uses condition variables and locks

Java Manual

When waiting upon a Condition, a “spurious wakeup” is permitted to occur, in general, as a concession to the underlying platform semantics. This has little practical impact on most application programs as a Condition should always be waited upon in a loop, testing the state predicate that is being waited for.

Structured Synchronization

- Identify objects or data structures that can be accessed by multiple threads concurrently
 - In OS/161 kernel, everything!
- Add locks to object/module
 - Grab lock on start to every method/procedure
 - Release lock on finish
- If need to wait
 - `while(needToWait()) { condition.Wait(lock); }`
 - Do not assume when you wake up, signaller just ran
- If do something that might wake someone up
 - Signal or Broadcast
- Always leave shared state variables in a consistent state
 - When lock is released, or when waiting

Remember the rules

- Use consistent structure
- Always use locks and condition variables
- Always acquire lock at beginning of procedure, release at end
- Always hold lock when using a condition variable
- Always wait in while loop
- Never spin in sleep()

Mesa vs. Hoare semantics

- Mesa
 - Signal puts waiter on ready list
 - Signaller keeps lock and processor
- Hoare
 - Signal gives processor and lock to waiter
 - When waiter finishes, processor/lock given back to signaller
 - Nested signals possible!

FIFO Bounded Buffer (Hoare semantics)

```
get() {  
    lock.acquire();  
    if (front == tail) {  
        empty.wait(lock);  
    }  
    item = buf[front % MAX];  
    front++;  
    full.signal(lock);  
    lock.release();  
    return item;  
}
```

```
put(item) {  
    lock.acquire();  
    if ((tail - front) == MAX) {  
        full.wait(lock);  
    }  
    buf[last % MAX] = item;  
    last++;  
    empty.signal(lock);  
    // CAREFUL: someone else ran  
    lock.release();  
}
```

Initially: front = tail = 0; MAX is buffer capacity
empty/full are condition variables

FIFO Bounded Buffer (Mesa semantics)

- Create a condition variable for every waiter
 - Queue condition variables (in FIFO order)
 - Signal picks the front of the queue to wake up
 - CAREFUL if spurious wakeups!
-
- Easily extends to case where queue is LIFO, priority, priority donation, ...
 - With Hoare semantics, not as easy

FIFO Bounded Buffer

(Mesa semantics, put() is similar)

```
get() {  
    lock.acquire();  
    myPosition = numGets++;  
    self = new Condition;  
    nextGet.append(self);  
    while (front < myPosition  
           || front == tail) {  
        self.wait(lock);  
    }  
    delete self;  
    item = buf[front % MAX];  
    front++;  
    if (next = nextPut.remove()) {  
        next->signal(lock);  
    }  
    lock.release();  
    return item;  
}
```

Initially: front = tail = numGets = 0; MAX is buffer capacity
nextGet, nextPut are queues of Condition Variables

Implementing Synchronization

Concurrent Applications

Semaphores

Locks

Condition Variables

Interrupt Disable

Atomic Read/Modify/Write Instructions

Multiple Processors

Hardware Interrupts

Implementing Synchronization

Take 1: using memory load/store

- See too much milk solution/Peterson's algorithm

Take 2:

Lock::acquire()

{ disable interrupts }

Lock::release()

{ enable interrupts }

Lock Implementation, Uniprocessor

```
Lock::acquire() {  
    disableInterrupts();  
    if (value == BUSY) {  
        waiting.add(myTCB);  
        myTCB->state = WAITING;  
        next = readyList.remove();  
        switch(myTCB, next);  
        myTCB->state = RUNNING;  
    } else {  
        value = BUSY;  
    }  
    enableInterrupts();  
}
```

```
Lock::release() {  
    disableInterrupts();  
    if (!waiting.Empty()) {  
        next = waiting.remove();  
        next->state = READY;  
        readyList.add(next);  
    } else {  
        value = FREE;  
    }  
    enableInterrupts();  
}
```

Multiprocessor

- Read-modify-write instructions
 - Atomically read a value from memory, operate on it, and then write it back to memory
 - Intervening instructions prevented in hardware
- Examples
 - Test and set
 - Intel: xchgb, lock prefix
 - Compare and swap
- Any of these can be used for implementing locks and condition variables!

Spinlocks

A spinlock is a lock where the processor waits in a loop for the lock to become free

- Assumes lock will be held for a short time
- Used to protect the CPU scheduler and to implement locks

```
Spinlock::acquire() {  
    while (testAndSet(&lockValue) == BUSY)  
        ;  
}  
  
Spinlock::release() {  
    lockValue = FREE;  
    memorybarrier();  
}
```

How many spinlocks?

- Various data structures
 - Queue of waiting threads on lock X
 - Queue of waiting threads on lock Y
 - List of threads ready to run
- One spinlock per kernel?
 - Bottleneck!
- Instead:
 - One spinlock per lock
 - One spinlock for the scheduler ready list
 - Per-core ready list: one spinlock per core

What thread is currently running?

- Thread scheduler needs to find the TCB of the currently running thread
 - To suspend and switch to a new thread
 - To check if the current thread holds a lock before acquiring or releasing it
- On a uniprocessor, easy: just use a global
- On a multiprocessor, various methods:
 - Compiler dedicates a register (e.g., r31 points to TCB running on the this CPU; each CPU has its own r31)
 - If hardware has a special per-processor register, use it
 - Fixed-size stacks: put a pointer to the TCB at the bottom of its stack
 - Find it by masking the current stack pointer

Lock Implementation, Multiprocessor

```
Lock::acquire() {  
    disableInterrupts();  
    spinLock.acquire();  
    if (value == BUSY) {  
        waiting.add(myTCB);  
        suspend(&spinlock);  
    } else {  
        value = BUSY;  
    }  
    spinLock.release();  
    enableInterrupts();  
}
```

```
Lock::release() {  
    disableInterrupts();  
    spinLock.acquire();  
    if (!waiting.Empty()) {  
        next = waiting.remove();  
        scheduler->makeReady(next);  
    } else {  
        value = FREE;  
    }  
    spinLock.release();  
    enableInterrupts();  
}
```

Compare Implementations

```
Semaphore::P() {  
    disableInterrupts();  
    spinLock.acquire();  
    if (value == 0) {  
        waiting.add(myTCB);  
        suspend(&spinlock);  
    } else {  
        value--;  
    }  
    spinLock.release();  
    enableInterrupts();  
}
```

```
Semaphore::V() {  
    disableInterrupts();  
    spinLock.acquire();  
    if (!waiting.Empty()) {  
        next = waiting.remove();  
        scheduler->makeReady(next);  
    } else {  
        value++;  
    }  
    spinLock.release();  
    enableInterrupts();  
}
```

Lock Implementation, Multiprocessor

```
Sched::suspend(SpinLock *lock) {  
    TCB *next;  
  
    disableInterrupts();  
    schedSpinLock.acquire();  
    lock->release();  
    myTCB->state = WAITING;  
    next = readyList.remove();  
    thread_switch(myTCB, next);  
    myTCB->state = RUNNING;  
    schedSpinLock.release();  
    enableInterrupts();  
}  
  
Sched::makeReady(TCB *thread) {  
  
    disableInterrupts ();  
    schedSpinLock.acquire();  
    readyList.add(thread);  
    thread->state = READY;  
    schedSpinLock.release();  
    enableInterrupts();  
}
```

Lock Implementation, Linux

- Most locks are free most of the time
 - Why?
 - Linux implementation takes advantage of this fact
- Fast path
 - If lock is FREE, and no one is waiting, two instructions to acquire the lock
 - If no one is waiting, two instructions to release the lock
- Slow path
 - If lock is BUSY or someone is waiting, use multiproc impl.
- User-level locks
 - Fast path: acquire lock using test&set
 - Slow path: system call to kernel, use kernel lock

Lock Implementation, Linux

```
struct mutex {                                // atomic decrement
    /* 1: unlocked ; 0: locked;              // %eax is pointer to count
       negative : locked,
       possible waiters */
    atomic_t count;
    spinlock_t wait_lock;
    struct list_head wait_list;
};

// lock decl (%eax)
jns 1f // jump if not signed
// (if value is now 0)
call slowpath_acquire
1:
```

Semaphores

- Semaphore has a non-negative integer value
 - P() atomically waits for value to become > 0 , then decrements
 - V() atomically increments value (waking up waiter if needed)
- Semaphores are like integers except:
 - Only operations are P and V
 - Operations are atomic
 - If value is 1, two P's will result in value 0 and one waiter
- Semaphores are useful for
 - Unlocked wait: interrupt handler, fork/join

Semaphore Bounded Buffer

```
get() {  
    fullSlots.P();  
    mutex.P();  
    item = buf[front % MAX];  
    front++;  
    mutex.V();  
    emptySlots.V();  
    return item;  
}
```

```
put(item) {  
    emptySlots.P();  
    mutex.P();  
    buf[last % MAX] = item;  
    last++;  
    mutex.V();  
    fullSlots.V();  
}
```

Initially: front = last = 0; MAX is buffer capacity
mutex = 1; emptySlots = MAX; fullSlots = 0;

Implementing Condition Variables using Semaphores (Take 1)

```
wait(lock) {  
    lock.release();  
    semaphore.P();  
    lock.acquire();  
}  
  
signal() {  
    semaphore.V();  
}
```


Implementing Condition Variables using Semaphores (Take 2)

```
wait(lock) {  
    lock.release();  
    semaphore.P();  
    lock.acquire();  
}  
signal() {  
    if (semaphore is not empty)  
        semaphore.V();  
}
```

Implementing Condition Variables using Semaphores (Take 3)

```
wait(lock) {  
    semaphore = new Semaphore;  
    queue.Append(semaphore); // queue of waiting threads  
    lock.release();  
    semaphore.P();  
    lock.acquire();  
}  
signal() {  
    if (!queue.Empty()) {  
        semaphore = queue.Remove();  
        semaphore.V();    // wake up waiter  
    }  
}
```

Communicating Sequential Processes (CSP/Google Go)

- A thread per shared object
 - Only thread allowed to touch object's data
 - To call a method on the object, send thread a message with method name, arguments
 - Thread waits in a loop, get msg, do operation
- No memory races!

Example: Bounded Buffer

```
get() {  
    lock.acquire();  
    while (front == tail) {  
        empty.wait(lock);  
    }  
    item = buf[front % MAX];  
    front++;  
    full.signal(lock);  
    lock.release();  
    return item;  
}
```

```
put(item) {  
    lock.acquire();  
    while ((tail - front) == MAX) {  
        full.wait(lock);  
    }  
    buf[tail % MAX] = item;  
    tail++;  
    empty.signal(lock);  
    lock.release();  
}
```

Initially: front = tail = 0; MAX is buffer capacity
empty/full are condition variables

Bounded Buffer (CSP)

```
while (cmd = getNext()) {  
    if (cmd == GET) {  
        if (front < tail) {  
            // do get  
            // send reply  
            // if pending put, do it  
            // and send reply  
        } else  
            // queue get operation  
    }  
  
    } else { // cmd == PUT  
        if ((tail - front) < MAX) {  
            // do put  
            // send reply  
            // if pending get, do it  
            // and send reply  
        } else  
            // queue put operation  
    }  
}
```

Locks/CVs vs. CSP

- Create a lock on shared data
 - = create a single thread to operate on data
- Call a method on a shared object
 - = send a message/wait for reply
- Wait for a condition
 - = queue an operation that can't be completed just yet
- Signal a condition
 - = perform a queued operation, now enabled

Remember the rules

- Use consistent structure
- Always use locks and condition variables
- Always acquire lock at beginning of procedure, release at end
- Always hold lock when using a condition variable
- Always wait in while loop
- Never spin in sleep()