





## NOTES:

- 1.ELECTRICALTEST: 100%OPEN, SHORT&MIS WIRE TEST.
- 2.CONTACT RESISTANCE: 0.5ohm,
- 3. INSULATOR RESISTANCE: 5M ohm.
- 4.HIGH VOLTAGE:DC 300V 0.01sec.
- 5.MUST BE ROHS COMPLIANT.

(10)	I.180150.0301R	PE BAG	180*150*0.04MM PE BAG	1	PCS
0	F.0501B0.0100R	TUBE	Ø5.5*20mm HEAT TUBE COLOR BLACK	1	PCS
8	I.000001.0400R	TIE	TIE BLACK L=70MM	1	PCS
$\overline{7}$	E.00254M.0600R	HOUSING	Dupont 2.54mm 1*6P HOUSING	1	PCS
6	D.00254F.1400R	TERMINAI	Dupont 2.54mm TERMINAL	6	PCS
$\bigcirc$	C.045P01.0100R	MOLDING	PVC 45P BLACK	5.5	G
(4)	C.000000.0000R	MOLDING	PE	2.5	G
(3)	J.000008.0500R	TIN WIRI		3.5	G
2	B.01004M.0N05R	CONNECTO	TTL-RS232-PCB(3.3V) TYPE C/M CONNECTOR   PLASTIC:BLACK	1	PCS
1	A.009X01.0603R	CABLE	UL2464 26AWG(7/0.16TC)*6C(RED,ORANGE,GREEN BLACK,YELLOW,BROWN)+AL FOIL PVC JACKET COLOR:BLACK OD=5.0±0.1mm L=980MM	1	PCS
NO.	PART NO	ITEM	DESCRIPTION		UNIT

	PIN WIRING	
21		P2
1.	RED(3.3V)	3(VCC)
2.	ODANCE	4(TXD)
_	VELI OW	` ,
3 · 1	CDEEN	5(RXD) 6(RTS#)
4 · 5 ·	DI ACV	1(GND)
) : 6 :	BROWN	2(CTS#)
1 1		- ( )

	RoHS COMPLIANT			朋联电子有限公司 DongGuan PengLian Electronics Co.,Ltd TEL:076938835098/38835095 FAX:076938835091			
			比例: FREE	例: FREE TITLE: 3.3V TYPE C CABLE TO 6P HOUSING			
	DRAWN BY		單位: mm	SUPPLIER'S ITEM: 9.00ACCA2234.000R			
	CHECKED BY			CUSTOMER: SPARK FUN			
	A DEDOLUTE DAY		$\oplus \Box$	CUSTOMER'S ITEM:			
1	APPROVED BY		T -	DRAWING NO. ACCA-2234 DATE 2018-07-12			