Computer Science and Engineering Department, SVNIT, Surat
M.Tech. I – Semester I
Design and Analysis of Algorithm (CSDS103)
Lab Assignment: Comprehensive Algorithmic Analysis
Lab Assignment 7: String Matching Algorithms

1 Introduction and Objectives

The string matching problem consists of finding all occurrences of a given pattern string P of length m within a text string T of length n ($m \leq n$). Both strings are constructed from an alphabet Σ. A pattern P is said to occur with shift s ($0 \leq s \leq n - m$) if:

$$T[s + j] = P[j] \quad \text{for all } 0 \leq j \leq m - 1 \tag{1}$$

This laboratory report implements, analyzes, and empirically benchmarks three classical string matching paradigms:

1. **Naive String Matching**: Direct sliding window without preprocessing.
2. **Knuth–Morris–Pratt (KMP)**: Preprocessing of P using the Longest Proper Prefix which is also Suffix (LPS) array to prevent redundant character backtracking.
3. **Rabin–Karp**: Rolling hash matching with character verification upon hash equivalence.

All implementations are coded from scratch in standard Python without relying on built-in substring search primitives (such as `in` or `str.find()`).

2 Problem 1: Naive String Matching Algorithm

2.1 Theoretical Formulation and Complexity

The Naive algorithm examines every possible shift $s \in [0, n - m]$ sequentially. For each shift, it performs character-by-character comparisons between $T[s \ldots s + m - 1]$ and $P[0 \ldots m - 1]$. As soon as a mismatch is detected, the search for the current shift terminates, and the pattern shifts rightward by 1 position ($s \leftarrow s + 1$).

- **Best-Case Time Complexity**: $O(n)$. Occurs when the very first character $P[0]$ fails to match $T[s]$ across all shifts, resulting in exactly 1 comparison per shift: $(n - m + 1) \times 1 = O(n)$.
- **Worst-Case Time Complexity**: $O((n - m + 1) \cdot m)$. Occurs when all characters match up to the $(m - 1)$-th position and mismatch at the last character (or when every position matches completely), forcing m comparisons for each of the $n - m + 1$ shifts.
- **Auxiliary Space Complexity**: $O(1)$. Only loop indices and comparison counters are maintained.

2.2 Python Implementation

Listing 1: Naive String Matching Implementation

```python
def naive_string_match(text, pattern):
    """
    Performs Naive String Matching without built-in functions.
    Returns:
        occurrences (list): 0-indexed starting positions of matches.
        comparisons (int): Total character comparisons performed.
    """
    n = len(text)
    m = len(pattern)
    occurrences = []
    comparisons = 0

    if m == 0 or m > n:
        return occurrences, comparisons

    for i in range(n - m + 1):
        match = True
        for j in range(m):
            comparisons += 1
            if text[i + j] != pattern[j]:
                match = False
                break
        if match:
            occurrences.append(i)

    return occurrences, comparisons
```

2.3 Execution and Verification

The algorithm was tested on the assignment test case:

$$T = \text{"AABAACAADAABAABA"}, \quad P = \text{"AABA"}$$

Listing 2: Problem 1 Execution Output on Sample Input

```
--- Problem 1: Basic Test ---
Text    : AABAACAADAABAABA
Pattern : AABA
Pattern found at indices: [0, 9, 12]
Total Character Comparisons: 30
```

2.4 Worst-Case Analysis Demonstration

To demonstrate the worst-case behavior, we construct an adversarial input where T is a string of 20 identical characters and P has 4 matching characters followed by a mismatching character:

$$T = \text{"AAAAAAAAAAAAAAAAAAAA"} \quad (n = 20), \qquad P = \text{"AAAAB"} \quad (m = 5)$$

Listing 3: Worst-Case Input Experiment

```
text_worst = "A" * 20
pattern_worst = "A" * 4 + "B"  # Length m = 5
n_w, m_w = len(text_worst), len(pattern_worst)

pos_worst, comp_worst = naive_string_match(text_worst, pattern_worst)
theoretical_worst = (n_w - m_w + 1) * m_w

print("--- Problem 1: Worst-Case Analysis ---")
print(f"Text    : {text_worst} (n = {n_w})")
print(f"Pattern : {pattern_worst} (m = {m_w})")
print(f"Occurrences found          : {pos_worst}")
print(f"Actual Comparisons Done    : {comp_worst}")
print(f"Theoretical Max (n-m+1)*m  : {theoretical_worst}")
print(f"Does actual reach max?     : {comp_worst == theoretical_worst}")
```

Listing 4: Problem 1 Worst-Case Execution Output

```
--- Problem 1: Worst-Case Analysis ---
Text    : AAAAAAAAAAAAAAAAAAAA (n = 20)
Pattern : AAAAB (m = 5)
Occurrences found          : []
Actual Comparisons Done    : 80
Theoretical Max (n-m+1)*m  : 80
Does actual reach max?     : True
```

Explanation of Repeated Comparisons: In the experiment above, for each shift $i \in [0, 15]$, the algorithm compares the first 4 characters successfully ($T[i+j] == P[j] =$ 'A' for $j \in \{0, 1, 2, 3\}$). The mismatch occurs on the 5th character ($T[i+4] =$ 'A' $\neq$ 'B' $= P[4]$). Because the Naive algorithm has **no memory of prior character matches**, it discards all 4 matched characters and shifts right by only 1 position ($i \leftarrow i + 1$). At the new shift, it re-compares the same text characters from scratch. This causes redundant repeated comparisons, confirming the $(20 - 5 + 1) \times 5 = 80$ operations.

3 Problem 2: Knuth–Morris–Pratt (KMP) String Matching

3.1 Theoretical Formulation and Complexity

The KMP algorithm eliminates redundant comparisons by preprocessing the pattern P into an array called **LPS** (Longest Proper Prefix which is also Suffix). For a pattern $P[0 \ldots m-1]$, $\text{LPS}[i]$ represents the length of the longest proper prefix of $P[0 \ldots i]$ that is also a suffix of $P[0 \ldots i]$.

When a mismatch occurs at $P[j]$ after matching j characters with $T[i]$:

1. We know that $P[0 \ldots j-1]$ matched $T[i-j \ldots i-1]$.
2. If $j > 0$, the next character to compare against $T[i]$ is $P[\text{LPS}[j-1]]$, thereby advancing the pattern without moving the text pointer i backwards.
3. If $j = 0$, no prefix matched, so the text pointer simply increments ($i \leftarrow i + 1$).

- **Preprocessing Time**: $O(m)$ to construct the LPS array.

- **Matching Phase Time**: $O(n)$ because each character of T is advanced forwards, and the pattern index j drops at most n times via LPS.
- **Total Time Complexity**: $O(n+m)$.
- **Auxiliary Space Complexity**: $O(m)$ to store the LPS array.

3.2 Python Implementation

Listing 5: LPS Array Computation and KMP Search

```python
def compute_lps(pattern):
    """
    Constructs the LPS (Longest Proper Prefix which is Suffix) array
    without using any built-in pattern matching functions.
    """
    m = len(pattern)
    lps = [0] * m
    length = 0  # Length of previous longest prefix-suffix
    i = 1

    while i < m:
        if pattern[i] == pattern[length]:
            length += 1
            lps[i] = length
            i += 1
        else:
            if length != 0:
                length = lps[length - 1]
            else:
                lps[i] = 0
                i += 1
    return lps

def kmp_search(text, pattern):
    """
    Performs Knuth-Morris-Pratt (KMP) search.
    Returns:
        occurrences (list): Starting indices of pattern matches.
        comparisons (int): Total character comparisons performed.
    """
    n = len(text)
    m = len(pattern)
    occurrences = []
    comparisons = 0

    if m == 0 or m > n:
        return occurrences, comparisons

    lps = compute_lps(pattern)
    i = 0  # Text index
    j = 0  # Pattern index

    while i < n:
        comparisons += 1
        if text[i] == pattern[j]:
            i += 1
```

```
            j += 1

        if j == m:
            occurrences.append(i - j)
            j = lps[j - 1]
        elif i < n and text[i] != pattern[j]:
            if j != 0:
                j = lps[j - 1]
            else:
                i += 1

    return occurrences, comparisons
```

3.3 Execution and Verification

3.3.1 LPS Array for Sample Pattern "ABABCABAB"

As specified in the assignment, we construct and verify the LPS array for pattern P = ”ABABCABAB”:

Listing 6: LPS Array Output

```
--- Problem 2: LPS Array Construction ---
Pattern: ABABCABAB
Indices: [0, 1, 2, 3, 4, 5, 6, 7, 8]
Chars  : ['A', 'B', 'A', 'B', 'C', 'A', 'B', 'A', 'B']
LPS    : [0, 0, 1, 2, 0, 1, 2, 3, 4]
```

LPS Breakdown:

- $i = 0$ ('A'): No proper prefix $\implies$ LPS[0] = 0.
- $i = 1$ ("AB"): Prefixes: {"A"}, Suffixes: {"B"} $\implies$ LPS[1] = 0.
- $i = 2$ ("ABA"): Proper prefix "A" matches suffix "A" $\implies$ LPS[2] = 1.
- $i = 3$ ("ABAB"): Proper prefix "AB" matches suffix "AB" $\implies$ LPS[3] = 2.
- $i = 4$ ("ABABC"): Character 'C' breaks suffix matching $\implies$ LPS[4] = 0.
- $i = 5 \ldots 8$: Suffixes matching prefixes build back up: "A" (1), "AB" (2), "ABA" (3), "ABAB" (4).

3.3.2 Search Execution and Comparison with Naive

Listing 7: KMP vs Naive Comparison on Standard and Repetitive Inputs

```
--- Problem 2: KMP Search Test ---
Text    : AABAACAADAABAABA
Pattern : AABA
KMP Occurrences: [0, 9, 12]
KMP Comparisons: 18
Naive Comparisons on same input: 30
```

```
--- Comparison on Repetitive Input ---
Naive Comparisons : 80
KMP Comparisons   : 20
Comparison reduction: 60 fewer comparisons with KMP!
```

On the repetitive worst-case input (T = "A"^{20}, P = "AAAAB"), KMP required only **20 comparisons** compared to **80 comparisons** in Naive—a massive **75% reduction** achieved purely through prefix information without any backtracking in the text.

4 Problem 3: Rabin–Karp String Matching Algorithm

4.1 Theoretical Formulation and Complexity

The Rabin–Karp algorithm utilizes a **rolling hash** technique. Instead of inspecting each character at every shift, it converts strings into numerical hash values. If the hash value of a length-m window $T[s \ldots s+m-1]$ matches the hash of P, a character-by-character verification is executed.

4.1.1 Hash Formulation and $O(1)$ Rolling Update

Let d be the radix (e.g., $d = 256$ for ASCII) and q be a prime modulus. The pattern hash p and initial text window hash t_0 are defined as:

$$p = \sum_{j=0}^{m-1} P[j] \cdot d^{m-1-j} \pmod{q}, \qquad t_0 = \sum_{j=0}^{m-1} T[j] \cdot d^{m-1-j} \pmod{q} \tag{2}$$

The hash value of the next window t_{s+1} is computed in $O(1)$ time from t_s using the rolling formula:

$$t_{s+1} = (d \cdot (t_s - T[s] \cdot h) + T[s+m]) \pmod{q} \tag{3}$$

where $h = d^{m-1} \pmod{q}$. If $t_{s+1} < 0$, we add q to keep it in the non-negative residue range $[0, q-1]$.

- **Average-Case Time Complexity**: $O(n+m)$. When the prime q is large, spurious hash matches are rare.
- **Worst-Case Time Complexity**: $O((n-m+1) \cdot m)$. Occurs if q is very small or if many distinct substrings collide to the same hash value, forcing verification at nearly every shift.
- **Auxiliary Space Complexity**: $O(1)$.

4.2 Python Implementation

Listing 8: Rabin-Karp Search with Verification Tracking

```
1 def rabin_karp_search(text, pattern, d=256, q=101):
2     """
3     Performs Rabin-Karp String Matching using rolling hash.
```

```
    Returns:
        occurrences (list): Match indices.
        hash_matches (int): Number of hash equality events.
        verifications (int): Number of character comparisons during verification.
    """
    n = len(text)
    m = len(pattern)
    occurrences = []
    hash_matches = 0
    verifications = 0

    if m == 0 or m > n:
        return occurrences, hash_matches, verifications

    # h = (d ** (m - 1)) % q
    h = 1
    for _ in range(m - 1):
        h = (h * d) % q

    p = 0
    t = 0

    for i in range(m):
        p = (d * p + ord(pattern[i])) % q
        t = (d * t + ord(text[i])) % q

    for s in range(n - m + 1):
        if p == t:
            hash_matches += 1
            match = True
            for j in range(m):
                verifications += 1
                if text[s + j] != pattern[j]:
                    match = False
                    break
            if match:
                occurrences.append(s)

        if s < n - m:
            t = (d * (t - ord(text[s]) * h) + ord(text[s + m])) % q
            if t < 0:
                t += q

    return occurrences, hash_matches, verifications
```

4.3 Execution and Verification

Listing 9: Rabin-Karp Search Output

```
--- Problem 3: Rabin-Karp Search Test ---
Text             : AABAACAADAABAABA
Pattern          : AABA
Matches Found    : [0, 9, 12]
Hash Matches     : 3
Char Verifications: 12
```

All 3 true occurrences were detected. With $q = 101$, exactly 3 hash matches occurred, each verified by 4 character checks ($3 \times 4 = 12$ verifications), meaning zero spurious hash hits occurred on this input.

4.4 Hash Collision Analysis

As mandated by the laboratory instructions, we demonstrate an explicit input producing a **spurious hit (hash collision)**. Using $d = 256$ and $q = 101$:

- String 1: `"AAB"` $\implies$ Hash = 4
- String 2: `"BEA"` $\implies$ Hash = 4

Listing 10: Hash Collision Demonstration

```
--- Hash Collision Demonstration ---
String 1: 'AAB' -> Hash: 4
String 2: 'BEA' -> Hash: 4
Hashes equal? : True
Strings equal?: False

Search pattern 'AAB' in text 'XYZBEAXYZ':
Pattern occurrences found: []
Hash matches triggered   : 1 (spurious hit due to collision!)
Verifications performed  : 1 (verification detected mismatch)
```

4.4.1 Theoretical Discussion of Hash Parameters

1. **Why a hash match does not imply pattern occurrence**: A hash function maps an infinite domain of strings Σ^m to a finite codomain $\mathbb{Z}_q = \{0, 1, \ldots, q-1\}$. By the **Pigeonhole Principle**, multiple distinct strings inevitably map to the identical residue modulo q. Therefore, a hash match is merely a *candidate condition*, necessitating full character verification.

2. **Effect of Modulus** q: The theoretical probability of a spurious hit between two random strings is approximately $1/q$. Selecting a large prime (e.g., $q \approx 10^9 + 7$) reduces the spurious collision rate to near zero, yielding consistent $O(n + m)$ average performance.

3. **Effect of Radix** d: The radix d should be at least equal to the alphabet size $|\Sigma|$ to prevent structural modular bias and ensure uniform dispersion across the hash space.

5 Problem 4: Experimental Comparison and Visualizations

5.1 Experimental Methodology

Controlled empirical benchmarks were run on synthetic datasets generated over varying input sizes and pattern lengths. Precise execution runtimes were measured using Python's `time.perf`$_{counter}()$, $and character comparisons were logged directly from the instrumented algorithms$

5.2 Graph 1: Input Size vs Execution Time

With a fixed pattern length ($m = 10$), the text size n was varied from $2,000$ to $30,000$ characters.




Figure 1: Input Text Size (n) vs Execution Time ($m = 10$).

Analysis: As seen in Figure 1, all three algorithms exhibit linear scaling with respect to input text length n on random alphabets. KMP and Naive execute faster due to lighter per-character loop overhead compared to modular arithmetic in Python-level Rabin--Karp.

5.3 Graph 2: Pattern Length vs Execution Time

With a fixed text size ($n = 20,000$), the pattern length m was varied from 5 to 150 characters.




Figure 2: Pattern Length (m) vs Execution Time ($n = 20,000$).

Analysis: Figure 2 illustrates that pattern length variation has negligible impact on KMP and Rabin–Karp search times because the search phase iterates through the text in $O(n)$ steps. Preprocessing costs $O(m)$ remain negligible for $m \ll n$.

5.4 Graph 3: Input Size vs Number of Comparisons

To clearly observe the theoretical advantage of KMP over Naive, text and pattern strings were generated over a binary alphabet $\Sigma = \{'A', 'B'\}$ with repeated prefixes ($P =$ "ABABABABAB"), with text size n varying from $1,000$ to $10,000$.




Figure 3: Input Size (n) vs Number of Character Comparisons (Repetitive Alphabet).

Analysis: Figure 3 demonstrates that on repetitive inputs with frequent partial matches, Naive requires significantly more comparisons due to shifting back to start each window. In contrast, KMP's LPS array prevents re-comparing matched prefixes, keeping comparisons strictly proportional to n.

6 Summary and Conclusion

Table 1: Comprehensive Algorithmic Comparison

Algorithm	Preprocessing	Matching Time	Space	Backtracking	Best Suit
Naive	None (0)	$O((n-m+1)m)$	$O(1)$	Yes	Small texts, lar
KMP	$O(m)$ (LPS)	$O(n)$	$O(m)$	No	Repetitive te
Rabin–Karp	$O(m)$ (Hash)	Avg: $O(n+m)$, Worst: $O(nm)$	$O(1)$	No	Multi-pattern sea

Final Remarks:

1. **Naive Matching** is simple to implement but performs poorly on repetitive data due to repeated character comparisons.
2. **KMP Algorithm** achieves optimal deterministic $O(n+m)$ runtime by using the LPS array to eliminate backtracking.
3. **Rabin--Karp Algorithm** introduces rolling hashes, offering excellent average-cas performance and a natural extension to 2D and multi-pattern matching problems.