A Survey of Self-Evolving Agents


What, When, How, and Where to Evolve on the Path to Artificial Super Intelligence

Huan-ang Gao[γ†], Jiayi Geng[α†], Wenyue Hua[ϵ†], Mengkang Hu[ω†], Xinzhe Juan[σμ†], Hongzhang Liu[ξ†], Shilong Liu[α†], Jiahao Qiu[αδ†], Xuan Qi[γ†], Qihan Ren[σ†], Yiran Wu[ρ†], Hongru Wang[k†✉], Han Xiao[τ†], Yuhang Zhou[λ†], Shaokun Zhang[ρ†], Jiayi Zhang[π], Jinyu Xiang, Yixiong Fang[θ], Qiwen Zhao[ζ], Dongrui Liu[σ], Cheng Qian[β], Zhenhailong Wang[β], Minda Hu[τ], Huazheng Wang[η], Qingyun Wu[ρ], Heng Ji[β], Mengdi Wang[αδ✉]

2026.10.22


张雨阳

近几年的发展轨迹



"It is not the most intellectual of the species that survives; it is not the strongest that survives; but the species that survives is the one that is able best to adapt and adjust to the changing environment in which it finds itself."

— Charles Darwin[1]


What to Evolve?
Context
Memory
Prompts
Store / Retrieve
Instruct
Agent
Plan, Reason
Call / Return
Models
Tools
Agentic Architecture
Single Agent
Query
Answer
Multi-Agent
Query
Answer
When to Evolve?
Task Completion
Intra-test-time Self-evolution
POST
Inter-test-time Self-evolution
Methods
ICL
SFT
RL
How to Evolve?
Reward-based
Textual
Internal
External
Implicit
Imitation & Demonstration
Self-Generated
Cross-Agent
Hybrid
Population-based
Single Agent
Multi-Agent
Cross-cutting Evolutionary Dimensions
Online/Offline
On/Off-policy
Granularity
Where to Evolve?
General Domain
General-purpose Applications
Specific Domain
Coding
GUI
Financial
Medical
Education
Others
Evaluation
Goals & Metrics
Adaptivity
Retention
Generalization
Efficiency
Safety
Paradigm
Static
Short-horizon
Long-horizon

一，定义与基础

环境（Environment）

将智能体系统的环境定义为部分可观测马尔可夫决策过程(POMDP)，记为元组

$$\mathrm{E} = (\mathrm{G}, \mathrm{S}, \mathrm{A}, \mathrm{T}, \mathrm{R}, \Omega, \mathrm{O}, \gamma)$$

其中：

G 是潜在目标的集合。

S 是状态集合。

A 是动作集合。

T 是状态转移概率函数。输入状态与动作对 (s, a)，输出下一状态的概率分布 T(s′ | s, a)。

R: S × A × G →ℝ 是以具体目标 g ∈ G 为条件的反馈 / 奖励函数。反馈 r = R(s, a, g) 通常表现为标量分数或文本反馈。

Ω 是智能体可获得的观测集合。

O 是观测概率函数。输入状态与动作对 (s, a)，输出智能体下一观测的概率分布 O(o′ | s, a)。

γ 是折扣因子。

智能体系统：

将一个（多）智能体系统定义为$\Pi = (\Gamma, \{\psi i\}, \{Ci\}, \{Wi\})$。架构Γ决定系统的控制流或多个智能体之间的协作结构，通常表示为由图或代码结构组织的一系列节点$(N_1, N_2, \ldots)$。每个节点：

ψ_i：底层 LLM

C_i上下文信息

W_i可用工具 / API 集合。

给定任务 (E, g)，即环境 E 及相应目标 g ∈ G，系统生成轨迹$\tau = (o_0, a_0, o_1, a_1, \ldots)$，并接收外部环境或内部信号提供的反馈 r

自演化策略:

$$f(\Pi, \tau, r) = \Pi' = (\Gamma', \{\psi i'\}, \{Ci'\}, \{Wi'\})$$

自演化智能体的目标

$$\max_f \sum_{j=0}^{n} U(\Pi_j, \mathcal{T}_j)$$

What to evolve?


对于一个智能体系统：

$$\Pi = (\Gamma, \{\psi i\}, \{Ci\}, \{Wi\})$$

ψ_i：底层 LLM

C_i上下文信息

W_i可用工具 / API 集合。



model(ψ_i：底层 LLM):

1 policy 策略

自演化智能体可以优化参数，提升目标任务表现。

SCA（Self-Challenging Agent）：


1. Agent 自己生成编程任务。
2. 尝试解决这些任务。
3. 收集成功的执行轨迹。
4. 利用这些轨迹微调模型参数。

2 Experience 经验

智能体不仅能通过调整内部参数演化，也能主动与环境交互甚至构建环境，获取经验并将其转化为推动迭代改进的学习信号。

Reflexion：

1. Agent 执行任务失败。
2. 对失败过程进行反思。
3. 将反思结果记录为自然语言经验。
4. 在后续尝试中利用这些经验改进决策。



context(C_i上下文信息)

1 记忆演化

基于 LLM 的智能体越来越多地采用长期记忆机制，随持续解决任务和环境交互而增长、调整。

记忆演化的关键在于从经验中学习启发式规则或技能。

2 提示优化

记忆演化关注保留哪些知识，提示优化（PO）则通过改进输入骨干模型的指令，让智能体在不修改权重的情况下直接改变模型行为。

智能体能自主改进提示策略，使提示文本成为随经验共同演化的可学习组件。

tool(W_i可用工具)

智能体的能力在根本上取决于其能够使用的工具。

1 自主发现与创建。

自主创建工具的首要动力是突破固定工具集的固有限制，获得按需创新的灵活性。

2 通过迭代改进掌握工具。

自创建工具越来越多，需要稳健的掌握机制：新生成的工具往往只是脆弱脚本，尚不是可靠函数。

3 可扩展的管理与选择。

当技能库达到数百或数千项，智能体面临“丰裕诅咒”：挑战从创建工具转向高效管理与选择。

Architecture

1 单智能体系统优化

1.1 LLM 调用节点优化

主要有两种策略。第一种固定工作流结构，只优化节点。第二种同时优化节点和工作流架构。

1.2 自主智能体优化

优化 Agent 的整体架构

修改 Agent 自身代码

2 多智能体系统优化

2.1 智能体工作流优化

优化多个 Agent 之间的连接结构、任务分工和执行顺序

2.2 多自主智能体优化


不仅优化 Agent 之间的连接关系，还让多个 Agent 通过交互学习，共同优化各自的行为策略

When to evolve?

自演化策略:

$$f(\Pi, \tau, r) = \Pi' = (\Gamma', \{\psi i'\}, \{Ci'\}, \{Wi'\})$$

在哪个阶段调用并应用策略 f?




单次测试内自演化

发生于任务执行期间：智能体识别在具体问题上的局限，启动针对性学习机制，实时增强能力

测试间自演化

发生在任务完成之间，利用累积经验改善未来表现。



How to evolve?

找到有效演化策略 f，即如何将系统

$$\Pi = (\Gamma, \{\psi i\}, \{Ci\}, \{Wi\})$$

转化为新状态

$$\Pi' = (\Gamma', \{\psi' i\}, \{C' i\}, \{W' i\})$$

基于奖励的自进化

文本反馈

隐式奖励

内部奖励

外部奖励

Textual Feedback

Natural language: *My plan was to ... However, the task says to... I should have …*

Implicit Reward

In-context RL using simple scalar signals



Internal Reward

Model's own probability estimates or certainty

External Reward

Environment, majority voting, or explicit rules

模仿与示范学习

1 自生成示范学习

自生成示范学习让智能体通过迭代改进创建自己的训练数据：从自身输出中生成并选择高质量样例，进而学习提升。

2 跨智能体示范学习

3 混合体示范学习

遇到问题：

示范质量问题：错误或低质量示范可能使模型性能下降。

示范多样性不足：只模仿有限的成功轨迹，可能导致泛化能力不足。

基于种群和演化的方法


操作	英文	含义
选择	Selection	保留表现较好的 Agent 版本
变异	Mutation	随机或有针对性地修改 Agent
交叉	Crossover	组合不同 Agent 版本中的部分特征

单智能体演化

搜索同一智能体的不同版本
可改变提示、模块或自身代码
自博弈

多智能体演化

多个智能体共同适应
可改变角色、通信和协作策略
多个 Agent 通过积累和共享知识实现团队能力提升


Agent Evolution
Learning Paradigm
Offline Learning
Data Generation
Filtering
Model Fine-tuning
Online Learning
Agent
Environment
Policy Consistency
On-policy Evolution
πθ
Env
Traj
Off-policy Evolution
πθ
Human Demos
Other agents
Replay Buffer
Reward Granularity
Process-based Reward
Hybrid Reward
Outcome-based Reward
Step 1
Step 2
Step 3
...
Outcome

Elon Musk ✓ 𝕏
@elonmusk

Subscribe

Let's see if @Grok 5 can beat the best human team @LeagueOfLegends in 2026 with these important constraints:

1. Can only look at the monitor with a camera, seeing no more than what a person with 20/20 vision would see.

2. Reaction latency and click rate no faster than human.

Join @xAI if you are interested in solving this element of AGI.

Note, Grok 5 is designed to be able to play any game just by reading the instructions and experimenting.

2:41 PM · Nov 25, 2025 · **22.8M** Views

4.9K 6.4K 75K 6.8K


T1 LoL ✓ @T1LoL · Nov 25, 2025

We are ready 👍 R U?



309 2.1K 14K 3.4M

How to evolve?



Reflexion: Language Agents with Verbal Reinforcement Learning

Noah Shinn
Northeastern University
noahshinn024@gmail.com

Federico Cassano
Northeastern University
cassano.f@northeastern.edu

Edward Berman
Northeastern University
berman.ed@northeastern.edu


Ashwin Gopinath
Massachusetts Institute of Technology
agopi@mit.edu

Karthik Narasimhan
Princeton University
karthikn@princeton.edu

Shunyu Yao
Princeton University
shunyuy@princeton.edu

NeurIPS 2023

失败是成功之母





Algorithm 1 Reinforcement via self-reflection

Initialize Actor, Evaluator, Self-Reflection: M_a, M_e, M_{sr}
Initialize policy $\pi_\theta(a_i|s_i)$, $\theta = \{M_a, mem\}$
Generate initial trajectory using π_θ
Evaluate τ_0 using M_e
Generate initial self-reflection sr_0 using M_{sr}
Set $mem \leftarrow [sr_0]$
Set $t = 0$
while M_e not pass or $t <$ max trials **do**
    Generate $\tau_t = [a_0, o_0, \ldots a_i, o_i]$ using π_θ
    Evaluate τ_t using M_e
    Generate self-reflection sr_t using M_{sr}
    Append sr_t to mem
    Increment t
end while
return


Experiments

ALFWorld——Agent 能否从错误行动中学习?





HotPotQA——反思能不能提升推理能力？



Automatic Prompt Optimization with "Gradient Descent" and Beam Search

Reid Pryzant, Dan Iter, Jerry Li, Yin Tat Lee, Chenguang Zhu, Michael Zeng
Microsoft Azure AI
{reidpryzant,iterdan,jerrl,yintatlee,chezhu,nzeng}@microsoft.com

Microsoft

EMNLP 2023

人工优化 Prompt

有两个突出问题：

一是需要大量试错；

二是很难系统性地知道 Prompt 到底应该往哪个方向改进。

ProTeGi

Prompt Optimization with Textual Gradients





Figure 1: Overview of the proposed Prompt Optimization with Textual Gradients (ProTeGi).

Algorithm 1 Prompt Optimization with Textual Gradients (ProTeGi)

Require: p_0: initial prompt, zb: beam width, r: search depth, m: metric function

$B_0 \leftarrow \{p_0\}$
for $i \leftarrow 1$ to $r-1$ **do**
  $C \leftarrow \emptyset$
  for all $p \in B_i$ **do**
    $C \leftarrow C \cup Expand(p)$
  end for
  $B_{i+1} \leftarrow Select_b(C, m)$
end for
$\hat{p} \leftarrow argmax_{p \in B_r} m(s)$
return $\hat{p}$



Beam Search

Experiments




Figure 3: Test performance (F1) vs API query budget per prompt candidate.

TextGrad: Automatic "Differentiation" via Text

Mert Yuksekgonul[1*] MERTY@STANFORD.EDU
Federico Bianchi[1*] FEDE@STANFORD.EDU
Joseph Boen[2*] TBOEN@STANFORD.EDU
Sheng Liu[2*] SHENGL@STANFORD.EDU
Zhi Huang[2*] ZHIHUANG@STANFORD.EDU
Carlos Guestrin[1,3] GUESTRIN@STANFORD.EDU
James Zou[1,2,3] JAMESZ@STANFORD.EDU

[1] DEPARTMENT OF COMPUTER SCIENCE, STANFORD UNIVERSITY
[2] DEPARTMENT OF BIOMEDICAL DATA SCIENCE, STANFORD UNIVERSITY
[3] CHAN ZUCKERBERG BIOHUB
CORRESPONDENCE: MERTY@STANFORD.EDU AND JAMESZ@STANFORD.EDU

Nature 2025

计算图示例：

$$\text{Prediction} = \text{LLM}(\textbf{Prompt} + \text{Question}),$$

$$\text{Evaluation} = \text{LLM}(\text{Evaluation Instruction} + \text{Prediction}),$$

$$\textbf{Prompt} + \text{Question} \xrightarrow{\text{LLM}} \text{Evaluation Instruction} + \text{Prediction} \xrightarrow{\text{LLM}} \text{Evaluation},$$

梯度计算示例：

$$\frac{\partial \text{Evaluation}}{\partial \text{Prediction}} = \nabla_{\text{LLM}}(\text{Prediction}, \text{Evaluation}),$$

$$\frac{\partial \text{Evaluation}}{\partial \textbf{Prompt}} = \frac{\partial \text{Evaluation}}{\partial \text{Prediction}} \circ \frac{\partial \text{Prediction}}{\partial \textbf{Prompt}} = \nabla_{\text{LLM}}(\textbf{Prompt}, \text{Prediction}, \frac{\partial \text{Evaluation}}{\partial \text{Prediction}}),$$

通过 TGD 更新简单计算图中的 Prompt 变量：（优化器）

$$\mathbf{Prompt}_{\mathbf{new}} = \mathrm{TGD.step}(\mathbf{Prompt}, \frac{\partial \mathrm{Evaluation}}{\partial \mathbf{Prompt}}).$$

$$x_{\mathrm{new}} = \mathrm{TGD.step}(x, \frac{\partial \mathcal{L}}{\partial x}) \triangleq \mathrm{LLM}(\texttt{Below are the criticisms on \{x\}:} \quad (9)$$

$$\left\{\frac{\partial \mathcal{L}}{\partial x}\right\}$$

$$\texttt{Incorporate the criticisms, and produce a new variable.}).$$

一般情况：

$$v = f_v(\text{PredecessorsOf}(v)) \quad \forall v \in \mathcal{V}$$

v:某个变量节点

PredecessorsOf(v):生成v的所有上游变量

$$\frac{\partial \mathcal{L}}{\partial v} = \bigcup_{w \in \text{SuccessorsOf}(v)} \nabla_{\text{f}} \left(v, w, \frac{\partial \mathcal{L}}{\partial w} \right),$$

w：是来自v产生的下游变量

$$v_{\text{new}} = \text{TGD.step} \left(v, \frac{\partial \mathcal{L}}{\partial v} \right)$$

Experiments：

leetcode 代码题：

Table 1: Code optimization for LeetCode Hard using `gpt-4o`. Results are averaged over 5 seeds.

Task	Method	Completion Rate
LeetCode Hard [26]	Zero-shot [26]	0.26
	Reflexion (1 demonstration, 5 iterations) [26]	0.31 ± 0.012
	TEXTGRAD (0 demonstrations, 5 iterations)	**0.36** ± 0.018

解决复杂问题：

Table 2: Solution optimization for zero-shot question answering with `gpt-4o`.

Dataset	Method	Accuracy (%)
Google-proof QA [27]	CoT [46, 47]	51.0
	Best reported [48]	53.6
	TEXTGRAD	**55.0**
MMLU-Machine Learning [45]	CoT [46, 47]	85.7
	TEXTGRAD	**88.4**
MMLU-College Physics [45]	CoT [46, 47]	91.2
	TEXTGRAD	**95.1**

为什么能发nature?

	ProTeGi	TextGrad
核心思想	文本梯度驱动 Prompt 更新	文本反馈驱动计算图中的变量更新
主要算法抽象	Gradient、Prompt Editing、Beam Search、Bandit	Variable、Function、Backward、Optimizer
研究重点	Prompt 搜索效率和性能	通用性、组件组合和跨领域优化
贡献类型	具体优化算法	优化框架与应用扩展

REASONINGBANK: Scaling Agent Self-Evolving with Reasoning Memory

Siru Ouyang[1*], Jun Yan[2†], I-Hung Hsu[2], Yanfei Chen[2], Ke Jiang[2], Zifeng Wang[2], Rujun Han[2], Long T. Le[2], Samira Daruki[2], Xiangru Tang[3], Vishy Tirumalashetty[2], George Lee[2], Mahsan Rofouei[4], Hangfei Lin[4], Jiawei Han[1], Chen-Yu Lee[2†] and Tomas Pfister[2]

[1]University of Illinois Urbana-Champaign, [2]Google Cloud AI Research, [3]Yale University, [4]Google Cloud AI

ICLR 2026


研究背景：Agent 正在从单次任务走向长期工作

缺乏提炼更高层次、可迁移推理模式的能力。


由于过度强调成功经验，它们对智能体自身失败中所蕴含的宝贵教训探索不足

记忆方式	保存什么	作者认为的不足
Trajectory Memory（轨迹记忆）	历史观察、推理、操作步骤	细节冗长、噪声较多，跨任务迁移不够直接
Workflow Memory（工作流记忆）	成功完成任务的操作流程	容易依赖具体任务流程，对失败教训的利用有限
ReasoningBank（本文）	从成功和失败经历中提炼的推理策略	目标是提供更抽象、可执行、可迁移的指导

ReasoningBank



MaTTS(memory-aware test-time scaling)



Models	Shopping (187)		Admin (182)		Gitlab (180)		Reddit (106)		Multi (29)		Overall (684)	
	SR	*Step*	*SR*	*Step*	*SR*	*Step*	*SR*	*Step*	*SR*	*Step*	*SR*	*Step*
Gemini-2.5-flash												
No Memory	39.0	8.2	44.5	9.5	33.9	13.3	55.7	6.7	10.3	10.0	40.5	9.7
Synapse	40.6	7.0	45.1	9.1	35.6	13.0	59.4	6.5	10.3	10.5	42.1	9.2
AWM	44.4	7.0	46.7	8.8	37.2	13.2	62.3	6.1	3.4	**7.7**	44.1	9.0
REASONINGBANK	**49.7**	**6.1**	**51.1**	**8.2**	**40.6**	**12.3**	**67.0**	**5.6**	**13.8**	8.8	**48.8**	**8.3**
+MATTS	53.0	6.3	53.8	7.6	42.8	11.9	70.8	5.4	17.2	8.0	51.8	7.9
Gemini-2.5-pro												
No Memory	45.5	7.6	51.1	8.7	35.0	11.6	71.7	6.0	6.9	8.8	46.7	8.8
Synapse	46.5	6.6	52.2	8.9	38.3	11.3	68.9	5.9	6.9	9.0	47.7	8.5
AWM	48.1	6.4	49.3	9.8	40.0	11.2	68.9	6.4	3.4	9.3	47.6	8.7
REASONINGBANK	**51.9**	**6.0**	**56.6**	**7.7**	**44.4**	**9.8**	**80.2**	**5.1**	**13.8**	**8.2**	**53.9**	**7.4**
+MATTS	54.0	5.9	58.2	7.4	46.7	9.1	83.0	5.3	20.7	7.2	56.3	7.1
Claude-3.7-sonnet												
No Memory	38.5	6.1	49.5	8.4	36.7	10.6	53.8	5.5	0.0	11.6	41.7	8.0
Synapse	39.6	5.8	50.5	8.5	38.0	10.0	53.8	6.1	0.0	11.8	42.6	7.9
AWM	39.6	7.2	47.8	9.3	34.6	10.9	52.8	7.0	0.0	12.4	40.8	8.9
REASONINGBANK	**44.9**	**5.6**	**53.3**	**7.6**	**41.1**	**9.5**	**57.5**	**5.2**	**3.4**	**10.5**	**46.3**	**7.3**
+MATTS	47.1	5.8	55.5	7.4	43.3	9.4	60.4	5.0	10.3	9.1	48.8	7.2

个人想法：

agent自进化文章过于套路化：

1 找一个已有 Agent 框架，例如 ReAct、Reflexion 或某种 Coding Agent。

2 加入 Memory、Skill LibraryReflection、Verifier 或 RL。

3 设计一个经验更新、技能选择或搜索机制。

4 在 SWE-bench、WebArena、ALFWorld 等 Benchmark 上证明性能提升。

5 将其称为 Self-Evolving Agent。

Generate → Evaluate → Select → Update（memory，skill，workflow）

期待能看到范式的更新！

一些想法，

1 加入筛选器，这次成功/失败的经验值不值得学习？

2 学习后，经验到底是否能提高agent的能力，如果不能，有没有一个feedback机制能估计这个经验的价值

二、创新点 2：Skill 动态评分与末位淘汰

这是与你现有想法重合度最高的部分。

最直接的先例：SPyCE

论文：SPyCE: Skill-Policy Co-evolution for Multimodal Agents ↗

发表时间：2026 年 7 月首次公开，已被 ACM MM 2026 接收。

它的 Skill Library 包含两类 Skill：高层的 Workflow Skills，以及具体操作层的 Execution Skills。

对于 Execution Skill，它会记录历史使用结果，计算：

$$SR(k) = \frac{N_{\text{success}}(k)}{\max(N_{\text{retrieval}}(k), 1)}$$

其中 N_{success} 是 Skill 被检索使用后成功的次数，$N_{\text{retrieval}}$ 是检索次数。

当 Skill Library 超出容量限制时，**直接按照经验成功率排序，删除排名最低的 Execution Skills**。对于 Workflow Skills，则采用匹配频次等信息进行容量管理。 arXiv

这与你提出的"新任务成功加分、失败扣分、末位淘汰"在核心机制上已经非常接近。

没有考用多条skill失败会不会污染正确skill，没有用到的skill是0，会被淘汰，但不一定没用，可以引入置信上界。
利用贝叶斯公式更新?