dsh-federation: A Semantic-Level Coordination and Transport Plane for Heterogeneous Cross-Machine LLM-Agent Federations

Lifeng Tian

November 2026

dsh-federation: A Semantic-Level Coordination and Transport Plane for Heterogeneous Cross-Machine LLM-Agent Federations

Abstract

Personal LLM-agent harnesses now run simultaneously on many heterogeneous machines (workstations, cloud servers, LAN boxes, offline nodes), yet each instance is a silo: its sessions, files, and learned lessons do not cross machine boundaries, and letting one agent operate another machine's shell is a security red line. We present **dsh-federation**, a zero-infrastructure method framework that federates *independent* agent instances through a single shared, plain-text context database. Its core is a **semantic-level transport model**: messages carry only speech-act headers (five performatives), four-coordinate identities, and monotonic timestamps; anything larger than a small threshold travels as a **content-addressed pointer** (path + SHA-256 + byte count) that is verified *outside* any agent's context window. We formalize the message calculus and prove three cost properties: per-delivery context cost is O(header) and independent of payload size; novelty detection is O(1) via fixed-width timestamp comparison; and k-hop relay adds zero repeated context payment because pointers are idempotent. Around the transport we specify organizational governance — a versioned, incident-driven handbook with red lines, role-scoped acknowledgment obligations, and time-triggered watchkeeping suited to turn-based agents. We report a sanitized eleven-day field deployment across five heterogeneous machines (protocol v1.0→v1.4, eight role types, 45 cross-machine lessons, 13 archived incidents, multi-thousand-file deliveries with per-file digest verification) and a 49-system novelty assessment. Per our search (2026-11), no public scheme is isomorphic to this combination; we state claims at a deliberately conservative level.

Keywords: multi-agent systems, LLM agents, agent communication, semantic communication, content addressing, coordination artifacts, organizational governance, field deployment.

1. Introduction

A single developer or small team today routinely operates several LLM-agent instances: one on a laptop, one on a cloud server, one on a LAN machine without external network, and so on. Each instance is *turn-based* (it acts, returns, and is re-invoked), *context-bounded* (its working memory is a token window that is billed and that degrades with length), and *environment-privileged* (it holds credentials and shell rights on exactly one machine). Three consequences follow.

1. **Silos.** Lessons learned on machine A (a command trap, a config pitfall, an incident root cause)

are invisible to machine B unless a human copies them.
2. **Context scarcity as the true bandwidth.** When agents collaborate, the scarce channel is not network bandwidth but the context window: every byte that enters it is paid for in tokens and competes with the task at hand.
3. **The remote-shell red line.** The naive fix — letting agent A ssh into machine B and run commands — merges trust domains and is exactly what operational red lines forbid ("never operate another machine on its behalf").

Existing answers address *single-host* multi-agent work (built-in agent teams, swarm frameworks) or *platform-scale* infrastructure (organization-level agent substrates with identity, discovery, and container orchestration). Neither fits the personal/small-team setting: independent heterogeneous instances, no open ports, no broker clusters, no budget for platform operations, and a human who must be able to audit everything by reading plain text.

Positioning as a research prototype. dsh-federation is a research prototype for cross-architecture, cross-harness multi-agent collaboration and work relay: independent agent instances on different machine architectures — and even different builds of DSH-class harnesses — hand work to one another through the federation, and compared with traditional single-session execution it obtains efficient deployment and convenient operation at near-zero marginal cost (no broker, no open ports, no platform team). Concurrently, the DeepSeek Harness team's Super-agent design exploration [31] reports the same attention bottleneck — a human sustains only 3–5 active sessions — and answers it inside one organization's footprint with a two-layer Router/Worker architecture, event-driven triggers, speculative execution, and a Watchdog session, while listing cross-instance A2A communication and cross-session human collaboration as open problems. We occupy exactly that open slot from the opposite direction: rather than redesigning the interior of one agent stack, we federate already-deployed independent instances with plain-text organizational artifacts, across machines and harness builds.

Contributions. (i) A method framework that federates independent, heterogeneous LLM-agent instances over one shared plain-text context database with **zero additional infrastructure** (§3). (ii) A **semantic-level transport model** with a message calculus and three cost propositions (§4), positioned against speech-act communication, tuple spaces, publish/subscribe with consumer offsets, content addressing, and provenance standards. (iii) An **organizational governance layer**: versioned incident-driven handbook, red-line evolution, role-scoped acknowledgment obligations, and time-triggered watchkeeping for turn-based agents (§5). (iv) A **sanitized field study** (five machines, eleven days) plus a 49-system × 10-dimension novelty assessment with an explicit claim ladder (§6, §7).

2. Setting and Constraints

Agents. Each node is a turn-based LLM-agent harness (we deploy on DeepSeek Harness; the method is harness-agnostic). An agent cannot block: between turns it is inert. Hence all liveness must come from *scheduled re-invocation*, not from listening sockets.

Substrate. One shared context database reachable by every node through *some* path: an outbound ssh tunnel, a local/sshfs mount, or — for a node with no network at all — a human or peer relay carrying files. The substrate stores UTF-8 text; binary payloads live in an attached store and are referenced, never embedded.

Threat and audit model. No inbound ports; no agent ever executes commands on another

machine; every coordination artifact is append-only plain text that a human can read end-to-end; integrity rests on SHA-256 digests computed outside agent contexts. Credentials never appear in the shared substrate.

Heterogeneity. Nodes differ in OS, model backend, network reachability, and uptime. The only required capability is reading and writing UTF-8 text files.

3. The Room: Coordination Artifact as Transport

The federation's coordination state lives in a *room*: a directory of append-only Markdown logs.

- `general.md` — the public channel;
- `inbox/<machine>.md` — per-machine inbound queue;
- `cursor/<machine>-<role>.md` — per-role consumption offsets;
- role and governance texts elsewhere in the shared database.

A **message** is a fenced block with a YAML-like header and a body:

```
mid: <machine>-<role>-<YYYYMMDDTHHMMSS>
from: <machine>
role: <role>
to: <machine> | general
ts: <ISO-8601>
type: ask | reply | note | data | ack
re: <mid>            # mandatory for reply
<body, or pointer lines for type=data>
```

Design rules, each traceable to a real incident in the field study:

- **R1 (append-only).** Logs are never rewritten; corrections are new messages. Provenance is structural.
- **R2 (seconds-granular ids).** `mid` embeds a fixed-width timestamp *with seconds*; two roles on one machine posting in the same minute collided before this rule.
- **R3 (tail-timestamp novelty).** "Have I seen this?" compares only the fixed-width timestamp suffix of `mid`. Comparing whole ids lexicographically is a trap: machine-name prefixes reorder ids across machines.
- **R4 (payload threshold).** Bodies above 2 KB must become `data` messages whose body is pointer lines `data: <path> sha256=<hex> bytes=<n>`.
- **R5 (one cursor per role).** Cursors are per (machine, role); sharing one cursor across roles on a multi-role machine lost messages.
- **R6 (no secrets).** The substrate carries no tokens, keys, or personal data; payloads with such content stay out of the shared store entirely.

4. Semantic-Level Transport Model

4.1 Message calculus

Definition 1 (semantic message). A message is a triple $d = (a, p, r)$ where a is the *act header* (performative $\pi \in \{\text{ask, reply, note, data, ack}\}$, identity four-tuple $(m_{from}, \rho_{from}, m_{to}, \rho^*_{to})$, monotonic timestamp t, and optional referent re), p is an optional *content-addressed pointer* (path, h, n) with $h = \text{SHA-256}$ and byte count n, and r is an optional inline residue with $|r| \leq B$ (deployment value $B = 2$ KB).

Definition 2 (channel). A channel C is an append-only sequence $d_1, d_2, \ldots$; its *semantic projection* is the sequence of headers and pointers only.

Definition 3 (cursor). For consumer (m, ρ), $\kappa(m, \rho) \in \mathbb{N}$ is the index of the last consumed element; novelty is the suffix test of R3 applied to elements beyond κ.

Definition 4 (delivery manifest). A delivery of payload set $P = \{f_1, \ldots, f_k\}$ is one `data` message whose pointer list enumerates $(\text{path}_i, h_i, n_i)$; acceptance requires, for each i, an out-of-context equality check SHA-256$(f_i) = h_i \wedge |f_i| = n_i$, after which the receiver posts `ack`.

Definition 5 (watch schedule). A function $W : \text{time} \to \{\text{invoke}, \varnothing\}$ re-invokes each role on a cadence (deployment: 1 h daytime, 2 h night), implementing time-triggered activation for agents that cannot listen.

4.2 Cost model

Let H be header+pointer size (hundreds of bytes) and $|P|$ payload size.

Proposition 1 (context cost). The context-window cost charged to sender and receiver for one delivery is $O(H)$, independent of $|P|$. *Sketch.* By R4 the payload never enters any context; only a and p do, plus one digest/boolean line from the out-of-context verifier. ■

Proposition 2 (O(1) novelty). Given cursor κ, detecting whether new messages exist costs one fixed-width string comparison per channel, not a scan of message bodies. *Sketch.* R3 makes the suffix a total order key; bodies are irrelevant to novelty. ■

Proposition 3 (relay idempotence). Forwarding a pointer across k hops charges $O(H)$ per hop and $O(H)$ total *semantic* cost to the federation: the pointer denotes the same content at every hop, so no hop re-pays payload context and verification remains end-to-end by digest equality. *Sketch.* Content addressing makes p location-independent; equality of h is transitive. ■

These properties map directly onto the failure taxonomy of LLM multi-agent systems (MAST): specification ambiguity is bounded by five performatives with mandatory referents; inter-agent misalignment is bounded by explicit ack obligations (§5); unrecoverable failures become visible because every act is logged append-only; and context poisoning/overflow is bounded by Proposition 1. We state this as *design intent*, not as measured efficacy.

4.3 Lineage

Speech acts → KQML → FIPA-ACL supply the performative discipline; Linda/blackboards supply shared coordination artifacts; publish/subscribe with consumer offsets (Kafka logs) supply cursors; Merkle/IPFS content addressing and W3C PROV supply pointers and provenance; event- vs time-triggered architecture supplies the watch schedule; goal-oriented semantic communication supplies the "transmit intent, not bits" stance. The combination — and its reduction to *plain files* as the universal narrow waist — is what we contribute.

5. Organizational Governance

Transport without governance decays: roles blur, obligations lapse, lessons evaporate. dsh-federation specifies four instruments.

Roles. Named posts per machine (diplomat, mechanic, editor, coordinator, ...); a machine may hold several; every message header carries the posting role, making responsibility auditable.

Versioned handbook with red lines. Cross-machine lessons live in an append-only handbook with numbered entries and an index; operational prohibitions are *red lines* with monotonic numbering (never renumbered). Crucially, red lines are **incident-driven patches**: each of the 13 archived incidents in the field study produced at least one rule (e.g., a session-registry overwrite incident produced the "never rewrite coordination state" family; a tunnel-death incident produced the watchdog rule). The handbook is thus a living patch series over the organization's failure surface.

Acknowledgment obligations. Borrowing commitment-based MAS semantics: a `data` or `ask` message creates a debtor obligation on its addressee, discharged only by `ack` or `reply`. A derived **ack board** (two columns: inbound obligations uncleared; outbound messages awaiting discharge) is computable from the logs alone and drives the watch turns.

Time-triggered watchkeeping. Because agents cannot block (Definition 5), liveness is a schedule. Cadence is a policy parameter (day/night tiers), and each watch turn is a fixed checklist: scan cursors, discharge obligations, update the board, escalate staleness.

6. Field Study (sanitized)

Five heterogeneous machines (a Windows workstation, a cloud Linux server hosting the shared database, a LAN node, a dormitory node, and an offline node served by relay) ran the method for eleven days (2026-10-22 → 11-02). Machine names are pseudonyms; all identifiers, paths, and contents are sanitized.

- **Protocol evolution:** v1.0 → v1.4 in ten days, all changes backward-compatible; each minor version traceable to incidents or onboarding friction.
- **Organization:** 8 role types; multi-role machines; one editor-in-chief owns the shared handbook (v2.1.2: four volumes, 45 cross-machine lessons, 15 red lines, 13 incident archives).
- **Deliveries:** multi-thousand-file packages (chapter drafts, figure sets, CSV matrices) moved as pointer manifests with per-file SHA-256 + byte verification; zero undetected corruption; context cost per delivery observed at header scale.
- **Liveness:** watch cadence institutionalized (1 h day / 2 h night); a 48-hour escalation rule for unanswered obligations; weekly digest.
- **Failure pedagogy:** the four protocol rules R2, R3, R5 and the newline-handling rule each exist because a real message was lost or misordered without them.

We report this as *existence evidence* for operability, not as a controlled evaluation.

7. Novelty Assessment and Claim Ladder

We compared 49 systems across 10 dimensions (single-host orchestrators; cross-machine protocols; Claude/DSH ecosystems; memory systems; academic simulations; governance toolkits). Nearest neighbors: (a) **platform substrates** for organization-scale persistent agents (identity/discovery/routing/containers; one ships a harness channel plugin) — different route: they *are* infrastructure, we require none; (b) **single-box swarm frameworks** with hierarchical memory — complementary, not cross-machine; (c) **built-in single-host agent teams** — complementary; (d) **concurrent single-organization super-agent architecture** (two-layer Router/Worker, event triggers with thread subscription, Inline & Spill and Chain-of-Recall context mechanics, Watchdog control loop; prototype plugin `dsh-superagent-prototype`) [31] — same motivation (attention bottleneck, session silos), different unit of redesign: they re-engineer one organization's agent interior with programmatic routing and push events on a single harness deployment,

whereas we leave every instance untouched and add only a cross-instance organizational layer that works across machines and harness builds; their stated open problems (A2A between agent instances, collaboration detached from sessions) are precisely the surfaces our room protocol, pointer delivery, and ack obligations specify. Per our search (2026-11), no public scheme combines heterogeneous cross-machine instances + a shared plain-text context database as the sole substrate + versioned incident-driven handbook governance + pointer-based delivery-integrity protocol + turn-driven time-triggered watchkeeping + field evidence. Our claim ladder states results at level L2 ("combination unseen in search") with contribution-style L3 sentences; "first-ever" claims are explicitly disclaimed, and the strongest single dimension is the delivery-integrity protocol (digest discipline outside context), the weakest are topology discovery and human-in-the-loop design.

8. Limitations

No push delivery (polling only); no server-side deduplication or permission isolation in the substrate (compensated by cursor discipline and red lines); a single shared trust root; parameters (2 KB, cadences) are deployment choices, not optima; metrics are self-reported from one organization; the MAST alignment is design intent, not measured efficacy; the comparison with concurrent super-agent designs [31] is qualitative — their measurements run on synthetic loads, ours on sanitized field logs, and no head-to-head benchmark exists.

9. Conclusion

dsh-federation shows that a federation of independent, heterogeneous LLM agents can be coordinated with *nothing but text*: semantic headers and content-addressed pointers keep the scarce resource — context — free of payloads, while a versioned handbook, ack obligations, and time-triggered watchkeeping keep the organization alive between turns. The eleven-day five-machine deployment suggests the design is not merely consistent but operable, and its incident-driven rule set is a reusable artifact for anyone running personal agent federations.

References

1. Searle, J. R. (1969). *Speech Acts: An Essay in the Philosophy of Language.* Cambridge University Press.
2. Finin, T., et al. (1994). KQML as an agent communication language. *CIKM '94.*
3. FIPA (2002). *FIPA Communicative Act Library Specification*, SC00037.
4. Gelernter, D. (1985). Generative communication in Linda. *ACM TOPLAS*, 7(1).
5. Nii, H. P. (1986). Blackboard systems. *AI Magazine*, 7(2).
6. Eugster, P. Th., Felber, P. A., Guerraoui, R., & Kermarrec, A.-M. (2003). The many faces of publish/subscribe. *ACM Computing Surveys*, 35(2).
7. Kreps, J., Narkhede, N., & Rao, J. (2011). Kafka: a distributed messaging system for log processing. *NetDB '11.*
8. Merkle, R. C. (1980). Protocols for public key cryptosystems. *IEEE Symposium on Security and Privacy.*
9. Benet, J. (2014). IPFS — content addressed, versioned, P2P file system. *arXiv:1407.3561.*
10. Moreau, L., et al. (2013). *PROV-Overview: An Overview of the PROV Family of Documents.* W3C.
11. Shannon, C. E., & Weaver, W. (1949). *The Mathematical Theory of Communication.* University of Illinois Press.

12. Kopetz, H. (1991). Event-triggered versus time-triggered real-time systems. *Dagstuhl Seminar: Operating Systems of the 90s*.
13. Theraulaz, G., & Bonabeau, E. (1999). A brief history of stigmergy. *Artificial Life*, 5(2).
14. Malone, T. W., & Crowston, K. (1994). The interdisciplinary study of coordination. *ACM Computing Surveys*, 26(1).
15. Esteva, M., Rodríguez-Aguilar, J. A., Sierra, C., García, P., & Arcos, J. L. (2001). On the formal specification of electronic institutions. *AMEC III*, Springer.
16. Hübner, J. F., Sichman, J. S., & Boissier, O. (2013). *Organizing Multi-Agent Systems*. Springer.
17. Singh, M. P. (1999). An ontology for commitments in multiagent systems. *Artificial Intelligence and Law*, 7(1).
18. Guo, T., et al. (2024). Large language model based multi-agents: a survey of progress and challenges. *arXiv:2402.01680* (IJCAI 2024).
19. Cemri, M., et al. (2025). Why do multi-agent LLM systems fail? *arXiv:2503.13657* (NeurIPS 2025 Datasets & Benchmarks).
20. Zhang, Z., et al. (2024). A survey on the memory mechanism of large language model based agents. *arXiv:2404.13501*.
21. Liu, N. F., et al. (2024). Lost in the middle: how language models use long contexts. *TACL* (arXiv:2307.03172).
22. Chen, L., Zaharia, M., & Zou, J. (2023). FrugalGPT: how to use large language models while reducing cost and improving performance. *arXiv:2305.05176*.
23. Goal-oriented semantic communication for intelligent networks: a survey. (2025). *arXiv:2512.12758*.
24. Wu, Q., et al. (2023). AutoGen: enabling next-gen LLM applications via multi-agent conversation. *arXiv:2308.08155*.
25. Hong, S., et al. (2023). MetaGPT: meta programming for a multi-agent collaborative framework. *arXiv:2308.00352*.
26. Qian, C., et al. (2023). Communicative agents for software development. *arXiv:2307.07924*.
27. Linux Foundation (2025). *Agent2Agent (A2A) protocol specification*.
28. inclusionAI (2026). *AverNet: infrastructure for persistent, organization-scale multi-agent systems* (repository documentation).
29. ruflo (formerly claude-flow) (2026). *Single-box agent swarm orchestration with hierarchical memory* (repository).
30. DeepSeek (2026). *deepseek-harness* and its built-in single-host Agent Teams; OpenViking shared context database.
31. DeepSeek Harness Team (2026). *Super-agent design exploration: Toward more autonomous agent systems* (in Chinese) (architecture exploration article, 2026-11-01; prototype: dsh-superagent-prototype); coverage: DoNews/PChome, 2026-11-01.