Murmuration: Federating LLM Agents Across Machines with Nothing but Text

Abstract

Personal LLM-agent harnesses now run simultaneously on many heterogeneous machines (workstations, cloud servers, LAN boxes, offline nodes), yet each instance is a silo: its sessions, files, and learned lessons do not cross machine boundaries, and letting one agent operate another machine's shell is a security red line. We present **Murmuration**, a method framework that federates *independent* agent instances through a single shared, plain-text context database, adding no broker or middleware beyond that store. Its core is a **semantic-level transport model**: messages carry only speech-act headers (five performatives), four-coordinate identities, and monotonic timestamps; anything larger than a small threshold travels as a **content-addressed pointer** (path + SHA-256 + byte count) that is verified *outside* any agent's context window. We formalize a message calculus and establish three cost properties under stated assumptions: per-delivery context cost scales with the pointer list rather than payload bytes, and drops to a constant header when the manifest itself travels as a file; novelty detection is O(1) via fixed-width timestamp comparison; and k-hop relay never re-pays payload context, since pointers are idempotent. Around the transport we specify organizational governance: a versioned, incident-driven handbook with red lines, role-scoped acknowledgment obligations, and time-triggered watchkeeping suited to turn-based agents. We report a sanitized eleven-day (elapsed) field deployment across five heterogeneous machines (protocol v1.0→v1.4, eight role types, 45 cross-machine lessons, 13 archived incidents, deliveries of up to 1,300+ files, each verified by per-file digest) and a 49-system novelty assessment. Within the window the room carried 283 structured messages (mean 26/day, peak 49/day) — 39 typed data deliveries, 27 asks, 87 acknowledgment discharges — with 179+ SHA-256 digests verified at byte equality and zero mismatches; payload content (scientific-experiment pipelines, document drafting, paper writing) never enters this paper, only counts and shapes. Per our search (2026-11), no public scheme is isomorphic to this combination; we state claims at a deliberately conservative level.

Keywords: multi-agent systems, LLM agents, agent communication, semantic communication, content addressing, coordination artifacts, organizational governance, field deployment.

1. Introduction

A single developer or small team today routinely operates several LLM-agent instances [18]: one on a laptop, one on a cloud server, one on a LAN machine without external network, and so on. Each instance is *turn-based* (it acts, returns, and is re-invoked), *context-bounded* (its working memory is a token window that is billed and that degrades with length), and *environment-privileged* (it holds credentials and shell rights on exactly one machine). Three consequences follow.

1. **Silos.** Lessons learned on machine A (a command trap, a config pitfall, an incident root cause) are invisible to machine B unless a human copies them.
2. **Context scarcity as the true bandwidth.** When agents collaborate, the scarce channel is not network bandwidth but the context window [21,22]: every byte that enters it is paid for in tokens and competes with the task at hand.
3. **The remote-shell red line.** The naive fix — letting agent A ssh into machine B and run commands — merges trust domains and is exactly what operational red lines forbid ("never operate another machine on its behalf").

Existing answers address *single-host* multi-agent work (built-in agent teams, swarm frameworks,

conversation orchestrators) [24,25,26,29,30] or *platform-scale* infrastructure and cross-machine agent protocols (organization-level substrates with identity, discovery, and container orchestration) [27,28]. Neither fits the personal/small-team setting: independent heterogeneous instances, no open ports, no broker clusters, no budget for platform operations, and a human who must be able to audit everything by reading plain text.

Positioning as a research prototype. murmuration is a research prototype for cross-architecture multi-agent collaboration and work relay (cross-harness by design): independent agent instances on different machine architectures — and different builds of the DeepSeek Harness (DSH) family [30] — hand work to one another through the federation, and compared with traditional single-session execution it delivers the same class of multi-agent coordination at near-zero marginal infrastructure cost in our deployment (no broker, no open ports, no platform team). Concurrently, the DeepSeek Harness team's Super-agent design exploration [31] reports the same attention bottleneck — a human sustains only 3–5 active sessions — and answers it inside one organization's footprint with a two-layer Router/Worker architecture, event-driven triggers, speculative execution, and a Watchdog session, while listing cross-instance agent-to-agent (A2A [27]) communication and cross-session human collaboration as open problems. We occupy exactly that open slot from the opposite direction: rather than redesigning the interior of one agent stack, we federate already-deployed independent instances with plain-text organizational artifacts, across machines and harness builds.

Contributions. (i) A method framework that federates independent, heterogeneous LLM-agent instances over one shared plain-text context database, adding **no broker or middleware beyond that store** (§3). (ii) A **semantic-level transport model** with a message calculus and three cost propositions (§4), positioned against speech-act communication, tuple spaces, publish/subscribe with consumer offsets, content addressing, and provenance standards. (iii) An **organizational governance layer**: versioned incident-driven handbook, red-line evolution, role-scoped acknowledgment obligations, and time-triggered watchkeeping for turn-based agents (§5). (iv) A **sanitized field study** (five machines, eleven days) plus a 49-system × 10-dimension novelty assessment with an explicit claim ladder (§6, §7).

2. Setting and Constraints

Agents. Each node is a turn-based LLM-agent harness. All five field nodes run DeepSeek Harness (DSH) builds [30]; the protocol requires only UTF-8 file I/O and is designed to be harness-agnostic, although a second harness family has not yet been fielded. An agent cannot block: between turns it is inert. Hence all liveness must come from *scheduled re-invocation*, not from listening sockets.

Substrate. One shared context database reachable by every node through *some* path: an outbound ssh tunnel, a local/sshfs mount, or — for a node with no network at all — a human or peer relay carrying files. The substrate stores UTF-8 text; binary payloads live in an attached store and are referenced, never embedded.

Threat and audit model. No inbound ports; no agent ever executes commands on another machine; every coordination artifact is append-only plain text that a human can read end-to-end; integrity rests on SHA-256 digests computed outside agent contexts (a corruption check, not an authenticity control; see §8). Credentials never appear in the shared substrate.

Heterogeneity. Nodes differ in OS, model backend, network reachability, and uptime. The only required capability is reading and writing UTF-8 text files.

3. The Room: Coordination Artifact as Transport

The federation's coordination state lives in a *room*: a directory of append-only Markdown logs.

- `general.md` — the public channel;
- `inbox/<machine>.md` — per-machine inbound queue;
- `cursor/<machine>-<role>.md` — per-role consumption offsets;
- role and governance texts elsewhere in the shared database.

A **message** is a fenced block with a YAML-like header and a body:

```
---
mid: <machine>-<role>-<YYYYMMDDTHHMMSS>
from: <machine>
role: <role>
to: <machine> | general
ts: <ISO-8601>
type: ask | reply | note | data | ack
re: <mid>            # mandatory for reply
---
<body, or pointer lines for type=data>
```

Design rules distilled from the field study; several are direct patches for recorded incidents (§6):

- **R1 (append-only).** Logs are never rewritten; corrections are new messages. Provenance is structural.
- **R2 (seconds-granular ids).** `mid` embeds a fixed-width timestamp *with seconds*; two roles on one machine posting in the same minute collided before this rule.
- **R3 (tail-timestamp novelty).** "Have I seen this?" compares only the fixed-width timestamp suffix of `mid`. Comparing whole ids lexicographically is a trap: machine-name prefixes reorder ids across machines.
- **R4 (payload threshold).** Bodies above 2 KB must become `data` messages whose body is pointer lines `data: <path> sha256=<hex> bytes=<n>`.
- **R5 (one cursor per role).** Cursors are per (machine, role); sharing one cursor across roles on a multi-role machine lost messages.
- **R6 (no secrets).** The substrate carries no tokens, keys, or personal data; payloads with such content stay out of the shared store entirely.

4. Semantic-Level Transport Model

4.1 Message calculus

Definition 1 (semantic message). A message is a triple $d = (a, p, r)$ where a is the *act header* (performative $\pi \in \{\text{ask, reply, note, data, ack}\}$, identity four-tuple $(m_{from}, \rho_{from}, m_{to}, \rho^*_{to})$ — the starred ρ^*_{to} denotes the target role, or a wildcard when the message addresses a machine rather than a specific post — a per-producer monotonic timestamp t, and an optional referent re), p is an optional *content-addressed pointer* (path, h, n) with $h = \text{SHA-256}$ and byte count n, and r is an optional inline residue with $|r| \leq B$ (deployment value $B = 2$ KB).

Definition 2 (channel). A channel C is an append-only sequence $d_1, d_2, \ldots$; its *semantic projection* is the sequence of headers and pointers only.




Figure 1: **Figure 1.** Murmuration at a glance. (a) Heterogeneous nodes coordinate through one shared plain-text store — public log, per-machine inboxes, per-role cursors — under a versioned governance handbook and time-triggered watchkeeping; payloads never enter the store and move over pre-existing point-to-point channels. (b) Pointer-delivery lifecycle: manifests and digests travel as text inside the context budget; files are fetched out-of-band and verified shell-side.

Definition 3 (cursor). For consumer (m, ρ) and channel C, the cursor $\kappa(m, \rho, C)$ records the identifier — and hence the embedded fixed-width timestamp — of the last consumed element; novelty is decided by R3's suffix comparison against that timestamp. Cursors are per-consumer *and* per-channel, and remain well-defined under partial replication (an offline node's replica).

Definition 4 (delivery manifest). A delivery of payload set $P = \{f_1, \ldots, f_k\}$ is one `data` message whose pointer list enumerates $(\text{path}_i, h_i, n_i)$; acceptance requires, for each i, an out-of-context equality check $\text{SHA-256}(f_i) = h_i \wedge |f_i| = n_i$, after which the receiver posts `ack`.

Definition 5 (watch schedule). A function $W : \text{time} \to \{\text{invoke}, \text{skip}\}$ re-invokes each role on a cadence (deployment: 1 h daytime, 2 h night), implementing time-triggered activation for agents that cannot listen.

4.2 Cost model

Let H be header+pointer size (hundreds of bytes) and $|P|$ payload size.

Proposition 1 (context cost). Assume manifests are generated and digest-verified entirely out of context, with only per-file boolean/summary lines entering it (the *manifest assumption*; this is exactly how the deployment's verification scripts run). Then the context-window cost charged to sender and receiver for one delivery of k files is $O(k \cdot H)$, independent of payload bytes $|P|$; and when the pointer list itself exceeds the inline threshold it is delivered as a file — one pointer, $O(H)$ — restoring a constant per-delivery context cost at any k. *Sketch.* By R4 the payload never enters any context; only a and p do, plus the verifier's summary. A manifest that is itself a payload is subject to R4 again, which yields the two-case bound. ■

Proposition 2 (O(1) novelty). Given cursor κ, detecting whether new messages exist costs one fixed-width string comparison per channel, not a scan of message bodies. *Sketch.* R3 makes the suffix a total order key; bodies are irrelevant to novelty. ■

Proposition 3 (relay idempotence). Forwarding a pointer across k hops charges $O(H)$ context per hop, and the payload context is paid zero times beyond the original posting: the pointer denotes the same content at every hop, and verification remains end-to-end by digest equality. *Sketch.* Content addressing makes p location-independent; under the standard assumption that SHA-256 is collision-resistant, h ties pointer identity to content at every hop. ■

These properties map directly onto the Multi-Agent System Failure Taxonomy (MAST) [19]: specification ambiguity is bounded by five performatives with mandatory referents; inter-agent misalignment is bounded by explicit ack obligations (§5); unrecoverable failures become visible because every act is logged append-only; and context poisoning/overflow is bounded by Proposition 1. We state this as *design intent*, not as measured efficacy.

4.3 Lineage

Speech acts [1] → KQML [2] → FIPA-ACL [3] supply the performative discipline; Linda and blackboards [4,5] supply shared coordination artifacts; publish/subscribe with consumer offsets (Kafka logs) [6,7] supply cursors; Merkle trees and IPFS content addressing [8,9] and W3C PROV [10] supply pointers and provenance; event- versus time-triggered architecture [12] supplies the watch schedule; goal-oriented semantic communication [11,23] supplies the "transmit intent, not bits" stance; and stigmergy [13] and coordination theory [14] frame the room itself as an indirect-coordination medium. The combination — and its reduction to *plain files* as the universal narrow waist — is what we contribute.

5. Organizational Governance

Transport without governance decays: roles blur, obligations lapse, lessons evaporate. murmuration specifies four instruments, in the tradition of electronic institutions and organizational design for MAS [15,16].

Roles. Named posts per machine (diplomat, mechanic, editor, coordinator, . . .); a machine may hold several; every message header carries the posting role, making responsibility auditable.

Versioned handbook with red lines. Cross-machine lessons live in an append-only handbook with numbered entries and an index; operational prohibitions are *red lines* with monotonic numbering (never renumbered). Crucially, red lines are **incident-driven patches**: each of the 13 archived incidents in the field study produced at least one rule (e.g., a session-registry overwrite incident produced the "never rewrite coordination state" family; a tunnel-death incident produced the watchdog rule). The handbook is thus a living patch series over the organization's failure surface.

Acknowledgment obligations. Borrowing from commitment-based MAS semantics [17]: a `data` or `ask` message creates a debtor obligation on its addressee, discharged only by `ack` or `reply`. A derived **ack board** (two columns: inbound obligations uncleared; outbound messages awaiting discharge) is computable from the logs alone and drives the watch turns.

Time-triggered watchkeeping. Because agents cannot block (Definition 5), liveness is a schedule. Cadence is a policy parameter (day/night tiers), and each watch turn is a fixed checklist: scan cursors, discharge obligations, update the board, escalate staleness.

6. Field Study (sanitized)

Five heterogeneous machines (a Windows workstation, a cloud Linux server hosting the shared database, a LAN node, a dormitory node, and an offline node served by relay) ran the method for eleven elapsed days (2026-10-22 → 11-02; twelve calendar days inclusive). Machine names are pseudonyms; all identifiers, paths, and contents are sanitized.

- **Protocol evolution:** v1.0 → v1.4 in ten days, all changes backward-compatible; each minor version traceable to incidents or onboarding friction.
- **Organization:** eight role types; multi-role machines; one editor-in-chief owns the shared handbook (v2.1.2: four volumes, 45 cross-machine lessons, 15 red lines, 13 incident archives).
- **Deliveries:** multi-thousand-file packages (chapter drafts, figure sets, CSV matrices) moved as pointer manifests with per-file SHA-256 + byte verification; zero digest mismatches across all verified files; per-delivery context cost stayed at header scale in operator observation (not separately metered).
- **Volume (sanitized counts only):** 283 structured messages across one public channel, five machine inboxes and eighteen role cursors during the window (mean 26/day, peak 49/day); 39 `data` deliveries, 27 `ask`s, 87 `ack`/`reply` discharges, 121 status notes; 179+ per-file SHA-256 digests checked with byte equality, largest single manifest above 1,300 files.
- **Task classes (abstracted):** scientific-experiment data pipelines, long-form document drafting, and paper writing; no payload content is disclosed — only counts, shapes and verification outcomes.
- **Liveness:** watch cadence institutionalized (1 h day / 2 h night); a 48-hour escalation rule for unanswered obligations; weekly digest.
- **Failure pedagogy:** the protocol rules R2, R3, R5, and a handbook parsing rule (message-fence handling) each exist because a real message was lost or misordered without them.

We report this as *existence evidence* for operability, not as a controlled evaluation.

Artifact availability. The framework source, plugin tools, and the research artifacts behind §7 — the 49-system × 10-dimension novelty matrix, the search log, the adversarial re-review, and the claim ladder — ship in the public repository accompanying this paper (github.com/xuanjat/murmuration, under `docs/research/`); documentation is licensed CC BY 4.0.

7. Novelty Assessment and Claim Ladder

We compared 49 systems across 10 dimensions (single-host orchestrators; cross-machine protocols; Claude/DSH ecosystems; memory systems; academic simulations; governance toolkits); the full matrix, search log, and adversarial re-review ship as repository artifacts.

Nearest neighbors: (a) **AverNet** [28], a platform substrate for organization-scale persistent agents (identity/discovery/routing/containers; since 2026-09 it also ships a DSH channel plugin) — a different route: it *is* infrastructure, whereas we require nothing beyond one shared store; (b) **ruflo** (formerly claude-flow) [29], a single-box swarm framework with hierarchical memory — complementary, not cross-machine; (c) **built-in single-host agent teams** [30] and conversation-based orchestrators [24,25,26] — complementary; (d) **concurrent single-organization super-agent architecture** (two-layer Router/Worker, event triggers with thread subscription, Inline & Spill and Chain-of-Recall context mechanics, Watchdog control loop; prototype plugin `dsh-superagent-prototype`) [31] — same motivation (attention bottleneck, session silos), different unit of redesign: they re-engineer one organization's agent interior with programmatic routing and push events on a single harness

deployment, whereas we leave every instance untouched and add only a cross-instance organizational layer that works across machines and harness builds; their stated open problems (A2A between agent instances, collaboration detached from sessions) are precisely the surfaces our room protocol, pointer delivery, and ack obligations specify. Cross-machine agent protocols such as A2A [27] standardize task exchange between reachable service endpoints but do not specify governance, delivery integrity, or watchkeeping for turn-based personal instances behind NAT or on offline links.

Per our search (2026-11), no public scheme combines heterogeneous cross-machine instances + a shared plain-text context database as the sole substrate + versioned incident-driven handbook governance + pointer-based delivery-integrity protocol + turn-driven time-triggered watchkeeping + field evidence. Our claim ladder — a repository discipline under which unqualified "first-ever" claims (L0/L1) are forbidden, qualified combination novelty is L2, contribution statements without uniqueness are L3, and reusability-only claims are L4 — states results at level L2 ("combination unseen in search") with contribution-style L3 sentences; "first-ever" claims are explicitly disclaimed, and the strongest single dimension is the delivery-integrity protocol (digest discipline outside context), the weakest are topology discovery and human-in-the-loop design.

8. Limitations

No push delivery (polling only); no server-side deduplication or permission isolation in the substrate (compensated by cursor discipline and red lines); a single shared trust root; parameters (2 KB, cadences) are deployment choices, not optima; metrics are self-reported from one organization; the MAST alignment is design intent, not measured efficacy; the comparison with concurrent super-agent designs [31] is qualitative — their measurements run on synthetic loads, ours on sanitized field logs, and no head-to-head benchmark exists.

Distributed-systems candor. (i) *Concurrent appends:* R1's history guarantee assumes appends do not interleave; network filesystems generally provide neither atomic append nor locking. The deployment compensates with role discipline (per-machine files, diplomat-mediated posting to the public channel) — discipline, not a filesystem guarantee. (ii) *Integrity versus authenticity:* SHA-256 digests detect corruption, not adversarial substitution; any writer with substrate access could replace a payload and recompute its digest. The threat model of §2 presumes a single, mutually trusted trust root. (iii) *Injection bus:* message bodies enter peers' contexts verbatim, so a compromised node could attempt to steer the others; current mitigations are procedural (red lines, human-auditable plain text), not a data/instruction separation mechanism — an open problem for LLM federations generally. (iv) *Clocks and collisions:* R3's ordering presumes bounded (NTP-grade) clock skew across machines, and seconds-granular `mid`s can still collide for two same-second messages from one (machine, role). (v) *Relay consistency:* replica merging and duplicate handling for offline nodes rest on cursor discipline, without a formal reconciliation protocol. (vi) *Unbounded growth:* append-only logs have no archival or garbage-collection policy; watch-turn scans grow with the log. (vii) *Liveness bound:* worst-case obligation latency is the watch cadence plus the 48-hour escalation window; nothing tighter is guaranteed.

9. Conclusion

murmuration suggests that a federation of independent, heterogeneous LLM agents can be coordinated with *nothing but text*: semantic headers and content-addressed pointers keep the scarce resource — context — free of payloads, while a versioned handbook, ack obligations, and time-triggered watchkeeping keep the organization alive between turns. The eleven-day, five-machine

deployment indicates that the design is not merely consistent but operable, and its incident-driven rule set is a reusable artifact for anyone running personal agent federations.

References

1. Searle, J. R. (1969). *Speech Acts: An Essay in the Philosophy of Language*. Cambridge University Press.
2. Finin, T., Fritzson, R., McKay, D., & McEntire, R. (1994). KQML as an agent communication language. In *Proceedings of CIKM '94*. ACM.
3. FIPA (2002). *FIPA Communicative Act Library Specification*, SC00037.
4. Gelernter, D. (1985). Generative communication in Linda. *ACM TOPLAS*, 7(1).
5. Nii, H. P. (1986). Blackboard systems. *AI Magazine*, 7(2).
6. Eugster, P. Th., Felber, P. A., Guerraoui, R., & Kermarrec, A.-M. (2003). The many faces of publish/subscribe. *ACM Computing Surveys*, 35(2).
7. Kreps, J., Narkhede, N., & Rao, J. (2011). Kafka: a distributed messaging system for log processing. *NetDB '11*.
8. Merkle, R. C. (1980). Protocols for public key cryptosystems. *IEEE Symposium on Security and Privacy*.
9. Benet, J. (2014). IPFS — content addressed, versioned, P2P file system. *arXiv:1407.3561*.
10. Moreau, L., et al. (2013). *PROV-Overview: An Overview of the PROV Family of Documents*. W3C.
11. Shannon, C. E., & Weaver, W. (1949). *The Mathematical Theory of Communication*. University of Illinois Press.
12. Kopetz, H. (1991). Event-triggered versus time-triggered real-time systems. In *Operating Systems of the 90s and Beyond* (Dagstuhl Seminar), LNCS 563, pp. 87–117. Springer.
13. Theraulaz, G., & Bonabeau, E. (1999). A brief history of stigmergy. *Artificial Life*, 5(2).
14. Malone, T. W., & Crowston, K. (1994). The interdisciplinary study of coordination. *ACM Computing Surveys*, 26(1).
15. Esteva, M., Rodríguez-Aguilar, J. A., Sierra, C., García, P., & Arcos, J. L. (2001). On the formal specification of electronic institutions. *AMEC III*, Springer.
16. Hübner, J. F., Sichman, J. S., & Boissier, O. (2013). *Organizing Multi-Agent Systems*. Springer.
17. Singh, M. P. (1999). An ontology for commitments in multiagent systems. *Artificial Intelligence and Law*, 7(1).
18. Guo, T., et al. (2024). Large language model based multi-agents: a survey of progress and challenges. *arXiv:2402.01680* (IJCAI 2024).
19. Cemri, M., et al. (2025). Why do multi-agent LLM systems fail? *arXiv:2503.13657* (NeurIPS 2025 Datasets & Benchmarks).
20. Zhang, Z., et al. (2024). A survey on the memory mechanism of large language model based agents. *arXiv:2404.13501*.
21. Liu, N. F., et al. (2024). Lost in the middle: how language models use long contexts. *TACL* (arXiv:2307.03172).
22. Chen, L., Zaharia, M., & Zou, J. (2023). FrugalGPT: how to use large language models while reducing cost and improving performance. *arXiv:2305.05176*.
23. Luo, J., Delfani, E., Salimnejad, M., & Pappas, N. (2025). From information freshness to semantics of information and goal-oriented communications. *arXiv:2512.12758*.
24. Wu, Q., et al. (2023). AutoGen: enabling next-gen LLM applications via multi-agent conversation. *arXiv:2308.08155*.

25. Hong, S., et al. (2023). MetaGPT: meta programming for a multi-agent collaborative framework. *arXiv:2308.00352*.
26. Qian, C., et al. (2023). Communicative agents for software development. *arXiv:2307.07924*.
27. Linux Foundation (2025). *Agent2Agent (A2A) protocol specification*.
28. inclusionAI (2026). *Avernet: infrastructure for persistent, organization-scale multi-agent systems*. https://github.com/inclusionAI/Avernet (repository documentation, accessed 2026-11).
29. ruflo (formerly claude-flow) (2026). *Single-box agent swarm orchestration with hierarchical memory*. https://github.com/ruvnet/ruflo (repository, accessed 2026-11).
30. DeepSeek (2026). *deepseek-harness* and its built-in single-host Agent Teams; OpenViking shared context database.
31. DeepSeek Harness Team (2026). [Super-agent design exploration: toward more autonomous agent systems] (architecture exploration article, 2026-11-01; prototype: dsh-superagent-prototype). Coverage: DoNews, https://www.donews.com/news/detail/1/6760986.html; PChome, https://article.pchome.net/news/16524.html (both 2026-11-01).