

ATTESTATION

of conformity with European Directives

BV LCIE CHINA Number 2466AS02SDEC53513

Product Moulded-case Circuit-breaker

Reference EasyPact EZS+400F, EZS+400N, EZS+400H

Issued to Schneider Electric (China) Co.,Ltd.

Address Building A, No. 6, East Wangjing Road, Chaoyang District BEIJING-China

Manufacturer Schneider Electric (China) Co.,Ltd

Technical characteristics See Annex

The submitted sample of the above equipment has been tested for **CE** marking according to following European Directive and following standards:
LVD Directive 2014/35/EU

<i>Standards</i>	<i>Report number</i>	<i>Report date</i>
EN 60947-2: 2017+A1:2020;	22119Y90038	2022-10-25
EN 60947-1: 2007 + A1: 2011 + A2: 2014	22119Y90038-M1	2024-01-17

The referred test report(s) show that the product complies with standard(s) recognized as giving presumption of compliance with the essential requirements in the specified European Directive

This verification does not imply assessment of the production of the product

The **CE** marking may be affixed if all relevant and effective European Directives with **CE** are applicable

Shanghai (P.R. China), Feb.20th, 2024



Charlie CHEN
PL Manager



This document shall not be reproduced, except in full, without the written approval of BV LCIE China. Information given in this document, are related to the tested specimen of the described electrical sample.

Annex

Selectivity category	A
Interruption medium	Air
Design	Moulded case
Method of controlling the operating mechanism	Independent manual
Suitability for isolation	Suitable
Provision for maintenance	Non-maintainable
Method of installation	Fixed
Type of release	Thermo-magnetic , MA
Rated operational voltage U_e : (V)	AC220/230V, 380/415V, 500V,690V
Rated insulation voltage U_i : (V)	1000V
Rated impulse withstand voltage U_{imp} : (kV)	8kV
Rated current I_n : (A)	250A,315A, 350A, 400A for Thermo-magnetic type 315A, 350A, 400A for MA type
Conventional free air thermal current I_{th} : (A)	Equal to I_n
Conventional enclosed thermal current I_{the} : (A)	N/A
Rated current for four pole circuit-breakers : (A)	Equal to I_n
Rated frequency : (Hz)	50/60Hz
Nature of supply :	AC
Total number of poles :	3P, 4P (3P+N, N marked, N has no over-current protection) for Thermo-magnetic type 3P for MA type
Number of protected poles :	3P
Rated duty	uninterrupted duty
Rated short-time making capacity I_{cm} : (A)	<u>F type:</u> 154kA/AC 220/230V, 75,6kA/ AC380/415V, 40kA/AC 500V , 7,65 kA/AC690V <u>N type:</u> 198kA/AC 220/230V, 105kA/ AC 380/415V, 52,5kA/AC 500V, 11,9kA/ AC690V <u>H type:</u> 220kA/AC 220/230V, 154kA/ AC380/415V, 75,6kA/AC 500V, 73,5kA/ AC690V

Annex

Rated ultimate short-circuit breaking capacity Icu : (A)_	<u>F type:</u> 70kA/AC 220/230V, 36kA/ AC380/415V, 20kA/AC 500V ,5kA/ AC690V <u>N type:</u> 90kA/AC 220/230V, 50kA/ AC 380/415V, 25kA/AC 500V, 7kA/ AC690V <u>H type:</u> 100kA/AC 220/230V, 70kA/ AC 380/415V, 36kA/AC 500V, 35kA/ AC690V (TMD type), 10kA/ AC690V (MA type)
Rated service short-circuit breaking capacity Ics : (A)	<u>F type:</u> 53kA/AC 220/230V, 36kA/ AC 380/415V, 20kA/AC 500V ,5kA/ AC 690V <u>N type:</u> 68kA/AC 220/230V, 50kA/ AC 380/415V, 25kA/AC 500V, 7kA/ AC690V <u>H type:</u> 75kA/AC 220/230V, 50kA/ AC 380/415V, 25kA/AC 500V, 10kA/ AC690V
Reference ambient calibration air temperature : (°C)	Thermo-magnetic (40°C)
Pollution degree	3
Material group :	IIIa
safety distance (short-circuit tests) :	Up/down: 100/0mm Left/right: 30/30mm Front/back: 30/0mm
Undervoltage release Us:(V)	MN: 230VAC, 400VAC
Shunt release Us:(V)	MX: 24VDC,222VDC, 230VAC, 400VAC
Electric operating mechanism Us:(V)	24VDC, 110VDC/110VAC, 220VDC/230VAC, 400VAC
Auxiliary circuit	Ui: 400V, Uimp: 2,5kA Ith: 3A AC-15: Ue/ Ie: AC400V/1.5A ; DC-13: Ue/ Ie: DC220V/0.15A 1NO1NC、2NO2NC