

CERTIFICATE OF QUANTITY & QUALITY



YOUR REF:

2023-HZ-1069-93G

OUR REF:

203942786/100

TYPE:

SK372.1-90LP/4 AR TF

QTY:

1

We hereby certify that the goods of above mentioned have been tested before shipment and that the delivered goods are of the highest quality. The finishing of the goods and the assembly of our products are subjected to an integrated quality control.

CHECKER:



APPROVED BY:

Linda

DATE:

2023 Y 11 M 17 D



Certificate of inspection

Qualified



工单号/Job Order: 203942786-100

数量/Qty: 1 pcs

检测Inspection				检测标准 (标准值) Checking Specification	作业员 检验记录 Operator Record	检验员 终检检验记录 Outgoing Inspector Record		
过程 Prs	分类 Type	项目 Item	频次 Freq.					
装配检查 Assembly Check	装配过程 Assembly Process	KS特殊说明 Specification	需要时 If need	客户特殊要求KS必须领会和理解清楚, 且严格遵照执行 Must understand Specification completely, carry out strictly.	☒ Yes ☐ No ☐ NA	☒ Yes ☐ No ☐ NA		
		查核零件 Check Parts	100%	核对料号、数量, 检查外观无明显缺陷并除尘擦拭 MN., Qty., no corrosion,damage and so on, then clean	☒ Yes ☐ No ☐ NA			
		齿隙 Tooth Mesh	100%	伞齿轮和蜗轮蜗杆系列涂蓝试验 Bevel/worm gearbox must be checked by blue	☐ Yes ☐ No ☒ NA			
		螺栓扭矩 Bolt Torque	100%	使用定扭矩工具及箱体联接螺栓扭矩校验 Use torque tools and connect bolts must be confirmed	☒ Yes ☐ No ☐ NA			
		装配方式 As Type	100%	接线盒(含风机), 油位塞, 放气阀, 法兰位置及输出轴方向正确 Position of T-box(include Forced fan),oil plug,vent plug,flange,outshaft are right	☒ Yes ☐ No ☐ NA	☒ Yes ☐ No ☐ NA		
		样机 Sample Unit	需要时 If need	遵照样机流程及标准 Must do according Sample Process and Specification	☒ Yes ☐ No ☐ NA	☒ Yes ☐ No ☐ NA		
	气密及运转检测 Air Seal & Running Testing	气密 Air Seal Test	100%	0.025~0.035Mpa 保持30秒不漏气 0.025~0.035Mpa keeps 30 seconds of air tight	☒ Yes ☐ No ☐ NA			
		异常噪音 Noises	100%	加油前运转测试不大于1min, 无异常敲击、噪音、振动、卡死等现象 Running test less than 1min before filling the oil,Noise and vibration on test-run must be acceptable	☒ Yes ☐ No ☐ NA			
		加油 add oil Lubricant	100%	按工单要求的型号及油量, 进行填加并复查 Correct oil, Qty. according order and double check	☒ Yes ☐ No ☐ NA			
	运转检测 Running Testing	异常噪音 Noises	100%	加油运转测试不小于1min, 无异常敲击、噪音、振动、卡死等现象 Running over 1 min., Noise and vibration on test-run must be acceptable (after filling the oil)	☒ Yes ☐ No ☐ NA			
		转速 Speed	100%	实测输出转速=工单输出转速x(1+(0~10%)) After running test, Actual speed = order output speedx(1+(0~10%))	R/Min: 263			
	外观检查 Outside Check	整机情况 Completely	100%	不许有损伤, 锈蚀, 污痕及缺件 No damage, rust, smear and so on	☒ Yes ☐ No ☐ NA	☒ Yes ☐ No ☐ NA		
		联接尺寸 Link Size	30% ≥ 5PCS	法兰直径及位置, 销孔直径和销孔位置; 联轴器尺寸正确 Dia. and position of flange; Dia. and position of Pin hole; adapter are ok.	☐ Yes ☐ No ☒ NA	法兰ΦD: NA	销孔Φd: NA	轴Φd: NA
				实心轴键/空心轴键槽尺寸以及转向, 输出轴直径以及长度 Diameter of solid shaft key and hollow shaft keyway and direction; Dia and length of output shaft	☒ Yes ☐ No ☐ NA	键/键槽LxW 8/28	轴ΦdxL 25*50	转向 NA
	其它要求 Others Requirements	其它 Others	100%	检查输出轴油封位、确认无损伤. check seal position of output shaft. Must be no damage.	☒ Yes ☐ No ☐ NA	☒ Yes ☐ No ☐ NA		
		扭矩限制器 EAS	100%	调整到工单要求的扭矩 Adjust the torque for EAS according job order required	☐ Yes ☐ No ☒ NA			
		标签 Label	100%	电机接线图齐全 Attaching the wiring diagram of motor	☒ Yes ☐ No ☐ NA			
		附件 Parts	100%	扭矩臂/锁紧盘/空心轴附件数量及尺寸正确 Torque arm/Shrink disc/Fixing part qty. and size are correct	☐ Yes ☐ No ☒ NA	☐ Yes ☐ No ☒ NA		
	油漆检查 Painting	喷漆质量 Paint	100%	颜色正确, 整机油漆表面均匀; 无漆瘤, 无流挂 Color correct,uniform surface	☐ Yes ☐ No ☒ NA	☐ Yes ☐ No ☒ NA		
		厚度 Thickness	100%	根据喷漆作业指导书的标准执行P/B/NSD2/NSD3/NSDC3/NSDF3/NSD4/NSD5 Thickness according standard by P/B/NSD2/NSD3/NSDC3/NSDF3/NSD4/NSD5	☐ Yes ☐ No ☒ NA	标准: NA	RAL: NA	厚度:um NA
装订铭牌及其它 Fixing Nameplate and Others	外观检查 Outside Check	标签 Label	100%	透气阀标签、旋向标签、客户条码及合格证等齐全 Attaching the label for vent plug、direction rotation, customer's code and Certificate	☒ Yes ☐ No ☐ NA	☒ Yes ☐ No ☐ NA		
		能效标签 EnergyLabel	100%	对应的能效标签贴在风扇罩上. corresponding energy efficiency stick on the fan cover.	☒ Yes ☐ No ☐ NA	☒ Yes ☐ No ☐ NA		
		铭牌 Nameplate	100%	铭牌方向正确, 铭牌数据准确, 清晰, 固定牢固 The direction and data of nameplate are correct and clear and riveted tightly	☒ Yes ☐ No ☐ NA	☒ Yes ☐ No ☐ NA		
		轴头防锈 Antirust	100%	轴头, 法兰加工面防锈油均匀, 无锈蚀, 损伤和污痕 Apply antirust oil to exposing axis,no the corrosion, damage and the stain	☒ Yes ☐ No ☐ NA	☒ Yes ☐ No ☐ NA		
		固定/密封 Fix/Seal	100%	电机及箱体的连接螺丝无松动, 整机无漏油 Binding screw is not loose, and unit does not have the oil leak	☒ Yes ☐ No ☐ NA	☒ Yes ☐ No ☐ NA		
		包装 Packing	包装要求 Packing Requirements	防护 Safety	100%	减速机得到满足运输的防护 Transport protection are met	☒ Yes ☐ No ☐ NA	☒ Yes ☐ No ☐ NA
随机附件 Accessory	100%		附件/使用手册/合格证/装箱单/标签/等数量规格正确: Qty of OI, Certificate, Packing list, Label are complete	☒ Yes ☐ No ☐ NA	☒ Yes ☐ No ☐ NA			
其它 Others	特殊说明 Specification		100%	客户特殊包装要求须领会和理解清楚, 且严格遵照执行 Must understand Specification completely, carry out strictly.	☒ Yes ☐ No ☐ NA	☒ Yes ☐ No ☐ NA		
签字 Sign	装配Assemblying/日期Date			喷漆Painting/日期Date	包装Packing/日期Date		检验QC/日期Date	备注Remark
	郭清				朱存杰		薛中飞	2023/11/17

