

Modeling, Learning and Reasoning about Preference Trees over Combinatorial Domains

Xudong Liu

Advisor: Dr. Mirosław Truszczyński

Department of Computer Science
College of Engineering
University of Kentucky
Lexington, KY, USA
Wednesday, 4/20/2016

Preferences Are Ubiquitous




Figure : Preferences of different forms

Describing Preferences

Car1



<mvan, 7m, gray, big, honda, med, med>



Car2



<sedan, 5, blue, med, vw, med, med>

Figure : How to express preferences?

① How will I rate cars?

- For BodyType, I will assign 7 points to minivans, 5 to sedans, ...
- For Color, I will assign 8 points to blue, 4 to gray, ...

② What are the desired properties I see in cars?

- I prefer minivans to sedans, ...
- If minivan, I prefer gray to blue; if sedan, I prefer blue to gray; ...

Describing Preferences

Car1



<mvan, 7m, gray, big, honda, med, med>

Car2



<sedan, 5, blue, med, vw, med, med>



Figure : How to express preferences?

① How will I rate cars? (**Quantitative**)

- For BodyType, I will assign 7 points to minivans, 5 to sedans, ...
- For Color, I will assign 8 points to blue, 4 to gray, ...

② What are the desired properties I see in cars? (**Qualitative**)

- I prefer minivans to sedans, ...
- If minivan, I prefer gray to blue; if sedan, I prefer blue to gray; ...

Combinatorial Domains

Let \mathcal{I} be a finite set of attributes $\{X_1, \dots, X_p\}$, associated with a set of finite domains $\{Dom(X_1), \dots, Dom(X_p)\}$ for each attribute X_i . A *combinatorial domain* $CD(\mathcal{I})$ is a set of *objects* described by combinations of values from $Dom(X_i)$:

$$CD(\mathcal{I}) = \prod_{X_i \in \mathcal{I}} Dom(X_i).$$

Combinatorial Domains: Example

Domain of cars over set \mathcal{I} of p binary attributes:

① **BodyType**: {mvan, sedan}.

② **Capacity**: {5, 7m}.

③ **Color**: {blue, gray}.

⋮

$$CD(\mathcal{I}) = \underbrace{\{\langle \text{sedan}, 5, \text{blue}, \dots \rangle, \langle \text{mvan}, 7\text{m}, \text{gray}, \dots \rangle, \dots \}}_{2^p \text{ outcomes, too many!}}.$$

Combinatorial Domains: Example

Domain of cars:

- ① **BodyType**: {mvan, sedan, sport, suv}.
- ② **Capacity**: {2, 5, 7m}.
- ③ **Color**: {black, blue, gray, red, white}.
- ④ **LuggageSize**: {big, med, small}.
- ⑤ **Make**: {bmw, ford, honda, vw}.
- ⑥ **Price**: {low, med, high, vhigh}.
- ⑦ **Safety**: {low, med, high}.

Single Agent

Car1



<mvan, 7m, gray, big, honda, med, med>

Car2



<sedan, 5, blue, med, vw, med, med>



Figure : Dominance and Optimization

Multi-Agent



Figure : Social Choice and Welfare

Research Problems of Interest

- ① Preference representation formalisms to compactly model qualitative preferences over combinatorial domains.
- ② Preference elicitation and learning methods to cast preferences of agents as a theory in a preference formalism.
- ③ Preference reasoning tasks:
 - Dominance and optimization
 - Preference aggregation

Q: How do we compactly represent qualitative preferences over combinatorial domains?

- ① Preference Trees (P-trees)^{1,12}
- ② Partial Lexicographic Preference Trees (PLP-trees)⁸
- ③ Lexicographic Preference Trees (LP-trees)^{4,10}

¹Niall M Fraser. "Ordinal preference representations". In: Theory and Decision (1994)

²Xudong Liu and Mirosław Trzuszczynski. "Preference Trees: A Language for Representing and Reasoning about Qualitative Preferences". In: Proceedings of the 8th Multidisciplinary Workshop on Advances in Preference Handling (MPREF). 2014

³Xudong Liu and Mirosław Trzuszczynski. "Learning Partial Lexicographic Preference Trees over Combinatorial Domains". In: Proceedings of the 29th AAAI Conference on Artificial Intelligence (AAAI). 2015

⁴Richard Booth et al. "Learning conditionally lexicographic preference relations". In: ECAI. 2010

⁵Xudong Liu and Mirosław Trzuszczynski. "Aggregating Conditionally Lexicographic Preferences Using Answer Set Programming Solvers". In: Proceedings of the 3rd International Conference on Algorithmic Decision Theory (ADT). 2013

Q: How do we learn predictive qualitative preference models over combinatorial domains?

- ① Partial Lexicographic Preference Trees (PLP-trees)^{6,7,8}
 - Compute a (possibly small) PLP-tree consistent with all the data
 - Compute a PLP-tree that agrees with the data as much as possible
- ② Empirical Learning of PLP-trees and PLP-forests⁹

⁶Michael Schmitt and Laura Martignon. "On the complexity of learning lexicographic strategies". In: The Journal of Machine Learning Research (2006)

⁷József Dombi, Csanád Imreh, and Nándor Vincze. "Learning lexicographic orders". In: European Journal of Operational Research (2007)

⁸Xudong Liu and Mirosław Truszczynski. "Learning Partial Lexicographic Preference Trees over Combinatorial Domains". In: Proceedings of the 29th AAAI Conference on Artificial Intelligence (AAAI). 2015

⁹Xudong Liu and Mirosław Truszczynski. "Learning Partial Lexicographic Preference Trees and Forests over Multi-Valued Attributes". In: Review by ECAI-16 Program Committee

Q: How do we reason about preferences over combinatorial domains?

① Preference Reasoning and Aggregation^{10,11,12,13}:

- Dominance testing: $o_1 \succ_P o_2$?
- Optimality testing: $o_1 \succ_P o_2$ for all $o_2 \neq o_1$?
- Optimality computing: what is the optimal outcome wrt P ?
- Winner determination: which candidate wins the election?
- “Strong” candidate: a candidate with score more than a threshold?

¹⁰Xudong Liu and Mirosław Truszczynski. “Aggregating Conditionally Lexicographic Preferences Using Answer Set Programming Solvers”. In: Proceedings of the 3rd International Conference on Algorithmic Decision Theory (ADT). 2013

¹¹Jérôme Lang, Jérôme Mengin, and Lirong Xia. “Aggregating Conditionally Lexicographic Preferences on Multi-issue Domains”. In: CP. 2012

¹²Xudong Liu and Mirosław Truszczynski. “Preference Trees: A Language for Representing and Reasoning about Qualitative Preferences”. In: Proceedings of the 8th Multidisciplinary Workshop on Advances in Preference Handling (MPREF). 2014

¹³Xudong Liu and Mirosław Truszczynski. “Reasoning with Preference Trees over Combinatorial Domains”. In: Proceedings of the 4th International Conference on Algorithmic Decision Theory (ADT). 2015

- ① Modeling qualitative preferences:
 - Preference trees (P-trees)
 - Partial lexicographic preference trees (PLP-trees)
- ② Learning PLP-trees and PLP-forests
- ③ Aggregating LP-trees
- ④ Future research directions

- ① Modeling qualitative preferences:
 - Preference trees (P-trees)
 - Partial lexicographic preference trees (PLP-trees)
- Learning PLP-trees and PLP-forests
- Aggregating LP-trees
- Future research directions

BodyType(X_1): $\{\text{mvan}(x_{1,1}), \text{sedan}(x_{1,2}), \text{sport}(x_{1,3}), \text{suv}(x_{1,4})\}$.

Capacity(X_2): $\{2(x_{2,1}), 5(x_{2,2}), 7\text{m}(x_{2,3})\}$.

Price(X_6): $\{\text{low}(x_{6,1}), \text{med}(x_{6,2}), \text{high}(x_{6,3}), \text{vhigh}(x_{6,4})\}$.

- ① $V = \{x_{1,1}, \dots, x_{1,4}, \dots, x_{6,1}, \dots, x_{6,4}, \dots\}$.
- ② Propositional formula φ over V represents a set of outcome assignments satisfying φ .
 - $x_{1,2} \wedge (x_{6,1} \vee x_{6,2})$: affordable sedans.
 - $\neg x_{2,1} \wedge (x_{6,1} \vee x_{6,2})$: affordable cars with reasonable capacity.

Preference Trees (P-Trees)

Let φ , ψ , and π be propositional formulas over the set V of propositional variables.




Figure : A P-tree

$$\varphi \wedge \psi \succ \varphi \wedge \neg\psi \succ \neg\varphi \wedge \pi \succ \neg\varphi \wedge \neg\pi.$$

Preference Trees (P-Trees)

Let φ , ψ , and π be propositional formulas over the set V of propositional variables.




Figure : A P-tree

$$\varphi \wedge \psi \succ \varphi \wedge \neg\psi \succ \neg\varphi \wedge \pi \succ \neg\varphi \wedge \neg\pi.$$

Total preorder

Example: The Cars Domain

- ① **BodyType**(X_1): {mvan($x_{1,1}$), sedan($x_{1,2}$), sport($x_{1,3}$), suv($x_{1,4}$)}.
- ② **Capacity**(X_2): {2, 5, 7m}.
- ③ **Color**(X_3): {black, blue, gray, red, white}.
- ④ **LuggageSize**(X_4): {big, med, small}.
- ⑤ **Make**(X_5): {bmw, ford, honda, vw}.
- ⑥ **Price**(X_6): {low, med, high, vhigh}.
- ⑦ **Safety**(X_7): {low, med, high}.

Example: Preference Trees over Cars

BodyType(X_1): {mvan($x_{1,1}$), sedan($x_{1,2}$), sport($x_{1,3}$), suv($x_{1,4}$)}.

Color(X_3): {black, blue, gray, red, white}.

Price(X_6): {low, med, high, vhigh}.




Figure : A P-tree over cars¹⁴

¹⁴ $\varphi = (x_{1,1} \wedge x_{3,5}) \vee (x_{1,2} \wedge x_{3,2})$.

Example: Preference Trees over Cars

BodyType(X_1): {mvan($x_{1,1}$), sedan($x_{1,2}$), sport($x_{1,3}$), suv($x_{1,4}$)}.

Color(X_3): {black, blue, gray, red, white}.

Price(X_6): {low, med, high, vhigh}.




Figure : A P-tree over cars¹⁴

Car2 \succ *Car1*


¹⁴ $\varphi = (x_{1,1} \wedge x_{3,5}) \vee (x_{1,2} \wedge x_{3,2})$.

Compact Representation of P-trees


BodyType(X_1): {mvan($x_{1,1}$), sedan($x_{1,2}$), sport($x_{1,3}$), suv($x_{1,4}$)}.

Color(X_3): {black, blue, gray, red, white}.

Price(X_6): {low, med, high, vhigh}.




(a) Full




(b) Compact

Figure : Compact P-trees

Compact Representation of P-trees



(a) Full



(b) Compact

Figure : Compact P-trees

Compact Representation of P-trees

A *compact P-tree* over $CD(\mathcal{I})$ is a binary tree where

- 1 every node is labeled with a Boolean formula over \mathcal{I} , and
- 2 every non-leaf node t labeled with φ has either two outgoing edges (Fig. (a)), or one outgoing edge pointing straight-down (Fig. (b)), left (Fig. (c)), or right (Fig. (d)).







Figure : Compact P-trees

Relative Expressivity of Preference Languages



Computational Complexity Results

Dominance-testing (DOMTEST): $o_1 \succ_T o_2$?

Optimality-testing (OPTTEST): o optimal w.r.t T ?

Optimality-with-property (OPTPROP): is there optimal o with property α ?

- ① DOMTEST $\in P$
- ② OPTTEST $\in coNP$ -complete:
 - The complement problem is reduced from the SAT problem.
- ③ OPTPROP $\in \Delta_2^P$ -complete:
 - The problem is reduced from the Maximum Satisfying Assignment (MSA) problem.

- ① Modeling qualitative preferences:
 - Preference trees (P-trees)
 - Partial lexicographic preference trees (PLP-trees)
- Learning PLP-trees and PLP-forests
- Aggregating LP-trees
- Future research directions

The Cars Domain

- ① **BodyType(B)**: {mvan, sedan, sport, suv}.
- ② **Capacity(C)**: {2, 5, 7m}.
- ③ **Color(O)**: {black, blue, gray, red, white}.
- ④ **LuggageSize(L)**: {big, med, small}.
- ⑤ **Make(M)**: {bmw, ford, honda, vw}.
- ⑥ **Price(P)**: {low, med, high, vhigh}.
- ⑦ **Safety(S)**: {low, med, high}.

Partial Lexicographic Preference Trees (PLP-Trees)

A *PLP-tree* over $CD(\mathcal{I})$ is a tree, where

- 1 every non-leaf node t is labeled with an attribute $Attr(t)$ in \mathcal{I} ,
- 2 every non-leaf node t has $|Dom(Attr(t))|$ outgoing edges labeled with a value of $Attr(t)$, and
- 3 every attribute appears *at most* once on every branch.




Figure : A PLP-tree over cars

Partial Lexicographic Preference Trees (PLP-Trees)

A *PLP-tree* over $CD(\mathcal{I})$ is a tree, where

- 1 every non-leaf node t is labeled with an attribute $Attr(t)$ in \mathcal{I} ,
- 2 every non-leaf node t has $|Dom(Attr(t))|$ outgoing edges labeled with a value of $Attr(t)$, and
- 3 every attribute appears *at most* once on every branch.




Figure : A PLP-tree over cars

Total preorder

Partial Lexicographic Preference Trees (PLP-Trees)

Car1



<mvan, 7m, gray, big, honda, med, med>

Car2



<sedan, 5, blue, med, vw, med, med>






Figure : A PLP-tree over cars

Car2 \succ Car1

Compact Representations of PLP-Tree




(a) Full




(b) Compact

Figure : Unconditional Importance & Unconditional Preference (UIUP)

Compact Representations of PLP-Tree



(a) Full



(b) Compact

Figure : Unconditional Importance & Conditional Preference (UICP)

Compact Representations of PLP-Tree




Figure : Conditional Importance & Unconditional Preference (CIUP)

Lexicographic Preference Trees (LP-Trees)

- ① An *LP-tree* \mathcal{L} over $CD(\mathcal{I})$ is a PLP-tree, where
- each attribute appears **exactly once** on every path from the root to a leaf.
 - Unlike PLP-trees, an LP-tree induces a total order.

Conclusion

- ① Generalizing LP-trees, PLP-trees compactly represent total *preorders* over combinatorial domains, by allowing agents to specify, on each path, only a subset of attributes (i.e., those useful ones).
- ② P-trees further generalize PLP-trees by labeling the nodes with *propositional formulas*, in practice, usually built with small number (e.g., at most 3) of attributes.
- ③ PLP-trees and P-trees are closely related to other preference formalisms in the literature.


- Modeling qualitative preferences:
 - Preference trees (P-trees)
 - Partial lexicographic preference trees (PLP-trees)
- ② Learning PLP-trees and PLP-forests
- Aggregating LP-trees
- Future research directions

Learning PLP-trees

Consistent Learning (CONSLearn)

Given an example set \mathcal{E} , decide whether there exists a PLP-tree T (of a particular type) such that T is consistent with \mathcal{E} .

($\langle \text{sdn}, 5, \text{blk}, m, h, m, m \rangle, \langle \text{suv}, 7m, \text{wht}, b, f, m, m \rangle$)
($\langle \text{spt}, 2, \text{wht}, s, \text{bmw}, h, h \rangle, \langle \text{spt}, 2, \text{wht}, s, \text{bmw}, \text{vh}, h \rangle$)
($\langle \text{mvn}, 7m, \text{gry}, b, f, m, m \rangle, \langle \text{sdn}, 5, \text{bl}, m, f, m, m \rangle$)



UIUP tree

Learning PLP-trees


Small Learning (SMALLLEARN)

Given an example set \mathcal{E} and a positive integer l ($l \leq |\mathcal{E}|$), decide whether there exists a PLP-tree T (of a particular type) such that T is consistent with \mathcal{E} and $|T| \leq l$.

($\langle \text{sdn}, 5, \text{blk}, m, h, m, m \rangle, \langle \text{suv}, 7m, \text{wht}, b, f, m, m \rangle$)

($\langle \text{spt}, 2, \text{wht}, s, \text{bmw}, h, h \rangle, \langle \text{spt}, 2, \text{wht}, s, \text{bmw}, \text{vh}, h \rangle$)

($\langle \text{mvn}, 7m, \text{gry}, b, f, m, m \rangle, \langle \text{sdn}, 5, \text{bl}, m, f, m, m \rangle$)



UIUP tree

Learning PLP-trees

Maixmal Learning (MAXLEARN)


Given an example set \mathcal{E} and a positive integer k ($k \leq m$), decide whether there exists a PLP-tree T (of a particular type) such that T satisfies at least k examples in \mathcal{E} .

($\langle \text{sdn}, 5, \text{blk}, m, h, m, m \rangle, \langle \text{suv}, 7m, \text{wht}, b, f, m, m \rangle$)

($\langle \text{spt}, 2, \text{wht}, s, \text{bmw}, h, h \rangle, \langle \text{spt}, 2, \text{wht}, s, \text{bmw}, \text{vh}, h \rangle$)

($\langle \text{mvn}, 7m, \text{gry}, b, f, m, m \rangle, \langle \text{sdn}, 5, \text{bl}, m, f, m, m \rangle$)

($\langle \text{suv}, 7m, \text{gry}, b, \text{vw}, \text{vh}, m \rangle, \langle \text{suv}, 7m, \text{gry}, b, \text{vw}, h, m \rangle$)



UIUP tree

Complexity Results on PLP-trees

	UP	CP
UI	P	NP
CI	NPC ¹⁵	P

(a) CONSLearn

	UP	CP
UI	NPC	NPC
CI	NPC	NPC

(b) SMALLLearn

	UP	CP
UI	NPC ¹⁶	NPC
CI	NPC	NPC

(c) MAXLearn

Figure : Complexity results for learning PLP-trees

¹⁵Booth et al., *Learning Conditionally Lexicographic Preference Relations*, 2010.

¹⁶Schmitt and Martignon, *On the Complexity of Learning Lexicographic Strategies*, 2006.

Experimentation




Figure : PLP-tree learning system

Datasets

Dataset	p	$ \mathcal{X} $	$ \mathcal{E}^> $	$ \mathcal{E}^{\approx} $
BreastCancerWisconsin	9	270	9,009	27,306
CarEvaluation	6	1,728	682,721	809,407
CreditApproval	10	520	66,079	68,861
GermanCredit	10	914	172,368	244,873
Ionosphere	10	118	3,472	3,431
MammographicMass	5	62	792	1,099
Mushroom	10	184	8,448	8,388
Nursery	8	1,266	548,064	252,681
SPECTHeart	10	115	3,196	3,359
TicTacToe	9	958	207,832	250,571
Vehicle	10	455	76,713	26,572
Wine	10	177	10,322	5,254

Figure : Preference Learning Library¹⁷


¹⁷<http://www.cs.uky.edu/~liu/preflearnlib.php>

Experimental Results: Best-Agreement vs. Greedy


Dataset	BA-UIUP	G-UIUP
BreastCancerWisconsin	88.4	88.2
CarEvaluation	84.8	83.6
CreditApproval	91.1	89.3
GermanCredit	72.2	72.2
Ionosphere	87.0	79.6
MammographicMass	87.5	86.8
Mushroom	84.8	70.3
Nursery	91.8	91.7
SPECTHeart	93.2	92.6
TicTacToe	72.1	71.9
Vehicle	76.8	76.6
Wine	96.0	95.5

Table : Accuracy (percentage of correctly handled testing examples) for UIUP PLP-trees learned using the best-agreement and the greedy methods on the learning data (250 of $\mathcal{E}^>$)


Experimental Results: Best-Agreement vs. Greedy




(a) CarEvaluation



(b) Ionosphere



(c) Mushroom



(d) Wine

Figure : Learning curves solving MAXLEARN for UIUP PLP-trees

Experimental Results: Greedy

Dataset	UIUP	CIUPB	CIUPD	CICP
BreastCancerWisconsin	90.7	91.0	90.7	91.4
CarEvaluation	85.8	85.8	85.9	86.0
CreditApproval	91.4	91.6	92.0	92.2
GermanCredit	74.3	74.3	74.5	75.7
Ionosphere	87.1	87.2	88.5	90.4
MammographicMass	88.2	87.3	86.9	90.0
Mushroom	71.6	77.1	75.6	76.6
Nursery	92.9	93.0	93.0	93.0
SPECTHeart	93.4	95.4	94.8	95.7
TicTacToe	73.9	74.4	75.4	76.2
Vehicle	79.2	80.3	80.0	81.2
Wine	95.5	97.8	97.5	97.8

Table : Accuracy percents on the testing data (30% of \mathcal{E}^{\succ}) for UIUP, CIUP and CICP PLP-trees, using models learned by the greedy algorithm from the learning data (the other 70% of \mathcal{E}^{\succ})

Experimental Results: Sizes of PLP-trees by Greedy

Dataset	UIUP	CIUPB	CIUPD	CICP
BreastCancerWisconsin	6.7	19.8	28.0	25.7
CarEvaluation	6.0	73.2	108.9	109.5
CreditApproval	9.0	31.3	78.6	81.1
GermanCredit	9.7	49.8	210.3	190.0
Ionosphere	9.6	19.8	31.5	30.6
MammographicMass	4.5	8.3	10.8	10.0
Mushroom	7.6	15.7	22.7	16.3
Nursery	8.0	56.2	121.0	116.9
SPECTHeart	8.4	13.0	18.4	19.0
TicTacToe	8.0	36.8	126.8	115.2
Vehicle	9.0	33.9	101.3	105.4
Wine	5.1	14.2	16.9	14.6

Table : Sizes of trees learned by the greedy algorithm from the training data (70% of \mathcal{E}^{γ})

Partial Lexicographic Preference Forests (PLP-Forests)

- ① Inspired by *random forests*, we proposed *PLP-forests* that are sets of PLP-trees; thus, the four classes.
- ② To reduce the overfitting of a PLP-tree, a PLP-forest
 - consists of *diverse* trees (learned from *small* training samples), and
 - aggregates its constituent trees using the *Pairwise Majority Rule* (PMR).

Experimental Results: Best-Agreement vs. Greedy

Dataset	BA+UIUP	G+UIUP
BreastCancerWisconsin	95.1	93.4
CarEvaluation	89.2	91.9
CreditApproval	93.1	91.5
GermanCredit	77.9	75.4
Ionosphere	92.5	83.0
MammographicMass	90.8	89.1
Mushroom	90.2	78.8
Nursery	94.0	93.2
SPECTHeart	94.9	93.7
TicTacToe	77.2	75.1
Vehicle	81.9	82.7
Wine	96.9	95.8


Table : Accuracy percents on the testing data (30% of \mathcal{E}^{\sim}) for UIUP trees and forests of 5000 UIUP trees, using the greedy and the best-agreement algorithms from the learning data (the other 70% of \mathcal{E}^{\sim})

Experimental Results: Greedy


Dataset	UIUP	CIUPB	CICP
BreastCancerWisconsin	93.4	93.7	94.0
CarEvaluation	91.9	91.4	91.4
CreditApproval	91.5	92.8	93.0
GermanCredit	75.4	76.1	76.2
Ionosphere	83.0	89.3	89.5
MammographicMass	89.1	90.0	90.2
Mushroom	78.8	92.2	91.8
Nursery	93.2	93.3	93.4
SPECTHeart	93.7	93.6	93.7
TicTacToe	75.1	76.6	76.9
Vehicle	82.7	83.2	83.4
Wine	95.8	97.5	97.8

Table : Accuracy percents on the testing data (30% of \mathcal{E}^{\succ}) for UIUP, CIUP and CICP PLP-forests of 5000 trees, using the greedy algorithm from the learning data (the other 70% of \mathcal{E}^{\succ})


Experimental Results: UIUP vs. CICP




(a) CarEvaluation



(b) Ionosphere



(c) Mushroom



(d) Wine

Figure : Greedy learning curves solving MAXLEARN for PLP-forests

Conclusion

- ① PLP-trees and PLP-forests are *expressive* preference models.
- ② PLP-forests aggregated by PRM provide in general *higher* accuracy than PLP-trees.
- ③ PLP-trees and PLP-forests learned by a greedy approximation method have accuracy *comparable* to best-agreement PLP-trees and PLP-forests.
- ④ The greedy algorithms are *fast*, can work with *large* datasets (of \sim half million examples), and can compute *small* models.

- Modeling qualitative preferences:
 - Preference trees (P-trees)
 - Partial lexicographic preference trees (PLP-trees)
- Learning PLP-trees and PLP-forests
- ③ Aggregating LP-trees
- Future research directions

Positional Scoring Rules

- k -approval: $(1, \dots, 1, 0, \dots, 0)$ with k being the number of 1's.
- (k, l) -approval: $(c, \dots, c, d, \dots, d, 0, \dots, 0)$, where c and d are constants ($c > d$), and the numbers of c 's and d 's equal to k and l .
- b -Borda: $(b, b - 1, \dots, b - m + 1)$, where b is a constant and m is the number of candidates.

The Evaluation and Winner Problems

The Evaluation Problem

Let r be a positional scoring rule with a scoring vector w , \mathcal{C} a class of LP-trees. Given a \mathcal{C} -profile P of n LP-trees over p attributes and a positive integer R , the *evaluation* problem is to decide whether there exists an alternative $o \in \mathcal{X}$ such that $s_w(o, P) \geq R$.

The Winner Problem

Let r be a positional scoring rule with a scoring vector w , \mathcal{C} a class of LP-trees. Given a \mathcal{C} -profile P of n LP-trees over p attributes, the *winner* problem is to compute an alternative $o \in \mathcal{X}$ with the maximum score $s_w(o, P)$.

Complexity of the Evaluation Problem: k -Approval

	UP	CP
UI	P	P
CI	P	P

(a) $k = 2^{p-1} \pm f(p)$, $f(p)$ is a poly

	UP	CP
UI	NPC	NPC
CI	NPC	NPC

(b) $k = 2^{p-c}$, $c > 1$ is a const

Figure : k -Approval

Complexity of the Evaluation Problem: (k, l) -Approval

	UP	CP
UI	P	P
CI	P	P

(a) $k = l = 2^{p-1}$

	UP	CP
UI	NPC	NPC
CI	NPC	NPC

(b) $k = l = 2^{p-c}$, $c > 1$ is a const

Figure : (k, l) -Approval

Complexity of the Evaluation Problem: b -Borda

	UP	CP
UI	P	NPC
CI	NPC	NPC

(a) $b = 2^p - 1$

	UP	CP
UI	NPC	NPC
CI	NPC	NPC

(b) $b = 2^{p-c} - 1$, $c \geq 1$ is a const

Figure : b -Borda

Conclusion

- ① When votes are total orders of candidates, computing a winner for a positional voting rule is computationally easy; not necessarily so, when they are LP-trees over combinatorial domains.
- ② For the cases when determining a winner is computationally hard, we solved this problem using ASP and empirically showed that ASP tools are *effective* on large instances (up to 3000 votes over up to 20 binary attributes).

- ① The languages of P-trees and PLP-trees:
 - P-trees are expressive with labels being propositional formulas.
 - PLP-trees are P-trees with labels being attributes.
 - Both are closely related to existing preference formalisms.
- ② Learning PLP-trees and PLP-forests:
 - PLP-trees are highly accurate in modeling preferences arising in practice, and can be effectively learned.
 - PLP-forests, collections of PLP-trees, are empirically shown with reduced overfitting and higher accuracy.
- ③ Aggregating LP-trees:
 - Preference aggregation problems for LP-trees using positional scoring rules are in general NP-hard.
 - Answer-set programming tools are effective for large instances.

- Modeling qualitative preferences:
 - Preference trees (P-trees)
 - Partial lexicographic preference trees (PLP-trees)
- Learning PLP-trees and PLP-forests
- Aggregating LP-trees
- ④ Future research directions

Data-Driven Preference Learning:

① Recommender Systems¹⁸:

- Collaborative
- Content-based
- Hybrid

② Machine Learning (fitting function):

- Supervised learning (e.g., decision trees, random forests)
- Label ranking¹⁹

③ Model-based Learning (learning interpretable decision models):

- Preference Elicitation (Human-in-the-Loop)
- Conditional Preference Networks, Preference Trees
- Stochastic Models (e.g., Choquet integral²⁰, TOPSIS-like models²¹)

¹⁸Gediminas Adomavicius and Alexander Tuzhilin. "Toward the next generation of recommender systems: A survey of the state-of-the-art and possible extensions". In: Knowledge and Data Engineering, IEEE Transactions on (2005)

¹⁹Eyke Hüllermeier et al. "Label ranking by learning pairwise preferences". In: Artificial Intelligence (2008)

²⁰Ali Fallah Tehrani, Weiwei Cheng, and Eyke Hüllermeier. "Choquistic Regression: Generalizing Logistic Regression using the Choquet Integral." In: EUSFLAT. 2011

²¹Manish Agarwal, Ali Fallah Tehrani, and Eyke Hüllermeier. "Preference-based Learning of Ideal Solutions in TOPSIS-like Decision Models". In: Journal of Multi-Criteria Decision Analysis (2014)

Preference Reasoning and Applications:

- ① Social Choice and Welfare^{22,23}:
 - Voting
 - Fair division
 - Strategyproof Social Choice
- ② Automated Planning and Scheduling^{24,25,26}:
 - Travel scheduling
 - Manufacturing
 - Traffic control

²²Kenneth J Arrow, Amartya Sen, and Kotaro Suzumura. Handbook of Social Choice and Welfare. Vol. 1 & 2. 2010

²³Felix Brandt, Vincent Conitzer, and Ulle Endriss. "Computational social choice". In: Multiagent systems (2012)

²⁴Tran Cao Son and Enrico Pontelli. "Planning with preferences using logic programming". In: Theory and Practice of Logic Programming (2006)

²⁵Meghyn Bienvenu, Christian Fritz, and Sheila A McIlraith. "Specifying and computing preferred plans". In: Artificial Intelligence (2011)

²⁶Hannah Bast et al. "Route planning in transportation networks". In: arXiv preprint (2015)

Questions?

Thank you!