

Genealogical Tree

Find all the descendant on any level of ancestry

0.0.1_be300d6

Generated:
Sun Jul 12 2015 21:16:27 on user@Andress-MacBook-Pro.local

Git Commit Hash:
be300d6

Git Details:
be300d6 (HEAD, origin/master, origin/develop, origin/HEAD, master, develop) Merge branch 'master' into develop

Contents

1	Genealogical Tree	1
1.1	Summary	1
1.2	Approach	1
2	Portability and documentation	3
2.1	Containers	3
2.1.1	NGINX server	3
2.2	Platforms	3
2.2.1	DEB Linux Type	3
2.2.2	RPM Linux type	4
2.2.3	OSX type	5
2.2.4	Windows type	5
2.3	Working with binaries & documentation	5
2.4	Generate only documentation	6
2.5	IDE hints	6
2.5.1	Atom	6
2.5.2	NGINX server	6
2.6	Development details	7
2.6.1	Code	7
2.6.2	DEB Linux Type	7
3	Generate diagrams from code or documentation	9
3.1	Working with binaries & documentation	9
3.2	Low level considerations	9
4	Templates to gather external information	10
4.1	Generate only documentation	10
5	Test your application	11
6	Measure your application	12
7	Simulate deployment infrastructure	13

8	Application Core Code	14
8.1	Summary	14
8.2	Realistic limits	14
8.3	Approach	14
9	Class Index	16
9.1	Class List	16
10	File Index	17
10.1	File List	17
11	Class Documentation	18
11.1	struct_index_t Struct Reference	18
11.2	union_id_t Union Reference	18
12	File Documentation	19
12.1	src/id.h File Reference	19
12.1.1	Detailed Description	19
12.2	src/main.cpp File Reference	20
12.2.1	Function Documentation	20
12.2.1.1	main	20
12.3	src/version.h File Reference	20
12.3.1	Detailed Description	20
12.3.2	Macro Definition Documentation	21
12.3.2.1	DEFINE_VERSION	21
	Index	22

Chapter 1

Genealogical Tree

1.1 Summary


Program should be able to **find all the descendant with name Bob for all the ascendants with name Will on any level of ancestry**. In order to present the capabilities of your app:

- implement the application to optimize the initialization time.
- application should have built in data about genealogical tree of people living in particular country.
- please generate a representative data that has sample people and relationships between them. Use all varieties of names (can be also generated) but also put two test names (Bob and Will) and connect them in different relationships.
- the application should possess tests that are checking possible edge cases and ensure the stability of the application.
- the designed data structure should ensure optimized search time on following fields: name, last name, date of birth and location.

1.2 Approach

Instead of starting directly with the problem core, don't test thoroughly edge cases, leaping into too early optimization, don't document your results/decisions/mistakes and ending with an app that only runs partially on your development environment, the **approach** will be the opposite one.

1. [Ensure a minimum of portability](#) on different environments.
2. [Generate diagrams from codex and documentation](#) to be able to track down all the changes.
3. [Use templates to gather external information](#) to document as much automatically as possible.
4. [Write tests](#) to cover your app and let you optimize knowing you're not breaking previous development.
5. [Measure your application](#) in order to compare improvements/regressions during the optimization stage.
6. [Simulate your deployment infrastructure](#) to hunt down integration issues as soon as possible.
7. [Solve the core problem](#) in the most simple and maintainable way at our disposal.



No doubt this approach is an overkill for a pet project but it's way more realistic for big, long C++ ones.

Chapter 2

Portability and documentation

A Modern C++ GNU compiler, g++ 4.9.2 or above, and a recent cmake, 3.1 or above, are the minimum. As well a valid *boost* library is supposed to be installed.

Mock servers are basically a bunch of **nodejs** and **go** scripts, so those languages are needed if you plan to execute or modify them. The recommended way to install **nodejs** and **go** is using **nvm** and **gvm** if possible.

2.1 Containers

Some **Dockerfiles** are provided to relieve the burden of installing. For example, getting a **documentation server**. One option to manage those *Docker* containers on *OSX* and *Windows* might be **Kitematic**

As well you can go directly for **Linux Containers** or mix both containers technologies. Visit **learning tools** for further instructions and related **vagrant** files.

2.1.1 NGINX server

A very simple **Dockerfile** is provided in the *doc* folder following **nginx example**

```
cd <project git folder>/doc
docker build -t nginx/doc .
docker run --name nginx_doc -d -p 8080:80 nginx/doc
```

Note: If you happen not to work on **Linux**, you should first install some *Linux Virtual Machine* as **docker server**. One option is to let **Kitematic** deal with that detail and use its *Docker CLI*.

2.2 Platforms

Several platforms were tested to some extent, although **Ubuntu** and **OSX** have been more thoroughly checked out:

2.2.1 DEB Linux Type

Regarding to documentation, *doxygen*, *latex*, *graphviz* and *plantuml.jar* are needed. For example, if you work with **Xubuntu** 15.04 or its **Docker** equivalent, the following commands might do the trick for you:

```
sudo apt-get -y install git build-essential libboost-all-dev
sudo apt-get -y install doxygen doxygen-latex openjdk-8-jdk graphviz
sudo add-apt-repository -y ppa:george-edison55/cmake-3.x
sudo apt-get -y update
sudo apt-get -y install cmake
sudo apt-get -y upgrade
```

```
sudo mkdir /opt/plantuml && sudo chmod a+wr /opt/plantuml
wget http://sourceforge.net/projects/plantuml/files/plantuml.jar/download \
-O /opt/plantuml/plantuml.jar
```

If you want to use latest *compiler*, you can use an *extra repository*:

```
sudo add-apt-repository ppa:ubuntu-toolchain-r/test
sudo apt-get update
sudo apt-get install gcc-5 g++-5
```

But then you might want to *compile newer *boost* libraries* with that compiler.

2.2.2 RPM Linux type

Another typical Linux platform is **CentOS**. Their **gcc** and **cmake** are very conservative, even for *CentOS 7*, so compile newer ones from **source code** might be a possibility:

CMake:

Download *tar.gz* with latest version and *untar* its source code

```
cd <building directory>
./bootstrap --prefix=/opt/cmake --mandir=/opt/cmake/man --docdir=/opt/cmake/doc
make
sudo make install
```

Compiler:

It's going to take long so try to use all the cores you got

```
mkdir ~/sourceInstallations
cd ~/sourceInstallations
svn co svn://gcc.gnu.org/svn/gcc/tags/gcc_5_1_0_release/
cd gcc_5_1_0_release/
./contrib/download_prerequisites
cd ~/sourceInstallations
mkdir gcc_5_1_0_release_build/
cd gcc_5_1_0_release_build/
../gcc_5_1_0_release/configure --enable-languages=c,c++ --prefix=/opt/gcc \
--program-suffix=-5 --disable-multilib
make -j <number of cores>
sudo make install

cd /usr/bin
sudo ln -s /opt/gcc/bin/gcc-5 gcc-5
sudo ln -s /opt/gcc/bin/g++-5 g++-5
```

Boost:

A long compilation that needs to *be told where* to get the proper *toolset*.

```
cd <folder with source code>
cp tools/build/example/user-config.jam .
```

Don't forget to edit *user-config.jam* to point to **g++-5**, i.e., using *gcc : 5 : /opt/gcc/bin/g++-5*

```
using gcc : 5 : /opt/gcc/bin/g++-5
:
<dll-path>/opt/gcc/lib64:/opt/gcc/boost/lib
<harcode-dll-paths>true
<cxxflags>-std=c++14
<cxxflags>-Wl,-rpath=/opt/gcc/lib64:/opt/gcc/boost/lib
<linkflags>-rpath=/opt/gcc/lib64:/opt/gcc/boost/lib
;
```

Note: Not all the targets might be created. If some of the missing ones are required for your apps, try to hack *boost* compilation scripts.


```
./bootstrap.sh --prefix=/opt/gcc/boost --with-toolset=gcc
sudo ./b2 -j8 install toolset=gcc-5 --prefix=/opt/gcc/boost \
    threading=multi define=BOOST_SYSTEM_NO_DEPRECATED stage release
```

Note: Take into account when compile with 'g++-5' on one Linux platform that got its own previous compiler version, you should let know to the **linker** where to get 'g++-5' libraries. Try to avoid **LD_LIBRARY_PATH** and use instead **RPATH**:

```
g++-5 -pthread --std=c++14 -Wl,-rpath=/opt/gcc/lib64 <rest of options>
```

In case of your linking against *boost* generates too many *auto_ptr* deprecated warnings:

```
g++-5 -pthread -std=c++14 -Wno-deprecated -Wl,-rpath=/opt/gcc/lib64:/opt/gcc/boost/lib \
    -I/opt/gcc/boost/include -L/opt/gcc/boost/lib -lboost_program_options <rest of options>.
```

Hint: If you generate those *cmake*, *gcc* and *boost* on one machine and then copy them onto another, remember that there is ****soft links** involved**.

2.2.3 OSX type

In order to use *GNU* compiler instead of *XCode clang* one, there are several options. The one followed for this project was *Homebrew*.

Note: If you happen to work with *OSX* and *Homebrew*, don't forget to compile **boost** with the previous **gcc** compiler, not with the default *clang* one:

```
brew install gcc
brew install boost --cc=gcc-5
```

2.2.4 Windows type

As well there are several options to get your *GNU* chaintool ready on windows instead of *Visual Studio*. For example, *Git* and *MinGW*.

Another option might be following *MSYS2* instruction:

```
pacman -Syu
pacman -S mingw-w64-x86_64-toolchain mingw-w64-x86_64-pkgconf make
pacman -S git mingw-w64-x86_64-cmake-git
```

2.3 Working with binaries & documentation

Usual commands:

```
mkdir build
cd build
cmake ..
make
make doc
```

Optionally you can invoke *make install* to install binaries or *make install_doc* / *make show* to install / preview documentation.

Note: If you happen to work with *OSX* and *Homebrew*, don't forget to invoke *cmake* pointing to the **GNU** compiler:

```
cmake -DCMAKE_CXX_COMPILER=/usr/local/bin/g++-5 ..
```

Note: If you happen to work with *Windows* and *Git/MinGW*, don't forget to invoke *cmake* pointing to the **GNU** generator:

```
cmake -G "MSYS Makefiles" ..
```

As well a script, called **show** or something similar, will be created in your *home* directory as a shortcut for generating & viewing documentation. Don't hesitate to use it as a *template* for your specific environment.

2.4 Generate only documentation

Similar commands to the previous ones, just the compiler is not required:

```
mkdir build
cd build
cmake -DONLY_DOC=TRUE ..
make doc
```

Note: If you happen to work with *Windows* and *Git/MinGW*, don't forget to invoke *cmake* pointing to the **GNU** generator:

```
cmake -G "MSYS Makefiles" -DONLY_DOC=TRUE ..
```

Note: If your **make** utility is not installed in the default place, define *CMAKE_BUILD_TOOL*

```
cmake -G "MSYS Makefiles" -DCMAKE_BUILD_TOOL=<your location> -DONLY_DOC=TRUE ..
```

As well, if you installed the documentation utility with **make show**, you're supposed to be able to recreate and view that documentation PDF through usual *ssh* connection with enabled X11:

```
ssh -X <user>@<location> "./show"
```

Note: By default **make install_doc** or **make show** copy the documentation *PDF* with the default project name in your **home** directory. You can define that target file with:

```
cmake <rest of options> -DDOC_PDF=<your path & name, ending in .pdf> ..
```

2.5 IDE hints

Apart from the omnipresent **vim**, a couple of *IDE* were used:

2.5.1 Atom

Basically for **nodejs** and **go** code.

To use **Atom** don't forget to install plugins for *markdown* and *html* previews. As well for *running make* files and edit *cmake* files.

Note: Two *Vim* plugins, *vim-mode* and *ex-mode*, might be downloaded if you're accustomed to that editor.

Note: If you happen to be only interested on generating documentation, don't forget to configure *doc* task at **make-runner** plugin when *build/Makefile* is selected.

2.5.2 NGINX server

Basically for **java** and **C++** code.

To use **NetBeans** don't forget to configure a *cmake* project with *custom build* folder. Add at that moment any extra customization in the command line used by *cmake* instruction. For example:

- `-DCMAKE_CXX_COMPILER=g++-5` for **OSX**
- `-DONLY_DOC=TRUE` for only documentation on **Linux/OSX**
- `-G "MSYS Makefiles"` for **Windows**
- `-G "MSYS Makefiles" -DONLY_DOC=TRUE` for only documentation on **Windows**

Note: If you happen to use *jVi* plugin on *OSX*, don't forget to use `-lc` instead of just `-c` for its `/bin/bash` flag.

Note: If you happen to be interested on launching *image* and *documentation*, don't forget to add *image* and *doc* tasks when *build/Makefile* is selected.

2.6 Development details

In order to generate binaries & documentation, the following versions were used:

2.6.1 Code

Pay attention to *cmake* and *gcc* versions. A minimum is required to work on several O.S. using modern C++. Feel free to locally hack **CMakeLists.txt** to meet your needs.

Linux (Xubuntu 15.04)

- **cmake** 3.2.2
- **gcc** 5.1
- **boost** 1.55

OSX (Yosemite 10.10.4)

- **cmake** 3.2.2
- **gcc** 5.1
- **boost** 1.58

Windows (Win7 x64)

- **cmake** 3.3.0
- **gcc** 5.1
- **boost** 1.58

2.6.2 DEB Linux Type

Environment variables to locate PlantUML *jar* and default *PDF* viewer can be defined to overwrite default values. See **CMakeLists.txt** for further information on your platform.

Linux

- **doxygen** 1.8.9.1
- **latex/pdfTeX** 2.6-1.40.15
- **graphviz/dot** 2.38.0
- **java/plantuml** 1.8.0_45/8026

OSX

- **doxygen** 1.8.9.1
- **latex/pdfTeX** 2.6-1.40.15
- **graphviz/dot** 2.38.0
- **java/plantuml** 1.8.0_40/8026

Windows

- **doxygen** 1.8.9.1
- **latex/pdfTeX** 2.9.5496-1.40.15
- **graphviz/dot** 2.38.0
- **java/plantuml** 1.8.0_45/8026

Note: Don't forget to configure *Doxyfile* and *CMakeLists.txt* to use **README.md** as *Main Page* for **latex** documentation.

Note: Don't repeat initial word at sections & subsections in the **README.md** files. That first word will be used as internal **ref** for **latex** documentation.

Chapter 3

Generate diagrams from code or documentation

Diagrams related directly to the current code are a key part of any kind of technical documentation. As well being able to track down partial changes **inside** of those images along the code itself right out off the bat it's a huge improvement.

3.1 Working with binaries & documentation

Note: Use different names for any image you create

Generated images are saved at *image* folder, regardless from where defined at the project. So when you refer to them from **markdown** README.md files, you should user *relative paths*.

But **doxygen** *latex* documentation goes directly to that folder, so use just the name of the image.

3.2 Low level considerations


The tool is **PlantUML** and the format usually used is **PNG**. The reason behind was that **metadata** information is embedded into those photos and it might be checked out images before even generating them. This way you can save a huge deal of time at big projects and avoid stesssing too much your *GIT* repositories with binaries.

As well **SVG** format will be used by *Presentation* as *Sozi*. Being pure text are more *friendly* to *GIT* but being able to contain **code**, *GitHub* and other repositories prevent them from being renderized for your README.md files.

Chapter 4

Templates to gather external information

The basic external information to be included is **GIT COMMIT HASH**. This way *code* and *documentation* are related by this piece of information.



As well information on the machine where **cmake** was invoked is collected.

Note: Take into account that **the last commit** information will be processed; if there are new changes not yet committed, they will be included anyway. So in order to generate *final official* documentation first commit all your changes, generate the documentation and, if needed, commit that generated document.

4.1 Generate only documentation

In order to add the specific **git commit hash** into code & documentation, *templates* are defined in the *template* folder for **Doxyfile**, **header.tex** & **version.h** files.



In order to **speed up** local compilations and let us hardcode our locally generated files, it's possible to instruct **cmake** to use this hardcoded header instead of usual GIT one.

The parameter to pass onto **cmake** is **VERSION_HARDCODED**:

```
cmake <rest of options> -DVERSION_HARDCODED=TRUE ..
```

Chapter 5

Test your application

Taking advantage of *boost* test cases as explained at [An Engineer's Guide to Unit Testing](#).

Chapter 6

Measure your application

Scripts to gather information on performance. Basically *statistical information* on execution time of different approaches.

Chapter 7

Simulate deployment infrastructure

An humble `electron` application to supervise different mock services that simulate the real project. Those mock services might be just `Docker` containers with a bunch of `nodejs` and/or `go` scripts.

Chapter 8

Application Core Code

Source folder for headers & code files directly involved with the core problem.

8.1 Summary

Some steps will be taken in order to circle problem to a manageable number of possibilities

8.2 Realistic limits

First of all, we should grasp a rough idea about which range of numbers to consider:

- Most Populous Country: China
Inhabitants: **around** 1400000000
- Another populous country, culturally diverse: USA
Number of first & last names: **around** 5200 & 152000
- Example of baptism registers: Ireland
Roman Catholic: **around** 19th century
- Marriageable age: world
Some common value: **around** 20
- Number of locations: India
Number of villages: **around** 640000

8.3 Approach

This way we can assume that taking into account around 200 years of sensible information on our ascendants, around 10 generations back in time, we suppose not to deal with more than 4000000000 individuals.

As well, we could consider that our application should only tackle around different 6000 first names or 60000 last names in our given country. Even we can take for granted that there aren't more than 60000 locations, that we might classify them in two levels; one coarse level easy to remember and another fine one more close to small places.

Translate into C++:

- First Name: unsigned short int (uint16_t)

- Last Name: unsigned short int (uint16_t)
- Year of Birth: unsigned char (uint8_t) < 200 years
- Coarse Location of Birth: unsigned short int (uint8_t)
- Month of Birth: unsigned char (uint8_t)
- Day of Birth: unsigned char (uint8_t)
- Fine location of Birth: unsigned short int (uint8_t)
- More information related to a specific subject: extra indexes.

This way we can use the **first 64 bits of information** as a valid **identification** for the individuals and with the advantage of getting the relevant information to debug first: *name and generation*.

Chapter 9

Class Index

9.1 Class List

Here are the classes, structs, unions and interfaces with brief descriptions:

struct_index_t	18
union_id_t	18

Chapter 10

File Index

10.1 File List

Here is a list of all documented files with brief descriptions:

src/ id.h	19
src/ main.cpp	20
src/ version.h	20

Chapter 11

Class Documentation

11.1 `struct_index_t` Struct Reference

Public Attributes

- char **year**

The documentation for this struct was generated from the following file:

- [src/id.h](#)

11.2 `union_id_t` Union Reference

Public Attributes

- uint64_t **id**
- [struct_index_t](#) **index**

The documentation for this union was generated from the following file:

- [src/id.h](#)

Chapter 12

File Documentation

12.1 src/id.h File Reference

```
#include <stdint>
#include <iostream>
```

Classes

- struct [struct_index_t](#)
- union [union_id_t](#)

Functions

- `std::ostream & operator<< (std::ostream &os, const union_id_t &u)`

Variables

- `static constexpr const union_id_t EMPTY_UNION_ID {0}`

12.1.1 Detailed Description

Define types for id's for our subjects

A first approach of getting packed id & basic information in form of indexes:

- First Name: unsigned short int ([uint16_t](#))
- Last Name: unsigned short int ([uint16_t](#))
- Year of Birth: unsigned char ([uint8_t](#)) < 200 years
- Coarse Location of Birth: unsigned short int ([uint8_t](#))
- Month of Birth: unsigned char ([uint8_t](#))
- Day of Birth: unsigned char ([uint8_t](#))

Grouping all that indexes we got a 64 bits identification

12.2 src/main.cpp File Reference

```
#include <iostream>
#include "version.h"
#include "id.h"
```

Functions

- int `main` (int argc, char **argv)
Main function.

12.2.1 Function Documentation

12.2.1.1 int main (int *argc*, char ** *argv*)

Main function.

Parameters

<i>argc</i>	An integer argument count of the command line arguments
<i>argv</i>	An argument vector of the command line arguments

Returns

an integer 0 upon exit success

12.3 src/version.h File Reference

Macros

- #define **DEFINE_VERSION_FIRST** "0"
- #define **DEFINE_VERSION_MIDDLE** "0"
- #define **DEFINE_VERSION_LAST** "1"
- #define **DEFINE_GIT_DETAILS** "be300d6 (HEAD, origin/master, origin/develop, origin/HEAD, master, develop) Merge branch 'master' into develop"
- #define **DEFINE_GIT_COMMIT_HASH** "be300d6"
- #define **DEFINE_VERSION**

Variables

- static const char * **VERSION** = "VERSION = " DEFINE_VERSION
- static const char * **GIT_DETAILS** = "GIT_DETAILS = " DEFINE_GIT_DETAILS

12.3.1 Detailed Description

This metadata information might be located through **strings** command

- Linux/Solaris/Mac:

```
strings <binary> | grep VERSION
strings <binary> | grep GIT_DETAILS
```

- Windows (MinGW):


```
strings <binary> | findstr VERSION
strings <binary> | findstr GIT_DETAILS
```



12.3.2 Macro Definition Documentation

12.3.2.1 #define DEFINE_VERSION

Value:

```
DEFINE_VERSION_FIRST "." \
    DEFINE_VERSION_MIDDLE "." DEFINE_VERSION_LAST \
    "_" DEFINE_GIT_COMMIT_HASH
```

Index

DEFINE_VERSION

version.h, [21](#)

main

main.cpp, [20](#)

main.cpp

main, [20](#)

src/id.h, [19](#)

src/main.cpp, [20](#)

src/version.h, [20](#)

struct_index_t, [18](#)

union_id_t, [18](#)

version.h

DEFINE_VERSION, [21](#)