SCG 止付螺絲固定式 / 剛性聯軸器

SCGS SET SCREW TYPE / RIGID COUPLING



|--|

Catalog Number 型號	D I	Ĭ	G	М	d1xd2 標準孔徑 (H7)		Mass** 重量
		_			Min	Max	(g)
SCG-16	16	24	6	М3	5	8	11
SCG-20	20	30	7	M4	6	10	20
SCG-25	25	36	9	M4	6	12	39
SCG-32	32	41	10	M5	8	16	71
SCGS-16	16	24	6	М3	5	8	31
SCGS-20	20	30	7	M4	6	10	53
SCGS-25	25	36	9	M4	6	12	105
SCGS-32	32	41	10	M5	8	16	190

性能 | Specifications

單位 / Unit:mm

				丰田 / Ome.mm
Catalog Number 型號	Rated Torque 一般扭力 (N.m)	Max. Torque 最大扭力 (N.m)	Max Rotational Frequency 最高回轉速 (Rpm/min)	Moment* of Inertia 慣性 (Kg・m²)
SCG-16	0.3	0.6	24000	4.4x10 ⁻⁷
SCG-20	0.5	1.0	19000	1.3x10 ⁻⁶
SCG-25	1.0	2.0	15000	3.9x10 ⁻⁶
SCG-32	2.0	4.0	12000	1.2x10-5
SCGS-16	0.3	0.6	24000	1.2x10 ⁻⁶
SCGS-20	0.5	1.0	19000	3.5x10 ⁻⁶
SCGS-25	1.0	2.0	15000	1.0x10 ⁻⁵
SCGS-32	2.0	4.0	12000	3.1x10 ⁻⁵