


# The Optimal Implementation of Hamiltonian Monte Carlo


Michael Betancourt  
@betanalpha  
Symplectomorphic, LLC




© 2019 Michael Betancourt  
For personal use only  
Not for public distribution

Machine Learning Summer School  
London, United Kingdom  
July 23, 2019


The performance of an implementation of Hamiltonian Monte Carlo is determined by its underlying geometry.




The performance of an implementation of Hamiltonian Monte Carlo is determined by its underlying geometry.




The performance of an implementation of Hamiltonian Monte Carlo is determined by its underlying geometry.




The performance of an implementation of Hamiltonian Monte Carlo is determined by its underlying geometry.




The performance of an implementation of Hamiltonian Monte Carlo is determined by its underlying geometry.



The performance of an implementation of Hamiltonian Monte Carlo is determined by its underlying geometry.




The performance of an implementation of Hamiltonian Monte Carlo is determined by its underlying geometry.




$$\pi_H = \pi_{H-1}(E) \wedge \pi_E$$


The momenta resampling, for example, determines how effectively we explore between energy level sets.




The momenta resampling, for example, determines how effectively we explore between energy level sets.




The momenta resampling, for example, determines how effectively we explore between energy level sets.



The efficacy in which we can explore the level sets themselves is determined by the integration time.




The efficacy in which we can explore the level sets themselves is determined by the integration time.




The optimal integration time, however, will in general *vary* from level set to level set.




The optimal integration time, however, will in general *vary* from level set to level set.




The optimal integration time, however, will in general *vary* from level set to level set.




The particular geometry of the level sets also determines the accuracy of symplectic integration.



The particular geometry of the level sets also determines the accuracy of symplectic integration.



The particular geometry of the level sets also determines the accuracy of symplectic integration.




The particular geometry of the level sets also determines the accuracy of symplectic integration.

$$\tilde{H}(q, p) = H(q, p) + \epsilon^2 H_2(q, p) + \dots$$


The particular geometry of the level sets also determines the accuracy of symplectic integration.

$$\tilde{H}(q, p) = H(q, p) + \epsilon^2 H_2(q, p) + \dots$$


We can exploit this geometric relationship to develop criteria to optimize the choice of integrator step size.




We can exploit this geometric relationship to develop criteria to optimize the choice of integrator step size.




The geometry of the modified level sets also provides sensitive diagnostic information about convergence.




The geometry of the modified level sets also provides sensitive diagnostic information about convergence.




The geometry of the modified level sets also provides sensitive diagnostic information about convergence.




The geometry of the modified level sets also provides sensitive diagnostic information about convergence.




Stable numerical integration indicates  
accurate exploration of the given level set.



Stable numerical integration indicates  
accurate exploration of the given level set.



Unstable numerical integration, which yields a *divergence*, indicates inaccurate exploration of the given level set.




© 2019 Michael Betancourt


For personal use only

Not for public distribution


Unstable numerical integration, which yields a *divergence*, indicates inaccurate exploration of the given level set.




More formally these divergences identify some of the pathologies which obstruct geometric ergodicity.




More formally these divergences identify some of the pathologies which obstruct geometric ergodicity.



More formally these divergences identify some of the pathologies which obstruct geometric ergodicity.



More formally these divergences identify some of the pathologies which obstruct geometric ergodicity.



These geometric properties defines novel diagnostics of geometric ergodicity for Hamiltonian Monte Carlo.

Warning messages:

1: There were 2 chains where the estimated Bayesian Fraction of Missing Information was low. See  
<http://mc-stan.org/misc/warnings.html#bfmi-low>

Warning messages:

1: There were 2 divergent transitions after warmup.  
Increasing adapt\_delta above 0.8 may help. See  
<http://mc-stan.org/misc/warnings.html#divergent-transitions-after-warmup>

© 2019 Michael Betancourt

For personal use only  
Not for public distribution

Software tools like Stan implement MCMC, allowing users to focus on building models and analyzing chains.



© 2019 Michael Betancourt  
For personal use only  
Not for public distribution

Software tools like Stan implement MCMC, allowing users to focus on building models and analyzing chains.



Modeling  
Language

©


For personal use only

Not for public distribution

Software tools like Stan implement MCMC, allowing users to focus on building models and analyzing chains.




Software tools like Stan implement MCMC, allowing users to focus on building models and analyzing chains.



Modeling  
Language

Automatic  
Differentiation

Hamiltonian  
Monte Carlo



## Michael Betancourt

Once and future physicist  
masquerading as an  
applied statistician.

📍 New York, NY

✉️ Email

🐦 Twitter

🐙 GitHub

## Writing

Preprints of my work are posted on the [arXiv](#) as much as possible. Highlights include a long but comprehensive [introduction to statistical computing and Hamiltonian Monte Carlo](#) targeted at applied researchers and a more theoretical treatment of the [geometric foundations of Hamiltonian Monte Carlo](#).

I've also been experimenting with a [nontraditional introduction](#) to some of the more formal aspects of probability theory and statistical computation, although fair warning that this draft is long overdue for a reorganization. Still, comments are always welcome.

Recently I have been taking advantage of notebook environments such as [knitr](#) and [Jupyter](#) to develop case studies demonstrating important concepts in statistical workflow and modeling with [Stan](#).

## Bayes Sparse Regression

In this case study I'll review how sparsity arises in frequentist and Bayesian analyses and discuss the often subtle challenges in implementing sparsity in practical Bayesian analyses.

[View \(HTML\)](#)

[betanalpha/knitr\\_case\\_studies/bayes\\_sparse\\_regression](#) (GitHub)

Dependences: R, knitr, RStan

Code License: BSD (3 clause)