

Machine Learning Basics

Neuroinformatics Tutorial 1

Duc Duy Pham¹

¹Intelligent Systems, Faculty of Engineering,
University of Duisburg-Essen, Germany


Content

- Motivation
- When does a Machine learn?
- Machine Learning tasks
- Broad types of Machine Learning Algorithms
- How do input/output look like?
- Data partitioning


Content

- Motivation
- When does a Machine learn?
- Machine Learning tasks
- Broad types of Machine Learning Algorithms
- How do input/output look like?
- Data partitioning


Motivation



Motivation



Difference Coding and ML?




Content

- Motivation
- When does a Machine learn?
- Machine Learning tasks
- Broad types of Machine Learning Algorithms
- How do input/output look like?
- Data partitioning

When does a Machine learn?

Mitchell (1997):
*„A computer is said to learn from experience E ,
 if its performance at tasks in T ,
 as measured by P ,
 improves with experience E ”*

0. Define task T
1. Try to solve task T with your Algorithm
2. Measure Algorithm performance by P
3. Gain experience E by doing so
4. Go to 1.





When does a Machine learn?

Mitchell (1997):
*„A computer is said to learn from experience E ,
 if its performance at tasks in T ,
 as measured by P ,
 improves with experience E ”*

0. Define task T

1. Try to solve task T with your Algorithm
2. Measure Algorithm performance by P
3. Gain experience E by doing so
4. Go to 1.




Content

- Motivation
- When does a Machine learn?
- Machine Learning tasks
- Broad types of Machine Learning Algorithms
- How do input/output look like?
- Data partitioning

Tasks

- Typical tasks:
 - Classification

Classification



Tasks


- Typical tasks:
 - Classification
 - Regression

Regression




Continuous
Output!


Regression




Regression



Regression



Interpolation



Tasks

- Typical tasks:
 - Classification
 - Regression (not the same as interpolation!)
- Further tasks:
 - Transcription

Transcription

- Speech to text
- Image to text



Tasks

- Typical tasks:
 - Classification
 - Regression (not the same as interpolation!)
- Further tasks:
 - Transcription
 - Machine Translation



Translate from Finnish

ääääääääääääää Edit

Edit

Turkish ▼

pokemon


[Open in Google Translate](#)

Feedback

Tasks

- Typical tasks:
 - Classification
 - Regression (not the same as interpolation!)
- Further tasks:
 - Transcription
 - Machine Translation
 - Anomaly Detection


Anomaly Detection



Tasks

- Typical tasks:
 - Classification
 - Regression (not the same as interpolation!)
- Further tasks:
 - Transcription
 - Machine Translation
 - Anomaly Detection
 - Synthesis


Image Synthesis



A: Real

B: Fake

Image Synthesis



Real

Image Synthesis



A: Real

B: Fake

Image Synthesis



Fake

Image Synthesis



A: Real

B: Fake

Image Synthesis



Fake

Image Synthesis



A: Real

B: Fake

Image Synthesis



Fake

Image Synthesis





Image Synthesis



Real



Real



Fake



Fake



Fake

Tasks

- Typical tasks:
 - Classification
 - Regression (not the same as interpolation!)
- Further tasks:
 - Transcription
 - Machine Translation
 - Anomaly Detection
 - Synthesis
 - Denoising
 - Imputation of missing values
 - Etc ...


Scope of this course

- Basic/Fundamental Machine Learning methods and algorithms
- Most tasks will be **classification** tasks

When does a Machine learn?

Mitchell (1997):
*„A computer is said to learn from experience E,
 if its performance at tasks in T,
 as measured by P,
 improves with experience E”*

0. Define task T
1. Try to solve task T with your Algorithm
2. Measure Algorithm performance by P
3. Gain experience E by doing so
4. Go to 1.



Content

- Motivation
- When does a Machine learn?
- Machine Learning tasks
- Broad types of Machine Learning Algorithms
- How do input/output look like?
- Data partitioning


Broad types of ML Algorithms

- Supervised Learning
- Unsupervised Learning
- Reinforcement Learning


Supervised Learning

- Desired output is known!
- „teacher tells us right solution “


Classification



Classification



Classification




Regression



Regression




Regression



Unsupervised Learning

- Try to find useful properties/structures in example data set
- „no teacher“


Unsupervised learning




Reinforcement Learning

- Learning by punishment / reward
- Feedback loop between learning system and environment
- „teacher points to right direction “


Reinforcement Learning




Reinforcement Learning





Reinforcement Learning




Reinforcement Learning




Reinforcement Learning



Reinforcement Learning



Reinforcement Learning



Reinforcement Learning

- Learning by punishment / reward
- Feedback loop between learning system and environment
- „teacher points to right direction “
- A little more complicated than illustration ;)
- More details in Computer Robot Systems


Content

- Motivation
- When does a Machine learn?
- Machine Learning tasks
- Broad types of Machine Learning Algorithms
- How do input/output look like?
- Data partitioning

When does a Machine learn?

Mitchell (1997):
*„A computer is said to learn from experience E ,
 if its performance at tasks in T ,
 as measured by P ,
 improves with experience E ”*

0. Define task T
1. Try to solve task T with your Algorithm
2. Measure Algorithm performance by P
3. Gain experience E by doing so
4. Go to 1.



What does the input look like?

- Usually a vector $x \in \mathbb{R}^N$
- Either raw observation vector
- or feature vector,
where each component may represent a specific feature

What are features?

- Salient properties of observation
- In generable measurable
- Sometimes needs to be extracted from observation

Example: Disease diagnosis

- Possible features (can be observed):
 - Oxygen partial pressure in blood
 - Carbon dioxide partial pressure
 - Heart rate
 - Etc ...

Example: Disease diagnosis

- Possible features (can be observed):
 - Oxygen partial pressure in blood
 - Carbon dioxide partial pressure
 - Heart rate
 - Etc ...

$$x = \begin{pmatrix} \textit{heart rate} \\ \textit{blood pressure} \\ \dots \\ \textit{nose length} \end{pmatrix}$$

Example: Iris classification

- Raw observation: image



Iris setosa




Iris versicolor



Iris virginica

Example: Iris classification

- (Manually) extracted features from image:



$$x = \begin{pmatrix} \textit{sepal length} \\ \vdots \\ \textit{petal width} \end{pmatrix}$$

Example: Iris classification

- Often samples are stored in arrays!
- Be sure you know how the data is structured!
- Example:

```
[[5.1 3.5 1.4 0.2]
 [4.9 3.  1.4 0.2]
 [4.7 3.2 1.3 0.2]
 [4.6 3.1 1.5 0.2]
 [5.  3.6 1.4 0.2]
 [5.4 3.9 1.7 0.4]
 [4.6 3.4 1.4 0.3]
 [5.  3.4 1.5 0.2]
 [4.4 2.9 1.4 0.2]
 [4.9 3.1 1.5 0.1]]
```

Example: Iris classification

- Often samples are stored in arrays!
- Be sure you know how the data is structured!
- Example:


```
[[5.1 3.5 1.4 0.2] ← First sample
 [4.9 3.  1.4 0.2]
 [4.7 3.2 1.3 0.2]
 [4.6 3.1 1.5 0.2]
 [5.  3.6 1.4 0.2]
 [5.4 3.9 1.7 0.4]
 [4.6 3.4 1.4 0.3]
 [5.  3.4 1.5 0.2]
 [4.4 2.9 1.4 0.2]
 [4.9 3.1 1.5 0.1]]
```

Example: Iris classification

- Often samples are stored in arrays!
- Be sure you know how the data is structured!
- Example:

```
[[5.1 3.5 1.4 0.2]
 [4.9 3.  1.4 0.2]
 [4.7 3.2 1.3 0.2]
 [4.6 3.1 1.5 0.2]
 [5.  3.6 1.4 0.2]
 [5.4 3.9 1.7 0.4]
 [4.6 3.4 1.4 0.3]
 [5.  3.4 1.5 0.2]
 [4.4 2.9 1.4 0.2]
 [4.9 3.1 1.5 0.1]]
```

Second sample




Example: Iris classification

- Often samples are stored in arrays!
- Be sure you know how the data is structured!
- Example:

```
[[5.1 3.5 1.4 0.2]
 [4.9 3.  1.4 0.2]
 [4.7 3.2 1.3 0.2]
 [4.6 3.1 1.5 0.2]
 [5.  3.6 1.4 0.2]
 [5.4 3.9 1.7 0.4]
 [4.6 3.4 1.4 0.3]
 [5.  3.4 1.5 0.2]
 [4.4 2.9 1.4 0.2]
 [4.9 3.1 1.5 0.1]]
```

Third sample



Example: Iris classification


- Often samples are stored in arrays!
- Be sure you know how the data is structured!
- Example:

Sepal length →

| | | | |
|------|-----|-----|-------|
| [5.1 | 3.5 | 1.4 | 0.2] |
| [4.9 | 3. | 1.4 | 0.2] |
| [4.7 | 3.2 | 1.3 | 0.2] |
| [4.6 | 3.1 | 1.5 | 0.2] |
| [5. | 3.6 | 1.4 | 0.2] |
| [5.4 | 3.9 | 1.7 | 0.4] |
| [4.6 | 3.4 | 1.4 | 0.3] |
| [5. | 3.4 | 1.5 | 0.2] |
| [4.4 | 2.9 | 1.4 | 0.2] |
| [4.9 | 3.1 | 1.5 | 0.1]] |

Example: Iris classification


- Often samples are stored in arrays!
- Be sure you know how the data is structured!
- Example:

Sepal width — 

```
[[5.1 3.5 1.4 0.2]
 [4.9 3. 1.4 0.2]
 [4.7 3.2 1.3 0.2]
 [4.6 3.1 1.5 0.2]
 [5. 3.6 1.4 0.2]
 [5.4 3.9 1.7 0.4]
 [4.6 3.4 1.4 0.3]
 [5. 3.4 1.5 0.2]
 [4.4 2.9 1.4 0.2]
 [4.9 3.1 1.5 0.1]]
```


Example: Iris classification

- Often samples are stored in arrays!
- Be sure you know how the data is structured!
- Example:

Petal length — 

```

[[5.1 3.5 1.4 0.2]
 [4.9 3.  1.4 0.2]
 [4.7 3.2 1.3 0.2]
 [4.6 3.1 1.5 0.2]
 [5.  3.6 1.4 0.2]
 [5.4 3.9 1.7 0.4]
 [4.6 3.4 1.4 0.3]
 [5.  3.4 1.5 0.2]
 [4.4 2.9 1.4 0.2]
 [4.9 3.1 1.5 0.1]]

```

Example: Iris classification

- Often samples are stored in arrays!
- Be sure you know how the data is structured!
- Example:


Petal width →

| | | | |
|------|-----|-----|-------|
| [5.1 | 3.5 | 1.4 | 0.2] |
| [4.9 | 3. | 1.4 | 0.2] |
| [4.7 | 3.2 | 1.3 | 0.2] |
| [4.6 | 3.1 | 1.5 | 0.2] |
| [5. | 3.6 | 1.4 | 0.2] |
| [5.4 | 3.9 | 1.7 | 0.4] |
| [4.6 | 3.4 | 1.4 | 0.3] |
| [5. | 3.4 | 1.5 | 0.2] |
| [4.4 | 2.9 | 1.4 | 0.2] |
| [4.9 | 3.1 | 1.5 | 0.1]] |

When does a Machine learn?


Mitchell (1997):
*„A computer is said to learn from experience E ,
 if its performance at tasks in T ,
 as measured by P ,
 improves with experience E “*

0. Define task T
1. Try to solve task T with your Algorithm
2. Measure Algorithm performance by P
3. Gain experience E by doing so
4. Go to 1.




How does the output look like?

- For supervised classification (categorical output):




How does the output look like?

- For supervised classification (categorical output):




How does the output look like?

- For supervised classification (categorical output)




How does the output look like?

- For supervised classification (categorical output):
- Numerical class labels!




How does the output look like?

- For supervised classification (categorical output):
- Numerical class labels!




How does the output look like?

- For supervised classification (categorical output):
- Numerical class labels!



How does the output look like?

- For supervised classification (categorical output):
- Numerical class labels!



Rather uncommon for multi-class tasks!


How does the output look like?

- For supervised classification (categorical output):
- Numerical class labels!
- More common for binary classification



How does the output look like?

- For supervised classification (categorical output):
- Numerical class labels!
- More common for binary classification




How does the output look like?

- For supervised classification (categorical output):
- Numerical class labels!
- More common for binary classification




How does the output look like?

- For supervised classification (categorical output):
- One-hot-Encoding!



How does the output look like?

- For supervised classification (categorical output):
- One-hot-Encoding!



How does the output look like?


- For supervised classification (categorical output):
- One-hot-Encoding!



When does a Machine learn?

Mitchell (1997):
*„A computer is said to learn from experience E,
 if its performance at tasks in T,
 as measured by P,
 improves with experience E”*

0. Define task T
1. Try to solve task T with your Algorithm
2. Measure Algorithm performance by P
3. Gain experience E by doing so
4. Go to 1.



Content

- Motivation
- When does a Machine learn?
- Machine Learning tasks
- Broad types of Machine Learning Algorithms
- How do input/output look like?
- Data partitioning

Caution!

- Differentiate between performance measure:
 - During learning phase (training)
 - > to improve ML model
 - After learning (testing)
 - > to estimate how good your model is on unseen data

Data partitioning

- Split your data into
 - Training data
 - > use this data to improve model during learning phase
 - Validation data
 - > **do not** use this data during learning!
 - > use it to measure model performance on unseen data
 - > use measurement for hyperparameter tuning!
 - Testing data
 - > **do not** use this data during learning!
 - > use it to measure model performance on unseen data
 - > **do not** use measurement for hyperparameter tuning!

Summary

- Motivation
- When does a Machine learn?
- Machine Learning tasks
- Broad types of Machine Learning Algorithms
- How do input/output look like?
- Data partitioning

Outlook – Biologically inspired

- McCulloch-Pitts Cell [Tutorial]
- Perceptron [Lecture + Tutorial]
- AdaLine [Lecture + Tutorial]
- Multilayer-Perceptron (MLP) [Lecture + Tutorial]
- Convolutional Neural Networks (CNN) [Tutorial]
- Radial Basis Function-Networks (RBF-Network) [Lecture + Tutorial]

Outlook – Non-Biologically inspired

- Naive Bayes Classifier [Tutorial]
- K-Means Clustering [Lecture]
- Support Vector Machines (SVM) [Lecture + Tutorial]

Further interesting ML algorithms

- Neural Gas
- Self Organizing Maps (SOMs)
- Random Forest
- AdaBoost
- Deep Learning in general
(we only shortly cover CNNs)

Relation to AI

