## **NAME**

curl\_easy\_recv - receives raw data on an "easy" connection

## **SYNOPSIS**

#include <curl/easy.h>

CURLcode curl\_easy\_recv( CURL \*curl, void \*buffer, size\_t buflen, size\_t \*n);

## DESCRIPTION

This function receives raw data from the established connection. You may use it together with *curl\_easy\_send(3)* to implement custom protocols using libcurl. This functionality can be particularly useful if you use proxies and/or SSL encryption: libcurl will take care of proxy negotiation and connection setup.

**buffer** is a pointer to your buffer that will get the received data. **buflen** is the maximum amount of data you can get in that buffer. The variable **n** points to will receive the number of received bytes.

To establish the connection, set **CURLOPT\_CONNECT\_ONLY(3)** option before calling  $curl\_easy\_per-form(3)$ . Note that  $curl\_easy\_recv(3)$  does not work on connections that were created without this option.

You must ensure that the socket has data to read before calling <code>curl\_easy\_recv(3)</code>, otherwise the call will return <code>CURLE\_AGAIN</code> - the socket is used in non-blocking mode internally. Use <code>curl\_easy\_getinfo(3)</code> with <code>CURLINFO\_LASTSOCKET</code> to obtain the socket; use your operating system facilities like <code>select(2)</code> to check if it has any data you can read.

#### **AVAILABILITY**

Added in 7.18.2.

## **RETURN VALUE**

On success, returns **CURLE\_OK**, stores the received data into **buffer**, and the number of bytes it actually read into \*n.

On failure, returns the appropriate error code.

If there is no data to read, the function returns **CURLE\_AGAIN**. Use your operating system facilities to wait until the data is ready, and retry.

Reading exactly 0 bytes would indicate a closed connection.

If there's no socket available to use from the previous transfer, this function returns CURLE\_UNSUP-PORTED\_PROTOCOL.

# **EXAMPLE**

See **sendrecv.c** in **docs/examples** directory for usage example.

## **SEE ALSO**

 $\pmb{curl\_easy\_setopt(3), curl\_easy\_perform(3), curl\_easy\_getinfo(3), curl\_easy\_send(3)}\\$