

String Manipulation and Regex in C# 10

Introducing Strings and Regex



Steve Gordon

.NET Engineer and Microsoft MVP

@stevejgordon www.stevejgordon.co.uk



Overview



Strings in C#

The importance of immutability

String encoding basics

Introduce regular expressions (Regex)




Later in This Course




**Comparing and
sorting strings**



**Searching
strings**



**Combining and
formatting
strings**



**Efficient string
manipulation
using a
StringBuilder**



Later in This Course

$(^A.*)$

Regular expressions



Version Check



This version was created by using:

- .NET 6.0
- C# 10
- Visual Studio 2022



Version Check



This course is 98% applicable to:

- .NET Core 3.1
- .NET 5.0
- .NET Framework
- Visual Studio 2013 to 2019
- Future .NET versions



Relevant Notes



A note on frameworks and libraries:


- A new version of .NET releases each year
- Strings are a stable and mature concept
- Microsoft aim to maintain backward compatibility between releases
- Most concepts shown in this course can be applied regardless of .NET version



Course Prerequisites



**Beginner to intermediate
knowledge of .NET**



**Experience with
C# fundamentals**



String Manipulation in C#: Best Practices

Steve Gordon


[app.pluralsight.com/library/courses/
string-manipulation-c-sharp-best-practices](https://app.pluralsight.com/library/courses/string-manipulation-c-sharp-best-practices)



Follow Along



Follow along: Download the exercise files



The solution requires the latest .NET 6.0.x SDK
<http://dot.net>



An IDE such as Visual Studio Community Edition or an editor such as Visual Studio Code



Let's Get Started



Introducing Strings





System.String

“A string represents text as a sequence of UTF-16 code units.”



Strings are used to represent textual information such as a username or hostname.



INSERT HANDWRITING VIDEO



Д

Aa

私

ألف

ב




```
string myString = "hello"
```



Properties of Strings

Built-in type of .NET and C#


Their design is optimized for performance

Reference types stored on the heap

Have value-based equality semantics

Tightly integrated within the .NET CLR

**Implemented with managed and
unmanaged code**



Immutability of Strings



Immutability

**Internal state cannot be modified
after initialization**

Strings are immutable, read-only instances

Character buffer cannot grow

Methods and operators return a new string



Advantages



Strings can be safely shared without the need to defensively copy them

Easy to reason about

Thread-safe by default

Can be optimized by the CLR



Immutability increases the number of objects in memory, which introduces a performance overhead.






Important!

Remember that operations do not modify the original string and cause at least one new string to be created.





```
static string W()  
{  
    var message = Console.ReadLine();  
    var name = Console.ReadLine();  
    message += name;  
    return message;  
}
```

Stack

Managed Heap



static string W()
{
var message = Console.ReadLine();
var name = Console.ReadLine();
message += name;
return message;
}

Stack

message (variable)

Managed Heap

object header

method table

data (length = 6)

String



```
static string W()  
{  
    var message = Console.ReadLine();  
    var name = Console.ReadLine();  
    message += name;  
    return message;  
}
```

Stack

message (variable)

name (variable)

Managed Heap

object header

method table

data (length = 6)

String

object header

method table

data (length = 5)

String



```
static string W()  
{  
    var message = Console.ReadLine();  
    var name = Console.ReadLine();  
    message += name;  
    return message;  
}
```

Stack

message (variable)

name (variable)

Managed Heap

object header

method table

data (length = 6)

String

object header

method table

data (length = 5)

String

object header

method table

data (length = 11)

String



```
static string W()  
{  
    var message = Console.ReadLine();  
    var name = Console.ReadLine();  
    message += name;  
    return message;  
}
```

Stack

message (variable)

name (variable)

Managed Heap

object header

method table

data (length = 6)

String

object header

method table

data (length = 5)

String

object header

method table

data (length = 11)

String



```
static string W()  
{  
    var message = Console.ReadLine();  
    var name = Console.ReadLine();  
    message += name;  
    return message;  
}
```

Stack

message (variable)

name (variable)

GC

Managed Heap

object header

method table

data (length = 5)

String

object header

method table

data (length = 11)


String




Character Encoding



Strings



Strings






Encoding

The means by which characters are mapped to bytes of binary data stored in memory, on disk or transmitted over a network.



ASCII



American Standard Code for Information Interchange

Developed in the 1960's

Uses 7-bits to encode up to 128 characters


Includes non-printing, control characters

Limited to only English characters

Used for HTTP/1 request line and headers



Unicode



Origins dating back to 1987

Uses a 16-bit character model

Original proposal had some limitations

- Version 2.0 removed the 16-bit limit with surrogate pairs

Continues to evolve with additional characters

Maintained by the Unicode Consortium

Contains 143,859 characters as of v13



Unicode Code Points



Integer value ranging from 0 to 1,114,111

Assigned to letters, symbols and control characters

Many code points are reserved for future use



Code Point Examples

Decimal	Hex	Example	Description
13	U+000D	n/a	Carriage return
65	U+0041	A	Latin capital letter A
1590	U+0636	ض	Arabic letter Ḍād
128512	U+1F600	😊	Grinning face emoji



Code Point Ranges

U+10000

U+10FFFF

Basic
Multilingual
Plane

Supplementary Planes

U+0000

U+FFFF

16-bits

65,536 code points

21-bits


1,048,576 code points



A Unicode Transformation
Format (UTF) encodes code
points to and from binary data.



UTF-16 Encoding



.NET uses UTF-16 encoding for strings

Requires at least two bytes per character (char)

Higher code points may require two chars

- Known as a surrogate pair
- Requires four bytes



UTF-8 and the Internet

UTF-8 is the most prevalent encoding on the web. Most sites accept UTF-8 encoded requests and return UTF-8 encoded data (HTML/JSON) in responses.



UTF-8 Encoding



Variable width character encoding

Can encode all Unicode code points

Length varies between 1 and 4 bytes

- 1 byte: Sufficient for US-ASCII
- 2 bytes: Supports an extra 1,920 characters
- 3 bytes: Sufficient for the whole BMP range
- 4 bytes: Supports the supplementary range

For most text, UTF-8 results in less data to transmit, vs. UTF-16 encoding



Variable Length Encoding

A	41	1-byte
---	----	--------


Ä	C3-84	2-bytes
---	-------	---------

诶	E8-AF-B6	3-bytes
---	----------	---------

😊	F0-9F-98-80	4-bytes
---	-------------	---------



.NET Encoding Classes



.NET includes classes to work with different encoding schemes

Derive from `System.Text.Encoding`

Encoding classes are accessible from static properties (e.g. `ASCII` and `UTF8`)

Encode characters/strings to bytes

Decode from bytes into characters/strings




```
string myString = "Treble Clef: 🎵";  
  
int length = myString.Length; // 15  
  
byte[] utf16Bytes = System.Text.Encoding.Unicode.GetBytes(myString);  
  
int utf16Length = utf16Bytes.Length; // 30  
  
byte[] utf8Bytes = System.Text.Encoding.UTF8.GetBytes(myString);  
  
int utf8Length = utf8Bytes.Length; // 17  
  
string roundTrippedString = System.Text.Encoding.UTF8.GetString(utf8Bytes);  
  
bool equal = myString == roundTrippedString; // true
```

Using the System.Text Encoding Classes

This sample code encodes a UTF-16 string to UTF-16 and UTF-8 bytes and then decodes the UTF-8 bytes back into a string representation (roundtripping).

Grapheme Cluster



Combines:



Woman



Medium Skin Tone

Zero Width Joiner



Curly Hair

Woman: Medium Skin Tone, Curly Hair



```
string womanEmoji = "👩"; // NOTE: VS does not render this as a single element

int womanEmojiLength = myString.Length; // 7

byte[] womanEmojiBytes = System.Text.Encoding.Unicode.GetBytes(womanEmoji);

int womanEmojiBytesLength = womanEmojiBytes.Length; // 14

var womanEmojiInfo = new System.Globalization.StringInfo(womanEmoji);

int womanEmojiTextElements = womanEmojiInfo.LengthInTextElements; // 1
```

String Length

The length of a string is the number of UTF-16 chars that it contains. This may not always align to the number of visible text elements.

Introducing Regular Expressions



Regular Expressions

An often indispensable tool for parsing complex strings.



Validating text input




**Complex search
matches**



**Removing or replacing
portions of strings**



Regex Patterns



Formed by a sequence of characters

Characters can represent:


- A literal character
- A metacharacter

Regex patterns can be complex and difficult to understand

Regex patterns can be used across languages



Regex Engines



Central component for processing regular expressions

.NET uses a backtracking, non-deterministic finite automaton (NFA) engine

Backtracking allows the engine to save state

- Offers greater control over string matching
- Matches can run slowly if they require lots of backtracking



Pattern Example

```
string pattern = "^A.*";
```

Character	Description
^	Positional anchor - Requires the match to start at the beginning of the string.
A	The literal Latin uppercase letter A.
.	Matches any single character except \n.
*	Greedy quantifier - Match the previous token zero or more times.



Preferring static Regex methods is recommended because it benefits from caching and may perform better.



```
string input = "A sample string.";
string pattern = "^A.*";
bool match = Regex.IsMatch(input, pattern);
```

Matching a Regular Expression

The IsMatch method indicates whether the regular expression finds a match in the input string.

IsMatch Results

```
string pattern = "^A.*";
```

Input	Result
“a sample string.”	False
“A string. Another string”	True
“The string. A string”	False
“A”	True



IsMatch Results

```
string pattern = " ^A.+";
```

Input	Pattern “^A.+”	Pattern “^A.*”
“A sample string.”	True	True
“a sample string.”	False	False
“A string. Another string”	True	True
“The string. A string”	False	False
“A”	False	True



Simplified Pattern

```
string pattern = "^A.";
```

Input	Regex.IsMatch(...)	Regex.Match(...).Value
"A sample string."	True	"A "
"a sample string."	False	N/A
"A string. Another string"	True	"A "
"The string. A string"	False	N/A
"A"	False	N/A



Regular Expressions are a
deep topic.





**[https://docs.microsoft.com/
en-us/dotnet/standard/base-types/
regular-expression-language-quick-
reference](https://docs.microsoft.com/en-us/dotnet/standard/base-types/regular-expression-language-quick-reference)**

Microsoft documentation





Regular Expression Fundamentals

Juliette Reinders Folmer

[app.pluralsight.com/library/courses/
regular-expressions-fundamentals](https://app.pluralsight.com/library/courses/regular-expressions-fundamentals)



Introducing the Sample Domain





Business Requirements



Console application to read, parse and process source data

Ingest historical data from legacy systems


Source data is text-based

Data formats vary across source data files

Data consistency and validity is not guaranteed



Plan of Attack



Use sample data files during initial development phase

Build a prototype data processing application

Tackle various scenarios from the business requirements







String Manipulation in C#: Best Practices

Steve Gordon

[app.pluralsight.com/library/courses/
string-manipulation-c-sharp-best-practices](https://app.pluralsight.com/library/courses/string-manipulation-c-sharp-best-practices)



Demo



Introducing the sample application



Up Next: Working with Strings

