

https://github.com/xuhancn/research_export_table.git

Windows: ordered symbols

Dependency Walker - [dummy_shared_lib.dll]
File Edit View Options Profile Window Help
[Icons]
DUMMY_SHARED_LIB.DLL
+ VCRUNTIME140.DLL
 ? API-MS-WIN-CRT-STDIO-L1-1-0.DLL
 ? API-MS-WIN-CRT-RUNTIME-L1-1-0.DLL
+ KERNEL32.DLL

	PI	Ordinal ^	Hint	Function	Entry Point
E					
[+]		1 (0x0001)	0 (0x0000)	?apple_func@@YAXXZ	0x00001100
[+]		2 (0x0002)	1 (0x0001)	?baby_func@@YAHH@Z	0x00001120
[+]		3 (0x0003)	2 (0x0002)	?caffe_hahaha@@YANNN@Z	0x00001000
[+]		4 (0x0004)	3 (0x0003)	?dog_func@@YAMHM@Z	0x00001050



gcc @ Linux: unordered symbols

```
(pytorch) xu@xu-21HW:~/github/research_export_table/build$ ls
CMakeCache.txt CMakeFiles cmake_install.cmake libdummy_shared_lib.so Makefile src
(pytorch) xu@xu-21HW:~/github/research_export_table/build$ readelf -s libdummy_shared_lib.so -W
```

Symbol table '.dynsym' contains 10 entries:

Num:	Value	Size	Type	Bind	Vis	Ndx	Name
0:	0000000000000000	0	NOTYPE	LOCAL	DEFAULT	UND	
1:	0000000000000000	0	NOTYPE	WEAK	DEFAULT	UND	__ITM_deregisterTMCloneTable
2:	0000000000000000	0	FUNC	GLOBAL	DEFAULT	UND	printf@GLIBC_2.2.5 (2)
3:	0000000000000000	0	NOTYPE	WEAK	DEFAULT	UND	__gmon_start__
4:	0000000000000000	0	NOTYPE	WEAK	DEFAULT	UND	__ITM_registerTMCloneTable
5:	0000000000000000	0	FUNC	WEAK	DEFAULT	UND	__cxa_finalize@GLIBC_2.2.5 (2)
6:	00000000000011f3	56	FUNC	GLOBAL	DEFAULT	14	__Z10apple_funcv
7:	00000000000011b7	60	FUNC	GLOBAL	DEFAULT	14	__Z9baby_func1
8:	0000000000001119	79	FUNC	GLOBAL	DEFAULT	14	__Z8dog_func1f
9:	0000000000001168	79	FUNC	GLOBAL	DEFAULT	14	__Z12caffe_hahahadd

Symbol table '.symtab' contains 30 entries:

Num:	Value	Size	Type	Bind	Vis	Ndx	Name
0:	0000000000000000	0	NOTYPE	LOCAL	DEFAULT	UND	
1:	0000000000000000	0	FILE	LOCAL	DEFAULT	ABS	crtstuff.c
2:	0000000000001060	0	FUNC	LOCAL	DEFAULT	14	deregister_tm_clones
3:	0000000000001090	0	FUNC	LOCAL	DEFAULT	14	register_tm_clones
4:	00000000000010d0	0	FUNC	LOCAL	DEFAULT	14	__do_global_ctors_aux
5:	0000000000004010	1	OBJECT	LOCAL	DEFAULT	25	completed.0
6:	0000000000003df0	0	OBJECT	LOCAL	DEFAULT	20	__do_global_ctors_aux_fini_array_entry
7:	0000000000001110	0	FUNC	LOCAL	DEFAULT	14	frame_dummy
8:	0000000000003de8	0	OBJECT	LOCAL	DEFAULT	19	__frame_dummy_init_array_entry
9:	0000000000000000	0	FILE	LOCAL	DEFAULT	ABS	src_a.cpp
10:	0000000000000000	0	FILE	LOCAL	DEFAULT	ABS	src_b.cpp
11:	0000000000000000	0	FILE	LOCAL	DEFAULT	ABS	crtstuff.c
12:	0000000000002190	0	OBJECT	LOCAL	DEFAULT	18	__FRAME_END__
13:	0000000000000000	0	FILE	LOCAL	DEFAULT	ABS	
14:	000000000000122c	0	FUNC	LOCAL	DEFAULT	15	__fini
15:	0000000000004008	0	OBJECT	LOCAL	DEFAULT	24	__dso_handle
16:	0000000000003df8	0	OBJECT	LOCAL	DEFAULT	21	__DYNAMIC
17:	000000000000205c	0	NOTYPE	LOCAL	DEFAULT	17	__GNU_EH_FRAME_HDR
18:	0000000000004010	0	OBJECT	LOCAL	DEFAULT	24	__TMC_END__
19:	0000000000003fe8	0	OBJECT	LOCAL	DEFAULT	23	__GLOBAL_OFFSET_TABLE__
20:	0000000000001000	0	FUNC	LOCAL	DEFAULT	10	__init
21:	0000000000000000	0	NOTYPE	WEAK	DEFAULT	UND	__ITM_deregisterTMCloneTable
22:	0000000000000000	0	FUNC	GLOBAL	DEFAULT	UND	printf@GLIBC_2.2.5
23:	0000000000001168	79	FUNC	GLOBAL	DEFAULT	14	__Z12caffe_hahahadd
24:	00000000000011f3	56	FUNC	GLOBAL	DEFAULT	14	__Z10apple_funcv
25:	0000000000000000	0	NOTYPE	WEAK	DEFAULT	UND	__gmon_start__
26:	00000000000011b7	60	FUNC	GLOBAL	DEFAULT	14	__Z9baby_func1
27:	0000000000001119	79	FUNC	GLOBAL	DEFAULT	14	__Z8dog_func1f
28:	0000000000000000	0	NOTYPE	WEAK	DEFAULT	UND	__ITM_registerTMCloneTable
29:	0000000000000000	0	FUNC	WEAK	DEFAULT	UND	__cxa_finalize@GLIBC_2.2.5

clang @ Linux: unordered symbols

```
(pytorch) xu@xu-21HW:~/github/research_export_table/build_cl$ ls
CMakeCache.txt CMakeFiles cmake_install.cmake libdummy_shared_lib.so Makefile src
(pytorch) xu@xu-21HW:~/github/research_export_table/build_cl$ readelf -s libdummy_shared_lib.so -W

Symbol table '.dynsym' contains 10 entries:
  Num:      Value              Size Type      Bind    Vis      Ndx Name
  0: 0000000000000000      0 NOTYPE   LOCAL   DEFAULT UND
  1: 0000000000000000      0 FUNC    GLOBAL   DEFAULT UND printf@GLIBC_2.2.5 (2)
  2: 0000000000000000      0 FUNC    WEAK     DEFAULT UND __cxa_finalize@GLIBC_2.2.5 (2)
  3: 0000000000000000      0 NOTYPE   WEAK     DEFAULT UND __ITM_deregisterTMCloneTable
  4: 0000000000000000      0 NOTYPE   WEAK     DEFAULT UND __gmon_start__
  5: 0000000000000000      0 NOTYPE   WEAK     DEFAULT UND __ITM_registerTMCloneTable
  6: 000000000000011f0     51 FUNC    GLOBAL   DEFAULT 11 _Z10apple_funcv
  7: 000000000000011b0     50 FUNC    GLOBAL   DEFAULT 11 _Z9baby_funcif
  8: 00000000000001110     66 FUNC    GLOBAL   DEFAULT 11 _Z8dog_funcif
  9: 00000000000001160     68 FUNC    GLOBAL   DEFAULT 11 _Z12caffe_hahahadd

Symbol table '.symtab' contains 30 entries:
  Num:      Value              Size Type      Bind    Vis      Ndx Name
  0: 0000000000000000      0 NOTYPE   LOCAL   DEFAULT UND
  1: 0000000000000000      0 FILE     LOCAL   DEFAULT ABS crtstuff.c
  2: 00000000000001050      0 FUNC    LOCAL   DEFAULT 11 deregister_tm_clones
  3: 00000000000001080      0 FUNC    LOCAL   DEFAULT 11 register_tm_clones
  4: 000000000000010c0      0 FUNC    LOCAL   DEFAULT 11 __do_global_ctors_aux
  5: 00000000000004010      1 OBJECT   LOCAL   DEFAULT 22 completed.0
  6: 00000000000003dc0      0 OBJECT   LOCAL   DEFAULT 17 __do_global_ctors_aux_fini_array_entry
  7: 00000000000001100      0 FUNC    LOCAL   DEFAULT 11 frame_dummy
  8: 00000000000003db8      0 OBJECT   LOCAL   DEFAULT 16 __frame_dummy_init_array_entry
  9: 00000000000000000      0 FILE     LOCAL   DEFAULT ABS src_a.cpp
 10: 00000000000000000      0 FILE     LOCAL   DEFAULT ABS src_b.cpp
 11: 00000000000000000      0 FILE     LOCAL   DEFAULT ABS crtstuff.c
 12: 00000000000002158      0 OBJECT   LOCAL   DEFAULT 15 __FRAME_END__
 13: 00000000000000000      0 FILE     LOCAL   DEFAULT ABS
 14: 00000000000002044      0 NOTYPE   LOCAL   DEFAULT 14 __GNU_EH_FRAME_HDR
 15: 00000000000004008      0 OBJECT   LOCAL   DEFAULT 21 __dso_handle
 16: 00000000000001224      0 FUNC    LOCAL   DEFAULT 12 __fini
 17: 00000000000001000      0 FUNC    LOCAL   DEFAULT 8 __init
 18: 00000000000003dc8      0 OBJECT   LOCAL   DEFAULT 18 __DYNAMIC
 19: 00000000000004010      0 OBJECT   LOCAL   DEFAULT 21 __TMC_END__
 20: 00000000000003fe8      0 OBJECT   LOCAL   DEFAULT 20 __GLOBAL_OFFSET_TABLE__
 21: 00000000000000000      0 FUNC    GLOBAL   DEFAULT UND printf@GLIBC_2.2.5
 22: 00000000000000000      0 FUNC    WEAK     DEFAULT UND __cxa_finalize@GLIBC_2.2.5
 23: 00000000000001160     68 FUNC    GLOBAL   DEFAULT 11 _Z12caffe_hahahadd
 24: 00000000000001110     66 FUNC    GLOBAL   DEFAULT 11 _Z8dog_funcif
 25: 000000000000011f0     51 FUNC    GLOBAL   DEFAULT 11 _Z10apple_funcv
 26: 000000000000011b0     50 FUNC    GLOBAL   DEFAULT 11 _Z9baby_funcif
 27: 00000000000000000      0 NOTYPE   WEAK     DEFAULT UND __ITM_deregisterTMCloneTable
 28: 00000000000000000      0 NOTYPE   WEAK     DEFAULT UND __gmon_start__
 29: 00000000000000000      0 NOTYPE   WEAK     DEFAULT UND __ITM_registerTMCloneTable
(pytorch) xu@xu-21HW:~/github/research_export_table/build_cl$
```