Sunflower 125kW / 261kWh PV Hybrid ESS

An integrated PV hybrid energy storage system combining 125kW backup output with 261kWh-class battery capacity.



125kW	261kWh class	Up to 250kW	IP54 / C4
BACKUP POWER	BATTERY	PV INPUT	PROTECTION

CORE SPECIFICATIONS

Backup output	**125kW**
Battery capacity	**261kWh class**
PV input	**Up to 250kW usable PV input**
Thermal management	**Liquid cooling**
Cycle life	**6,000 cycles at cabinet level, 25 °C / 0.5C / 90% DOD; up to 8,000 at cell level**
Ingress protection	**IP54**
Anti-corrosion grade	**C4**
Application	**PV hybrid energy storage**

APPLICATIONS

PV hybrid projects | Commercial backup | Distributed energy projects

COMPLIANCE AND DOCUMENTATION

Standards referenced across the range. The model-specific certificate package for the destination market is issued with the confirmed order configuration.

IEC 62619 | IEC 62477 | IEC 63056 | IEC 61000 | UL | CE | UN38.3 | MSDS | ISO 9001 | ROHS

Certification applicability depends on product model, order configuration, and destination market. Request the latest matching certificate package before final quotation.

STANDARD COMMERCIAL TERMS

Quotation response	Technical review and quotation target within 24 working hours of a complete inquiry.
Product warranty	Warranty terms are stated per model and per battery platform in the quotation.
Minimum order quantity	MOQ is confirmed per model; project and distributor volumes are quoted separately.
Samples	Sample units are available for qualified distributors and project developers.
Lead time	Lead time is confirmed in writing per model and quantity before order confirmation.
Incoterms	FOB, CIF, and DDP terms are supported according to destination and project scope.
Payment terms	T/T and L/C terms are available; final terms are agreed in the sales contract.
OEM / ODM	Private-label and custom configuration projects are supported through the manufacturing partner.

PARAMETERS CONFIRMED PER CONFIGURATION

The following are model- and project-specific. They are stated in the quotation and in the order documentation rather than as blanket figures on a platform datasheet.

- Round-trip efficiency
- Derating curve and ambient limits
- Operating temperature range
- Communication protocols
- Grid-code compliance
- Warranty term in years
- Certificate numbers for this variant
- Single-line diagram and terminal layout
- Transport and container data
- Acoustic noise level

Jiangxi Ruibit Intelligent Technology Co., Ltd. · Ruibit Power

sales@ruibitpower.com · WhatsApp **+86 189 7035 0893**
ruibitpower.com · Jiangxi, China
Manufacturing partner: Yichun Dawnice Manufacture & Trade Co., Ltd.

© 2026 Jiangxi Ruibit Intelligent Technology Co., Ltd.. All specifications describe the standard platform and are subject to confirmation in the quotation. Certification applicability depends on product model, order configuration, and destination market.