

# Dynamic sampling pointnet notes

xyz

Feb 2018

# Contents

<b>1</b>	<b>Deep 3D Learning Notes</b>	<b>2</b>
1.1	potential solutions for over fitting . . . . .	2
1.2	Important improvements . . . . .	2
1.3	Theory . . . . .	3
1.3.1	bidxmap . . . . .	3
1.3.2	group sampling configuration . . . . .	3
1.3.3	Sparse voxel 3DCNN . . . . .	4
1.3.4	multi-scale classification . . . . .	4
1.3.5	Data Augmentation . . . . .	4
1.4	batch size . . . . .	6
1.4.1	bs=27 vs bs=81 . . . . .	6
1.5	feed elements . . . . .	7
1.6	model . . . . .	9
1.7	integration: matterport3d . . . . .	9
1.8	multi scales & mat 1083 . . . . .	12
1.9	multi scales & mat 21826 . . . . .	13
1.10	multi scales & scannet 12887 . . . . .	14
1.11	integration: scannet . . . . .	14
1.12	Semantic segmentation expamples . . . . .	16
1.12.1	good: 1083, train, 0.946 . . . . .	16
1.12.2	bad: 18737,eval 0.071 . . . . .	18
1.13	point++ . . . . .	19
1.13.1	scannet seg . . . . .	19
1.14	whole room global block & multi scales & scan 305 . . . . .	20
1.15	Sparse voxel net . . . . .	22
1.15.1	90000 . . . . .	22
1.15.2	30000 . . . . .	23
1.16	Charles Point++, fast distance sampling . . . . .	24
1.16.1	MODELNET40 . . . . .	24
1.17	MODELNET40, My point++ . . . . .	24
1.17.1	3m . . . . .	26
1.17.2	4m . . . . .	27
1.17.3	5m . . . . .	30
<b>2</b>	<b>res3d</b>	<b>32</b>
2.1	learning rate and batch norm decay . . . . .	32
2.2	aug none and all . . . . .	33
2.2.1	voxel . . . . .	33
2.2.2	Pointnet++ residual . . . . .	33
2.3	aug rotation . . . . .	34

# 1 Deep 3D Learning Notes

## 1.1 potential solutions for over fitting

- combine auxiliary tasks:
  1. use nxnynz as auxiliary loss
  2. boundary
  3. planet
- data augmentation: rotation, different size scale
- data regulation: group norm
- dropout
- combine ShapeNet data
- more powerful network to learn more systematic information:
  1. use large global block size
  2. dynamic sampling
- smaller net

## 1.2 Important improvements

- Generate bxmh5 online. So the randomly missing part in each epoch is different. This maybe solve the info missing problem for sparse voxel 3d cnn, especially considering that block merging cannot be applied for voxel cnn. However, on line sampling can only solve missing problem of training, test missing still need some tricks to perform block merging.
- Check this: my usage of `tf.gather_nd` should cost a lot of memory, maybe too much!

### 1.3 Theory

#### 1.3.1 bidxmap

$bd, bp, bi$   
 $ad, ap, \Rightarrow a_i$

$bs = [bs_0, bs_1]$   
 $= [bi * bd, bi * bd + bp]$   
 $as = [a_i * ad, a_i * ad + ap]$

(1)

$ap \geq bp$

$\begin{cases} as_0 \leq bs_0 \\ as_1 \geq bs_1 \end{cases} \Rightarrow \begin{cases} a_i * ad \leq bi * bd \\ a_i * ad + ap \geq bi * bd + bp \end{cases}$

$\Rightarrow \begin{cases} a_i \leq \frac{bi * bd}{ad} \\ a_i \geq \frac{bi * bd + bp - ap}{ad} \end{cases}$

(2)  $ap \leq bp$

$\begin{cases} as_0 \geq bs_0 \\ as_1 \leq bs_1 \end{cases} \Rightarrow \begin{cases} a_i \geq \frac{bi * bd}{ad} \\ a_i \leq \frac{bi * bd + bp - ap}{ad} \end{cases}$

#### 1.3.2 group sampling configuration

$$steps = [0.1, 0.3, 0.9, 2.7] + [-6.3]$$

$$strides = [0.1, 0.2, 0.6, 1.8] + [-3.6]$$

$$voxel\ size = [3, 4, 4, 3]$$

principles:

(1)Alignment between differert scales:

$$steps[i] = steps[i - 1] + strides[i - 1] * (k - 1) \quad (k = \text{voxel size})$$

(2)Alignment between voxels on one scale:

$$strides[i] \% steps[i - 1] == 0$$

Examples:

$$0.3 = 0.1 + 0.1 * 2 \Rightarrow \text{voxel size} = 3$$

$$0.2 = 0.1 * 2$$

$$0.9 = 0.3 + 0.2 * 3 \Rightarrow \text{voxel size} = 4$$

$$0.6 = 0.3 * 2$$

$$6.3 = 2.7 + 1.8 * 2$$

$$3.6 = 1.8 * 2$$

### 1.3.3 Sparse voxel 3DCNN

#### 1.3.4 multi-scale classification

#### 1.3.5 Data Augmentation

- (1.1) Rotate corrdinate reference: Rotate both point and voxel box  
Performed by rotating points after sampling and grouping.  
This should only be applied to point position (cascade 0). What if also to features (upper cascades).
- (1.2) Rotae point only, or rotate voxel box only.
  - a) It can be performed by rotating points before sampling and grouping.
  - b) If rotate angle is integral times of pi/2, it can be performed by rotating point indices inside the voxel.
 Rotate voxel can be applied to all cascades.
- (2.1) Rotate the global block by the same angle
- (2.2) Rotate each voxel by seperate angle in each scale.  
Since the features are calculated independently in each voxel, it should be fine to apply different rotatio angle for each voxel. It doesn't matter that the rotation center is voxel center or global block center. It alos doesn't matter that it rotates refference or only rotates voxel.

Sparse voxel 3D CNN

$(b, n_1, c_1)$

grouping:  $g_1$  is inconsistent

$(b, [g_1]_{n_2}, c_1)$

extend:  $g_{1m}$  is maximum  $g_1$ . Tile 0!

$(b, n_2, g_{1m}, c_1)$

Transform:  $g_{1i}$  is the intact number of the voxel

$(b, n_2, g_{1i}, c_1)$   
 $(b, n_2, d_1, h_1, w_1, c_1)$

3D CONV MLP

$(b, n_2, d_{2a}, h_{2a}, w_{2a}, c_{2a})$   
 $(b, n_2, d_{2b}, h_{2b}, w_{2b}, c_{2b})$   
 $(b, n_2, 1, 1, 1, c_2)$

$n_2$  is the number of aim block. Get the feature of each aim block.

$(b, n_2, c_2)$

Two main obstacles for performing 3D convolution on point cloud are: (1) there are too many vacant points, (2) the position of points are not aligned. The key idea of sparse voxel is to perform 3D CONV on cascades from the second. Because the positions are actually almost aligned. At the same time, the vacant rate within a small block is acceptably large. Above all, it may be possible to do apply 3D-CONV within a small block.

Centres of blocks in cascades other than first one are actually aligned to the grid. So it is possible to perform 3d convolution directly. However, the average position of points inside these blocks are not aligned. Thus it is also maybe beneficial to utilise a transform net to align them.

On the other hand, there are many vacant points in the block. I am wondering if it is beneficial to set the features of vacant points by a T-net from around existing points.

Purpose of T-Net: fix number + align + till

There are some interesting problems for Transform net:

- Only depend on position or feature.
- Should be resolution invariant.
- If it should be constant for all channels.
- If it should be constant for all local aim blocks.

Reasons that we do not need the T-Net:

- 3d-conv can till features of the vacant points.
- If the base-points are not strictly aligned, add the position to feature map.  
Or get a special feature of positions within the block and then add ot the main feature map.

Transform net:

$(b, n, g_m, 3)$

$(b, n, g_m, c_1)$

$(b, n, g_m, c_2)$

$(b, n, g_m, g_i)$

## 1.4 batch size

### 1.4.1 bs=27 vs bs=81

batch size: 9,27,81

data: xyz-color\_1norm

model: 1AG

sampling & grouping: stride\_0d1\_step\_0d1\_bmap\_nh5\_2048\_0d5\_1\_fmn1-160\_32-32\_12-0d2\_0d6-0d2\_0d6

Figure 1: bs=9



Figure 2: bs=27



## 1.5 feed elements

epoch num = 100

stride\_0d1\_step\_0d1\_bmap\_nh5.2048\_0d5.1\_fmnl-160\_32-32\_12-0d2\_0d6-0d2\_0d6



Figure 3: bs=81



model	batch size	data elements	acc	loss
1AG	9	xyz color	0.890	0.356
1AG	27	xyz color	0.920	0.240
3AG	27	xyz color	0.912	0.273
2A	27	xyz color	0.908	0.294
2AG	27	xyz color	0.902	0.293
1A	27	xyz color	0.883	0.351
1AG	81	xyz color	0.978	0.072
1AG	9	xyz	0.861	0.427
1AG	27	xyz	0.907	0.257
1AG	81	xyz	0.975	0.078
1A	27	xyzmid color	0.889	0.357
3AG	27	xyzmid color	0.933	0.193
2A	27	xyzmid color	0.939	0.177
2AG	27	xyzmid color	0.929	0.208
3AG	27	xyz xyzmid color	0.924	0.230
2A	27	xyz xyzmid color	0.898	0.317
2AG	27	xyz xyzmid color	0.908	0.280
1A	27	xyz xyzmid color	0.910	0.281
1AG	27	xyz xyzmid color	0.944	0.163
1AG	81	xyz xyzmid color	0.976	0.078
2A	81	xyz xyzmid color	0.942	0.173
3AG	81	xyz xyzmid color	0.949	0.147

1. large batch size is better
  2.  $1AG(0.92) > 3AG(0.912) > 2A(0.908) > 2AG(0.902) > 1A(883)$   
1AG is much better than 1A
  - 1AG is a bit better than 3AG ???**
  3. xyz-color is only a bit better than xyz
  4. xyzmid-color is much better than xyz-color
  5. **xyzmid-color is normally much better than xyz-xyzmid-color**
- ???

## 1.6 model

batch size: 50

data: xyz\_midnorm\_block-color\_1norm

epoch\_num = 600

sampling & grouping: stride\_0d1\_step\_0d1\_bmap\_nh5\_12800\_1d6\_2\_fmn3-600\_64\_24-60\_16\_12-0d2\_0d6\_1d2-0d2\_0d6\_1d2

model	acc	loss
3A	0.909	0.248
3AG	0.913	0.231
4AG	0.912	0.232

batch size: 32

data: xyz\_midnorm\_block-color\_1norm

sampling & grouping: stride\_0d1\_step\_0d1\_bmap\_nh5\_12800\_1d6\_2\_fmn6-2048\_256\_64-32\_32\_16-0d2\_0d6\_1d2-0d1\_0d3\_0d6

matterport3d

feed\_data\_elements: ['xyz\_midnorm\_block', 'color\_1norm']

feed\_label\_elements: ['label\_category', 'label\_instance']

train data shape: [ 362 12800 6]

test data shape: [ 384 12800 6]

max epoch = 500

model	acc	loss
1AG	0.944/0.431	0.161/4.633
4AG	0.835/0.401	0.520/3.644

## 1.7 integration: matterport3d

stride_0d1_step_0d1_bmap_nh5_12800_1d6_2_fmn3-512_64_24-48_16_12-0d2_0d6_1d2-0d2_0d6_1d2 17D_1LX_1pX_29h_2az				
model	batch size batch num shuffle	lr ds	data elements	epoch-acc mean-std train/eval

1aG	30/60	0.005	'xyz_midnorm_block', 'color_lnorm', 'nxnynz'	250-0.981
1DSaG	30/60	0.001-40	'xyz_midnorm_block', 'color_lnorm', 'nxnynz'	300-0.914-0.775
1DSaG	30/60	0.001-40	'xyz_midnorm_block', 'color_lnorm', 'nxnynz'	300-0.914-0.775
1DSaG kp0.5	30/60	0.001-80 300-3e-4	'xyz_midnorm_block', 'color_lnorm', 'nxnynz'	300-0.942-0.842
1DSaG kp0.2	30/60	0.001-80 300-3e-4	'xyz_midnorm_block', 'color_lnorm', 'nxnynz'	300-0.928-0.797
1DSaG kp0.5	30/60	0.005-80 300-1.7e-3	'xyz_midnorm_block', 'color_lnorm', 'nxnynz'	300-0.970-0.916
1DSaG kp0.2	30/60	0.005-80 300-1.7e-3	'xyz_midnorm_block', 'color_lnorm', 'nxnynz'	300-0.966-0.924
1DSaG kp0.8	30/60	0.005-80 300-1.7e-3	'xyz_midnorm_block', 'color_lnorm', 'nxnynz'	300-0.976-0.933 500-0.984-0.954
1aG	30/1083	0.003	'xyz_midnorm_block', 'color_lnorm', 'nxnynz'	200-0.947
1aG	30/1083	0.01	'xyz_midnorm_block', 'color_lnorm'	200-0.783 500-0.791
1aG	30/1083	0.003/30 300-0.00012	'xyz_midnorm_block', 'color_lnorm'	200-0.903 300-0.921
1bG	25/1083	0.001-30 100-3e-4 300-4e-5	'xyz_midnorm_block'	100-0.854 200-0.918 300-0.936
1bG	25/1083	0.001-30 100-3e-4 300-4e-5	'xyz_midnorm_block', 'color_lnorm', 'nxnynz'	100-0.914 200-0.957 300-0.966
1bG	25/1083	0.02	'xyz_midnorm_block', 'color_lnorm'	200-0.655 300-0.718
1bG	25/1083	0.02	'xyz_midnorm_block', 'color_lnorm', 'nxnynz'	200-0.772 300-0.823
1bG	25/1083	0.001	'xyz'	200-0.772 90-0.553-0.210
4bG	25/1083	0.001-30 100-3e-4 200-1e-4 300-4e-5	'xyz_midnorm_block', 'color_lnorm', 'nxnynz'	100-0.752 200-0.816 300-0.832

2 1DSaG	30/1083	0.002-80	'xyz_midnorm_block', 'color_lnorm', 'nxnynz'	200-0.930-0.830/0.450 460-0.952-0.881/0.471
1aG	30/19755	0.001-30 50-7e-4 100-3e-4	'xyz_midnorm_block', 'color_lnorm', 'nxnynz'	50-0.752/0.580 100-0.843/0.574 (NoShuf) 102-0.806/0.570 (Shuffle)
1bG	25/19755	0.001-30	'xyz_midnorm_block', 'color_lnorm', 'nxnynz'	38-0.719/0.587 80-0.823/0.583 (NoShuf) 81-0.782/0.587 (Shuffle)
1aG	30/19755	0.02	'xyz_midnorm_block', 'color_lnorm'	56-0.562
1aG	30/19755	0.02 127-0.00483	'xyz_midnorm_block', 'color_lnorm', 'nxnynz'	87-0.616 127-0.686
1bG	25/18737	0.001 N	'xyz_midnorm_block', 'color_lnorm', 'nxnynz'	24-0.682/0.509 70-0.858/0.509
1bG	25/18737	0.001 Y	'xyz_midnorm_block', 'color_lnorm', 'nxnynz'	24-0.738/0.573 70-0.876/0.563 90-0.897/0.561
4bG	25/18737	0.001 Y	'xyz_midnorm_block', 'nxnynz'	24-0.576/0.545
4bG	25/18737	0.001 Y	'xyz_midnorm_block', 'color_lnorm', 'nxnynz'	24-0.594/0.569
1DSaG	30/18737	0.002-80 Y	'xyz_midnorm_block', 'color_lnorm', 'nxnynz'	20-0.688-0.394/0.428-0.224 36-0.742/0.395
1DSaG	30/18737	0.007-80 Y	'xyz_midnorm_block', 'color_lnorm', 'nxnynz'	20-0.725-0.453/0.435-0.206 38-0.783/0.396
Conclusion: 1: nxnynz helps a lot 2: 1bG is much deeper than 1aG, why worse than 1aG 3: learning rate is important, cannot be too large				

## 1.8 multi scales & mat 1083

nh5: stride_0d1_step_0d1_pl_nh5-1d6_2/17D_1LX_1pX_29h_2az bxmh5: stride_0d1_step_0d1_bxmh5-12800_1d6_2_fm4-480_80_24-80_20_10-0d2_0d6_1d2-0d2_0d6_1d2-3A1					
model	bs/bn	lr-decay	elements	loss weight in drop	epoch-pacc-cacc train/eval
4bG_111	20/1083	2-40	xyz_midnorm_color_1norm-nxnynz	1Eck-	110-0.898-0.763 160-0.931-0.827 300-0.967-0.915
4bG_444	15/1083	3-40	xyz_midnorm_color_1norm-nxnynz	1Eck-	60-0.729-0.614 100-0.857-0.721 160-0.920-0.834 260-0.952-0.890 300-0.958-0.913
4bG_444	15/1083	2-40	xyz_midnorm_color_1norm-nxnynz	1Eck-	60-0.778-0.608 100-0.878-0.758 160-0.930-0.838 260-0.957-0.901 300-0.964-0.912
4bG_144	18/1083	2-40	xyz_midnorm_color_1norm-nxnynz	1Eck-	60-0.786-0.637 100-0.876-0.767 160-0.926-0.820 260-0.959-0.885 300-0.962-0.906
4bG_114	20/1083	2-40	xyz_midnorm_color_1norm-nxnynz	1Eck-	60-0.772-0.611 100-0.874-0.764 160-0.926-0.851 260-0.958-0.893 /par 300-0.963-0.904
3aG_444	45/1083	2-40	xyz_midnorm_color_1norm-nxnynz	1Eck-	60-0.893-0.737 100-0.908-0.786 /par 160-0.934-0.833 260-0.950-0.868 /par 300-0.952-0.882
2aG_144	30/1083	2-40	xyz_midnorm_color_1norm-nxnynz	1Eck-	60-0.890-0.754 100-0.922-0.820 /par 160-0.942-0.858: 260-0.957-0.897 /par 300-0.960-0.911

## 1.9 multi scales & mat 21826

nh5: stride_0d1_step_0d1_pl_nh5-1d6_2/ bxmh5: stride_0d1_step_0d1_bxmh5-12800_1d6_2_fm4-480_80_24-80_20_10- 0d2_0d6_1d2-0d2_0d6_1d2-3A1 eval: 17D_1LX_1pX_29h_2az					
model	bs/bn	lr-decay	elements	loss weight in drop	epoch-pacc-cacc train/eval
4bG_114	20/1080	1-30	xyz midnorm color nxnynz	E N	40-0.784-0.545/0.579-0.451 80-0.883-0.699/0.584-0.439 140-0.925-0.795/0.575-0.429
4bG_111	20/1080	2-30	xyz midnorm color nxnynz	E N	40-0.737-0.489/0.587-0.412 80-0.836-0.614/0.582-0.411 95-0.867/0.588
4bG_144	20/1200	2-30	xyz midnorm color nxnynz	E N	40-0.761-0.543/0.601-0.416 80-0.864-0.693/0.602-0.426 95-0.888/0.597
Conclusion: (1) Nein 114 is better than 111					

### 1.10 multi scales & scannet 12887

nh5: stride_0d1_step_0d1_pl_nh5-1d6_2/ bxmh5: stride_0d1_step_0d1_bxmh5-12800_1d6_2_fmnh4-480_80_24-80_20_10-0d2_0d6_1d2-0d2_0d6_1d2-3A1 eval: test					
model	bs/bn	lr-decay	elements	loss weight in drop	epoch-pacc-cacc train/eval
2aG_144	30/420	2-30	xyz midnorm	E N	40-0.833-0.546/0.686-0.89 100-0.926-0.727/0.683-0.326
3aG_144	48/260	2-30	xyz midnorm	E N	40-0.841-0.530/0.668-0.346 100-0.924-0.709/0.673-0.327 200-0.949-0.782/0.673-0.332 <b>300-0.955-0.802/0.671-0.330</b>
4bG_111	22-580	2-30	xyz midnorm	E N	60-0.738-0.434/0.706-0.344 100-0.796-0.506/0.699-0.315 180-0.863-0.589/0.695-0.308
4bG_111	22-580	7-30	xyz midnorm	E N	60-0.705-0.378/0.684-0.362
4bG_144	18-700	2-30	xyz midnorm	E N	40-0.714-0.470/0.6910.433 100-0.794-0.481/0.682-0.393 160-0.849-0.582/0.676-0.362
4aG_1a4	55-220	2-30	xyz midnorm	CN N	40-0.775-0.482/0.654-0.304 100-0.877-0.637/0.661-0.298 160-0.901-0.690/0.660-0.311 220-0.908-0.707/0.655-0.334
4aG_1a4	55-220	2-30	xyz midnorm	E N	40-0.819-0.527/0.684-0.333 100-0.923-0.706/0.681-0.304
Conclusion: (1) 3aG is much better than 4bG. Potential reasons:(a) 4bG is too wide and deep, so that needs more time to train. (b) The batch size of 4bG is too small (2) nein 144 seems is not better than 111 (3) Learning rate 0.002 is better than 0.007 (4) Loss weight CN does not help					

### 1.11 integration: scannet


stride_0d1_step_0d1_bmap_nh5_12800_1d6_2_fm3-256_48_16-56_8-8-0d2_0d6_1d2-0d2-0d6_1d2					
scannet train					
model	loss: E,N,C input drop (No)	batch size batch num shuffle	lr ds	data elements	epoch-point ac-class ac train/eval
1bG	E	25/12887 test Y	0.001 40	xyzmid	23-0.732-0.326/0.664-0.260 25-0.746-0.340/0.669-0.273
1bG	N	25/12887 Y	0.001 40	xyzmid	25-0.733-0.390/0.666-0.252
1bG	C	25/12887 Y	0.001 40	xyzmid	25-0.703-0.356/0.655-0.252
1bG	CN	25/12887 Y	0.001 40	xyzmid	25-0.681-0.366/0.611-0.237
1DSaG	E idp9	30/12887 Y	0.003 80	xyzmid	40-0.738-0.376/0.513-0.228 90-0.832/0.496
1bG	E	25/13091 train_300 Y	0.002 80	xyzmid	60-0.765-0.389/0.700-0.252
1bG	E	25/13091 Y	0.003 80	xyzmid	10-0.646/0.689 60-0.753-0.349/0.691-0.234 100-0.833-0.480/0.672-0.261
1bG	CN	25/13091 Y	0.002 80	xyzmid	60-0.738-0.409/0.670-0.237
1bG	E idp9	25/13091 Y	0.003 80	xyzmid	10-0.641/0.585 16-0.646/0.633
1DSaG	E	30/13091 Y	0.003 80	xyzmid	40-0.794-0.456/0.420-0.154 100-0.872-0.602/0.417-0.153
Conclusion:					
4bG	CN	25/2998- 3521 Y	0.001 40	xyzmid	142-0.726-0.445/0.625-0.242
4bG	E	25/2998- 3521 Y	0.001 40	xyzmid	145-0.792-0.506/0.656-0.257




## 1.12 Semantic segmentation examples

### 1.12.1 good: 1083, train, 0.946


```
log: log-model_1bG-gsbb_3B1-bs25-lr1-ds_30-xyz_midnorm_block-color_1norm-nxnynz-
12800-mat_1083
  model: 1bG
  sampling & grouping:
    stride_0d1_step_0d1_bmap_nh5_12800_1d6_2_fm3-512_64_24-48_16_12-0d2_0d6_1d2-
0d2_0d6_1d2
  batch size: 25
  learning rate: 0.001000
  decay_epoch_step: 30
  matterport3d
  feed_data_elements:['xyz_midnorm_block', 'color_1norm', 'nxnynz']
  feed_label_elements:['label_category', 'label_instance']
  train data shape: [ 1083 12800 9]
```




(a) colorized point cloud




(b) raw point cloud



(c) gt



(d) pred



(e) err

Figure 4: 17DRP5sb8fy\_1\_2\_a946



Figure 5: 17DRP5sb8fy\_0\_25\_a946

### 1.12.2 bad: 18737,eval 0.071

model: 1bG

sampling & grouping: stride\_0d1\_step\_0d1\_bmap\_nh5\_12800\_1d6\_2\_fmn3-512\_64\_24-48\_16\_12-0d2\_0d6\_1d2-0d2\_0d6\_1d2

batch size: 25

learning rate: 0.001000

decay\_epoch\_step: 50

epoch 0 train IsShuffleIdx: True

```

epoch 0 train IsShuffleIdx: True
matterport3d
feed_data_elements:['xyz_midnorm_block', 'color_1norm', 'nxnynz']
feed_label_elements:['label_category', 'label_instance']
train data shape: [18737 12800 9]
test data shape: [ 4172 12800 9]

```



Figure 6: qoi\_r1Q\_r47\_rPc\_rqf\_2\_3\_a0d071 (raw,gt,pred,err,crt)

### 1.13 point++

#### 1.13.1 scannet seg

each room as a block, total 40 block			
batch size batch num	lr ds	data elements	epoch-point ac-class ac train/eval/eval whole scene
30/40	0.001	xyzmid	200-0.675/0.757-0.54/0.799-0.52
25	0.001	xyzmid	200-0.689/0.787-0.556/0.815-0.517i

### 1.14 whole room global block & multi scales & scan 305

nh5: stride_0d1_step_0d1_pl_nh5-1d6.2/ bxmh5: stride_0d1_step_0d1_bxmh5-12800_1d6.2_fm4-480_80_24-80_20_10- 0d2_0d6_1d2-0d2_0d6_1d2-3A1 eval: 17D_1LX_1pX_29h.2az					
model	bs/bn	lr- decay	elements	loss weight in drop	epoch-pacc-cacc train/eval
5bG_114	6/40	2-30	xyz midnorm color	E N	100-0.805-0.645 200-0.865-0.708 300-0.880-0.773
5aG_114	2/140	2-30	xyz midnorm color	E N	100-0.802-0.619 200-0.873-0.694 300-0.895-0.784
5aG_114	2/140	2-30	xyz midnorm color	E idp5	100-0.807-0.687 200-0.877-0.729 300-0.895-0.778
Conclusion: (1) Nein 114 is better than 111					



### 1.15 Sparse voxel net

1.15.1 90000

nh5: 90000_gs-3d6_-6d3/ bxmh5: 90000_gs-3d6_-6d3_fmn1444-6400_2400_320_32-32_16_32_48-0d1_0d3_0d9_2d7- 0d1_0d2_0d6_1d8-pd3-mbf-4A1 eval: test						
model	bs/bn	lr-decay	elements	norm in-net aug	loss weight in drop	epoch-pacc-cacc train/eval
5VaG_114	16/113	1-50	xyz mid	No	Num lw dp:3N5 N shuffle	20-0.764-0.556/0.645-0.362 40-0.864-0.695/0.675-0.351 100-0.935-0.842/0.682-0.380 200-0.961-0.897/0.671-0.374 300-0.969-0.920/0.676-0.360
5VaG_114	30/40	2-40	xyz mid color	No	Num lw dp:466 Y shuffle	20-0.605-0.443/0.577-0.381 40-0.668-0.490/0.544-0.372 100-0.795-0.581/0.653-0.384 120-0.805-0.594/0.676-0.377
5VaG_114	30/40	2-40	xyz mid color	No	Num lw dp:4N6 Y shuffle	20-0.677-0.520/0.607-0.373 40-0.801-0.624/0.659-0.373 100-0.906-0.754/0.687-0.368 120-0.911-0.776/0.692-0.421
5VaG_114	30/40	2-40	xyz mid color	No	Num lw dp:N66 Y shuffle	20-0.614-0.457/0.566-0.344 40-0.685-0.500/0.552-0.356 60-0.741-0.552/0.650-0.357 80-0.770-0.564/0.649-0.392 98-0.797-/0.675
5VaG_114	30/40	2-40	xyz mid color	Mid	Num lw dp:555 Y shuffle	100-0.746/0.649 300-0.823-0.608/0.682-0.377
5VaG_114	39/40	2-40	xyz mid color	Mid	Num lw dp:5N5 Y shuffle	40-0.839-0.649/0.656-0.353 100-0.918-0.771/0.681-0.381
5VaG_114	36/40	1-40	xyz mid color	Mid	Num lw dp:NN5 Y shuffle	40-0.833-0.655/0.628-0.329 100-0.916-0.772/0.682-0.339 178-0.941/0.686
5VaG_114	7/240	2-40	xyz mid color	Mid Group Norm	Num lw dp:NN5 Y shuffle	40-0.664/0.577 100-0.816-0.586 150-0.869-0.592
5VaG_114	9	2-40	xyz mid color	Rotate Ref	Num lw dp:NN5 Y shuffle	40-0.787-0.620/0.662-0.401 100-0.907-0.755/0.699-0.410 200-0.939-0.816/0.6990.430 300-0.950-0.845/0.691-0.430

Conclusion:

Mid norm in sub block seems worse than no.

The influence of input drop seems not obvious.

Dropout of cnn (0.5) makes the net really hard to train. Seems no good for overfitting.

Group norm is poor.

### 1.15.2 30000

bxmh5: 30000_gs-2d4_-3d4_fmn1444-2048_1024_128_24-48_32_48_27-0d1_0d4_1_2d2-0d1_0d2_0d6_1d2-pd3-mbf-4B1 eval: test Void point id deleted						
model	bs	lr-decay	elements	norm in-net aug	loss weight in drop	epoch-pacc-cacc train/eval
5VaG_114	9	2-40	xyz mid color	Rotate Ref	Num lw dp:5N5 Y shuffle	20-0.749/0.645 30-0.810/0.705 40-0.870/0.744 80-0.917-0.737/0.7540.422 120-0.929-0.765 200-0.953-0.774 300-0.962/0.774
<pre> train[200-280] t(d,c):[4.1 25.5 79.6] loss: 0.337 acc: 0.954-0.041 acc histogram: [0.000e+00 0.000e+00 0.000e+00 0.000e+00 3.084e-04 1.850e-03 8.973e-02 8.668e-01 4.009e-02] weighted class pre/rec/IOU: 0.962 0.954 0.918 N=97.290000M points ave/std: 0.954 0.041 class ave pre/rec/IOU : 0.825/ 0.948/ 0.799 class_pre: -0.00, 0.98, 0.98, 0.92, 0.89, 0.83, 0.91, 0.88, 0.88, 0.76, 0.81, 0.76, 0.79, 0.79, 0.77, 0.71, 0.80, 0.84, 0.57, 0.84, class_rec: -0.00, 0.90, 0.93, 0.96, 0.91, 0.94, 0.98, 0.98, 0.95, 0.92, 0.98, 0.96, 0.97, 0.94, 0.96, 0.94, 0.97, 0.96, 0.96, 0.94, class_IOU: -0.00, 0.89, 0.91, 0.90, 0.84, 0.81, 0.91, 0.88, 0.86, 0.72, 0.80, 0.76, 0.78, 0.76, 0.76, 0.69, 0.78, 0.82, 0.56, 0.80, number(K): 0,34786,31997, 5563, 4131, 1808, 2598, 1901, 3002, 278, 272, 223, 880, 631, 2163, 815, 113, 462, 432, 2761, classname: unann, wall,floor,chair,table, desk, bed,books, sofa, sink,batht,toile,curta,count, door,windo,showe,refri,pictu,cabin,o ---- eval[200-79] t(d,c):[4.0 11.6 81.8] loss: 22.747 acc: 0.774-0.179 acc histogram: [0.007 0.007 0.011 0.015 0.038 0.064 0.141 0.207 eval[200-79] t(d,c):[4.0 11.6 81.8] loss: 22.747 acc: 0.772-0.178 acc histogram: [0.005 0.006 0.012 0.013 0.042 0.072 0.148 0.207 weighted class pre/rec/IOU: 0.822 0.772 0.703 N=28.290000M points ave/std: 0.772 0.178 class ave pre/rec/IOU : 0.429/ 0.344/ 0.278 class_pre: -0.00, 0.82, 0.94, 0.68, 0.58, 0.45, 0.60, 0.43, 0.57, 0.37, 0.44, 0.52, 0.11, 0.42, 0.20, 0.07, 0.28, 0.33, 0.03, 0.4 class_rec: -0.00, 0.88, 0.92, 0.68, 0.52, 0.30, 0.51, 0.38, 0.55, 0.20, 0.36, 0.38, 0.03, 0.30, 0.06, 0.00, 0.15, 0.16, 0.00, 0.3 class_IOU: -0.00, 0.74, 0.88, 0.54, 0.43, 0.24, 0.43, 0.27, 0.41, 0.16, 0.28, 0.30, 0.02, 0.22, 0.05, 0.00, 0.11, 0.13, 0.00, 0.2 number(K): 0,10626, 8669, 1584, 1231, 587, 725, 460, 888, 66, 47, 62, 222, 243, 675, 100, 16, 94, 54, 80 classname: unann, wall,floor,chair,table, desk, bed,books, sofa, sink,batht,toile,curta,count, door,windo,showe,refri,pictu,cabi Model saved in file: model.ckpt-200 **** Epoch 201 **** 2018-05-06 11:42:20 </pre>						
Conclusion:						



## 1.16 Charles Point++, fast distance sampling

### 1.16.1 MODELNET40

config	epoch-train acc/eval acc-eval cls acc
batch_size=32, decay_rate=0.7, decay_step=200000, learning_rate=0.001, log_dir='log', max_epoch=251, model='pointnet2_cls_ssg', momentum=0.9, normal=False, num_gpus=2, num_point=1024, optimizer='adam'	4-0.746/0.819-0.748 10-0.802/0.848-0.788 40-0.886/0.875-0.858 60-0.916/0.892-0.859
aug=True, batch_size=32, decay_rate=0.7, decay_step=200000, gpu=1, indrop=True, learning_rate=0.001, log_dir='log', max_epoch=251, model='pointnet2_cls_ssg', momentum=0.9, normal=True, num_point=8 192, optimizer='adam', shuffle=True	10-0.806/0.853-0.817 60-0.939/0.8946/0.868 100-0.971/0.9036-0.883

## 1.17 MODELNET40, My point++

*After fix shuffle problem*



### 1.17.1 3m

bxmh5:1024_gs3_3_fmn1444-1024_320-24_32-0d2_0d4-0d1_0d2-pd3-2M1						
No block merging. Replicate redundant.						
model	bs	lr bn de- cay	elements group pos	norm in- net aug	loss weight in drop	epoch-pacc-cacc train/eval
3m	36	1-30 7-7	xyzg bc	Rotate Ref	E, NN5	1-0.707/0.775 2-0.744/0.804 4-0.785/0.817 10-0.831/0.826 30-0.906/0.857 60-0.967/0.852
3m	36	1-30 7-7	xyzg mean	Rotate Ref	E, NN5	1-0.704/0.754 2-0.747/0.781 4-0.783/0.810 10-0.839/0.835 60-0.969/0.865
3m	36	1-30 7-7	xyzrsg mean	Rotate Ref	E, NN5	10-0.844/0.830 60-0.978/0.868
3m	36	1-30 7-7	xyzrsg, nrxnynz mean	Rotate Ref	E, NN5	10-0.887/0.881 60-0.985/0.890
bxmh5:4096_gs3_3_fmn1444-1024_320-48_32-0d2_0d4-0d1_0d2-pd3-2M2						
No block merging. Replicate redundant.						
3m	28	1-30 7-7	xyzg mean	Rotate Ref	E, NN5	1-0.698/0.795 10-0.834/0.853 60-0.962/0.874
3m	28	1-30 7-7	xyzg bc	Rotate Ref	E, NN5	1-0.703/0.786 10-0.832/0.847 60-0.957/0.867
3m	28	1-30 7-7	xyzrsg mean	Rotate Ref	E, NN5	1-0.695/0.764 10-0.840/0.847 60-0.976/0.880
3m	28	1-30 7-7	xyzrsg, nrxnynz mean	Rotate Ref	E, NN5	1-0.747/0.814 10-0.882/0.879 60-0.985/0.897 160-0.998/0.905
bxmh5:4096_mgs1_gs2_2_fmn14_mvpl-1024_240_1-48_27_160-0d2_0d4-0d1_0d2-pd3-mbf-neg-2M2p						
3Vm	58	1-30 5-5	xyzrsg nrxnynz mean	Rotate Ref	E, NN5	1-0.549/0.635 10-0.852/0.812 30-0.961/0.840 60-0.984/0.837 100-0.994/0.828
3Vm	58	1-30 5-5	xyzrsg nrxnynz mean	Rotate Ref	E, 3N5	1-0.543/0.614 10-0.852/0.798 20-0.926/0.825 27-0.955/0.800
3m	52	1-30 5-5	xyzrsg nrxnynz mean	RotateRef	E, NN5	10-9.763/0.803 60-0.879-0.876 100-0.921/0.872

Conclusion:

(0) The performance of pointnet++ based on fareset distance sampling is better. The reason may be on line sampling, the last part is each epoch is different

### 1.17.2 4m

bxmh5:4096_mgs1_gs2_2d2_fmn1444_mvp1-3200_1024_48_1-18_24_56_56-0d1_0d2_0d6-0d0_0d1_0d4-pd3-mbf-neg-3M1						
model	bs	lr bn de- cay	elements group pos	aug	loss weight in drop	epoch-pacc-cacc train/eval
4m	16	1-30	xyzrsg- nxxnynz	RotateRef	E NN5	10-0.688/0.755 60-0.845/0.859 100-0.873/0.875 200-0.914/0.880
4m	16	1-30	xyzg	RotateRef	E NN5	10-0.635/0.680 60-0.784/0.807 120-0.837/0.830 241-0.878/0.846
4m	16	1-30	xyzrsg- nxxnynz	RotateRef	E 3N5	10-0.623/0.671 60-0.766/0.793 120-0.821/0.810
4m	16	1-30	xyzg- nxxnynz	RotateRef	E NN5	10-0.691/0.726 60-0.840/0.853 1100-0.874/0.862 120-0.886/0.861
4Vm	56	1-30	xyzg- nxxnynz	RotateRef	E NN5	10-0.894/0.817 60-0.993/0.834 79-0.997/0.842

bxmh5:4096_mgs1_gs2_2d2_fmnl444_mvpl-3200_1024_48_1-18_24_56_56-0d1_0d2_0d6-0d0_0d1_0d4-pd3-neg-3M1 No Block Merging						
4m	16	1-30	xyzg-nxnynz	RotateRef	E NN5	10-0.711/0.705 60-0.878/0.850 100-0.912/0.869
4m	16	1-30	xyzg	RotateRef	E NN5	10-0.644/0.682 60-0.778/0.802 100-0.816/0.827
4m	16	1-30	xyzs	RotateRef	E NN5	10-0.637/0.676 60-0.784/0.792 100-0.821/0.828
4m	16	1-30	xyzr	RotateRef	E NN5	10-0.658/0.698 60-0.801/0.821 70-0.815/0.819
4Vm	30	1-30	xyzg-nxnynz	RotateRef	E NN5	10-0.890/0.830 51-0.992/0.841 100-0.999/0.847 113-0.999/0.853 129-0.999/0.847
4Vm	30	1-30	xyzg-nxnynz	RotateRef	E 575	10-0.846/0.796 49-0.982/0.841
4Vm	30	1-30	xyzg-nxnynz	RotateRef	E N75	10-0.848/0.824 60-0.989/0.831
4Vm	28	1-30	xyzg	RotateRef	E NN5	10-0.884/0.821 60-0.994/0.838 80-0.996/0.842
4Vm	30	1-30	xyzg-nxnynz	RotateRef RotateVox	E NN5	10-0.752/0.663 60-0.949/0.828 79-0.969/0.814
Conclusion: (1) Input drop out increase overfitting here. This is not reasonable! (2) Learns much slower than 3m? (3) The variance is greater, maybe because of small batch size. (4) Block merge is a little bit helpful for pointnet++ (5) xyzs is a little bit better than xyzg for pointnet++						

bxmh5:4096_mgs1_gs2_2d2_fmn1444_mvp1-3200_1024_48_1-18_24_56_56-0d1_0d2_0d6-0d0_0d1_0d4-pd3-neg-3M1 No Block Merging						
4Vm-S2	30	3-30	xyzs	RotateRef RotateVox	E NN5	10-0.885/0.815 30-0.979/0.847 40-0.982/0.855
4Vm-S2	30	3-30	xyzs nxnynz	RotateRef RotateVox	E NN5	10-0.889/0.843 30-0.980/0.843 60-0.995/0.848
4Vm-S3	30	3-30	xyzs nxnynz	RotateRef RotateVox	E NN5	10-0.894/0.838 30-0.981/0.851 60-0.996/0.853
4Vm-S4	30	3-30	xyzs nxnynz	RotateRef RotateVox	E NN5	10-0.888/0.862 30-0.976/0.865 48-0.989/0.850
4Vm-S3 normal label	50	1-20	xyzg	RotateRef RotateVox	E NN5	10-0.930/0.829 30-0.983/0.841 50-0.991/0.847 69-0.998/0.861 80-0.998/0.855
4Vm-S3 normal label	50	1-20	xyzrsg	RotateRef RotateVox	E NN5	10-0.923/0.847 30-0.981/0.837 52-0.996/0.865 53-0.993/0.856
4Vm-S2L2	29	1-30	xyzs nxnynz	RotateRef RotateVox	E NN5	10-0.900/0.841 30-0.981/0.838 60-0.996/0.851
4Vm-S3L3	29	1-30	xyzs nxnynz	RotateRef RotateVox	E NN5	10-0.899/0.841 30-0.992/0.847 60-0.996-0.854
Conclusion:						
bxmh5:4096_mgs1_gs2_2d2_fmn1444_mvp1-3200_1024_48_1-18_24_56_56-0d1_0d2_0d6-0d0_0d1_0d4-pd3-neg-3M1 No Block Merging						
4Vm1	24	1-10	xyzs nxnynz	RotateIn	E	10-0.862/0.859
4Vm1-S3	24	1-10	xyzs nxnynz	RotateIn	E	10-0.874/0.867 11-0.883/0.873 20-0.952/0.868 40-0.990/0.862

### 1.17.3 5m

bxmh5:10000_gs3_3d5_fmnl444_mvp1-2560_1024_80_16_1-24_32_48_27_48-0d0_0d2_0d5_1d1-0d0_0d1_0d3_0d6-pd3-mbf-neg-4M1						
model	bs	lr bn de- cay	elements group pos	aug	loss weight in drop	epoch-pacc-cacc train/eval
5m1	32	1-30	xyzg	RotateRef	E	60-0.956/0.843 200-0.998/0.845
5m	48	1-30	xyzrsg- nxnyznz	RotateRef	E	60-0.852/0.837 100-0.894/0.866 119-0.923-0.878 150-0.938-0.867
5Vm	32	1-30	xyzr	N	E	10-0.853/0.802 60-0.985/0.829 160-0.998/0.831
Conclusion: (0)						





## 2 res3d

### 2.1 learning rate and batch norm decay

Merged_tfrecord/6_mgs1_gs2_2-mbf-neg_fmnl4_mvp1-1024_240_1-64_27_256-0d2_0d4-0d1_0d2-pd3-2M2pp	
model bs feed aug lr0 bnd optimizer filters0	train/eval
pl34m 64 xyzg-nxnynz none 0.01 0.5 adam 32	0-?/0.12 5-0.337/0.175 10-0.425/0.368 30-0.544/0.625
pl34m 64 xyzg-nxnynz none 0.01 0.997 adam 32	0-?/0.033 5-0.073/0.048 10-0.056/0.044 20-0.099/0.119
pl34m 64 xyzg-nxnynz none 0.001 0.5 adam 32	0-?/0.580 5-0.781/0.756 15-0.854/0.818
pl34m 64 xyzg-nxnynz none 0.001 0.997 adam 32	0-?/0.041 5-0.491/0.687 10-0.712/0.503 20-0.973/0.853
pl34m 64 xyzg-nxnynz all 0.001 0.7 adam 32	0-0.090/0.110 24-0.557/0.524
pl34m 32 xyzg-nxnynz none 0.001 0.7 adam 32	0-0.016/0.516 24-0.815/0.823
pl34m 64 xyzg-nxnynz none 0.0001 0.7 adam 32	0-0.037/0.417 24-0.935/0.812
pl34m 64 xyzg-nxnynz none 0.001 0.7 adam 32	0-0.047/0.560 24-0.897/0.825
pl34m 64 xyzg-nxnynz none 0.001 0.9 adam 32	0-0.029/0.464 24-0.883/0.821
pl34m 64 xyzg-nxnynz all 0.001 0.7 momentum 32	0-0.055/0.078 24-0.577/0.472
pl34m 64 xyzg-nxnynz none 0.0001 0.7 momentum 32	0-4.177/3.609-0.015/0.164 30-0.640/1.087-0.911/0.775
pl34m 64 xyzg-nxnynz none 0.001 0.7 momentum 32	0-0.022/0.478 24-0.987/0.829
pl34m 64 xyzg-nxnynz none 0.001 0.9 momentum 32	0.058/0.547 24-0.980/0.833
pl34m 32 xyzg-nxnynz none 0.001 0.7 momentum 32	0-0.045/0.608 24-0.965/0.849
Conclusion: (0) Learning rate too high leads to no convergence (1) Batch norm decay seems always better. Especially can allow high learning rate. () bnd 0.5, 0.997 doesnt work () lr 0.001 > 0.01	

## 2.2 aug none and all

### 2.2.1 voxel

Merged.tfrecord/6_mgs1_gs2_2-mbf-neg_fmn14_mvp1-1024_240_1-64_27_256-0d2_0d4-0d1_0d2-pd3-2M2pp	
model bs feed aug lr0 bnd optimizer filters0	train/eval
rs34V 48 xyzg-nxnynz all 0.001 0.9 adam 32	0-113.598/2.431-0.084/0.448 9-1.675/1.232-0.687/0.755 35-0.341/1.007-0.980/0.850
rs34V 48 xyzg-nxnynz f 0.001 0.9 adam 32	0-7.958/2.025-0.027/0.581
rs34V 48 xyzg-nxnynz none 0.0001 0.9 adam 32	0-4.220/1.459-0.059/0.712 15-0.481/1.612-0.976/0.803
rs34V 48 xyzg-nxnynz none 0.001 0.9 adam 32	0-7.067/3.760-0.052/0.509 9-0.732/1.176-0.890/0.812 25-0.365/1.026-0.974/0.844 6-0.307/1.025-0.993/0.870 7615 40-0.180/1.284-0.999/0.860 16041
rs34V 48 xyzg-nxnynz r 0.001 0.9 adam 32	0-8.119/2.267-0.011/0.486 9-0.842/0.982-0.864/0.819 40-0.275/1.147-0.990/0.852
rs34V 48 xyzg-nxnynz s 0.001 0.9 adam 32	0-43.883/2.201-0.047/0.585 9-0.710/1.168-0.893/0.790 40-0.229/1.042-0.994/0.876
Conclusion: (0) $s > r$	

### 2.2.2 Pointnet++ residual

Merged.tfrecord/6_mgs1_gs2_2-mbf-neg_fmn14_mvp1-1024_240_1-64_27_256-0d2_0d4-0d1_0d2-pd3-2M2pp	
model bs feed aug lr0 bnd optimizer filters0	train/eval
rs34m 16 xyzg-nxnynz none 0.001 0.9 adam 32	625-4.059/1.490-0.041/0.671 6160-0.558/1.032-0.949/0.832 19075-0.418/0.937-0.991/0.878
rs34m 48 xyzg-nxnynz none 0.0001 0.9 adam 32	8220-0.402/1.013-1.000/0.837
rs34m 48 xyzg-nxnynz none 0.01 0.9 adam 32	0-26.717/1.521-0.016/0.703 215 9-0.665/1.004-0.902/0.816 2060 35-0.303/0.758-0.998/0.894 30-0.149/0.678-1.000/0.897 13950
rs34m 96 xyzg-nxnynz none 0.001 0.9 adam 32	0-4.485/1.356-0.035/0.721 112 9-0.530/1.044-0.958/0.832 1030 35-0.382/0.966-1.000/0.876 3682

### 2.3 aug rotation

Merged_tfrecord/6_mgs1_gs2_2-mbf-neg_fmnl4_mvp1-1024_240_1-64_27_256-0d2_0d4-0d1_0d2-pd3-2M2pp	
model bs feed aug lr0 bnd optimizer filters0	train/eval
rs34m 32 xyzs none 0.001 0.9 adam 32	1 4.067/1.980-0.054/0.579 10 0.674/1.242-0.914/0.771 25 0.517/1.245-0.961/0.804 40 0.391/1.158-1.000/0.837
rs34m 64 xyzg none 0.001 0.9 adam 32	1 4.251/1.741-0.034/0.644 10 0.678/1.145-0.913/0.791 25 0.502/1.343-0.963/0.802
rs34m 32 xyzs none 0.01 0.9 adam 32	1 10.757/1.779-0.016/0.623 0.796/1.124-0.859/0.771 25 0.658/0.981-0.880/0.819 35 0.270/0.879-0.999/0.860
rs34m 64 xyzs none 0.01 0.9 adam 32	
rs34m 64 xyzs none 0.001 0.9 adam 32	1 4.133/1.766-0.016/0.620 10 0.582/1.199-0.945/0.808 25 0.454/1.501-0.980/0.774 40 0.389/1.187-1.000/0.838
rs34m 64 xyzs r-360_0_0 0.01 0.9 adam 32	1 48.100/2.417-0.014/0.440 10 1.038/1.276-0.796/0.731 25 0.705/1.248-0.868/0.743 40 0.318/0.979-0.986/0.839
rs34m 64 xyzs r-0_360_0 0.01 0.9 adam 32	1 44.500/3.347-0.009/0.246 9 1.481/1.560-0.696/0.668
rs34m 64 xyzs r-0_0_360 0.01 0.9 adam 32	1 53.404/2.661-0.009/0.375 10 1.302/1.431-0.719/0.688