Table 1: Group-wise H=20 comparison on the 840-instance Caserta benchmark. Entries are arithmetic means of per-instance R/N; lower is better.

Group	N	Leveling	GP-C	GP-C+E	GP-C+O	GP-C+E+O	MoE-LoRA
3-3	9	0.6861	0.5665	0.5723	0.5690	0.5693	**0.5639**
3-4	12	0.6188	0.5253	0.5287	0.5274	0.5275	**0.5188**
3-5	15	0.5783	0.4706	0.4708	0.4707	0.4708	**0.4683**
3-6	18	0.5875	0.4704	0.4700	0.4700	0.4702	**0.4694**
3-7	21	0.5595	0.4454	**0.4450**	0.4456	0.4454	0.4464
3-8	24	0.5427	0.4514	0.4504	0.4518	0.4506	**0.4458**
4-4	16	0.8594	0.6899	0.6891	0.6903	0.6888	**0.6526**
4-5	20	0.8962	0.6817	0.6813	0.6833	0.6815	**0.6713**
4-6	24	0.7906	0.6100	0.6131	0.6152	0.6134	**0.6017**
4-7	28	0.7991	0.6016	0.6039	0.6049	0.6044	**0.5914**
5-4	20	1.0938	0.8424	0.8464	0.8505	0.8453	**0.8033**
5-5	25	1.1190	0.8381	0.8453	0.8465	0.8478	**0.8053**
5-6	30	1.1042	0.8023	0.8127	0.8164	0.8120	**0.7825**
5-7	35	1.0721	0.7518	0.7575	0.7626	0.7576	**0.7307**
5-8	40	1.0650	0.7423	0.7435	0.7494	0.7450	**0.7310**
5-9	45	1.0550	0.7288	0.7334	0.7376	0.7332	**0.7233**
5-10	50	1.0535	0.7217	0.7261	0.7298	0.7271	**0.7193**
6-6	36	1.3528	0.9830	0.9853	0.9942	0.9872	**0.9431**
6-10	60	1.3058	0.8578	0.8641	0.8660	0.8650	**0.8524**
10-6	60	2.4896	1.6515	1.6507	1.6725	1.6563	**1.4808**
10-10	100	2.3028	1.4385	1.4549	1.4579	1.4560	**1.4202**
Overall	–	1.0444	0.7557	0.7593	0.7625	0.7597	**0.7344**

Notes: Each size group contains 40 fixed Caserta instances. GP entries average 30 independently evolved rules per terminal set; MoE-LoRA entries average three formal training seeds; Leveling is deterministic. No seed was selected using Caserta performance. Group S-W denotes initial height S and number of stacks W, so $N = S \times W$.