







	构	件	明		细	表	
*		长度	ŧ	1 1 (kg)			
集号	規格	(mn)	Ĩ	- #	小 计	备	往
401	Q345L110X8	8739	1	118.26	118.3	非 例订	
402	Q345L110X8	8739	2	118.26	236.5		
403	0345L110X8	8739	1	118.26	118.3		
404	L56X5	5078	8	21.59	172.7		
405	L40X3	1402	8	2.60	20.8		
406	L40X3	1252	8	2.32	18.5		
407	L40X3	1408	8	2.61	20.9	加角	
408	L56X5	5040	8	21.43	171.4		
409	L40X3	1368	8	2.53	20.3		
410	L40X3	1208	8	2.24	17.9		
411	L40X3	1558	8	2.89	23.1	領角	
412	L56X5	4687	8	19.92	159.4		
413	L40X3	1283	8	2.38	19.0		
414	L40X3	1126	8	2.09	16.7		
415	L40X3	1558	8	2.89	23.1	領角	
416	Q345L110X8	670	4	9.07	36.3	撤	
417	-6X162	226	8	1.72	13.8		
418	-10X50	50	4	0.20	0.8		
	合 计			1207.8	kg		
螺栓、脚钉、垫圈明细表							

	滁性、脾10、匙圆90利4 5							
名称	级别	規格	符号	敷量	1 1(kg)	¥	推	
_	6.8	M16X40	Ø	80	11.7			
集		M16X50	Ø	68	10.9			
		M16X60)Q(8	1.4			
		M20X55	Ø	80	23.6			
栓								
Ħ	6.8	M16X180	0	20	6.5			
er er		M20X200	1 🖺	2	1.2			
ì	Q235	-3(ø17.5)	規格(个個	œ	0.1			
		-4(ø17.5)	/	16	0.2			
合 计			55.6 kg					

	国家电网公司 W STATE GRID								
110~	110~500kV輸电线路通用设计				施工图	版次	1		
批准									
审核									
校枝									
设计									
CAD 制图									
	比例	1:20	图号	2B3	3-ZMC3-05				