







		构	件		ļ	yj		细	表	
集号	規	格	K (mn)	ŧ	敷量	1	#	(kg) 小 计	备	推
901	L56X4		499	8	4	17.	25	68.9	开始处理	
902	-6X23	4	23	37	8	2.	61	20.9		
903	L50X4		287	7	2	8.80		17.6		
904	L50X4		2877		2	8.80		17.6		
905	L50X4		287	877 2		8.80		17.6	領角	
906	L50X4		2877 2		2	8.80		17.6	加力	
907	L40X3		592		2	1.10		2.2	開角	
908	L40X3		592		2	1.10		2.2	加角	
909	L40X3		59	592		1.10		4.4		
910	L40X3		1924		4	3.56		14.3		
911	L40X3		465		4	0.86		3.4		
912	L40X3		1079		4	2.00		8.0	- 45 8	
913	-5X282		282		4	3.12		12.5		
				T						
				T						
	合 i	ŀ			21	17.2 k	9			
	į	螺栓	、胸	旬	. 4		明	细表		
名称	级别	拠	格	4	手	数量	1	i i (kg)	쑠	淮
_	6.8	M16X40		-	<u>a</u>	84	Т	12.3		

	国家电网公司 W STATE GRID												
110~	500kV输	电线路通用		萬工图	版次 1								
批准													
审核			2B3-ZMC4直线塔 場面面針 地図 9										
校枝	I-ZMC4直线塔	(9)											
设计			横隔面结构图 タ										
CAD 制图													
	比例	1: 20	图号	2B3	3-ZMC4-10								