

	!	螺栓、脚	钉、垫		明细表				构	件		明	细	表(插入式
\$ \$	級則	规格	# 5	*	重量(kg)	*	推	*	規格	长度	#	1 I	(kg)	* ±
_		M16X40	(a)	332	48.5			-	Q420L125X12	(mm) 9810	1	222.65	222.6	香胸钉
1		M16X50	Ø	96	15.4				Q420L125X12		3	222.65	668.0	7.0.1
	6.8≰	M20X45	Ô	88	23.6				L75X5	7934	4	46.16	184.6	
		M20X55	Ø	80	23.0				L75X5	7934	4	46.16	184.6	
		M20X65	×	168	52.6				L45X4	759	8	2.08	16.6	
÷									L40X4 L45X4	1449 1468	8	3.51 4.02	28.1 32.2	
									L40X4	1871	8	4.02	36.2	
_	0.04	M16X180		20	7.6				L50X5	2177	8	8.21	65.7	
ī	6.8₡	M20X200	P	1	0.7				L40X4	1501	8	3.64	29.1	
									L50X4	2072	8	6.34	50.7	
	Q235	-3(ø17.5)	裁数X个最	24	0.3				L45X4	2886	4	7.90	31.6	初角
	4200	l							L45X4	2886	4	7.90	31.6	切角
	^	Ħ	11	71.7	(g				L45X4	1705	4	4.66	18.6	
									L45X4 L56X4	1705 2404	4	4.66 8.28	18.6 33.1	
									L56X4	2404	4	8.28	33.1	
									-12X60	60	8	0.34	2.7	整块
									L63X5	6930	4	33.42	133.7	
									L90X7	4330	4	41.81	167.2	切角
									L90X7	4330	4	41.81	167.2	
									L50X4	2351	8	7.19	57.5	
									L50X4 0420L110X10	1823 530	8	5.58 8.85	70,8	##
									Q420L110X10		16	4.58	73.3	7 8
									-6X231	264	8	2.87	23.0	
									-8X338	356	4	7.56	30.2	# 360mm
									-8X159	259	8	2.59	20.7	
								929	L50X5	3976	2	14.99	30.0	
									L50X5	3976	2	14.99	30.0	切角
									L50X5	3976	2	14.99	30.0	切角
									L50X5	3976	2	14.99	30.0	
									L50X5 L45X4	2371 801	2	8.94 2.19	35.8 4.4	初業
									L45X4	801	2	2.19	4.4	初角
									L45X4	801	4	2.19	8.8	7.7
								937	L45X4	1573	4	4.30	17.2	一端切胶
									L45X4	607	4	1.66	6.6	
									-6X165	165	4	1.28	5.1	
									L40X3	977	8	1.81 5.61	7.2	-
									L45X4 L50X4	2052 2907	8	8.89	71.1	1
										4887	8	20.77	166.2	
									II bbXb		, -			
									L56X5 L45X4	1558	8	4.26	34.1	
								944 945	L45X4 L45X4	1558 1614	8	4.42	35.4	切角
								944 945 946	L45X4 L45X4 L40X3	1558 1614 930	8	4.42 1.72	35.4 13.8	
								944 945 946 947	L45X4 L45X4 L40X3 -6X136	1558 1614 930 181	8 8 4	4.42 1.72 1.16	35.4 13.8 4.6	火曲
								944 945 946 947 948	L45X4 L45X4 L40X3 -6X136 -6X136	1558 1614 930 181 181	8 8 4 4	1.72 1.16 1.16	35.4 13.8 4.6 4.6	火曲
								944 945 946 947 948 949	L45X4 L45X4 L40X3 -6X136 -6X136 -6X141	1558 1614 930 181 181 182	8 8 4 4 4	4.42 1.72 1.16 1.16 1.21	35.4 13.8 4.6 4.6 4.8	火曲 火曲 火曲
								944 945 946 947 948 949 950	L45X4 L45X4 L40X3 -6X136 -6X136 -6X141 -6X141	1558 1614 930 181 181 182 182	8 8 4 4 4 4	4.42 1.72 1.16 1.16 1.21 1.21	35.4 13.8 4.6 4.6 4.8 4.8	大曲 大曲 大曲 大曲
								944 945 946 947 948 949	L45X4 L45X4 L40X3 -6X136 -6X136 -6X141	1558 1614 930 181 181 182	8 8 4 4 4	4.42 1.72 1.16 1.16 1.21	35.4 13.8 4.6 4.6 4.8 4.8 4.0	火曲 火曲 火曲
								944 945 946 947 948 949 950	L45X4 L45X4 L40X3 -6X136 -6X136 -6X141 -6X141 -6X143	1558 1614 930 181 181 182 182 148 148 169	8 4 4 4 4 4 4 4	4.42 1.72 1.16 1.16 1.21 1.21 1.00 1.00	35.4 13.8 4.6 4.6 4.8 4.8 4.0 4.0	文章 文章 文章 文章 文章 文章
								944 945 946 947 948 949 950 951 952 953 954	L45X4 L45X4 L40X3 -6X136 -6X136 -6X141 -6X141 -6X143 -6X143 -6X142 -6X142	1558 1614 930 181 181 182 182 148 148 169	8 8 4 4 4 4 4 4 4	4.42 1.72 1.16 1.16 1.21 1.21 1.00 1.00 1.13	35.4 13.8 4.6 4.6 4.8 4.8 4.0 4.0 4.5	
								944 945 946 947 948 950 951 952 953 954 955	L45X4 L45X4 L40X3 -6X136 -6X136 -6X141 -6X141 -6X143 -6X143 -6X142 -6X142 -6X153	1558 1614 930 181 181 182 182 148 148 169 169	8 8 4 4 4 4 4 4 4 4	1.72 1.16 1.16 1.21 1.21 1.00 1.00 1.13 1.13	35.4 13.8 4.6 4.6 4.8 4.8 4.0 4.0 4.5 4.5	大色 大色 大色 大色 大色 大色 大色 大色
								944 945 946 947 948 949 950 951 952 953 954	L45X4 L45X4 L40X3 -6X136 -6X136 -6X141 -6X141 -6X143 -6X143 -6X142 -6X142	1558 1614 930 181 181 182 182 148 148 169	8 8 4 4 4 4 4 4 4	4.42 1.72 1.16 1.16 1.21 1.21 1.00 1.00 1.13	35.4 13.8 4.6 4.6 4.8 4.8 4.0 4.0 4.5	

	国家电网公司 STATE GRID										
11	0~5	500k'	√ 输电线路	通用设计	t	施	I	图	版次		
ž	推										
¥	椎			2B5-J1 粮魚客 30.0m 客頭結构图(二)							
枚	枚										
Ř	ij										
CAD	齫										
		比例	1:20	H 7		2B5-	-J1-	-10(2	2/2)		

3132.5 kg

合计