



		构	件	I	y	细	表	
*			* 1	#	1	ਛੇ (kg)		
ij	規	格	(mm)	1	- #	小 计	备 注	
301	Q345L	90X7	6308	3 1	60.9	1 60.9	帯御钉	
302	Q345L90X7		6308		60.9			
303	L56X4		397		13.7	54.8	切角	
304	L56X4		397	7 4	13.7	54.8		
305	L56X4		378	1 4	13.0	3 52.1	切角	
306	L56X4		378	1 4	13.0	3 521		
307	L70X5		1825	5 4	9.8	5 39.4	切角	
308	L70X5		1825	5 4	9.8			
309	Q345L90X7		2088		20.1			
	L40X3		964		1.7			
311	L40X3		964		1.7		切角	
	L40X3		130		2.4			
313	L40X3		1093		2.0		切角	
	L40X3		1093		2.0			
	L40X3		945		1.7	5 7.0		
	L40X3		945		1.7	7.0	切角	
	L40X3		1458		2.7	21.6	別用	
	L40X3		1089		2.0		切角	
		L40X3			2.0	2 8.1		
320		L40X3		1 4	1.1		切角	
	L40X3		60		1.1		切角	
322	L40X3		803		1.4			
323	-5X175		270		1.8			
324	-6X200		355		3.3		卷边 50mm	
325 326	-6X220		425 585		15.9	70.0	火火火火火火火火火火火火火火火火火火火火火火火火火火火火火火火火火火火火火火火	
327	Q345-8X435		58		15.9	32.0	火火火火火火火火火火火火火火火火火火火火火火火火火火火火火火火火火火火火火火火	
328	Q345-8X435 Q345L90X7		2088		20.1			
329		-8X230	525		7.5		火曲 电焊	
		-8X230	525		7.5		火曲电焊	
331	L40X3		2252		4.1		AM TON	
	L50X4		1494		4.5			
333	-6X6		120		0.3			
334	-8X5		50		0.3			
335	-10X5		50		0.2			
336	-10X50		100	-	0.2			
550	1000		-,0		0.0	1.0		
	A i	+		925.1	ka	•		
_								
	!	螺栓	. 脚	盯. 9		月细表		
名称	级别	拠	格	符号	蒙	1 1 (kg)	备注	
	<u> </u>	M16X40 M16X50 M20X45		a	133	17.2		
麋	Ι.			Ž	40	6.4		
	6.8			<u>~</u>	164	44.3		
	ı	M20X55		ğ	16	4.7		
				~				
					1 1			
*			\dashv		+			
栓								
杜		M16X18	0	θ	13	4.2		

76.8 kg

	国家电网公司 STATE GRID													
11	10~5	00k	V输	电线路通用	设计 施工图 版次 1			版次 1						
批	堆													
穿	审核校核设计 CAD制图													
校					2B3-ZMC2直线塔(3)									
说					▼ 「									
CAD \$														
		比	例	1:20	图号	2E	3-ZMC2-04							