Parser Documentation

Adam, Brandon Cann, Xin Wang [1]

May 12, 2020
v1.0

[1]document compiled by Xin Wang

Contents

1 Introduction

According to the provided project briefing, a netlist describing the circuit will be provided in a file using a reduced SPICE format. It is required by the team to formulate an approach to read the file and store the information in a comprehensible data structure.

This document will research the format of the SPICE netlist and explore the different approaches in storing the information a certain way. This document is primarily used for planning the most effective way to approach the problem as well as allowing fellow teammates to engage productively on a equal knowledge footing.

2 Input (.cir) file

Source file for any version of SPICE has the following format [1].

```
TITLE
ELEMENT
.MODEL STATEMENTS
ANALYSIS COMMANDS
OUTPUT COMMANDS
.END
```

Important points to note:

- First line `TITLE` is used as a title on output files.

- File must end with command `.END` followed by a new line.

- Comment begins with '*' which covers entire line.

3 Netlist Element Format

A circuit description is called a **netlist** which consists of statements defining a each circuit element.

Connections are described by naming nodes [Actually stored as numbers].

Format of an element description is:

$$< D >< \texttt{description} >< \texttt{n1} >< \texttt{n2} > [\texttt{value}][\texttt{parameters}]$$

- $< D >$: A character that is a unique identifier for each type of support circuit component

- $< \texttt{description} >$ A string without space e.g. 5

- [$\texttt{value}$]: The value a circuit component takes e.g. 500 ohms

We have to consider the situation where the input syntax is correct but the circuit represented is wrong. To overcome this, we need a function to check if the circuit described is realistic.

3.1 Passive Elements in `'letter'`

Passive elements are composed of the following:

- Resistors: `R`

$$R < \text{description} >< \text{n1} >< \text{n2} >< \text{value} >$$

- Capacitor: `C` where we can specify the initial value of C for transient analysis.

$$C < \text{description} >< \text{n1} >< \text{n2} >< \text{value} > [\text{ic} =< \text{value} >]$$

- Inductor: `L` where we can specify the initial value of L for transient analysis.

$$L < \text{description} >< \text{n1} >< \text{n2} >< \text{value} > [\text{il} =< \text{value} >]$$

3.2 Independent Sources

- Voltage Sources

$$V < \text{description} >< \text{n1} >< \text{n2} >< \text{value} >$$

- Current Sources

$$I < \text{description} >< \text{n1} >< \text{n2} >< \text{value} >$$

The character after the letter must be a unique instance name and followed by the nodes associated with + and - respectively.

When users are entering component values, it is important that the software recognises common abbreviations for units.

3.3 Support for powers of ten

In order to support `spice` format, the following abbreviations for powers of ten must be recognised:

- f [femto]: 10^{-15}

- p [pico]: 10^{-12}

- n [nano]: 10^{-9}

- u [micro]: 10^{-6}

- m [milli]: 10^{-3}

- k [kilo]: 10^{+3}

- M [mega]: 10^{+6}

- G [giga]: 10^{+9}

- T [tera]: 10^{+12}

Any unrecognised characters are ignored.

4 Network Diagram/Graphs

Network Graphs show the relationships between a set of entries. Each entry is represented by a *Node* and the connections between nodes are represented through *Edges*.

There are four main types of network graphs:

- Undirected and Unweighted

- Directed and Unweighted

- Undirected and Weighted

- Directed and Weighted

A graph $G = (X, U)$ consists of: [2]

- a finite set $X = x1, x2, ..., xn$ whose elements are called nodes or vertices

- a subset U of the Cartesian product XxX, the elements of which are called arcs.

The network graph defined will consist of two vector structure:

- Vector of nodes in the circuit

- Vector of branches in the circuit

The theoretical output is an ordered vector of branches and an ordered vector of nodes. **Position starts from 1 as node 0 indicates GND.**

This area will be explored more in-depth in the analysis module.

5 Implementation

Block diagram depicting the breakdown of Parse Netlist module:

Figure 1: Netlist module breakdown

5.1 CirElement struct

```
CirElement
{
    variables:

        letter: component name
        name: name of node
        node1: node this node is connected to
        node2: node this node is connected to
        value: float
        initial_val: float
}
```

5.2 Parser

```
parser(cin)
    {
        Tokenise
        Put in values into respective variables
        Detect values, pass into custom_pow
        Detect if initial_val is entered:
            Pass into variable otherwise default 0
        Push CirElement into vector
    }
```

5.2.1 custom pow

```
custom_pow(string: input)
    {
        Check if there are keywords e.g. k, m, M, G

        If not present, two scenario:
            Unknown letter present: extract digits
            Convert to float
            Empty string (End of recursion): return 0

        If present:
            Find position where keyword appears
            Take string before keyword and convert
            Multiply/divide the digit by keyword
            Recursion to cover case: 5M7k
    }
```

5.2.2 tokeniser

```
tokeniser(string: input)
    {
        Call regex to tokenise the string
        Push each token into a vector
        Return vector
    }
```

5.2.3 isdigit

```
isdigit(string: input)
    {
        Iterate over string
        Take each character and into 'isdigit' test
        Return boolean
    }
```

5.3 Node N

```
getnodeN(vector<CirElement>: input)
{
    Declare counter: M
    Find vector size: S
    Scan entire vector
    {
        Find times 'V' or 'I' occur
    }
    'N' is S - M
    Return N
}
```

5.4 Node M

```
getnodeN(vector<CirElement>: input)
{
    Declare counter: M
    Scan entire vector
    {
        Find times 'V' or 'I' occur
    }
    Return M
}
```

6 Miscellaneous

There are more components to consider such as:

- Voltage controlled dependent sources

- Current controlled dependent sources

- Diodes

- BJT

- MOSFET

- Python implementation

- Efficient way to use recursion and not efficient to use matrix but more accurate.

References

[1]   Phyllis R. Nelson. *Introduction to spice source files*. DOI: `https://www.cpp.edu/~prnelson/courses/ece220/220-spice-notes.pdf`.

[2]   Archana Shankar, David Gilbert, and Michael Jampel. "Transient Analysis and Synthesis of Linear Circuits using Constraint Logic Programming". In: (Oct. 1996).