

# **Unit 13**

# **Concurrency Control**

# Content

---

- ❑ 13.1 Introduction
- ❑ 13.2 Serializability      可串聯的
- ❑ 13.3 Locking Technique
- ❑ 13.4 Two-Phase Locking

# **13.1 Introduction**

---

# Concurrency Control: Introduction

---

## ■ The Problem


- In a multiple-user DBMS, how to ensure **concurrent transactions** do not interfere with each other's operation?

## ■ Why concurrent transaction?

- minimize response time
- maximize throughput

## ■ Concurrency control techniques

- Locking
  - 2PL (§13.4)
  - Tree protocol locking
  - ⋮
- Optimistic method
  - Timestamp ordering
  - ⋮



# Problem: Lost Update

- The problem when works without concurrency control
  1. Lost Update: Fig. 13.1
  2. Uncommitted Dependence: Fig. 13.2

## <Example 13.1> Lost Update




Fig. 13.1: Transaction A loses an update at time t4

if A--> B :  $R = (10+1) * 2 = 22$

if B--> A :  $R = (10*2) + 1 = 21$

### <Example 13.2> Uncommitted Dependence



## 13.2 Serializability

---

# Serializability: Definition

---

- A formal criterion for correctness. 交錯並聯
- Def : A given **interleaved execution (schedule)** of some set of transactions is said to be **serializable** iff it produces the same result as some serial execution of those transactions, for any given initial database state.
- Assumptions:
  - all transactions are individually correct.
  - Any serial execution of those transactions is also correct.
  - Transactions are all independent of one another.

**Note:** if **T<sub>x</sub> A** does have to be run before **T<sub>x</sub> B**, then user cannot submit **T<sub>x</sub> B** until **T<sub>x</sub> A** is committed.



# Serializability: Example 13.3

---

- <Example 13.3>

$T1 = \{ r1(d), w1(d) \}$

$T2 = \{ r2(a), w2(a) \}$

- **Serial execution** :  $\frac{r1(d), w1(d)}{T1}, \frac{r2(a), w2(a)}{T2}$

$T1 \longrightarrow T2$

交錯並聯

- **Interleaved execution** :  $\frac{r1(d)}{T1}, \frac{r2(a)}{T2}, \frac{w1(d)}{T1}, \frac{w2(a)}{T2}$   
(schedule)

- Serializable?

- Serialization: the serial execution that equivalent to the serializable execution, e.g. T1 - T2

# Serializability: Example 13.4(a)

---

## <Example 13.4>

Given : T1: Add 1 to A

T2: Double A

T3: Display A and set A to 1

Initial value:  $A = 0$

<a> How many possible correct results ?  $3! = 6$ .

T1 - T2 - T3 :  $A=1$

T1 - T3 - T2 :  $A=2$

T2 - T1 - T3 :  $A=1$


T2 - T3 - T1 :  $A=2$

T3 - T1 - T2 :  $A=4$

T3 - T2 - T1 :  $A=3$

# Serializability: Example 13.4(b)

<b> Suppose the internal structures of T1, T2, T3 are :



<p>T1:</p> <p>F1: Fetch A into t1</p> <p>t1 := t1 + 1</p> <p>U1: Update A from t1</p>	<p>T2 :</p> <p>F2 : Fetch A into t2</p> <p>t2 := t2 * 2</p> <p>U2 : Update A from t2</p>	<p>T3 :</p> <p>F3 : Fetch A into t3</p> <p>display t3</p> <p>U3 : Update A to 1</p>
---------------------------------------------------------------------------------------	------------------------------------------------------------------------------------------	-------------------------------------------------------------------------------------

How many possible interleaved executions? 90

Fi- Fj- Fk- Up- Uq- Ur:  $3*2*1*3*2*1 = 36$

Fi- Fj- Up- Fk- Uq- Ur:  $3*2*2*1*2*1 = 24$

Fi- Fj- Up- Uq- Fk- Ur:  $3*2*2*1*1*1 = 12$

Fi- Up- Fj- Fk- Uq- Ur:  $3*1*2*1*2*1 = 12$

Fi- Up- Fj- Uq- Fk- Ur:  $3*1*2*1*1*1 = 6$

Fi- Up- Uq- Fj- Fk- Ur ?

# Serializability: Example 13.4(c)

---

<c> Is there any interleaved executions that produces "correct" result but is not serializable ?

Consider the schedule ( $\Delta$ ):

$\Delta$  : F1- F2- F3- U3- U2- U1 = 1 (if A=0) same as T1-T2-T3

But, Consider initial value of A is 10:

T1-T2-T3 : 1

T1-T3-T2 : 2

T2-T1-T3 : 1

T2-T3-T1 : 2

T3-T1-T2 : 4

T3-T2-T1 : 3

**F1-F2-F3-U3-U2-U1=11  $\neq$  any serial execution**

**(10) (10) (10) (1)(20) (11)**

$\therefore$  not serializable !

- An **interleaved execution (schedule)** of some set of transactions is considered to be **correct** iff it is **serializable** !

# Testing for Serializability

---

- Two operations are said to be **conflict** if
  - <1> they come from different transaction.
  - <2> they operate on the same data element.
  - <3> at least one of them is write operation.
- <e.g.> T1= { r1(a), w1(b) }  
T2= { r2(b), w2(c) }  
T3= { r3(c), w3(a) }
  - r1(a), w3(a) are conflict
  - r2(b), w1(b) are conflict
  - r3(c), w2(c) are conflict

# Testing for Serializability (cont.)

## ■ Transaction Dependency Graph:


- Nodes: transactions, e.g. T1, T2, T3
- Arcs: dependence

**T1 --> T2 if O1 and O2 are conflict, and O1 before O2 in a schedule S.**


<e.g.> S1: r1(a), r3(c), r2(b), w1(b), w3(a), w2(c)

S2: r1(a), r2(b), w1(b), w2(c), r3(c), w3(a)

S1 :



S2 :



T2→T1→T3

## ■ The Acyclicity Theorem

- An interleaved transaction schedule is serialization iff its transaction dependency graph is acyclic.

## **13.3 Locking Technique**

---

# Locking Technique: Concept

---

- The effect of a lock is to lock other transaction out of the object.
- Two kinds of locks
  - Exclusive lock (X locks ): for UPDATE
  - Shared lock (S locks): for RETRIEVE
- Compatibility matrix

A \ B	X	S	—
X	N	N	Y
S	N	Y	Y
—	Y	Y	Y

— : no lock

N : request not compatible

Y : request compatible



# Locking Technique: Concept (cont.)

---

A \ B	X	S	—
X	N	N	Y
S	N	Y	Y
—	Y	Y	Y

— : no lock

N : request not compatible

Y : request compatible

<e.g.> if transaction A holds a S lock on R, then

<1> a request from B for X lock on R

=> B goes into wait state.

<2> a request from B for S lock on R

=> B also hold the S lock on R

**Ref:** X locks and S locks are normally held until the next synchpoint. (Ref. p.12-12)

# How locking solves the problems

## ■ The lost Update Problem




Fig. 13.4: No update is lost, but deadlock occurs at time  $t4$ .

# How locking solves the problems (cont.)

## ■ The Uncommitted Dependence Problem




Fig 13.5: Transaction A is prevented from seeing an uncommitted change at time t2.

# Deadlock Detection: Wait-for-Graph

## ■ Deadlock Detection: **Wait-for-Graph**

- **node**: transactions
- **arc**: an edge from node  $T_i$  to  $T_j$  means  $T_i$  request a lock on an object that is hold by  $T_j$ .
- the system draw an edge from  $T_i$  to  $T_j$  when the request is issued and erase that edge when  $T_j$  release the lock.
- if there are edges from  $T_1$  to  $T_2$ ,  $T_2$  to  $T_3$ , ...,  $T_{n-1}$  to  $T_n$ , and  $T_n$  to  $T_1 \implies T_1, T_2, \dots, T_n$  are deadlocked.




Fig. 13.7:  
An example of deadlock.

# Locking Protocol

---

- **Locking Protocol:** to ensure the Serializability
  1. Two-phase locking (2PL)
  2. Non-two-phase locking
    - Tree protocol locking
    - Directed acyclic graph protocol

# Testing for Serializability

---

## ■ Testing for Serializability in Locking Protocol

### • Precedence Graph:

- **Node:** transactions
- **Arc:** an **arc** from  $T_i$  to  $T_j$  ( $T_i \longrightarrow T_j$ )  
if  $O_i \in T_i$ ,  $O_j \in T_j$  and
  - <1>  $O_i$  and  $O_j$  operates on the same data.
  - <2>  $O_i$  is UNLOCK,  $O_j$  is LOCK.
  - <3>  $O_i$  precedes  $O_j$ .
- e.g.  $T_1, T_2$

$T_1 \longrightarrow T_2$

$T_1$  UNLOCK(d)

$T_2$  LOCK(d)

$T_2 \longrightarrow T_1$

$T_2$  UNLOCK(d)


$T_1$  LOCK(d)

# Theorem for Testing Serializability

- **Thm 13.1:** If the precedence graph of a schedule contains **no cycle** then schedule is **serializable**.

## <Example 13.6>


Consider the following three transactions:



- A schedule for T1, T2, and T3:

- (1) T1 : LOCK A
- (2) T2 : LOCK B
- (3) T2 : LOCK C
- (4) T2 : UNLOCK B      From (4), (5) we have T2 → T1
- (5) T1 : LOCK B
- (6) T1 : UNLOCK A      From (6), (7) we have T1 → T2
- (7) T2 : LOCK A
- (8) T2 : UNLOCK C      From (8), (11) we have T2 → T3
- (9) T2 : UNLOCK A
- (10) T3 : LOCK A
- (11) T3 : LOCK C
- (12) T1 : UNLOCK B
- (13) T3 : UNLOCK C
- (14) T3 : UNLOCK A

- The precedence graph of the schedule is:



## **13.4 Two-Phase Locking**

---



# Two-Phase Locking (2PL): Definition

---


- A protocol that guarantees **serializability**.
- A transaction obeying the **two-phase locking protocol (2PL)** if
  - <a> before operating on any object, the transaction first acquires a lock on that object (the locking phase)
  - <b> after releasing a lock, the transaction never acquires any more lock (the unlocking phase )i.e. in any transaction, all locks must precede all unlock.

# 2PL: Example

---

<e.g.>

T1:	T2:	T3:
LOCK A	LOCK A	LOCK B
LOCK B	LOCK C	LOCK C
UNLOCK A	UNLOCK C	UNLOCK B
UNLOCK B	UNLOCK A	LOCK A
		UNLOCK C
		UNLOCK A



T1 obey 2PL  
T2 obey 2PL  
T3 not obey 2PL

<e.g.1> T1, T2 any interleaved  
schedules are serializable.

<e.g.2> T1, T2 , T3 perhaps

**Note:** In practice, a lock releasing phase is often compressed into the single operation of COMMIT (or ROLLBACK) at end-of-transaction.

# 2PL: Theorm

- **Thm 13.2:** If all transactions obey the “2PL” protocol, then all possible interleaved schedules are serializable.

[proof]: [by contradiction]

Suppose not. Then by Thm 13.1, the **precedence Graph G** for **S** has a cycle, say

$T_{i1} \Rightarrow T_{i2} \Rightarrow \dots \Rightarrow T_{ip} \Rightarrow T_{i1}$ .

eg.  $T_1 \rightarrow T_2 \rightarrow T_3 \rightarrow T_1$

Then some LOCK by  $T_{i2}$  follows an UNLOCK by  $T_{i1}$ ;

some LOCK by  $T_{i3}$  follows an UNLOCK by  $T_{i2}$ ;

⋮

some LOCK by  $T_{i1}$  follows an UNLOCK by  $T_{ip}$ ;

$\Rightarrow$  A LOCK by  $T_{i1}$  follows an UNLOCK by  $T_{i1}$

$\Rightarrow$   $T_{i1}$  disobey of 2L protocol !!      **Q.E.D. #**

UNLOCK    LOCK

$T_{i1} \rightarrow T_{i2}$

$T_{i2} \rightarrow T_{i3}$

⋮

$T_{ip} \rightarrow T_{i1}$

$\Rightarrow$

One lock of  $T_{i1}$   
is after unlock!!

<e.g.1>  $T_1, T_2$  any interleaved  
schedules are serializable.

<e.g.2>  $T_1, T_2, T_3$  perhaps

# 2PL: Example 13.4(d)

---

## <Example 13.4(d)>

<d> Is there any interleaved execution of T1, T2, T3 that is serializable but could not be produced if all three transactions obeyed the 2PL?

**T1 :**

F1 : Fetch A into t1

t1 := t1+1

U1 : Update A from t1

**T2 :**

F2 : Fetch A into t2

t2 := t2\*2

U2 : Update A from t2

**T3 :**

F3 : Fetch A into t3

display t3

U3 : Update A from t1


## 2PL: Example 13.4(d) (cont.)

★ Yes ! F1 - F3 - U1 - U3 - F2 - U2 = T1-T3-T2 is serializable

↑        ↑        ↑  
SLOCK SLOCK wait until T3 terminates

∴ Operation U1 will not be able to proceed until that SLOCK by F3 has been released, and that will not happen until T3 terminates.

**In fact,** transaction T3 and T1 will deadlock when U3 is reached.



△ Ref. p.13-12

<Note>  $2PL \leq \text{Serializable} \leq \text{"Correct"} \leq \text{All interleaved schedules}$

---

end of unit 13