

**UNIVERSIDAD POLITÉCNICA DE MADRID**

**ESCUELA TÉCNICA SUPERIOR  
DE INGENIEROS DE TELECOMUNICACIÓN**



**MÁSTER UNIVERSITARIO EN INGENIERÍA DE  
TELECOMUNICACIÓN**

**TRABAJO FIN DE MÁSTER**

**DESIGN AND IMPLEMENTATION OF AN ABR VIDEO  
STREAMING SIMULATION MODULE FOR NS-3.  
ANALYSIS AND COMPARISON OF ABR VIDEO  
STREAMING ALGORITHMS OVER VARIOUS MOBILE  
NETWORK SCENARIOS.**

**XINXIN LIU  
JUNIO 2021**



## TRABAJO DE FIN DE MÁSTER

**Título:** Diseño e implementación de un módulo de ABR video streaming para NS-3. Análisis y comparación de algoritmos de ABR video streaming sobre varios escenarios de redes móviles.

**Título (inglés):** Design and implementation of an ABR video streaming simulation module for NS-3. Analysis and comparison of ABR video streaming algorithms over various mobile network scenarios.

**Autor:** Xinxin Liu

**Tutor:** Marcus Ihlar (Ericsson AB)

**Ponente:** Carlos Mariano Lentisco Sanchez (ETSIT-UPM)

**Departamento:** Departamento de Ingeniería de Sistemas Telemáticos

## MIEMBROS DEL TRIBUNAL CALIFICADOR

**Presidente:** —

**Vocal:** —

**Secretario:** —

**Suplente:** —

**FECHA DE LECTURA:**

**CALIFICACIÓN:**



**UNIVERSIDAD POLITÉCNICA DE MADRID**

**ESCUELA TÉCNICA SUPERIOR DE  
INGENIEROS DE TELECOMUNICACIÓN**

Departamento de Ingeniería de Sistemas Telemáticos



**TRABAJO FIN DE MÁSTER**

**DESIGN AND IMPLEMENTATION OF AN ABR VIDEO  
STREAMING SIMULATION MODULE FOR NS-3.  
ANALYSIS AND COMPARISON OF ABR VIDEO  
STREAMING ALGORITHMS OVER VARIOUS MOBILE  
NETWORK SCENARIOS.**

**Xinxin Liu**

Junio 2021



# Resumen

El streaming de vídeo con tasa de bits adaptativa se está convirtiendo en la técnica más utilizada para las plataformas de vídeo en línea. Con la pandemia mundial *COVID-19*, el streaming de vídeo se ha convertido en una de las principales fuentes de entretenimiento durante los confinamientos. De hecho, más de la mitad de la cuota de tráfico de la red se utiliza hoy en día para streaming de vídeo [7].

El objetivo de este Trabajo Fín de Máster es construir un framework en *ns-3*, implementado en *C++*, para probar algoritmos de adaptación de vídeo y comparar algunas implementaciones sobre diferentes escenarios de red. El primer paso es estudiar *ns-3*, familiarizarse con algunos módulos de *ns-3* y construir varios escenarios de red *LTE*. El segundo paso es construir un módulo que pueda simular servidores y clientes de vídeo *ABR*, estudiar algunos enfoques de los algoritmos de adaptación de la tasa de bits de vídeo e implementar dichos algoritmos, incluyendo soluciones basadas en el ancho de banda, en el buffer y algoritmos híbridos. Por último, podemos comparar y evaluar el rendimiento de diferentes algoritmos *ABR* en escenarios con condiciones variables con diferentes métricas objetivas de *QoE*.

//// Resultados

Este proyecto se ha llevado a cabo con la cátedra Ericsson-UPM en software y sistemas.

**Palabras clave:** DASH, ABR, ns-3, streaming de video por HTTP, simulación, QoE





# Abstract

Adaptive bitrate video streaming is becoming the most used technique for online video platforms. With the *COVID-19* worldwide pandemic, video streaming has become one of the primary sources of entertainment during the shutdown. In fact, more than half of the network traffic share today is used by video streaming [7].

The objective of this Master's Thesis is to build a framework in *ns-3*, implemented in *C++*, for testing video adaptation algorithms and to compare some implementations over different network scenarios. The first step is to study *ns-3*, familiarize with some *ns-3* modules, and build various LTE network scenarios. The second step is to build a module that can simulate *ABR* video servers and clients, study some approaches of video bitrate adaptation algorithms and implement those algorithms, including throughput based, buffer based and hybrid solutions. Finally we can compare and evaluate the performance of different *ABR* algorithms on scenarios with varying conditions with different objective *QoE* metrics.

//// Resultados

This project has been carried out with the Ericsson-UPM scholarship in software and systems.

**Keywords:** DASH, ABR, ns-3, HTTP video streaming, simulation, QoE



## Acknowledgements



# Contents

<b>Resumen</b>	<b>I</b>
<b>Abstract</b>	<b>III</b>
<b>Acknowledgements</b>	<b>V</b>
<b>Contents</b>	<b>VII</b>
<b>Lista de Figuras</b>	<b>XI</b>
<b>List of Tables</b>	<b>XIII</b>
<b>Listings</b>	<b>XV</b>
<b>Glossary</b>	<b>XVII</b>
<b>1 Introduction</b>	<b>1</b>
1.1 Context . . . . .	1
1.2 Objectives . . . . .	3
1.3 Structure of the thesis . . . . .	3
<b>2 State of the Art</b>	<b>5</b>
2.1 ABR Video Streaming . . . . .	5
2.2 Dynamic Adaptive Streaming over HTTP . . . . .	7
2.2.1 MPD . . . . .	8
2.2.2 Adaptation Algorithms . . . . .	9
2.2.3 QoS & QoE Metrics . . . . .	12
2.3 LTE Fundamentals . . . . .	12
2.3.1 History . . . . .	13
2.3.2 Architecture . . . . .	13
2.3.3 Wireless Fundamentals . . . . .	14
2.3.4 Antennas & MIMO . . . . .	16
2.3.5 Physical Layer . . . . .	17
2.3.6 Medium Access Control Layer . . . . .	20
2.3.7 Radio Link Control Layer . . . . .	20

2.3.8	Packet Data Convergence Protocol Layer . . . . .	21
<b>3</b>	<b>Network Simulator 3</b>	<b>23</b>
3.1	ns-3 Concepts . . . . .	23
3.2	Logging Module . . . . .	24
3.3	Command Line Arguments . . . . .	25
3.4	Tracing System . . . . .	26
3.4.1	ASCII Tracing . . . . .	26
3.4.2	PCAP Tracing . . . . .	26
3.5	ns-3 Modules & Models . . . . .	26
3.5.1	Antenna Module . . . . .	27
3.5.2	Application Module . . . . .	28
3.5.3	Buildings Module . . . . .	29
3.5.4	Internet Module . . . . .	31
3.5.5	Mobility Module . . . . .	31
3.5.6	Network Module . . . . .	32
3.5.7	PointToPoint NetDevice . . . . .	33
3.5.8	LTE Module . . . . .	33
3.6	Parameter Configuration . . . . .	36
<b>4</b>	<b>ABR Module for ns-3</b>	<b>37</b>
4.1	Design Objectives . . . . .	37
4.2	Architecture . . . . .	37
4.3	Models . . . . .	39
4.3.1	AbrClient . . . . .	39
4.3.2	AbrServer . . . . .	41
4.3.3	AbrVariables . . . . .	42
4.3.4	AbrHelper . . . . .	43
4.3.5	AbrAlgorithm . . . . .	43
4.4	Adaptation Algorithms . . . . .	43
4.5	QoS & QoE Metrics . . . . .	43
<b>5</b>	<b>Simulations and Results</b>	<b>45</b>
<b>6</b>	<b>Conclusions and Future Work</b>	<b>47</b>
	<b>References</b>	<b>i</b>
	<b>Appendix A Impact</b>	<b>v</b>
A.1	Social Impact . . . . .	v
A.2	Economic Impact . . . . .	v

A.3	Ambiental Impact . . . . .	v
A.4	Ethic Impact . . . . .	v
<b>Appendix B</b>	<b>Budget</b>	<b>vii</b>
<b>Appendix C</b>	<b>ns-3 Tutorial</b>	<b>ix</b>
C.1	Getting Started . . . . .	ix
C.2	LTE Module . . . . .	xii





# List of Figures

1.1	Global application category total traffic share during COVID-19 lockdown. Source: Sandvine [7]	2
2.1	Evolution of segment quality with time	6
2.2	DASH client-server architecture. Source: MPEG [27]	8
2.3	The MPD hierarchical data model. Source: MPEG [27]	9
2.4	Bandwidth based algorithms. Source: [13]	10
2.5	BOLA's bitrate choice as function of buffer level. Source: [28]	11
2.6	LTE Architecture	14
2.7	Evolved Packet Core (EPC) Architecture	15
2.8	Shadowing effect. Source: [24]	16
2.9	Fading loss effect. Source: [24]	16
2.10	LTE Time-Frequency Grid. Source: [30]	18
3.1	ns-3 High-level node architecture. Source: [25]	24
3.2	Coordinate system of the AntennaModel. Source: nsnam [25]	27
3.3	Example Radio Environment Map. Source: [25]	36
4.1	ABR Module architecture.	38
4.2	ABR Client.	40
4.3	ABR Server.	41



# List of Tables

2.1	Number of Resource Blocks against each channel bandwidth. Source: [29]	19
2.2	4-Bit CQI Table . . . . .	19
C.1	Prerequisites for ns-3 . . . . .	ix



# Listings

3.1	Enabling logging in ns-3 . . . . .	25
3.2	Enable LTE trace outputs . . . . .	34
C.1	Download and installation of ns-3 . . . . .	ix
C.2	Enabling logging in ns-3 . . . . .	x
C.3	Disabling logging in ns-3 . . . . .	x
C.4	Command line arguments . . . . .	x
C.5	ASCII tracing . . . . .	x
C.6	PCAP tracing . . . . .	xi
C.7	ns-3 Socket programming . . . . .	xi
C.8	Socket callbacks . . . . .	xi
C.9	PointToPointHelper . . . . .	xi
C.10	LteHelper usage . . . . .	xii
C.11	UE Automatic Attachment . . . . .	xii
C.12	Enable Evolved Packet Core . . . . .	xiii
C.13	MAC Scheduler . . . . .	xiii
C.14	AMC Model . . . . .	xiii
C.15	Mobility Model . . . . .	xiv
C.16	Pathloss Model . . . . .	xiv
C.17	Antenna & MIMO Model . . . . .	xiv
C.18	Radio Environment Maps helper . . . . .	xv
C.19	Configuration parameters . . . . .	xv
C.20	Configuration parameters . . . . .	xvi



# Glossary

**3GPP** - 3<sup>rd</sup> Generation Partnership Project

**ABR** - Adaptive BitRate

**AMC** - Adaptive Modulation and Coding

**API** - Application Programming Interface

**ARP** - Address Resolution Protocol

**ASCII** - American Standard Code for Information Interchange

**BOLA** - Buffer Occupancy based Lyapunov Algorithm

**CDN** - Content Delivery Network

**CPU** - Central Processing Unit

**CQI** - Channel Quality Indicator

**DASH** - Dynamic Adaptive Streaming over HTTP

**DHCP** - Dynamic Host Configuration Protocol

**DRM** - Digital Rights Management

**EARFCN** - E-UTRA Absolute Radio Frequency Channel Number

**e-NodeB** - enhanced Node B

**EPC** - Evolved Packet Core

**EPS** - Evolved Packet System

**GSM** - Global System for Mobile communications

**HARQ** - Hybrid Automatic Repeat reQuest

**HDS** - HTTP Dynamic Streaming

**HLS** - HTTP Live Streaming

**HSS** - Home Subscriber Server

**HTTP** - HyperText Transfer Protocol

**IEC** - International Electrotechnical Commission

**IETF** - Internet Engineering Task Force

**IIS** - Internet Information Services

**IP** - Internet Protocol

**ISO** - International Organization for Standardization

**ITU-T** - International Telecommunication Union - Telecommunication standardization

**KPI** - Key Performance Indicator

**LENA** - LTE-EPC Network simulator

**LTE** - Long Term Evolution

**MAC** - Medium Access Control

**MCS** - Modulation and Coding Scheme

**MIMO** - Multiple Input Multiple Output

**MME** - Mobility Management Entity

**MMS** - Multimedia Message Service

**MPEG** - Moving Picture Experts Group

**MPD** - Media Presentation Description

**MSS** - Microsoft Smooth Streaming

**NAT** - Network Address Translation

**NR** - New Radio

**ns-3** - network simulator 3

**OFDMA** - Orthogonal Frequency Division Multiple Access



**OSMF** - Open Source Media Framework

**PCRF** - Policy Charging and Rule Function

**PGW** - Packet data network GateWay

**PHY** - LTE PHYsical Layer

**QoE** - Quality of Experience

**QoS** - Quality of Service

**RB** - Resource Block

**RE** - Resource Element

**REM** - Radio Environment Map

**RLC** - Radio Link Control

**ROHC** - RObust Header Compression

**SC-FDMA** - Single-Carrier Frequency Division Multiple Access

**SGW** - Serving GateWay

**SRS** - Sounding Reference Signal

**TCP** - Transmission Control Protocol

**UDP** - User Datagram Protocol

**UE** - User Equipment

**UHD** - Ultra High Definition

**UMTS** - Universal Mobile Telecommunications System

**URL** - Universal Resource Locators

**XML** - eXtensible Markup Language



# Chapter 1 | Introduction

## 1.1 Context

There is no doubt about the importance of online video streaming. According to Sandvine [7], in 2020, 57% of the global internet traffic was used by video streaming. Moreover, one of the key predictions made by Cisco in 2018 [8] stated that by year 2022, video traffic will make up 82% of all *IP* traffic.

Consequently, many challenges arise. Due to the growth in the number and diversity of connected video-capable devices, and the increasing bandwidth and higher quality content available, the client and the server need to adapt the video content to the network and the devices. The technique of taking account the varying network conditions and computing resources of the user device to choose the adequate quality level is denominated as *Adaptive BitRate (ABR)*. Adaptation may be performed by monitoring different parameters such as estimated bandwidth, client's buffer level, CPU load or screen size.

The *Dynamic Adaptive Streaming over HTTP (DASH)* is one of the standards that implements adaptive bitrate video streaming and was developed by the *Moving Picture Experts Group (MPEG)* [19]. *MPEG-DASH* enables provisioning and delivering media using existing *HTTP*-delivery networks supports dynamic adaptation with seamless switching. By using *HTTP*, the player will not have firewall problems. The quality selection relays on the client thus providing better scalability, and there is no need to have session at the server.

The *MPEG-DASH* standard was published in 2012 and revised in 2019 by the *International Organization for Standardization (ISO) / International Electrotechnical Commission (IEC)* as *MPEG-DASH ISO/IEC 23009-1:2019* [15]. In addition, the *3<sup>rd</sup> Generation Partnership Project (3GPP)* defines the use of *DASH* as the standard continuous delivering of



**Figure 1.1:** Global application category total traffic share during COVID-19 lockdown.  
Source: Sandvine [7]

multimedia content in mobile networks, specifically in 4G such as *LTE* and 5G networks.

*DASH* divides the media file into small chunks or segments. and defines the *Media Presentation Description (MPD)*, which is an XML manifest file that contains the *Universal Resource Locators (URL)* of the segments. Different qualities are defined as representations, the *MPD* contains information for each representation such as the codec, bandwidth, resolution or framerate.

However, the *DASH Standard* [15] only defines the data formats for the media reproduction and do not provide the adaptation algorithm. The *DASH Industry Forum* [10] provides an open source *MPEG-DASH* player implemented in *JavaScript* with different adaptation algorithms. Similarly, *hls.js* is an implementation of a *HTTP Live Streaming*<sup>1</sup> client.

The adaptation algorithms needs to be tested in different scenarios (they can be simulated) and be tweaked to provide the maximum perceived quality by the users. Also, there are algorithms that perform better in some specific scenarios and worse in others. The adaptation algorithm is the responsible for avoiding problems that may have a negative impact on the *Quality of Experience (QoE)*. One problem is that, the algorithm can over-

---

<sup>1</sup>HTTP Live Streaming is a HTTP-based adaptive bitrate streaming protocol developed by Apple Inc. [4]

estimate the bandwidth and it would cause a pause in the reproduction because all the segments in the buffer are emptied. The algorithm can also underestimate the bandwidth, the video player requests media segments with inferior quality than the quality at which the bandwidth available of the network can allow. Lastly, the algorithm should avoid constant bitrate switches result of bandwidth fluctuations, and provide a smooth and seamless video watching experience.

The *ns-3* simulator is an open-source and extensible discrete-event network simulator. The extensible nature of this tool allows us to develop a new module for *ns-3* mimicking the behaviour of *ABR* clients and servers. With this new module, *ns-3* will be able to simulate diverse mobile network scenarios and test the performance of adaptation algorithms.

## 1.2 Objectives

The objectives of this thesis is to build a framework for testing *ABR* adaptation algorithms, and implement some adaptation algorithms and compare them in various mobile network scenarios with different objective *QoE* metrics. In order to achieve the proposed objectives, the following steps will be proposed:

1. Study and understand *ns-3* and basic modules such as the core module, the internet module, applications module, *LENA* module among others. Build basic *LTE* scenarios tweak radio parameters, and output results.
2. Design a new module in *ns-3* that simulates behaviours of *ABR* clients and servers. Study and implement existing adaptation algorithms.
3. Implement objective *QoE* and *QoS* metrics. Build new *LTE* scenarios and compare the performances of the implemented adaptation algorithms.

## 1.3 Structure of the thesis

**Chapter 1.** Presents the context, the motivations and the objectives of this thesis.

**Chapter 2.** The State of the Art. Includes an introduction to *ABR* and *DASH*. The

architecture and video quality adaptation algorithms. Also, an brief explanation of LTE, its architecture and fundamentals.

**Chapter 3.** A starting guide to use *ns-3*. Brief introduction and usage of relevant *ns-3* modules for this thesis.

**Chapter 4.** Introduces a new module for *ns-3*. /////

**Chapter 5.** dddd

## Chapter 2 | State of the Art

This chapter will introduce the main concepts and tools that will be used during the development of the project. The section 2.1 will explain the different methods of content distribution over *HTTP* and different types and implementations of adaptive streaming. The section 2.2 will make a introduction to the *DASH* standard, different types of adaptation algorithms and *QoE* and *QoS* metrics. The section 2.3 will describe basic architecture and fundamentals of 4G LTE, such as the radio interface, propagation loss model, fading model, antenna model, etc.

### 2.1 ABR Video Streaming


There are three ways of media delivery over *HTTP*. The first method is by **file download**, the media file is downloaded in its entirety in a local hard disk and then it can be played. The second method is called **progressive download**, this method is similar to the file download, but instead the download starts from the beginning and the media starts playing once enough data are playable. However, these two methods have disadvantages like waste of bandwidth or *DRM* issues and also requiring a reliable transmission. The last method is called **streaming**, contrary to the former two, the file itseft is not stored locally, smaller chunks of video are sent from the server and the client needs a data buffer to store the data that is being downloaded. The client plays the multimedia content from the buffer, and when the session is closed the data are deleted.

Streaming media also comes with some challenges. There are a lot of network variability and a big heterogeneity in video capable devices. Therefore, to overcome these shortcomings, *Adaptive bitrate streaming (ABR)* was created.

The basic idea of *Adaptive bitrate streaming* is to adapt the media content for the user

by monitoring different parameters like estimated bandwidth, buffer level or *CPU load*, see Figure 2.1. There are many proprietary adaptive streaming solutions:

- **Apple HTTP Live Streaming (HLS):** *HTTP Live Streaming HLS* is an implementation of an *ABR* protocol over *HTTP* developed by Apple [4] as part of the QuickTime software and the mobile operating system *iOS*. *HLS* supports live streaming and video on demand. *HLS* is proposed in 2009 as a standard to the *IETF* [18].
- **Microsoft Smooth Streaming (MSS):** *Smooth Streaming* is part of *Internet Information Services (IIS) Media Services* for delivering media over *HTTP* [22]. Their *MSS* technology was used for several sports events such as the Beijing Summer Olympic Games in 2008 and the 2010 Winter Olympics in Vancouver [23].
- **Adobe HTTP Dynamic Streaming (HDS):** *HTTP Dynamic Streaming* is the implementation of adaptive streaming by Adobe. *HDS* enables high-quality, network efficient *HTTP* streaming for media delivery that is tightly integrated with Adobe software [3]. The solution is based in using *Open Source Media Framework (OSMF)* and Adobe Flash Player.



**Figure 2.1:** Evolution of segment quality with time

But there was no official standardization for adaptive video delivery over *HTTP*. For that reason, a new international standard called *MPEG-DASH* was developed and published.



## 2.2 Dynamic Adaptive Streaming over HTTP

*DASH* was developed from January 2009 to March 2010 and published in April 2012. The most recent revision of the standarization was released in 2019 as *MPEG-DASH ISO/IEC 23009-1:2019* [15]. *Moving Picture Experts Group* from *ISO/IEC* and the *3GPP* collaborated on the *DASH* standard. The *3<sup>rd</sup> Generation Partnership Project* defined the use of *DASH* as the standard of digital media delivery in mobile networks (4G *LTE*, 5G) in [2].


The objective of *DASH* was to create a unique standard that replaces the proprietary solutions from Microsoft, Apple and Adobe. Also, it will offer the interoperability and the convergence needed for the expansion of large-scale video streaming solutions. Also, the *DASH Industry Forum (DASH-IF)* was created to promote and help the expansion of *DASH*. Microsoft, Apple, Netflix, Qualcomm, Ericsson and Samsung are some of the companies members of the *DASH-IF*.

One of the biggest advantages of *DASH* is that the video streaming is over *HTTP* version 1.1 protocol (*HTTP/1.1*). The use of *HTTP* means that reusing existing internet infrastructure and media content distribution tecniques using *CDN (Content Delivery Networks)* can be done. Another convenience of using *DASH* is that due to using *HTTP* encapsulation, problems with passing through firewalls and the *Network Address Translation (NAT)* are not existent.

All the control of the media content delivery is located in the *DASH* client side. The standard does not define any web delivery mechanism nor the bitrate adaptation algorithm. What *DASH* does define in [15] are:

- ***The Media Presentation Description (MPD) File Format:*** The *MPD* file uses the *eXtensible Markup Language (XML)* and contains the specifications of the media content and the *URL* of the segments in the *HTTP* video servers.
- ***Segment format:*** *DASH* defines the characteristics of the necessary codifications and the way that the media content is divided in small fragments called *segments*.

The Figure 2.2 presents a simple *DASH* architecture. The video and audio content are processed and stored on an *HTTP* server. To access the content, the client sends *HTTP* requests to the server. But first, the client needs to download the *MPD* file, normally



**Figure 2.2:** DASH client-server architecture. Source: MPEG [27]

through *HTTP*. The client then does the parsing of the *MPD*, extract information such as the duration of a segment, media types or resolutions. Finally, the *DASH* client chooses the adequate quality and starts the streaming of the content using *HTTP GET* request to fetch the segments.

The *DASH* client stores the segments in a buffer and consumes the content. It continues to fetch new segments and by monitoring network variables it will decide which quality (higher or lower bitrate) to request next to avoid problems like buffer underflow and maintain at least a set number of segments in the buffer.

### 2.2.1 MPD

The *MPD* file is an *XML* document that describes the characteristics of the different media components that composes the media content (e.g. video, audio, subtitles).

The structure of the *MPD* is hierarchical as illustrated in Figure 2.3. The media content is divided in a sequence of **periods**, each period has a starting time and a duration. In a period, the set of encoded versions of the media content is consistent, that is, the same bitrates, languages and so on.

Each period consists of one or multiple **adaptation sets**. A collection of interchangeable encoded versions of one or more media content components is referred to as an adaptation set. For instance, an adaptation set may contain the different bitrates of the video




- **Client device:** The screen resolution, CPU capabilities, Buffer size, etc.
- **Network:** Type of access network (Mobile, Fixed), available bandwidth, etc.

The following subsections will explain different types of adaptation algorithms and the algorithms implemented for this thesis in *ns-3*.

### 2.2.2.1 Bandwidth throughput based algorithms

This group of algorithms uses estimations of bandwidth throughput as the main rule to select the qualities of the multimedia content for the client. The main difference between algorithms of this kind is the bandwidth estimation method and how the estimation relates to the qualities.



*Figure 2.4: Bandwidth based algorithms. Source: [13]*

- **HLS.js** [9]. The algorithm is called Bandwidth estimation.

The algorithm processes two EWMA (Exponentially Weighted Moving Averages) and chooses the minimum of the two as the bandwidth estimation. Then the bandwidth estimation is multiplied by a factor to reduce oscilation. And finally it selects the first quality with a bitrate less than the adjusted bandwidth estimation.

- **DASH.js** [11]. The Throughput Rule.


This algorithm is basically the same as the Bandwidth estimation from HLS.js. It computes the average throughput, and uses a safety factor to avoid oscillations. And then chooses the quality based on the safe average and creates a new *SwitchRequest*.

### 2.2.2.2 Buffer based algorithms

This group of algorithms uses buffer occupancy information to try to choose the highest level of bitrate for the multimedia content. These algorithms are usually used to avoid buffer underflow.

- **BOLA** [28]. Buffer Occupancy based Lyapunov Algorithm.

The BOLA adaptation algorithm uses the Lyapunov optimization to make decisions. This is an utility theory and it is configurable with a tradeoff parameter to choose between rebuffering potential and bitrate maximization.



**Figure 2.5:** BOLA's bitrate choice as function of buffer level. Source: [28]

BOLA tries to maximize  $V_n + \gamma S_n$ . where:

- $V_n$  is the bitrate utility.
- $S_n$  is the playback smoothness.
- $\gamma$  is the tradeoff weight parameter.

### 2.2.2.3 Control theory based or hybrid algorithms

This class of algorithms uses a combination of throughput estimation and buffer occupancy and tries to maximize the bitrate selection with decision-taking indicators calculated making use of control theory or stochastic optimal control equations.

### 2.2.3 QoS & QoE Metrics

The *Quality of Service (QoS)* is defined by the *ITU-T* in the document P.10/G.100 [21] as "The totality of characteristics of a telecommunications service that bear on its ability to satisfy stated and implied needs of the user of the service". And the *Quality of Experience (QoE)* is defined as "The degree of delight or annoyance of the user of an application or service".

The standard *ISO/IEC 23009* defines a list of parameters for *Quality of Service (QoS)* and *Quality of Experience (QoE)* for the adaptation algorithms to base on. There parameters is also used to evaluate the overall quality in the multimedia distribution service.

Some of the metrics defined in [2] and [15] are as follows:

- **Average Throughput:** This is a *QoE* metric that defines a list in which the average Throughput observed in the client during a measuring period.
- **Initial Playout Delay:** This is a *QoE* metric that represents the initial delay in the reproduction of the media content.
- **Representation Switch Events:** This is a *QoS* metric for measuring the number of representation switch events of the multimedia content.
- **Buffer Level:** This is a *QoS* metric that monitors the level of occupancy of the buffer during the reproduction of the multimedia content.

## 2.3 LTE Fundamentals

*Long Term Evolution (LTE)* was first introduced in 2008 in the Release 8 of the *3GPP* specification [1]. The objective of *LTE* was to migrate the *3GPP* systems into a optimized

system based on packet switching (all *IP*), with greater bitrates, lower latency y multiple radio access technologies support.

### 2.3.1 History

The first mobile phone call was made in 1973 [16]. New generations of mobile networks are developed almost every decade. The first generation 1G launched years later, but it was only capable of doing voice calls. In 1991, the second generation 2G (*GSM*) of mobile networks was introduced. *GSM* provided improved wireless capabilities and introduced by the first time multimedia content with *Multimedia Message Service (MMS)*. But it was the third generation 3G, launched in 2001, that enabled new internet-driven services such as video conferencing and streaming. Later in 2009, the *LTE* 4G standard was commercially deployed. With theorical download bandwidth of almost 100Mbps made high-quality streaming into reality. 5G technologies improves in bandwidth even more and brings video streaming in *UHD* and more.

The consumption of multimedia content on mobile networks is becoming increasingly relevant with the rise of bandwidth and ease of access. This section will provide a brief introduction to the basic concepts of mobile networks, their architecture and fundamentals.

### 2.3.2 Architecture

The design of the *LTE* architecture was done from the ground up. The goal was to build a flat, all *IP* architecture using packet-switching, well structured (separation of control plane and user plane) and with few elements.

The *Evolved Packet System (EPS)* is constituted by the following elements:

- ***User Equipment (UE)***: An *UE* is any device used by an end user to communicate in a mobile network.
- ***Evolved UMTS Terrestrial Radio Access Network (E-UTRAN)***: The only elements in the *E-UTRAN* are the *e-NodeB*. An *enhanced Node B (e-NodeB)* works as a base station and a controller.





Figure 2.6: LTE Architecture

- **Evolved Packet Core (EPC):** The *EPC* is made up of a network of gateways, control servers, and databases linked by a *IP* backbone. The main elements of the *EPC* are:
  - **Mobility Management Entity (MME):** The *MME* is a server used for managing the signalling of the operation.
  - **Serving Gateway (SGW):** The *SGW* is the gateway used for communicating the access network *E-UTRAN* and the *PGW*.
  - **Packet Data Network Gateway (PGW):** The *PGW* is the gateway for the traffic between the core network and external packet data networks.
  - **Home Subscriber Server (HSS):** The *HSS* is a database containing information about the *EPC* network users.
  - **Policy Charging and Rule Function (PCRF):** The *PCRF* is used for *QoS*, policy and charging management.

### 2.3.3 Wireless Fundamentals

Large-scale wireless networks, such as LTE, are fundamentally inefficient and prone to interference. Supporting mobility while also obtaining high levels of power efficiency, such as through directional antennas, can be really challenging. Base stations must be selectively installed but accommodate vast user populations in order to be cost-effective, resulting in a significant amount of self-interference. As a result, achieving high coverage, capacity, and dependability at low cost and used power is extremely difficult, if not impossible.





**Figure 2.7:** Evolved Packet Core (EPC) Architecture

The following list highlights the main parameters affecting the received signal in a wireless system.

### 2.3.3.1 Propagation loss


The amount of transmitted power that actually reaches the receiver is the first visible difference between wired and wireless channels. The transmitted signal energy extends along a spherical wavefront if an isotropic antenna is utilized, hence the energy received at an antenna  $d$  distant is inversely proportional to the sphere surface area,  $4\pi d^2$ . However, in reality the propagation environment is not free space, we may also take into account other factors such as reflections.

### 2.3.3.2 Shadowing


Obstacles such as trees and buildings, as shown in Figure 2.8, may be situated between the transmitter and receiver, causing temporary signal degradation, whereas a temporary line-of-sight transmission path would result in abnormally high received power.

### 2.3.3.3 Fading loss

The fading effect is another aspect of wireless channels. Fading is generated by the receiving of multiple versions of the same signal (multipath), unlike path loss or shadowing, which are large-scale attenuation effects induced by distance or obstacles.



*Figure 2.8: Shadowing effect. Source: [24]*



*Figure 2.9: Fading loss effect. Source: [24]*

The reflections may arrive at very short intervals. For example, if there is local dispersion around the receiver, or they may arrive at relatively longer intervals, for instance, if the transmitter and receiver are on multiple pathways. Figure 2.9 illustrates this.

### 2.3.4 Antennas & MIMO

An antenna is a device that uses electromagnetic waves to transmit or receive information. The transmitting antenna turns electrical currents into electromagnetic waves, and vice versa (receiving antenna).

*Multiple Input, Multiple Output (MIMO)* is a technique for increasing the capacity of

a radio link by employing multiple transmitting and receiving antennas to take advantage of multipath propagation. MIMO has become a key component of wireless communication technologies such as LTE.

There are several implementations of MIMO in LTE:


- **Single antenna:** Most simple wireless links employ this type of radio transmission. One antenna transmits a single data stream, which is received by one or more antennas. It is also known as SISO.
- **Transmit diversity:** This type of LTE MIMO method makes use of several antennas to transmit the same data stream.
- **Open loop spatial multiplexing:** This type of MIMO involves delivering two information streams through two or more antennas.
- **Close loop spatial multiplexing:** Similar to the above but with a close loop feedback.
- **Closed loop with pre-coding:** This type of MIMO transmits a single code word over a single spatial layer.
- **Multi-User MIMO:** Single-user SU-MIMO's per-user throughput is better suited to more sophisticated user devices with more antennas, whereas MU-MIMO is more practical for low-complexity mobile phones with a small number of reception antennas.
- **Beam-forming & MIMO:** This is the most advanced MIMO mode. It allows the antenna to focus on a specific location.

### 2.3.5 Physical Layer

#### 2.3.5.1 OFDMA and SC-FDMA

The cellular communication systems need to have a strategy for multiple access. In LTE, the *Orthogonal Frequency Division Multiple Access (OFDMA)* is used for downlink and the *Single-Carrier Frequency Division Multiple Access (SC-FDMA)* is used for uplink. Both are very similar, consisting in allocating each subscriber some portion of the subcarriers for certain amount of time.

In the Figure 2.10, a transmission structure of LTE is presented. The two dimensions of the plane are time and frequency. Two important concepts are defined as:



**Figure 2.10:** LTE Time-Frequency Grid. Source: [30]

- **Resource Element (RE):** A Resource Element is the basic element of resource, it is defined as one subcarrier in a symbol period.
- **Resource Block (RB):** A Resource Block is composed by twelve subcarriers (180 kHz) in a time interval of 0.5 ms (7 OFDM symbols).

Users are assigned resources in resource blocks across a subframe, i.e., 12 subcarriers over  $2 \times 7 = 14$  OFDM symbols for a total of 168 Resource Elements. Because some of the 168 resource components are utilized for various layer 1 and layer 2 control messages, not all of them can be used for data.

The number of Resource Blocks available for each channel bandwidth is given by the Table 2.1.

Bandwidth	1.4 MHz	3 MHz	5 MHz	10 MHz	15 MHz	20 MHz
Number of RBs available	6	15	25	50	75	100

**Table 2.1:** Number of Resource Blocks against each channel bandwidth. Source: [29]

### 2.3.5.2 AMC & CQI

AMC stands for Adaptive Modulation and Coding, is a terminology used in LTE to describe how modulation and coding are matched to the radio link's conditions.

The eNB applies AMC by selecting the appropriate MCS based on quality estimations supplied by the UE mobile terminal via the *Channel Quality Indication (CQI)* parameter.

CQI Index	Modulation	Code Rate $\times 1024$	Efficiency
0	out of range		
1	QPSK	78	0.1523
2	QPSK	120	0.2344
3	QPSK	193	0.3770
4	QPSK	308	0.6016
5	QPSK	449	0.8770
6	QPSK	602	1.1758
7	16QAM	378	1.4766
8	16QAM	490	1.9141
9	16QAM	616	2.4063
10	64QAM	466	2.7305
11	64QAM	567	3.3223
12	64QAM	666	3.9023
13	64QAM	772	4.5234
14	64QAM	873	5.1152
15	64QAM	948	5.5547

**Table 2.2:** 4-Bit CQI Table

MCS

### 2.3.5.3 EARFCN

The *E-UTRA Absolute Radio Frequency Channel Number (EARFCN)* is a number between 0-65535 used for designating uplink and downlink carrier frequencies.

$$F_{downlink} = FDL_{Low} + 0.1(NDL - NDL_{Offset}) \quad (2.1)$$

$$F_{uplink} = FUL_{Low} + 0.1(NUL - NUL_{Offset}) \quad (2.2)$$

Where  $NDL$  is the downlink EARFCN,  $NUL$  is the uplink EARFCN.

### 2.3.5.4 Sounding Reference Signal

*Sounding Reference Signal (SRS)* are wideband reference signals used by the eNode-B to determine uplink channel quality information in order to allocate uplink resources. There are three types of SRS transmissions, single SRS, periodic SRS and aperiodic SRS.

### 2.3.6 Medium Access Control Layer

The *Medium Access Control (MAC)* layer essentially provides the higher layer with radio resource allocation and data transfer services and connects the RLC layer and the PHY layer. The MAC layer executes procedures such as logical channel priority, power headroom reporting, UL grant and DL assignment, and so on as part of the radio resource allocation service. The MAC layer performs functions like scheduling requests, buffer status reporting, random access, and HARQ as part of the data transmission service.

### 2.3.7 Radio Link Control Layer

The RLC layers's key functions include data unit segmentation and concatenation, error correction via the ARQ protocol, and packet delivery in sequence to higher levels. It has three modes of operation:

- **Transparent Mode (TM)** is the most basic mode, with no RLC header, data

segmentation, or concatenation, and is used for specialized applications like random access.

- **Unacknowledged Mode (UM)** The UM mode detects packet loss and allows for packet reordering and reassembly, but does not require the missing protocol data units to be retransmitted (PDUs).
- **Acknowledged Mode (AM)** is set up to request retransmission of missing PDUs in addition to the UM mode's features.

### 2.3.8 Packet Data Convergence Protocol Layer

The PDCP layer's main features are IP packet header compression and decompression based on the *RObust Header Compression (ROHC)* protocol, data and signaling ciphering, and signaling integrity protection. Per bearer, there is only one PDCP entity at the eNode-B and the UE.





## Chapter 3 | Network Simulator 3

The *ns-3* simulator is an open, extensible discrete-event network simulator designed primarily for educational and network research purposes [25].

In summary, *ns-3* provides models of how packet data networks work and operate, as well as a simulation engine that allows users to run simulation experiments. To do research that are more difficult or impossible to do with real systems, to examine system behavior in a highly controlled, reproducible setting, and to understand about how networks work.

*ns-3* is a collection of modules that can be used together as well as with other software libraries. This tool works mainly at the command line on *Linux* or *MacOS* and with *C++* and *Python* programming languages and development tools.

### 3.1 ns-3 Concepts

This section will go over several networking concepts that have a specific meaning in *ns-3*.

**Node:** A `Node` in *ns-3* is the basic computing device abstraction. The `Node` class has methods for managing computing device representations in simulations.


**Application:** A *ns-3* application run on *ns-3* `Nodes`. An `Application` is the basic abstraction for a user program that generates some simulated activity. The `Application` class provides functions for controlling the representations of the simulated version of user-level applications.

**Channel:** A `Channel` in *ns-3* is an abstraction of the basic communication subnetwork in which `Nodes` are connected in. It can be as simple as a wire or as complicated as a large Ethernet switch.

**Net Device:** A `NetDevice` in *ns-3* simulates a *Network Interface Card (NIC)* and the software controlling the *NIC*. A `NetDevice` is installed in a `Node` to allow it to communicate over `Channels` with other `Nodes` in the simulation.

**Helpers:** Helper objects are created to make some common tasks easier. Such as connecting `NetDevices` to `Nodes`, `NetDevices` to `Channels`, assigning IP addresses, etc.

The Figure 3.1 shows a high level node architecture.



*Figure 3.1: ns-3 High-level node architecture. Source: [25]*

## 3.2 Logging Module

Message logging is a basic feature for large softwares, and *ns-3* is no different. *ns-3* offer a complete module for message logging with configurable verbosity levels. This means that logging functions of specific components can be enabled and other can be disabled

completely.

There are different levels of log messages of ascending verbosity defined in *ns-3*:

- **LOG\_ERROR**: For error messages (associated function: `NS_LOG_ERROR`).
- **LOG\_WARN**: For warning messages (associated function: `NS_LOG_WARN`).
- **LOG\_DEBUG**: For relatively rare, ad-hoc debugging messages (associated function: `NS_LOG_DEBUG`).
- **LOG\_INFO**: For informational messages about program progress (associated function: `NS_LOG_INFO`).
- **LOG\_FUNCTION**: For messages describing each function called (two associated function: `NS_LOG_FUNCTION` used for member functions, and `NS_LOG_FUNCTION_NOARGS`, used for static functions)).
- **LOG\_LOGIC**: For messages describing logical flow within a function (associated function: `NS_LOG_LOGIC`).
- **LOG\_ALL**: Log everything mentioned above (no associated function).

To enable all logs, it is as simple as modifying a shell variable. In the next example the logging for the class `UdpEchoClientApplication` and `UdpEchoServerApplication` is enabled with all levels, the time and the function prefixes:

---

```
1 $ export 'NS_LOG=UdpEchoClientApplication=level_all|prefix_func|
    prefix_time:UdpEchoServerApplication=level_all|prefix_func|
    prefix_time'
```

---

*Listing 3.1: Enabling logging in ns-3*

For more information with the logging module see [25].

### 3.3 Command Line Arguments

There are local and global variables that can be changed in the command line without editing the scripts. To be able to know what variables are available, the option `-PrintHelp` is used.

## 3.4 Tracing System

The main goal of the simulations is to extract and generate output, and *ns-3* offers two mechanisms for this. Also, since *ns-3* is a C++ software, using `std::cout` for output is also available.

### 3.4.1 ASCII Tracing

*ns-3* includes helper function that encapsulates the low-level tracing system and guides you through the technicalities of establishing some simple packet traces. If you enable this feature, the output will be in ASCII files, hence the name.

To enable ASCII Tracing, right before the call to `Simulator::Run ()`, create an `AsciiTraceHelper` and call the function `EnableAsciiAll`. This will generate the output into the home directory of *ns-3*.

### 3.4.2 PCAP Tracing

The *ns-3* device helpers can also create `.pcap` trace files. The *pcap* file contains the packets captured during the simulation. *Wireshark* or *tcpdump* are programs capable of reading and visualizing *pcap* files.

To enable *pcap* tracing simply add the `EnablePcapAll` function. And it will create various `.pcap` files in the format `"myfirst-0-0.pcap"`, meaning the trace file for node 0 and device 0.

## 3.5 ns-3 Modules & Models

In this section, modules used in this thesis will be presented, based on the official manual from [25]. But first, It is essential to understand the difference between modules and models:

- **Modules** are the different libraries that form *ns-3*.
- **Models** are the simulated, abstract representations of real-life objects, protocols, devices, etc.

As the reader may already know, *ns-3* is modular. A new module will be introduced in the chapter 4 as a result of this Master final project.

### 3.5.1 Antenna Module

The Antenna module provides a `AntennaModel` base class as an interface for radiation pattern modelling of an antenna. Also, there are a set of classes derived from this base class that implements types of antennas with different radiation patterns.

#### 3.5.1.1 AntennaModel

The `AntennaModel` uses a coordinate system as shown in the Figure 3.2. This model uses, for a point  $p$  in the space with Cartesian coordinates used by the `MobilityModel`, the coordinates  $(x, y, z)$  and transforms into spherical coordinates  $(r, \theta, \phi)$ .

The radiation pattern is express as a mathematical function  $g(\theta, \phi) \rightarrow \mathbb{R}$



*Figure 3.2: Coordinate system of the AntennaModel. Source: nsnam [25]*

- `IsotropicAntennaModel`

The `IsotropicAntennaModel` is omnidirectional, this means that the radiation pattern have a 0dB gain for all direction.

- **CosineAntennaModel**

The antenna gain of the `CosineAntennaModel` is defined as:

$$g(\phi, \theta) = \cos^n \left( \frac{\phi - \phi_0}{2} \right) \quad (3.1)$$

with  $\phi_0$  as the antenna's azimuthal orientation, this is, the direction of maximum gain. And the exponential

$$n = -\frac{3}{20 \log_{10} \left( \cos \frac{\phi_{3dB}}{4} \right)} \quad (3.2)$$

determines the wanted 3db beamwidth  $\phi_{3dB}$ .

- **ParabolicAntennaModel**

In the `ParabolicAntennaModel`, the antenna gain is determined as:

$$g(\phi, \theta) = -\min \left( 12 \left( \frac{\phi - \phi_0}{\phi_{3dB}} \right)^2, A_{max} \right) \quad (3.3)$$

where  $A_{max}$  is the maximum attenuation in dB of the antenna.

### 3.5.2 Application Module

The `Application` class is a base class for *ns-3* applications. Nodes can have one or more applications. Each node maintains a list of smart pointers (references) to all its applications. The `Applications` are the responsables to create the sockets, if needed.

There are a few implementations of `Applications` in *ns-3*:

- **BuldSendApplication.** This traffic generator basically sends data as quickly as possible until `MaxBytes` is reached or the application is terminated (if `MaxBytes` is zero)
- **OnOffApplication.** After `StartApplication` is called, this traffic generator alternates between "On" and "Off" states.
- **PacketSink.** This application is for receiving packets from any other applications, for example, from `BulkSendApplication` or `OnOffApplication`.

### 3.5.3 Buildings Module

The Buildings module provide various models, but these are the most relevant for this thesis:

#### 3.5.3.1 Building class

The `Building` model implements and tries to simulate real-life buildings, which affects wireless communications in different ways.

A `Building` can be residential, office or commercial, has different types of external wall (wood, concrete with/out windows, stone blocks), has a number of floors and rooms in each floor.

Some limitations have to be made:

- A `Building` is represented as a rectangular parallelepiped.
- The walls needs to be parallel to the cardinal coordinates.
- A `Building` is a grid of rooms, with z axis as the floor number and the x and y room indexes start from 1 and increses along the x and y axis.
- All the rooms are the same size.

#### 3.5.3.2 MobilityBuildingInfo class

The `MobilityBuildingInfo` keeps track of the mobility and positional information of the nodes with respect to buildings in a simulation. A node can be inside or outside of a building and if the node is indoors, this class knows in which building and in which room the node is positioned.

#### 3.5.3.3 ItuR1238PropagationLossModel

This class provides an ITU P.1238-based building-dependent indoor propagation loss model that includes losses owing to building type (i.e., residential, office and commercial). The following is the analytical expression:

$$L_{total} = 20 \log f + N \log d + L_f(n) - 28[dB] \quad (3.4)$$

where  $N$  is the power loss coefficient,  $L_f$  is the loss depending of type of building,  $f$  is the frequency [MHz] and  $d$  is de distance [m].

#### 3.5.3.4 BuildingPropagationLossModel

The `BuildingsPropagationLossModel` adds a set of pathloss model elements that are building-dependent and can be used to design various pathloss logics. The elements of the pathloss model are discussed in the subsections below.

- **External Wall Loss**

This component simulates the loss of communication from indoors to outdoors and vice versa through walls.

- **Internal Wall Loss**

This component simulates the loss of penetration in indoor-to-indoor communications within a single building.

- **Height Gain Model**

This component simulates the gain caused by the transmitting equipment being on a higher floor than the ground.

- **Shadowing Model**

The shadowing is represented using a log-normal distribution with a variable standard deviation as a function of the `MobilityModel` instances' relative position (inside or outdoor). For each pair of `MobilityModels`, a single random value is generated and remains constant during the simulation. As a result, the model is only suitable for static nodes.

#### 3.5.3.5 Pathloss logics

The pathloss logic provided by inheriting from `BuildingsPropagationLossModel` is described in the following sections.



- **HybridBuildingsPropagationLossModel**

In order to imitate multiple outdoor and interior circumstances, as well as indoor-to-outdoor and outdoor-to-indoor scenarios, the `HybridBuildingsPropagationLossModel` was created by combining various well-known pathloss models. In particular, this class combines the pathloss models listed below:

- **OhBuildingPropagationLossModel** This is a simpler propagation loss model. It uses the `OkumuraHataPropagationLossModel` and also taking account the pathloss elements of the `BuildingPropagationLossModel`.

### 3.5.4 Internet Module

This module includes the implementations of TCP/IP related components like IPv4, ARP, UDP, TCP and so on. A `Node` with the Internet Stack installed is called a Internet Node.

In order to use the Internet Protocol, a node should be assigned an IP address. It can be done manually or through the *Dynamic Host Configuration Protocol (DHCP)*.

Full bidirectional TCP with connection setup and close logic is supported by the native *ns-3* TCP model. Various TCP congestion algorithms are also available, such as New Reno, Cubic, HighSpeed, etc.

### 3.5.5 Mobility Module

The mobility module in *ns-3* includes model to keep track the position and movement of the nodes and objects in cartesian coordinates and also a number of helper classes used for placing nodes and set up mobility models.

The `MobilityModel` is the base class for all the subclasses for different moving paths or behaviours. The class `PositionAllocator` is typically used for setting the initial position of objects. `MobilityHelper` combines a mobility model and position allocator used for adding mobility capabilities for a set of nodes.

Some useful subclasses of `MobilityModel` are:

- `ConstantPositionMobilityModel` for stationary nodes.
- `ConstantVelocityMobilityModel` for constant velocity moving nodes.
- `RandomWalk2SMobilityModel` for random walking in a 2D plane.

### 3.5.6 Network Module

The Network Module includes implementations of network related classes like `Packet`, `NetDevice`, TCP and UDP Sockets, etc.

#### 3.5.6.1 Packets

A network packet is composed by a byte buffer, a group of tags and metadata. The serialized content of the headers and trailers added to a packet is stored in the byte buffer. The serialized form of these headers is expected to match the serialized representation of real network packets bit for bit, implying that the content of a packet buffer is supposed to be the same as that of a real packet.

#### 3.5.6.2 Sockets

A socket is an abstraction that enables applications to communicate with other Internet hosts, among other services, and exchange reliable byte streams and unreliable datagrams.

- **ns-3 Sockets API**

The native sockets API for *ns-3* provides an interface to TCP and UDP. Although, the `ns3::Socket` have some differences compared to real sockets.

- **Using Sockets**

In *ns-3*, if an application wants to use sockets must create one first. By calling `CreateSocket`, *ns-3* creates a smart pointer to a `Socket` object. *ns-3* sockets have all the functions of a real socket, including `bind`, `connect`, `send`, `receive` and `close`.

In addition, the `Socket` class can set up events to make callbacks. For example, `SetConnectCallback` is called when a connection is made, whether it succeeded or failed, `SetSendCallback` is invoked when the send buffer is available and `SetRecvCallback` will notify when the data is received.

### 3.5.7 PointToPoint NetDevice

The *ns-3* point-to-point model simulates a very basic point-to-point data link that connects two `PointToPointNetDevice` devices across a `PointToPointChannel`. This can be compared to a full duplex RS-232 or RS-422 connection with no handshaking and no null modem.

The create point-to-point net devices and channels, `PointToPointHelper` is used. To connect two nodes, simply call the `Install` function.

### 3.5.8 LTE Module

There are two main components in the LTE-EPC simulation model.

- **LTE Model.** Includes models for the UE and the eNodeB nodes. Also the LTE Radio Protocol Stack (PHY, MAC, RLC, etc.).
- **EPC Model.** Includes models for the entities, interfaces and protocols in the Evolved Packet Core.

#### 3.5.8.1 LteHelper

The `LteHelper` is a helper which manages the LTE radio access network's configuration as well as the setup and release of EPS bearers. The API definition and implementation are both provided by the `LteHelper` class.

A code snippet to create UEs and eNodeBs with `LteHelper` is found in section C.2

- **Network Attachment**

To connect an UE to the network, the UE needs to be attached to an eNodeB. This is done by calling the `LteHelper::Attach` function. There are two possible ways for network attachment.

- **Automatic Attachment**

This method uses the strength of the received signal as the criteria to choose, in the initial cell selection process, which eNodeB to connect to.

- **Manual Attachment** Alternatively, selecting the eNodeB at the beginning of the simulation is also possible.

- **Simulation Output**

The LTE module offer PHY, MAC, RLC, and PDCP level *Key Performance Indicators (KPI)* that can be enabled using **LteHelper**:

---

```
1  lteHelper->EnablePhyTraces ();
2  lteHelper->EnableMacTraces ();
3  lteHelper->EnableRlcTraces ();
4  lteHelper->EnablePdcPTraces ();
```

---

*Listing 3.2: Enable LTE trace outputs*

### 3.5.8.2 EpcHelper

The **EpcHelper** allows the simulation of the Evolve Packet Core. The usage of EPC with LTE devices allows for IPv4 and IPv6 networking. To put it another way, it is possible to use standard *ns-3* apps and sockets across IPv4 and IPv6 via LTE, as well as connect an LTE network to any other IPv4 and IPv6 network in the simulation.

It is possible to access the SGW and PGW nodes by calling the **GetSgwNode** and the **GetPgwNode** respectively.

### 3.5.8.3 MAC

- **MAC Scheduler**

In *ns-3*, there are several types of MAC schedulers available. User can choose which one to use with the **LteHelper**:

- FD-MT (Frequency Domain Maximum Throughput Scheduler)
- TD-MT (Time Domain Maximum Throughput Scheduler)
- TTA (Throughput to Average Scheduler)
- FD-BET (Frequency Domain Blind Average Throughput Scheduler)
- TD-BET (Time Domain Blind Average Throughput Scheduler)
- FD-TBFQ (Frequency Domain Token Bank Fair Queue Scheduler)
- TD-TBFQ (Time Domain Token Bank Fair Queue Scheduler)
- PSS (Priority Set Scheduler Scheduler)

- **AMC & CQI**

In terms of selecting MCSs and generating CQIs, the simulator offers two options. The first is the implementation by [17] and operates on a per-RB basis, and the other is based on the physical error mode.

#### 3.5.8.4 Mobility Model with Buildings

The propagation model to be used with the LTE module is defined in the Buildings module.

This creates a residential building, concrete with windows, with 3 floors and 6 rooms each floor. It is set that all UEs are in a constant position, but other mobility models are also possible.

The LTE module is also compatible with existing propagation loss models. Only the propagation from the UEs to the base stations are computed.

#### 3.5.8.5 AntennaModel & MIMO Model

Any model of `AntennaModel` is supported, by default, the `IsotropicAntennaModel` is used for both eNBs and UEs. In case of using multiple antennas, *ns-3* offers different MIMO operation modes.

#### 3.5.8.6 Radio Environment Maps

With this class is possible to create a Radio Environment Map (REM), which is a uniform 2D grid of values that reflect the signal-to-noise ratio in the downlink with regard to the eNB with the strongest signal at each point, to a file by using the class `RadioEnvironmentMapHelper`.

Using a software like gnuplot<sup>1</sup>, the output file can be visualized.

Figure 3.3 shows an example of a Radio Environment Map.

---

<sup>1</sup><http://www.gnuplot.info/>



*Figure 3.3: Example Radio Environment Map. Source: [25]*

## 3.6 Parameter Configuration

The *ns-3* attribute system is the entity that manages all the parameters. It is possible to use input files using `ConfigStore` and set initial values for default and global parameters.

It is important to include `#include "ns3/config-store.h"` in the script. Then create a text file named as defined before and specify the new default values to be used.

## Chapter 4 | ABR Module for ns-3

This chapter will introduce a new module for *ns-3* for ABR streaming simulation. The section 4.1 will set the objective and the scope of the design. The section 4.2 will present the architecture of the module. The section 4.3 will go over the models the module is composed of. Finally, the section 4.4 will explain the adaptation algorithms implemented in this module.


### 4.1 Design Objectives

The main objective of this chapter is to design and implement a *ns-3* module able to simulate the behavior of video streaming devices in mobile network scenarios. To build a framework capable of testing new adaptation algorithms and be possible to extract metrics to measure quality of services and quality of experience.

### 4.2 Architecture

The ABR module provides:

- **AbrClient.** This class mimics a video streaming application. It has an instance of *AbrAlgorithm*, which is responsible of deciding which quality of media content to download from the *AbrServer*. It is an implementation of *ns3::Application*.
- **AbrServer.** This class simulates a video streaming HTTP server. It receives requests from clients and sends the multimedia segments requested. It is an implementation of *ns3::Application*.
- **AbrVariables.** This class is used for storing common variables between the clients



*Figure 4.1: ABR Module architecture.*

and the servers. It contains the definition of Segment, Representation, AbrTask, etc.

- **AbrHelper.** This is a Helper class for the ABR module. It is the responsible for managing the instances of the ABR clients and servers. In addition, AbrHelper can be used for extracting QoS and QoE metrics.
- **AbrAlgorithm.** This is a base class to be implemented with different adaptation algorithms.
- **HLSjs.** This is an implementation of AbrAlgorithm based on [9].
- **DASHjs.** This is an implementation of AbrAlgorithm based on [11]. It also contains the implementation of the buffer based BOLA algorithm.
- **abr-example.cc.** An basic example script with two nodes linked with a PointTo-Point connection and a unstable connection.



The Figure 4.1 shows the architecture of the ABR module. Although this module was designed to be used in mobile environments, it can be used with any other `Application` class in *ns-3*, meaning that the ABR clients and servers can be installed in any `Node` and work with other *ns-3* modules and models.

## 4.3 Models

This section will go through all the models, classes and helpers in the ABR module and how they work together.

### 4.3.1 AbrClient

The `AbrClient` is an implementation of `ns3::Application`. This class uses an implementation of `AbrAlgorithm` to create HTTP-like requests to the `AbrServer` and mimics the playing of the media content.

The `AbrClient` is created with the `AbrHelper` and the server address and port as parameters. Then the client application needs to be installed on the client nodes. When the simulation starts, the function `StartApplication` is called and the simulator is scheduled to call `HandlePlay` function to simulate video watching. The client will create a new socket, in this case a TCP socket, to connect with the server. The socket is set with various callback functions:

- `ConnectionSucceeded`. is called if the connection succeeded. Then it calls the `CheckAlgorithm` function.
- `ConnectionFailed`. is called if the connection failed. This should not happen if the simulation script is correctly written.
- `HandleRead`. is called when new packets are received. It stores the segments to the segment buffer, and checks the adaptation algorithms after one entire segment is downloaded.

The `CheckAlgorithm` method asks the `AbrAlgorithm` and returns one or more `AbrTasks`. The client will call the scheduled functions depending on the designated task and delay.




Figure 4.2: ABR Client.


### 4.3.2 AbrServer

The `AbrServer` is an implementation of `ns3::Application`. This class receives HTTP-like requests from the `AbrClient` and sends the requested segment.

The request is in the format:

**GET qualityIndex numberOfSegments startSegment**

For example, "GET 4 1 3" means "GET 1 segment of quality index 4 starting from the 3<sup>rd</sup> segment".



*Figure 4.3: ABR Server.*

The `AbrServer` is created with the `AbrHelper` and the listening port as the parameter. Then the server application needs to be installed on the server node. When the simulation starts, the function `StartApplication` is called. The server will create a socket, binds it and starts to listen. The socket is set with callback functions. When the sockets are connected, the server will schedule new callbacks to handle reading requests and sending data.

### 4.3.3 AbrVariables

The `AbrVariables` class contains variables and functions used by the `AbrClient` and `AbrServer`, including the definition of a set of essential data structures. These data structures are:

- **Segment.** It is an abstraction of a media segment. A `Segment` has a size (in bytes), a start time and a duration.
- **Representation.** Describes a certain version of a encoded media. A `Representation` include the resolution, the frames per second and the encoding bitrate.
- **SegmentInfo.** This is a additional data structure for `Segment`. A `SegmentInfo` contains information about download start/finish time, playback start/finish time, the bandwidth estimation used to download that segment and the quality index of the segment.
- **PlayerStates.** This class keeps track on the player status.
- **AbrTask.** An `AbrTask` is a used to schedule tasks for `AbrClients`.

`AbrVariables` has these variables:

- **m\_segments.** It is a two-dimentional vector containing all the segments for the simulation. Each row has de the same quality and the higher the row index, the higher the quality. The segments are ordered in time in the columns.
- **m\_representations.** It is a vector containing all the `Representations`. The row index also means the quality level.
- **m\_segmentDuration.** The duration of the segment in milliseconds. By default, it is `2000ms`.

Before the simulation starts, the `AbrVariables` class initializes the variables. Starting with the representations, there are a predefined set of `Representations` by default, but they can be changed in the source file. Continuing with the segments, their sizes are calculated based on the resolution, framerate and the encoding bitrate for each representation.

Also, the possibility of creating a MPD file parser has been considered, but it can be done in the future as an improvement.

#### 4.3.4 AbrHelper

`AbrHelper` are helper classes providing the functionality of managing the ABR clients and servers (creating, setting attribute, etc.). There are two classes, `AbrServerHelper` and `AbrClientHelper`. The `AbrClientHelper` have methods to extract QoE metrics after the simulation ends.

#### 4.3.5 AbrAlgorithm

`AbrAlgorithm` serves as the base class for the implementations of adaptation algorithms. In the next section, two implementations of `AbrAlgorithm` are presented.

### 4.4 Adaptation Algorithms

### 4.5 QoS & QoE Metrics

////



## Chapter 5 | Simulations and Results





## Chapter 6 | Conclusions and Future Work



# Bibliography

- [1] 3GPP. 3<sup>rd</sup> Generation Partnership Project; Technical Specification Group Services and System Aspects; Technical Specifications and Technical Reports for a GERAN-based 3GPP system (Release 8). Technical Report 3GPP TS 41.101, 2009.
- [2] 3GPP. *Transparent end-to-end Packet-switched Streaming Service (PSS); Progressive Download and Dynamic Adaptive Streaming over HTTP (3GP-DASH)*. 3GPP TS 26.247 v16.4.1, 2020.
- [3] Adobe. Live Streaming. <https://www.adobe.com/es/products/hds-dynamic-streaming.html>.
- [4] Apple. HTTP Live Streaming. <https://developer.apple.com/streaming>.
- [5] Benny Bing. *Next-generation video coding and streaming*. Wiley, 1st edition, 2015.
- [6] Julián Cabrera. *Apuntes de Sistemas y Servicios de Multimedia (MUIT)*. Universidad Politécnica de Madrid, 2020.
- [7] Lyn Cantor. The global internet phenomena report covid-19 spotlight. Technical report, Sandvine, 2020.
- [8] Cisco. Cisco predicts more ip traffic in the next five years than in the history of the internet. <https://newsroom.cisco.com/press-release-content?type=webcontent&articleId=1955935>, 11 2018.
- [9] Dailymotion. HLS.js. <https://github.com/dailymotion/hls.js>.
- [10] DASH-IF. DASH Industry Forum. <https://dashif.org/>.
- [11] DASH-IF. dash.js. <https://github.com/Dash-Industry-Forum/dash.js>.
- [12] Universidad Politécnica de Valencia. Vídeo adaptativo a través de MPEG-DASH. <https://www.comm.upv.es/es/dash/>.
- [13] Streaming Media East. Adapting your player logic to your use case: how to use ABR to your advantage. <https://es.slideshare.net/EricaBeavers/abr-algorithms-2017-streaming-media-east>, 2017.

## BIBLIOGRAPHY

---

- [14] electronicsnotes. LTE EARFCN Radio Channel Numbers. <https://www.electronics-notes.com/articles/connectivity/4g-lte-long-term-evolution/lte-earfcn-radio-channel-numbers.php>.
- [15] International Organization for Standardization. *Information technology — Dynamic adaptive streaming over HTTP (DASH) - Part 1: Media presentation description and segment formats*. International Organization for Standardization, ISO/IEC 23009-1:2019(E) edition, 2019.
- [16] William. E. Gibson. First Cellular Phone Call Was Made 45 Years Ago. <https://www.aarp.org/politics-society/history/info-2018/first-cell-phone-call.html>, 2018.
- [17] Giuseppe Piro, Nicola Baldo, Marco Miozzo. *An LTE Module for the ns-3 network simulator*. CTTC Catalan Telecommunications Technology Centre, 2011.
- [18] IETF. RFC 8216 - HTTP Live Streaming - IETF Tools. <https://tools.ietf.org/html/rfc8216>, August 2017.
- [19] ISO. MPEG-DASH. <http://www.iso.org/iso/home/standards.htm>.
- [20] ITU-T. *Recommendation E.800 : Definitions of terms related to quality of service*. ITU, 2017.
- [21] ITU-T. *Recommendation P.10/G.100: Vocabulary for performance, quality of service and quality of experience*. ITU, 2017.
- [22] Microsoft. Silverlight. <https://www.microsoft.com/silverlight/smoothstreaming/>.
- [23] Christopher Mueller. Microsoft smooth streaming. <https://bitmovin.com/microsoft-smooth-streaming-mss/>, 2015.
- [24] Rias Muhamed, Arunabha Ghosh, Jun Zhang, and Jeffrey G Andrews. *Fundamentals of LTE*. Prentice Hall Communications Engineering and Emerging Technologies Series from Ted Rappaport. Pearson, 2010.
- [25] ns 3. A Discrete-Event Network Simulator. <https://www.nsnam.org/>.
- [26] Miguel Ángel Aguayo Ortuño. Contribución a los mecanismos de adaptación dinámica para servicios de distribución multimedia sobre redes móviles. December 2020.
- [27] Iraj Sodagar. White paper on MPEG-DASH Standard. MPEG-DASH: The Standard for Multimedia Streaming Over Internet. Technical report, ISO/IEC, 2012.
- [28] Kevin Spiteri, Rahul Urgaonkar, and Ramesh K. Sitaraman. Bola: Near-optimal bitrate adaptation for online videos. In *IEEE INFOCOM 2016 - The 35th Annual IEEE International Conference on Computer Communications*, pages 1–9, 2016.
- [29] Techplayon. LTE FDD System Capacity and Throughput Calculation. <https://www.techplayon.com/lte-fdd-system-capacity-and-throughput-calculation/>.
- [30] Luis Mendo Tomas. *Apuntes de Comunicaciones Móviles (GITST)*. Universidad Politécnica de Madrid, 2018.

- [31] Hubregt J. Visser. *Antenna theory and applications*. 2012.
- [32] SeungJune Yi, SungDuck Chun, YoungDae Lee, SungJun Park, and SungHoon Jung. *Radio Protocols for LTE and LTE-Advanced*. O'Reilly Media, Inc., 2021.

## *BIBLIOGRAPHY*

---

## Appendix A | Impact

### A.1 Social Impact

### A.2 Economic Impact

### A.3 Ambiental Impact

### A.4 Ethic Impact





## Appendix B | Budget



## Appendix C | ns-3 Tutorial

### C.1 Getting Started

The prerequisites for the *ns-3* release version 3.32 are the following tools:

Prerequisite	Package/version
C++ compiler	clang++ or g++ (g++ version 4.9 or greater)
Python	python3 version $\geq 3.5$
Git	any recent version
tar	any recent version
bunzip2	any recent version

*Table C.1: Prerequisites for ns-3*

Start by downloading the source archive from nsnam or gitlab. Then build *ns-3* with `build.py`:

```
1  # Download from nsnam
2  $ cd
3  $ mkdir workspace
4  $ cd workspace
5  $ wget https://www.nsnam.org/release/ns-allinone-3.32.tar.bz2
6  $ tar xjf ns-allinone-3.32.tar.bz2
7  $ cd ns-allinone-3.32
8  # Building ns-3
9  $ ./build.py --enable-examples --enable-tests
10 # Running a script
11 # Create or copy a script to the scratch directory
```

```
12 $ cp examples/tutorial/first.cc scratch/myfirst.cc
13 $ ./waf --run scratch/myfirst
```

---

*Listing C.1: Download and installation of ns-3*

### Logging Module

Enable logging:

---

```
1 $ export 'NS_LOG=UdpEchoClientApplication=level_all|prefix_func|
    prefix_time:UdpEchoServerApplication=level_all|prefix_func|
    prefix_time'
```

---

*Listing C.2: Enabling logging in ns-3*

To disable logging simply type:

---

```
1 $ export NS_LOG=
```

---

*Listing C.3: Disabling logging in ns-3*

### Command Line Arguments

An example of a command could be like this:

---

```
1 # To check help
2 $ ./waf --run "scratch/myfirst --PrintHelp"
3 # To check variables for PointToPointNetDevice
4 $ ./waf --run "scratch/myfirst --PrintAttributes=ns3::
    PointToPointNetDevice"
5 # We set the Datarate to 5Mbps
6 $ ./waf --run "scratch/myfirst --ns3::PointToPointNetDevice::DataRate=5
    Mbps"
```

---

*Listing C.4: Command line arguments*

### ASCII Tracing

To enable ASCII Tracing, right before the call to `Simulator::Run ()`, add the following lines of code:

---

```
1 AsciiTraceHelper ascii;
2 pointToPoint.EnableAsciiAll (ascii.CreateFileStream ("out.tr"));
```

---

*Listing C.5: ASCII tracing*

This will generate the output from `pointToPoint` to a file named `out.tr`.

### PCAP Tracing

To enable *pcap* tracing simply add:

---

```
1 pointToPoint.EnablePcapAll ("myfirst");
```

---

*Listing C.6: PCAP tracing*

### Sockets

Creating a socket:

---

```
1 Ptr<Node> node;
2 // Create a TCP socket
3 Ptr<Socket> mySocket = Socket::CreateSocket (node, TcpSocketFactory::
    GetTypeId ());
4 // Functions
5 mySocket->Bind();
6 mySocket->Connect( ... );
7 mySocket->Send( ... );
8 mySocket->Recv( ... );
9 mySocket->Close();
```

---

*Listing C.7: ns-3 Socket programming*

For callbacks:

---

```
1 mySocket->SetConnectCallback (
2     MakeCallback (&MyClass::ConnectionSucceeded, this),
3     MakeCallback (&MyClass::ConnectionFailed, this)
4 );
5 mySocket->SetSendCallback (MakeCallback (
6     &MyClass::HandleSend, this));
7 mySocket->SetRecvCallback (MakeCallback (
8     &MyClass::HandleRead, this));
```

---

*Listing C.8: Socket callbacks*

### PointToPoint NetDevice

---

```
1 NodeContainer n;
2 n.Create (2);
3 PointToPointHelper p2ph;
```

---

```
4 p2ph.SetDeviceAttribute ("DataRate", StringValue ("10Mbps"));
5 p2ph.SetChannelAttribute ("Delay", StringValue ("5ms"));
6 NetDeviceContainer devs = p2ph.Install (n);
```

---

*Listing C.9: PointToPointHelper*

## C.2 LTE Module

### LteHelper

---

```
1 // Create LteHelper and the nodes
2 Ptr<LteHelper> lteHelper = CreateObject<LteHelper> ();
3 NodeContainer enbNodes;
4 enbNodes.Create (1);
5 NodeContainer ueNodes;
6 ueNodes.Create (2);
7
8 // Set the mobility model
9 MobilityHelper mobility;
10 mobility.SetMobilityModel ("ns3::ConstantPositionMobilityModel");
11 mobility.Install (enbNodes);
12 mobility.SetMobilityModel ("ns3::ConstantPositionMobilityModel");
13 mobility.Install (ueNodes);
14
15 // Install NetDevices to the nodes
16 NetDeviceContainer enbDevs;
17 enbDevs = lteHelper->InstallEnbDevice (enbNodes);
18 NetDeviceContainer ueDevs;
19 ueDevs = lteHelper->InstallUeDevice (ueNodes);
20
21 // Attach UEs to the eNodeB
22 lteHelper->Attach (ueDevs, enbDevs.Get (0));
```

---

*Listing C.10: LteHelper usage*

### Network Attachment

---

```
1 lteHelper->Attach (ueDevs); // attach one or more UEs to a strongest
   cell
2 lteHelper->Attach (ueDevs, enbDev); // attach one or more UEs to a
```

---

```
single eNodeB
```

---

*Listing C.11: UE Automatic Attachment***EpcHelper**


---

```
1  Ptr<LteHelper> lteHelper = CreateObject<LteHelper> ();
2  Ptr<PointToPointEpcHelper> epcHelper = CreateObject<
    PointToPointEpcHelper> ();
3  lteHelper->SetEpcHelper (epcHelper);
4
5  // To access PGW or SGW
6  Ptr<Node> pgw = epcHelper->GetPgwNode ();
7  Ptr<Node> sgw = epcHelper->GetSgwNode ();
```

---

*Listing C.12: Enable Evolved Packet Core***MAC**


---

```
1  Ptr<LteHelper> lteHelper = CreateObject<LteHelper> ();
2  lteHelper->SetSchedulerType ("ns3::FdMtFfMacScheduler");    // FD-MT
    scheduler
3  lteHelper->SetSchedulerType ("ns3::TdMtFfMacScheduler");    // TD-MT
    scheduler
4  lteHelper->SetSchedulerType ("ns3::TtaFfMacScheduler");      // TTA
    scheduler
5  lteHelper->SetSchedulerType ("ns3::FdBetFfMacScheduler");    // FD-BET
    scheduler
6  lteHelper->SetSchedulerType ("ns3::TdBetFfMacScheduler");    // TD-BET
    scheduler
7  lteHelper->SetSchedulerType ("ns3::FdTbfqFfMacScheduler");  // FD-TBFQ
    scheduler
8  lteHelper->SetSchedulerType ("ns3::TdTbfqFfMacScheduler");  // TD-TBFQ
    scheduler
9  lteHelper->SetSchedulerType ("ns3::PssFfMacScheduler");      //PSS
    schedulerUIntegerValue(yourvalue));
```

---

*Listing C.13: MAC Scheduler***AMC & CQI**


---

```
1  // Piro
2  Config::SetDefault ("ns3::LteAmc::AmcModel", EnumValue (LteAmc::
    PiroEW2010));
3  // Physical error model
4  Config::SetDefault ("ns3::LteAmc::AmcModel", EnumValue (LteAmc::
    MiErrorModel));
```

---

---

*Listing C.14: AMC Model***Building**

---

```
1  MobilityHelper mobility;
2  mobility.SetMobilityModel ("ns3::ConstantPositionMobilityModel");
3
4  Ptr<Building> b = CreateObject <Building> ();
5  // Box (xmin, xmax, ymin, ymax, zmin, zmax)
6  b->SetBoundaries (Box (0.0, 10.0, 0.0, 20.0, 0.0, 20.0));
7  b->SetBuildingType (Building::Residential);
8  b->SetExtWallsType (Building::ConcreteWithWindows);
9  b->SetNFloors (3);
10 b->SetNRoomsX (3);
11 b->SetNRoomsY (2);
12
13 mobility.Install (ueNodes);
14 mobility.Install (enbNodes);
15 BuildingsHelper::Install (ueNodes);
16 BuildingsHelper::Install (enbNodes);
```

---

*Listing C.15: Mobility Model*

---

```
1  Ptr<HybridBuildingsPropagationLossModel> propagationLossModel =
    CreateObject<HybridBuildingsPropagationLossModel> ();
2  lteHelper->SetAttribute ("PathlossModel", StringValue ("ns3::
    HybridBuildingsPropagationLossModel"));
3  lteHelper->SetPathlossModelAttribute ("ShadowSigmaExtWalls",
    DoubleValue (1));
4  lteHelper->SetPathlossModelAttribute ("ShadowSigmaOutdoor",
    DoubleValue (0));
5  lteHelper->SetPathlossModelAttribute ("ShadowSigmaIndoor",
    DoubleValue (0));
```

---

*Listing C.16: Pathloss Model***AntennaModel & MIMO**

---

```
1  lteHelper->SetEnbAntennaModelType ("ns3::CosineAntennaModel");
2  lteHelper->SetEnbAntennaModelAttribute ("Orientation",
    DoubleValue (0.0));
```



```
3  lteHelper->SetEnbAntennaModelAttribute ("Beamwidth",
    DoubleValue (70));
4  // MaxGain in dBs
5  lteHelper->SetEnbAntennaModelAttribute ("MaxGain",
    DoubleValue (0.0));
6  // Set the MIMO transmission mode
7  Config::SetDefault ("ns3::LteEnbRrc::DefaultTransmissionMode",
    UIntegerValue (2)); // MIMO Spatial Multiplexity (2
    layers)
```

---

*Listing C.17: Antenna & MIMO Model*

### Radio Environment Maps

---

```
1  Ptr<RadioEnvironmentMapHelper> remHelper = CreateObject<
    RadioEnvironmentMapHelper> ();
2  remHelper->SetAttribute ("Channel", PointerValue (lteHelper->
    GetDownlinkSpectrumChannel ()));
3  remHelper->SetAttribute ("OutputFile", StringValue ("rem.out"));
4  remHelper->SetAttribute ("XMin", DoubleValue (-400.0));
5  remHelper->SetAttribute ("XMax", DoubleValue (400.0));
6  remHelper->SetAttribute ("XRes", UIntegerValue (100));
7  remHelper->SetAttribute ("YMin", DoubleValue (-300.0));
8  remHelper->SetAttribute ("YMax", DoubleValue (300.0));
9  remHelper->SetAttribute ("YRes", UIntegerValue (75));
10 remHelper->SetAttribute ("Z", DoubleValue (0.0));
11 remHelper->SetAttribute ("UseDataChannel", BooleanValue (true));
12 remHelper->SetAttribute ("RbId", IntegerValue (10));
13 remHelper->Install ();
```

---

*Listing C.18: Radio Environment Maps helper*

### Parameter Configuration

At the beginning of the main function, include:

---

```
1  Config::SetDefault ("ns3::ConfigStore::Filename", StringValue ("sim-
    input.txt"));
2  Config::SetDefault ("ns3::ConfigStore::Mode", StringValue ("Load"));
3  CommandLine cmd (__FILE__);
4  cmd.Parse (argc, argv);
5  ConfigStore inputConfig;
6  inputConfig.ConfigureDefaults ();
```

```
7  cmd.Parse (argc, argv);
```

---

*Listing C.19: Configuration parameters*

Example input file

---

```
1  default ns3::LteHelper::Scheduler "ns3::PffMacScheduler"
2  default ns3::LteHelper::PathlossModel "ns3::
    FriisSpectrumPropagationLossModel"
3  default ns3::LteEnbNetDevice::DlBandwidth "25"
4  default ns3::LteEnbNetDevice::DlEarfcn "100"
5  default ns3::LteEnbNetDevice::UlEarfcn "18100"
6  default ns3::LteUePhy::TxPower "10"
7  default ns3::LteEnbPhy::TxPower "30"
8  default ns3::LteEnbRrc::SrsPeriodicity "40"
9  default ns3::TcpSocket::SndBufSize "524280"
10 default ns3::TcpSocket::RcvBufSize "524280"
11 global RngSeed "24"
12 global simTime "10.0"
13 global nRB "100"
```

---

*Listing C.20: Configuration parameters*