

Spring Bean Scope

5 types of bean scopes supported:

1. Singleton (*default) – Return a single bean instance per Spring IoC container
2. prototype – Return a new bean instance each time when requested
3. request – Return a single bean instance per HTTP request. *
4. session – Return a single bean instance per HTTP session. *
5. globalSession – Return a single bean instance per global HTTP session. *

In most cases, you may only deal with the Spring's core scope – singleton and prototype, and the default scope is singleton.

*P.S * means only valid in the context of a web-aware Spring ApplicationContext*

```
<beans xmlns="http://www.springframework.org/schema/beans"
       xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
       xsi:schemaLocation="http://www.springframework.org/schema/beans
http://www.springframework.org/schema/beans/spring-beans-2.5.xsd">

    <bean id="customerService" class="com.mkyong.customer.services.CustomerService"
          scope="prototype"/>

</beans>
```

```
@Service
@Scope("prototype")
public class CustomerService
{
    String message;

    public String getMessage() {
        return message;
    }

    public void setMessage(String message) {
        this.message = message;
    }
}
```

```
<beans xmlns="http://www.springframework.org/schema/beans"
       xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
       xmlns:context="http://www.springframework.org/schema/context"
       xsi:schemaLocation="http://www.springframework.org/schema/beans
http://www.springframework.org/schema/beans/spring-beans-2.5.xsd
http://www.springframework.org/schema/context
http://www.springframework.org/schema/context/spring-context-2.5.xsd">

    <context:component-scan base-package="com.mkyong.customer" />

</beans>
```