

Setting Oracle Datasource in JBoss AS 7

Submitted by [srikanth.s.nair](#) on Thu, 10/20/2011 - 04:06.

Tags:

- [Application Servers](#)
- [Current stuff](#)

Here are step by step directions on how to configure JBoss AS 7 to communicate with Oracle XE.

1. Create directory for the oracle driver deployment

```
$ cd $JBOSS_HOME/modules
$ mkdir -p com/oracle/odbc6/main
$ vi module.xml
```

Add the following snippet to the newly created module.xml file

```
<module xmlns="urn:jboss:module:1.0" name="com.oracle.odbc6">
  <resources>
    <resource-root path="odbc6.jar"/>
  </resources>
  <dependencies>
    <module name="javax.api"/>
  </dependencies>
</module>
```

Copy the odbc6.jar to \$JBOSS_HOME/modules/com/oracle/odbc6/main [make sure your jar META-INF folder is having a Services dir with a file called java.sql.Driver]

Next, create the driver definition in the standalone configuration file

```
$ vi $JBOSS_HOME/standalone/configuration/standalone.xml
```

Look for

```
<subsystem xmlns="urn:jboss:domain:datasources:1.0">
```

this is where the datasource and driver configuration will go. Within this subsystem, look for the section and add the following:

```
<driver name="oracle" module="com.oracle.odbc6">
  <xa-datasource-class>
    oracle.jdbc.OracleDriver
  </xa-datasource-class>
</driver>
```

Then create the datasource configuration, also in the standalone configuration file. The following block will go just below the <datasources> element.

```
<datasource jndi-name="WorkCenterDS" pool-name="OracleDS" enabled="true"
jta="true" use-java-context="true" use-ccm="true">
  <connection-url>jdbc:oracle:thin:@localhost:1521:oradb1</connection-url>
  <driver>oracle</driver>
  <transaction-isolation>TRANSACTION_READ_COMMITTED</transaction-isolation>
  <pool>
    <prefill>true</prefill>
    <use-strict-min>false</use-strict-min>
    <flush-strategy>FailingConnectionOnly</flush-strategy>
  </pool>
  <security>
    <user-name>user1</user-name>
    <password>1234</password>
  </security>
</datasource>
```

Restart JBoss and look for the following lines in your log file to determine if the deployment succeeded.