


OTHER SURFACES 1.6







TECHNICAL REQUIREMENTS
1. Mark the drawing number on the workpiece. All dimensions are final dimensions.
2. Unless otherwise specified, chamfer hole edges and sharp edges C0.5.
3. Surfaces shall be smooth and free of scratches, dents, burrs and other visible defects.
4. Use 100-mesh fine abrasive for sandblasting.
5. All dimensions are in mm.
6. Dimensional tolerances for all screw holes and counterbores shall be +/-0.20mm, regardless of manufacturing process.

Machine unspecified chamfers according to the 3D model.

GENERAL TOLERANCES (UNLESS OTHERWISE SPECIFIED)			
X.	± 0.5	X.°	± 1°
.X	± 0.2	.X°	± 0.5°
.XX	± 0.05	.XX°	± 0.1°
.XXX	± 0.01	.XXX°	± 0.01°

For sheet metal, welding, casting, stamping and similar processes, unspecified linear and geometric tolerances shall conform to in-house standards.

MATERIAL	SUS304
FINISH	
QTY	

EQUIPMENT NAME	FA-060 Screw crimp to driver mount and pre-fix cable
EQUIPMENT NO.	
APPROVED	
CHECKED	
DESIGNED	
DRAWN	

BARCODE

DRAWING NO.

SCALE	SHEET	REV.
8:1		X1