



6-Spring Web MVC Annotations

Author: [Vincent Lau](#)

Note: This material is intended for educational purposes only. All rights reserved. Any unauthorized sharing or copying of this material, in any form, to any individual or party, for any use without prior permission, is strictly prohibited.

Learning Objectives

- List and describe the use of various Spring Web annotations.
- Apply various Spring Web annotations to implement RESTful controllers.
- Implement a centralized exception handler to handle exceptions.

Overview

- In this tutorial, we'll explore Spring Web annotations with a concrete example.
- In the example, we'll create a RESTful controller that allows users to retrieve and persist book data.

Domain Model

- This is what the *Book* class looks like. Note that we use the static *idCount* field to simulate the auto-incrementing book ID generator.
- `AtomicLong` is used for **thread-safety** purpose.

```
1 public class Book {
2     private static final AtomicLong idCount = new AtomicLong(0);
3     private final Long id;
4     private final String title;
5     private final String author;
6     private final Integer page;
7
8     public Book(String title, String author, Integer page) {
9         this.id = idCount.incrementAndGet();
10        this.title = title;
11        this.author = author;
12        this.page = page;
13    }
14
15    // getters and other methods
16 }
```

The Book Controller

- We define a bean called *BookController* with `@RestController` and `@RequestMapping`.

@RestController

- Recall the `@RestController` annotation combines `@Controller` and `@ResponseBody`.

```
1 @RestController
2 public class BookController {
3     ...
4 }
```

@RequestMapping

- Here we are applying `@RequestMapping` on a class level. It defines the **default settings for all handler methods** in a `@Controller` class.

- The only exception is the URL, which Spring **won't override** with method-level settings, but **appends the two path parts**.

```
1 @RestController
2 @RequestMapping("/books")
3 public class BookController {
4
5     // http://localhost:8080/books/{bookId}
6     @GetMapping("/{bookId}")
7     public Book getBookById(...) {
8         ...
9     }
10
11 }
```

@GetMapping

- Note that we're using `@GetMapping`, which is a shortcut for `@RequestMapping`. The equivalent is:

```
1 @RequestMapping(value = "/{bookId}", method = RequestMethod.GET)
2 public Book getBookById(...) {
3     ...
4 }
```

Mock Data

- We've predefined some mock data in the *BookController* for retrieval purpose.
- Note that we're using `ConcurrentHashMap` to store the *Book* objects for thread-safety purpose because an application can receive multiple requests simultaneously, which will spawn multiple threads to retrieve or persist data at the same time.
- The *BookController* is also a Spring bean. With the `@PostConstruct` annotation, the *BookController* will initialize and populate the `ConcurrentHashMap` with mock data right after the bean has been created.

```
1 @RestController
2 @RequestMapping("/books")
3 public class BookController {
```

```

4     private final Map<Long, Book> bookmap = new ConcurrentHashMap<>();
5
6     @PostConstruct
7     private void init() {
8         Book b1 = new Book("Spring in Action", "Craig Walls", 521);
9         Book b2 = new Book("Spring Boot in Action", "Craig Walls", 266);
10        Book b3 = new Book("Thinking in Java", "Bruce Eckel", 1079);
11        Book b4 = new Book("On Java 8", "Bruce Eckel", 1778);
12        Book b5 = new Book("Effective Java", "Joshua Bloch", 413);
13
14        bookmap.put(b1.getId(), b1);
15        bookmap.put(b2.getId(), b2);
16        bookmap.put(b3.getId(), b3);
17        bookmap.put(b4.getId(), b4);
18        bookmap.put(b5.getId(), b5);
19    }
20
21        ...
22 }

```

The GET Endpoints

- In this example, we'll create two GET endpoints:
 - Finding books by keyword
 - Finding books by book ID
- Although it is possible to combine the two endpoints into one, we've separated them for clarity purpose.

Find Books by Keyword

- This endpoint accepts an optional *keyword* parameter.
- When the *keyword* parameter is not provided, we will return all the available books in the repository.
- When it is provided, we will compare the keyword against the *title* and *author name* of each book, and return the matching results.

```

1 // http://localhost:8080/books?q=Java
2 @GetMapping
3 public List<Book> findBooks(@RequestParam(name = "q", required = false) String
  keyword) {

```

```

4     if (Strings.isBlank(keyword)) {
5         return new ArrayList<>();
6     }
7
8     final Predicate<Book> keywordMatcher = (book) ->
9         book.getTitle().toLowerCase().contains(keyword.toLowerCase())
10        || book.getAuthor().toLowerCase().contains(keyword.toLowerCase());
11
12    return bookmap.values().stream()
13        .filter(keywordMatcher)
14        .collect(Collectors.toList());
15 }

```

@RequestParam

- We use `@RequestParam` to access HTTP request parameters.
- The parameter which is marked with this annotation will be injected value coming from the request.
- The equivalent of this is:

```

1 @GetMapping
2 public List<Book> findBooks(HttpServletRequest request) {
3     String keyword = request.getParameter("q");
4     ...
5 }

```

GET localhost:8080/books?q=java

Params ● Authorization Headers (7) Body Pre-request Script Tests Settings

Body Cookies Headers (5) Test Results

Pretty Raw Preview Visualize JSON ▾

```
1 [
2   {
3     "id": 3,
4     "title": "Thinking in Java",
5     "author": "Bruce Eckel",
6     "page": 1079
7   },
8   {
9     "id": 4,
10    "title": "On Java 8",
11    "author": "Bruce Eckel",
12    "page": 1778
13  },
14  {
15    "id": 5,
16    "title": "Effective Java",
17    "author": "Joshua Bloch",
18    "page": 413
19  }
20 ]
```

Find Books by ID

- Here we use `@PathVariable` to extract the *bookId* from the URL so that we can use it to retrieve the corresponding book.

```
1 // http://localhost:8080/books/{bookId} -> e.g. http://localhost:8080/books/1
2 @GetMapping("/{bookId}")
3 public Book getBookById(@PathVariable(name = "bookId") Long bookId) {
4     return bookRepository.get(bookId);
5 }
```


@PathVariable

- The `@PathVariable` is used to map a URL path value to a parameter of the handling method.
- Moreover, we can mark a path variable optional by setting the argument *required* to false:

```
1 @GetMapping("/{bookId}")
2 public Book getBookById(@PathVariable(name = "bookId", required = false) Long
   bookId) {
3     ...
4 }
```

@RequestParam vs @PathVariable

- Even though both are used to extract data from a URL,
 - `@RequestParam` is used to retrieve *query parameters* (i.e. anything after `?` in the URL)
 - `@PathVariable` is used to retrieve *values from the URL* itself



The POST Endpoint

- Let's add a POST endpoint for adding new books.

```
1 /*
2 http://localhost:8080/books
3
4 {
```

```

5     "title": "Sample Book",
6     "author": "Sample Author",
7     "page": 500
8 }
9
10 */
11 @PostMapping
12 public ResponseEntity<Void> addBook(@RequestBody Book book) {
13     bookRepository.put(book.getId(), book);
14     return ResponseEntity.ok().build();
15 }

```

@PostMapping

- Note that we apply the `@PostMapping` annotation to map HTTP POST requests to the corresponding handling method.
- Specifically, `@PostMapping` is a shortcut for `@RequestMapping(method = RequestMethod.POST)`.

@RequestBody

- The `@RequestBody` annotation maps the body of the HTTP request to an object.
- The deserialization is automatic and depends on the content type of the request


The screenshot shows a REST client interface with the following details:

- Method:** POST
- URL:** localhost:8080/books
- Body Type:** raw (selected)
- Body Content:**

```

1 {
2     "title": "Book #6",
3     "author": "Author #6",
4     "page": 600
5 }

```

Exception Handling

- Requests sent to an application will not always succeed. An application should be able to handle exceptions when they occur.
- One of the scenarios to throw an exception is when the requesting *book ID* does not exist in the repository.
- For this, we define a custom *ResourceNotFoundException* class:

```
1 public class ResourceNotFoundException extends Exception { //check exception
2     public ResourceNotFoundException(String message) {
3         super(message);
4     }
5 }
```

- The GET endpoint for finding books by ID should be updated to throw an exception in case of non-existent book ID:

```
1 @GetMapping("/{bookId}")
2 public Book getBookById(@PathVariable(name = "bookId") Long bookId)
3 throws ResourceNotFoundException {
4     if (!bookRepository.containsKey(bookId)) {
5         throw new ResourceNotFoundException(
6             String.format("Book [%s] not found", bookId));
7     }
8 }
```

```

7     }
8     return bookRepository.get(bookId);
9 }

```

- We should define a global exception handler that handles various types of exceptions that will be potentially thrown in the application.

@ControllerAdvice

- The `@ControllerAdvice` annotation is used to indicate a class which is responsible for handling exceptions thrown when processing client requests.
- `@ControllerAdvice` mostly applies to the MVC architecture pattern. For RESTful services, `@RestControllerAdvice` is a better idea.

@RestControllerAdvice

- Although `@RestControllerAdvice` has similar responsibility as `@ControllerAdvice`, the returning result will be serialized to JSON or XML.
- In fact, `@RestControllerAdvice` is a combination of `@ControllerAdvice` and `@ResponseBody`.

@ExceptionHandler

- In the global exception handler, we can specify a method to handle a particular set of exceptions.
- An exception handler can contain several of these methods. We apply `@ExceptionHandler` to the handling methods.
- Spring calls these exception handling methods when any of the specified exceptions is thrown. The caught exception can be passed to the method as an argument:

```


1  @RestControllerAdvice
2  public class GlobalExceptionHandler {
3
4      @ResponseStatus(HttpStatus.NOT_FOUND)
5      @ExceptionHandler(ResourceNotFoundException.class)
6      public ErrorResult handleException(ResourceNotFoundException ex) {
7          return new ErrorResult("[GlobalExceptionHandler] " + ex.getMessage());
8      }
9
10 }
11
12 public class ErrorResult {

```

```

13     private final String message;
14
15     public ErrorResponse(String message) {
16         this.message = message;
17     }
18
19     public String getMessage() {
20         return message;
21     }
22 }

```



@ResponseStatus

- We can specify the desired HTTP status of the response if we annotate a request handler method with this annotation.
- We can declare the status code with the *code* argument, or its alias, the *value* argument.
- Also, we can provide a reason using the *reason* argument.

```

1 @ResponseStatus(code = HttpStatus.NOT_FOUND, reason = "Book Not Found")
2 ...

```

Other @RequestMapping Shortcuts

- There are a few more shortcuts for `@RequestMapping` which have not been covered here. To understand more, read [this](#).

- `@PutMapping` (Make sure you know the difference between `PutMapping` and `PostMapping`)
- `@DeleteMapping`
- `@PatchMapping`

Questions

- What are the different ways to extract data from a request URL?
- What is the difference between `@Controller` and `@RestController`?
- What is the difference between `@ControllerAdvice` and `@RestControllerAdvice`?
- How do we implement an exception handler in Spring Web MVC?