



# 32-Java 8: Optional

Author: [Vincent Lau](#)

*Note: This material is intended for educational purposes only. All rights reserved. Any unauthorized sharing or copying of this material, in any form, to any individual or party, for any use without prior permission, is strictly prohibited.*

## Learning Objectives

---

- | Identify issues with *null* as a return value
- | Write code that uses *Optional* and its common methods
- | Understand when NOT to use *Optionals*

## Overview

---

### What is *Optionals*?

- Introduced in **Java 8**. Provides a type-level solution for representing optional values instead of using *null* references

- Similar to checking whether a collection is empty, *Optional* allows us to check whether a single object is empty.

## Why *Optionals*?

- *NullPointerException* is the most common type of exceptions thrown in Java code.
- *null* can be assigned to any reference variables.
- Methods cannot communicate that they might return *null* except in documentation.
- Before Java 8 (The world without *Optional*), we had to either catch *NullPointerException* explicitly or perform null checks all over the place - both are unsustainable and error-prone.

## How does *Optional* work?

- Represents a value that *might* be present.
- Uses generics - `Optional<T>` can represent any object type.
- An *Optional* communicates that the method **might not return a value** - it **forces you to check and extract an object from *Optional* before performing operations on the object, thus avoiding *NullPointerException*.**

## Creating Optionals

- The *Optionals* class provides three *static factory methods* to construct an *Optional*:
  - *Optional.empty()*
  - *Optional.of()*
  - *Optional.ofNullable()*

```
1 // Approach #1
2 public static<T> Optional<T> empty() {
3     // returns an empty Optional instance which contains no value
4 }
5
6 // Approach #2
7 public static <T> Optional<T> of(T value) {
8     // returns an Optional which contains a non-null value
9     // throws NullPointerException if value is null
10 }
11
12 // Approach #3
13 public static <T> Optional<T> ofNullable(T value) {
```

```
14 // returns an Optional which contains the given value if non-null
15 // returns an empty optional if value is null
16 }
```

## Example

```
1 Optional<String> empty = Optional.empty();
2 System.out.println(empty.isPresent()); // prints false
3
4 String name = "John Doe";
5 Optional<String> opt = Optional.of(name);
6 System.out.println(opt.isPresent()); // prints true
7
8 String name = null;
9 Optional.of(name); // runtime exception, throws NullPointerException
10
11 String name = "John Doe";
12 Optional<String> opt = Optional.ofNullable(name);
13 System.out.println(opt.isPresent()); // prints true
14
15 String name = null;
16 Optional<String> opt = Optional.ofNullable(name);
17 System.out.println(opt.isPresent()); // prints false
```

## *orElse()*, *orElseGet()*, *orElseThrow()* and *ifPresent()*

- The **Optionals** class also provides ways for us to define a *default* value, action or exception to throw in case the **Optional** is empty by chaining methods.
  - **orElse()** - returns a default value if no value is present
  - **orElseGet()** - invokes a **Supplier** implementation to return a default value
  - **orElseThrow()** - invokes an *Exception Supplier* implementation to throw an exception
  - **ifPresent()** - invokes a *Consumer* implementation to perform some action on the given value, but without returning anything

## Example

```
1 // given a *non-null* value
2 Optional<String> opt1 = Optional.ofNullable("John");
```

```

3
4 String defaultWithOrElse1 = opt1.orElse("default value");
5 System.out.println(defaultWithOrElse1); // prints "John"
6
7 // orElseGet takes a Supplier implementation
8 String defaultWithOrElseGet1 = opt1.orElseGet(() -> "default value");
9 System.out.println(defaultWithOrElseGet1); // prints "John"
10
11 // orElseThrow takes an Exception Supplier implementation
12 String defaultWithOrElseThrow1 = opt1.orElseThrow(() -> new SomeException());
13 System.out.println(defaultWithOrElseThrow1); // prints "John"
14
15 // ifPresent() takes a Consumer implementation
16 opt1.ifPresent(value -> System.out.println(value)); // prints "John"
17
18 // given a null value
19 Optional<String> opt2 = Optional.ofNullable(null);
20
21 String defaultWithOrElse2 = opt2.orElse("default value");
22 System.out.println(defaultWithOrElse2); // prints "default value"
23
24 // *orElseGet* takes a *Supplier* implementation
25 String defaultWithOrElseGet2 = opt2.orElseGet(() -> "default value");
26 System.out.println(defaultWithOrElseGet2); // prints "default value"
27
28 // *orElseThrow* takes an *Exception Supplier* implementation
29 String defaultWithOrElseThrow2 = opt2.orElseThrow(() -> new SomeException());
30 System.out.println(defaultWithOrElseThrow2); // throws SomeException
31
32 // *ifPresent()* takes a *Consumer* implementation
33 opt2.ifPresent(value -> System.out.println(value)); // prints nothing

```

## When NOT to Use *Optionals*

- **Optionals** should **ONLY** be used as a return value of a method.
- It is **NOT** recommended to use *Optionals* as object fields especially when the object is *Serializable*, because **Optionals** is currently **NOT Serializable**.
  - Unexpected results may occur when you attempt to serialize *Optionals*.
  - Thus, it is also **NOT** recommended to use *Optionals* when **an object needs to be converted to JSON** or be **mapped to JPA entities**.

## Example 1

## Problem - Optional as a Type in POJO

```
1 @Entity
2 public class UserOptionalField implements Serializable {
3     @Id
4     private long userId;
5
6     private Optional<String> firstName;
7
8     // ... getters and setters
9 }
10
11 // main logic
12 UserOptionalField user = new UserOptionalField();
13 user.setUserId(11);
14 user.setFirstName(Optional.of("BaeIdung")); // its ok
15 entityManager.persist(user); // Error Occur
```

### Error Occur

```
1 Caused by: javax.persistence.PersistenceException: [PersistenceUnit:
  com.baeldung.optionalReturnType] Unable to build Hibernate SessionFactory
2     at
  org.hibernate.jpa.boot.internal.EntityManagerFactoryBuilderImpl.persistenceExce
  ption(EntityManagerFactoryBuilderImpl.java:1015)
3     at
  org.hibernate.jpa.boot.internal.EntityManagerFactoryBuilderImpl.build(EntityMan
  agerFactoryBuilderImpl.java:941)
4     at
  org.hibernate.jpa.HibernatePersistenceProvider.createEntityManagerFactory(Hiber
  natePersistenceProvider.java:56)
5     at
  javax.persistence.Persistence.createEntityManagerFactory(Persistence.java:79)
6     at
  javax.persistence.Persistence.createEntityManagerFactory(Persistence.java:54)
7     at com.baeldung.optionalReturnType.PersistOptionalTypeExample.<clinit>
  (PersistOptionalTypeExample.java:11)
8 Caused by: org.hibernate.MappingException: Could not determine type for:
  java.util.Optional, at table: UserOptionalField, for columns:
  [org.hibernate.mapping.Column(firstName)]
```

### Solution

- Keep the class field nullable, but we can provide a method to return the nullable value as Optional data type. It's a good practice.

```
1 @Column(nullable = true)
2 private String firstName;
3
4 public Optional<String> getFirstName() {
5     return Optional.ofNullable(firstName);
6 }
```

## Example 2

### Problem - Optional as method input parameter

- A method with an input parameter of Optional Type

```
1 public static List<Person> search(List<Person> people,
2                                   String name, Optional<Integer> age) {
3     // Null checks for people and name
4     return people.stream()
5         .filter(p -> p.getName().equals(name))
6         .filter(p -> p.getAge().get() >= age.orElse(0)) // Null Pointer
7         .collect(Collectors.toList());
8 }
```

- What if .... A developer calls the method by putting null as parameter. *NullPointerException will be thrown out during runtime.*

```
1 // this call will cause search() NullPointerException
2 someObject.search(people, "Peter", null);
```

## Solution

```
1 public static List<Person> search(List<Person> people,
2                                   String name, Integer age) {
3
4     final Integer ageFilter = age != null ? age : 0;
5 }
```

```

6     return people.stream()
7         .filter(p -> p.getName().equals(name))
8         .filter(p -> p.getAge().get() >= ageFilter)
9         .collect(Collectors.toList());
10 }

```

## Real Example - enum

```

1 public enum OrderStatus {
2     CONFIRMED(1, "Ordered"), //
3     PAID(2, "Paid"), //
4     READY_TO_SHIP(3, "Ready To Ship"), //
5     DELIVERED(4, "Delivered"), //
6     UNKNOWN(99, "Unknown"),
7     ;
8
9     private final int code;
10    private final String value;
11
12    private OrderStatus(int code, String value) {
13        this.code = code;
14        this.value = value;
15    }
16
17    public int getCode() {
18        return this.code;
19    }
20
21    public String getValue() {
22        return this.value;
23    }
24
25    /**
26     * @return the Enum representation for the given string.
27     * @throws IllegalArgumentException
28     *         if unknown string.
29     */
30    public OrderStatus fromCode(int code) {
31        return Arrays.stream(OrderStatus.values()) //
32            .filter(e -> e.getCode() == code) // return Stream<OrderStatus>
33            .findFirst() // Optional<OrderStatus>
34            // .orElse(OrderStatus.UNKNOWN);
35            .orElseThrow(() -> new IllegalArgumentException()); // runtime
exception

```



```
36    }  
37 }
```

## Questions

---

- Why should we use *Optionals*? What are the problems with returning *null* as a value?
- Under what circumstances should we NOT use *Optionals*? *Why*?
- Write a program that returns *Optionals* instead of *null* when values are not present.