



2-Spring Boot Configurations

Author: [Vincent Lau](#)

Note: This material is intended for educational purposes only. All rights reserved. Any unauthorized sharing or copying of this material, in any form, to any individual or party, for any use without prior permission, is strictly prohibited.

Learning Objectives

- | Write an application.properties or application.yml file to configure a Spring Boot application
- | Describe why the YAML format is preferred over the Properties format
- | Access external configurations using various approaches in Spring Boot

Overview

- A **common practice** in Spring Boot is using an **external configuration** to define our properties. This allows us to use the same application code in **different environments**(dev/ test/ uat/ pre-prod/ prod).
- We can use **properties** files, **YAML** files, **environment variables** and **command-line arguments**.

Properties Configuration

- Although not absolutely necessary, if the `application.properties` file exists, it will be **auto-loaded** for configuring the Spring Boot Application.
- By default, Spring Boot can access configurations set in an `application.properties` file, which uses a **key-value format**:

```
1 spring.datasource.url=jdbc:h2:dev
2 spring.datasource.username=SA
3 spring.datasource.password=password
```

- Each line is a single configuration, so we need to express hierarchical data by using the same prefixes for our keys. In this example, every key belongs to *spring.datasource*.
- Other configurations may include server, database and security settings, etc.
- For example, the Spring Boot embedded Tomcat server listens to **port 8080 by default**. It is possible to change the default port by adding a property in the `application.properties` file.

```
1 server.port: 8081
```

Placeholder in Properties

- Within our values, we can use placeholders with the `${}` syntax to refer to the contents of other keys, system properties, or environment variables:

```
1 app.name=MyApp
2 app.description=${app.name} is a Spring Boot application
```

Multiple Profiles

- Spring Boot supports configurations for **different environments** (e.g. **dev**, **test**, **prod**), and will take in an environment variable upon startup to pick up the configurations based on the specified environment.

```
1 // Approach #1
```

```

2 mvn spring-boot:run -Dspring-boot.run.profiles=dev
3
4 // Approach #2
5 java -jar -Dspring.profiles.active=dev <JAR file name>.jar

```

- We can define the configurations for each profile all in the same file:

```

1 logging.file.name=myapplication.log
2 bael.property=defaultValue
3 #---
4 spring.config.activate.on-profile=dev
5 spring.datasource.password=password
6 spring.datasource.url=jdbc:h2:dev
7 spring.datasource.username=SA
8 bael.property=devValue
9 #---
10 spring.config.activate.on-profile=prod
11 spring.datasource.password=password
12 spring.datasource.url=jdbc:h2:prod
13 spring.datasource.username=prodUser
14 bael.property=prodValue

```

- Note we use the `#---` notation to indicate where we want to split the document.
- Alternatively, we can **store multiple profiles across different files**. We achieve this by putting the name of the profile in the file name - for example, `application-dev.yml`
**or `application-dev.properties`.

YAML Configuration

YAML Format

- As well as Java properties files, we can also use YAML-based configuration files in our Spring Boot application. **YAML is a convenient format for specifying hierarchical configuration data.**

```

1 spring:
2   datasource:
3     password: password
4     url: jdbc:h2:dev

```

Multiple Profiles

- We can also store configurations for different profiles in the same YAML file, except with more clarity than the `application.properties` file:

```
1 logging:
2   file:
3     name: myapplication.log
4 ---
5 spring:
6   config:
7     activate:
8       on-profile: staging
9   datasource:
10    password: 'password'
11    url: jdbc:h2:staging
12    username: SA
13 bael:
14   property: stagingValue
```

- It is **highly recommended not to include** both `application.properties` and `application.yml` in your project at the same time. **Stick to one format only.**

Accessing Configurations

- There are three ways to access external configurations in Spring Boot:
 - By using the `@Value` annotation
 - By using the `Environment` object
 - By using the `@ConfigurationProperties` annotation

Using @Value

- Here the property `server.port` is injected via field injection into one of our objects:

```
1 @Value("${server.port}")
2 private String serverPort;
```

Using Environment Object

```

1 @Autowired
2 private Environment env;
3
4 public String getSomeKey() {
5     return env.getProperty("server.port");
6 }

```

Using @ConfigurationProperties

```

1 @Configuration // from class to bean
2 @ConfigurationProperties(prefix = "server") // from yml to class
3 public class ServerConfig {
4     String port;
5
6     String anotherField;
7
8     public String getPort() {
9         return port;
10    }
11
12    public void setPort(String port) {
13        this.port = port;
14    }
15 }

```

- application.yml

```

1 server:
2   port: 8081
3   anotherField: 'field value'

```

- We can also use the `@ConfigurationProperties` annotation to bind our properties to type-safe structured objects:
- Then we can access the configuration object just like any other beans:

```

1 @Autowired
2 private ServerConfig serverConfig;
3
4 public String getSomeKey(){

```

```
5     return serverConfig.getPort();  
6 }
```

Questions

- How do we access an environment variable from the application.yml file?
- Why do we prefer using YAML format to write configuration file?
- What are the different ways to access external configurations in Spring Boot?