



4-Conditionals

Author: [Vincent Lau](#)

Note: This material is intended for educational purposes only. All rights reserved. Any unauthorized sharing or copying of this material, in any form, to any individual or party, for any use without prior permission, is strictly prohibited.

Learning Objectives

Understand and use various types of conditionals, if-else & switch

Conditionals


- Conditionals are used for **choosing between two or more paths in a program**. There are two main types of conditionals in Java:
 - `if-else` statements
 - `switch` statements

If-else statements

In Java, the conditional statement `if-else` allows you to **execute different blocks** of code based on certain conditions.

Here's an introduction to the `if-else` statement with examples for beginners to learn:

- The condition is a boolean expression that determines whether the code inside the `if` block or the `else` block is executed.
- If the condition evaluates to `true`, the code inside the `if` block is executed.
- If the condition evaluates to `false`, the code inside the `else` block is executed.



```
1 if (condition) {  
2     // Code to be executed if the condition is true  
3 } else {  
4     // Code to be executed if the condition is false  
5 }
```

Now, let's look at some examples to illustrate the usage of the `if-else` statement:

Example 1: Checking if a number is positive or negative

```
1 int number = -5;  
2  
3 if (number > 0) {
```

```
4     System.out.println("The number is positive.");
5 } else {
6     System.out.println("The number is negative.");
7 }
8 // what is printed?
```

In this example, the condition `number > 0` is evaluated.

If it is `true`, the message "The number is positive." is printed. Otherwise, the message "The number is negative." is printed.

Example 2: Determining the maximum of two numbers

```
1 int a = 10;
2 int b = 7;
3 int max = 0;
4
5 if (a > b) {
6     max = a;
7 } else {
8     max = b;
9 }
10 System.out.println("The maximum number is: " + max);
11 // max = ?
```

In this example, the condition `a > b` is evaluated. If it is `true`, the value of `a` is assigned to `max`. Otherwise, the value of `b` is assigned to `max`.

Example 3: Checking if a number is even or odd

```
1 int number = 12;
2
3 if (number % 2 == 0) {
4     System.out.println("The number is even.");
5 } else {
6     System.out.println("The number is odd.");
7 }
8 // what is the printed?
```

In this example, the condition `number % 2 == 0` is evaluated.

If it is `true`, the message "The number is even." is printed. Otherwise, the message "The number is odd." is printed.

Example 4: String with if-else

```
1 String day = "Sunday";
2
3 if (day.equals("Sunday")) {
4     System.out.println("It's a weekend!");
5 } else {
6     System.out.println("It's a weekday.");
7 }
8 // what is printed?
```

In this example, the `if` condition checks if the `day` variable is equal to "Sunday".

If it is, the message "It's a weekend!" is printed. Otherwise, the `else` block is executed, and the message "It's a weekday." is printed.

Example 5: boolean with if-else

```
1 boolean isRaining = true;
2
3 if (isRaining) {
4     System.out.println("Remember to take an umbrella!");
5 } else {
6     System.out.println("No need for an umbrella.");
7 }
```

In this example, the `if` condition checks if the `isRaining` variable is `true`.

If it is, the message "Remember to take an umbrella!" is printed. Otherwise, the `else` block is executed, and the message "No need for an umbrella." is printed.


Example 5: char with if-else

```
1 char grade = 'B';
2
3 if (grade == 'A' || grade == 'B') {
4     System.out.println("Well done!");
5 } else {
6     System.out.println("Work harder for a better grade.");
7 }
```

```
7 }  
8
```

In this example, the `if` condition checks if the `grade` variable is 'A' or 'B'. If it is, the message "Well done!" is printed. Otherwise, the `else` block is executed, and the message "Work harder for a better grade." is printed.

Example 6: if, else if & else




```
1 int score = 85;  
2  
3 if (score >= 90) {  
4     System.out.println("Excellent!");  
5 } else if (score >= 80) {  
6     System.out.println("Good job!");  
7 } else if (score >= 70) {  
8     System.out.println("Keep it up!");  
9 } else {  
10    System.out.println("You can do better.");  
11 }
```

In this example, the `if`, `else if`, and `else` statements are used to determine the grade based on the `score` variable. The conditions are checked sequentially, and the appropriate message is printed based on the score range.

Challenge

```
1 int numericGrade = 78;
2 boolean isPassed = true;
3 char letterGrade = 'Z';
4
5 if (numericGrade <= 0) { // fulfill ?
6     throw new IllegalArgumentException("Grade must be larger than zero!");
7 }
8
9 if (numericGrade >= 50) { // fulfill ?
10     isPassed = true;
11 } else {
12     isPassed = false;
13 }
14
15 // What's next?
16 if (numericGrade >= 90) {
17     letterGrade = 'A';
18 } else if (numericGrade >= 80) {
19     letterGrade = 'B';
20 } else if (numericGrade >= 70) {
21     letterGrade = 'C';
22 } else if (numericGrade >= 60) {
23     letterGrade = 'D';
24 } else if (numericGrade >= 50) {
25     letterGrade = 'E';
26 } else {
27     letterGrade = 'F';
28 }
29
30 System.out.println("isPassed: " + isPassed); // isPassed = ?
31 System.out.println("numericGrade: " + numericGrade); // numericGrade = ?
32 System.out.println("letterGrade: " + letterGrade); // letterGrade = ?
```

Switch statements



In Java, the `switch` statement provides a way to perform different actions based on the value of a variable or expression. It offers a more concise alternative to multiple `if-else if-else` statements.

Here's an introduction to the `switch` statement with examples covering various scenarios:

The basic syntax of the `switch` statement is as follows:

```
1 switch (expression) {
2     case value1:
3         // Code to be executed if expression matches value1
4         break;
5     case value2:
6         // Code to be executed if expression matches value2
7         break;
8     // ...
9     default:
10        // Code to be executed if expression does not match any case
11        break;
12 }
```

Here's an explanation of the different parts of the `switch` statement:

- `expression` : A variable or expression whose value is being compared.
- `case value` : Specifies the possible values that the expression can match.
- `break` : Terminates the `switch` block and prevents the execution of subsequent cases. It is typically included after each case.
- `default` : Represents the code to be executed if the expression does not match any of the cases. It is optional and can appear at any position within the `switch` block.

Now, let's look at examples that cover various scenarios:

Example 1: Matching Integer Values

```
1 int dayOfWeek = 3;
2 String dayName;
3
4 switch (dayOfWeek) {
5     case 1:
6         dayName = "Sunday";
7         break;
8     case 2:
9         dayName = "Monday";
10        break;
11    case 3:
12        dayName = "Tuesday";
13        break;
14    case 4:
15        dayName = "Wednesday";
16        break;
17    case 5:
18        dayName = "Thursday";
19        break;
20    case 6:
21        dayName = "Friday";
22        break;
23    case 7:
24        dayName = "Saturday";
25        break;
26    default:
27        dayName = "Invalid day";
28        break;
29 }
30
31 System.out.println("Day of the week: " + dayName);
```


In this example, the `switch` statement matches the value of `dayOfWeek` and assigns the corresponding day name to the `dayName` variable. The output will be "Day of the week: Tuesday" since `dayOfWeek` is 3.

Example 2: Matching Characters

```
1 char grade = 'B';
2
3 switch (grade) {
4     case 'A':
5     case 'B':
6         System.out.println("Excellent!");
7         break;
8     case 'C':
9         System.out.println("Good job!");
10        break;
11    case 'D':
12        System.out.println("You passed.");
13        break;
14    case 'F':
15        System.out.println("You failed.");
16        break;
17    default:
18        System.out.println("Invalid grade.");
19        break;
20 }
21
```

In this example, the `switch` statement matches the value of `grade` and prints a corresponding message. Since `grade` is 'B', the output will be "Excellent!".

Example 3: Matching Strings

```
1 String fruit = "apple";
2
3 switch (fruit) {
4     case "apple":
5         System.out.println("It's an apple.");
6         break;
7     case "banana":
8         System.out.println("It's a banana.");
9         break;
10    case "orange":

```

```
11     System.out.println("It's an orange.");
12     break;
13     default:
14         System.out.println("Unknown fruit.");
15         break;
16 }
```

In this example, the `switch` statement matches the value of `fruit` and prints the corresponding message. Since `fruit` is "apple", the output will be "It's an apple".

These examples demonstrate the usage of the `switch` statement in Java. It allows you to simplify decision-making based on different values of a variable or expression, resulting in more concise and readable code.

Challenge 1

```
1  int numericGrade = 20;
2  char letterGrade = ' ';
3
4  switch (numericGrade) {
5      case 90: {
6          letterGrade = 'A';
7      }
8      case 80: {
9          letterGrade = 'B';
10     }
11     case 70: {
12         letterGrade = 'C';
13     }
14     case 60: {
15         letterGrade = 'D';
16     }
17     case 50: {
18         letterGrade = 'E';
19     }
20     default: {
21         letterGrade = 'F';
22     }
23 }
24
25 System.out.println("letterGrade: " + letterGrade); // letterGrade = ?
```

Challenge 2

```
1 int numericGrade = 78;
2
3 // "Case 78" fulfill? What's next?
4 switch (numericGrade) {
5     case 50: {
6         letterGrade = 'B';
7     }
8     case 78: {
9         letterGrade = 'A';
10    }
11    case 80: {
12        letterGrade = 'D';
13    }
14    default: {
15        letterGrade = 'C';
16    }
17 }
18
19 System.out.println("The letter grade is " + letterGrade); // letterGrade = ?
```

Questions

- Practice if, else if & else statement as much as possible.
- Did you try various logical operators & if-else statement together?
- Break is important & good practice when you are using a switch. Try to code switch statement yourself & make sure you get familiar with switch.