

Python Questions and Answers – List Comprehension

[« Prev](#)[Next »](#)

This set of Python Multiple Choice Questions & Answers (MCQs) focuses on “List Comprehension”.

1. What will be the output of the following Python code snippet?

→ print(i) is executed if the given char is not a vowel.


```
k = [print(i) for i in my_string if i not in "aeiou"]
```

- a) prints all the vowels in my_string
- b) prints all the consonants in my_string
- c) prints all characters of my_string that aren't vowels**
- d) prints only on executing print(k)

[View Answer](#)

Sanfoundry Certification Contest of the Month is Live. 100+ Subjects. Participate Now!

advertisement



2. What is the output of print(k) in the following Python code snippet?

```
k = [print(i) for i in my_string if i not in "aeiou"]
print(k)
```

- B ☒ a) all characters of my_string that aren't vowels
☒ b) a list of Nones *print() returns None.*
 c) list of Trues
 d) list of Falses

[View Answer](#)

Check this: [Programming MCQs](#) | [Information Technology Books](#)

3. What will be the output of the following Python code snippet?

advertisement

Q5.


```
x = [i**+1 for i in range(3)]; print(x);
```

- A ☒ a) [0, 1, 2]
 b) [1, 2, 5]
 c) error, **+ is not a valid operator
 d) error, ',' is not allowed

```
my_string = "hello world"
```

```
k = [(i.upper(), len(i)) for i in my_string]
print(k)
```

- iterating over each letter in the string.*
- B ☒ a) [('HELLO', 5), ('WORLD', 5)]
☒ b) [('H', 1), ('E', 1), ('L', 1), ('L', 1), ('O', 1), (' ', 1), ('W', 1), ('O', 1), ('R', 1), ('L', 1), ('D', 1)]
 c) [('HELLO WORLD', 11)]
 d) none of the mentioned



Q10.

10. Which of the following is the same as list(map(lambda x: x**-1, [1, 2, 3]))?

- a) `[x**-1 for x in [(1, 2, 3)]]`
 b) `[1/x for x in [(1, 2, 3)]]`
 c) `[1/x for x in (1, 2, 3)]`
 d) error

C

4. Which of the following is the correct expansion of list_1 = [expr(i) for i in list_0 if func(i)]?

a)

```
list_1 = []
for i in list_0:
    if func(i):
        list_1.append(i)
```

b)

```
for i in list_0:
    if func(i):
        list_1.append(expr(i))
```

C (c)

→ create an empty list.

```
list_1 = []
for i in list_0:
    if func(i):
        list_1.append(expr(i))
```


→ loop over the contents of the existing list
 Check if a condition is satisfied
 before performing operations
 and adding it to the new list.

d) none of the mentioned

View Answer

5. What will be the output of the following Python code snippet?

```
x = [i**+1 for i in range(3)]; print(x);
```



d) error, ';' is not allowed

View Answer

6. What will be the output of the following Python code snippet?

```
print([i.lower() for i in "HELLO"])
```

- A ☒ a) ['h', 'e', 'l', 'l', 'o']
 b) 'hello'
 c) ['hello']
 d) hello

↳ Iterating over each letter
in the string

View Answer

7. What will be the output of the following Python code snippet?

```
print([i+j for i in "abc" for j in "def"])
```

- ☒ a) ['da', 'ea', 'fa', 'db', 'eb', 'fb', 'dc', 'ec', 'fc']
 b) [['ad', 'bd', 'cd'], ['ae', 'be', 'ce'], ['af', 'bf', 'cf']]
 c) [['da', 'db', 'dc'], ['ea', 'eb', 'ec'], ['fa', 'fb', 'fc']]
 d) ['ad', 'ae', 'af', 'bd', 'be', 'bf', 'cd', 'ce', 'cf']

i: outer loop
j: inner loop

View Answer

8. What will be the output of the following Python code snippet?

```
print([[i+j for i in "abc"] for j in "def"])
```

- B ☒ a) ['da', 'ea', 'fa', 'db', 'eb', 'fb', 'dc', 'ec', 'fc']
 b) [['ad', 'bd', 'cd'], ['ae', 'be', 'ce'], ['af', 'bf', 'cf']]
 c) [['da', 'db', 'dc'], ['ea', 'eb', 'ec'], ['fa', 'fb', 'fc']]
 d) ['ad', 'ae', 'af', 'bd', 'be', 'bf', 'cd', 'ce', 'cf']

the inner list is
generated once for
each value of j.


View Answer

9. What will be the output of the following Python code snippet?

```
print([if i%2==0: i; else: i+1; for i in range(4)])
```

→ Syntax Error.

- C ☒ a) [0, 2, 2, 4]
 b) [1, 1, 3, 3]
 c) error
- i=0, 0 i=3 4
 i=1 2
 i=2 2



Python Questions and Answers – List Comprehension – 1

[« Prev](#)[Next »](#)

This set of Python Multiple Choice Questions & Answers (MCQs) focuses on “List Comprehension – 1”.

1. What will be the output of the following Python code?

0001 0010 0011 0100 0101

```
l=[1,2,3,4,5]
```

```
[x&1 for x in l]    → AND-ed with 1
```

a) [1, 1, 1, 1, 1]

☒ b) [1, 0, 1, 0, 1]


c) [1, 0, 0, 0, 0]

d) [0, 1, 0, 1, 0]

[View Answer](#)

Subscribe Now: [Python Newsletter](#) | [Important Subjects Newsletters](#)

advertisement



2. What will be the output of the following Python code?

```
l1=[1,2,3]
```

```
l2=[4,5,6]
```

```
[x*y for x in l1 for y in l2]
```

→ returns $x * y$.
(x in l1, y in l2)

a) [4, 8, 12, 5, 10, 15, 6, 12, 18]

b) [4, 10, 18]

c) [4, 5, 6, 8, 10, 12, 12, 15, 18] → 顺序: 1x4, 1x5, 1x6
2x4, 2x5, 2x6
3x4, 3x5, 3x6.

d) [18, 12, 6, 15, 10, 5, 12, 8, 4]

View Answer

Become [Top Ranker in Python Programming](#) Now!

3. Write the list comprehension to pick out only negative integers from a given list 'l'.

a) [x<0 in l]

b) [x for x<0 in l]

c) [x in l for x<0]

d) [x for x in l if x<0]

View Answer

advertisement

4. What will be the output of the following Python code?



a) Error

b) ['PUNE', 4, 'MUMBAI', 6, 'DELHI', 5]

c) [PUNE, 4, MUMBAI, 6, DELHI, 5]

d) [('PUNE', 4), ('MUMBAI', 6), ('DELHI', 5)]

① return each word in Upper Case.

→ ② + length of the word.

[View Answer](#) $s = ['pune', 'mumbai', 'delhi']$ advertisement $[w.upper(), len(w)]$ for w in s .

- if we need to generate 2 results, we need to put it in the form of tuple.

5. What will be the output of the following Python code?

l1=[2,4,6]

l2=[-2,-4,-6]

for i in zip(l1, l2):

print(i)

(2, -2)

(4, -4)

(6, -6)

a)

2, -2

4, -4

6, -6

c. b) [(2, -2), (4, -4), (6, -6)]

c)

(2, -2)

'\ ' '\ '



d) [-4, -16, -36]

[View Answer](#)

6. What will be the output of the following Python code?

```
l1=[10, 20, 30]
l2=[-10, -20, -30]
l3=[x+y for x, y in zip(l1, l2)] → returns x+y.
l3
```

- a) Error
b) 0
c) [-20, -60, -80]
D c) [0, 0, 0]

[View Answer](#)

7. Write a list comprehension for number and its cube for l=[1, 2, 3, 4, 5, 6, 7, 8, 9].

- A a) [x**3 for x in l]
b) [x^3 for x in l]
c) [x**3 in l]
d) [x^3 in l]

[View Answer](#)

8. What will be the output of the following Python code?

```
l=[[1, 2, 3], [4, 5, 6], [7, 8, 9]]
[[row[i] for row in l] for i in range(3)]
```

- a) Error
B b) [[1, 4, 7], [2, 5, 8], [3, 6, 9]]
c)

↓ index.
if number > index : return Error.

1 4 7
2 5 8
3 6 9

d)

(1 4 7)



[View Answer](#)

9. What will be the output of the following Python code?

```
import math
[str(round(math.pi)) for i in range(1, 6)]
```

*round(pi(3.14)) = 3,
done 5 times*

- a) ['3', '3', '3', '3', '3', '3']
 b) ['3.1', '3.14', '3.142', '3.1416', '3.14159', '3.141582']
 c) ['3', '3', '3', '3', '3']
 d) ['3.1', '3.14', '3.142', '3.1416', '3.14159']

[View Answer](#)

10. What will be the output of the following Python code?

```
l1=[1,2,3]
l2=[4,5,6]
l3=[7,8,9]
for x, y, z in zip(l1, l2, l3):
    print(x, y, z)
```

A a)

1 4 7
 2 5 8
 3 6 9

b)

(1 4 7)
 (2 5 8)
 (3 6 9)

- c) [(1, 4, 7), (2, 5, 8), (3, 6, 9)]
 d) Error

[View Answer](#)

Sanfoundry Global Education & Learning Series - Python

