REQUEST FOR PURCHASE

Project Number: #####

MATERIAL REQUEST NO.

RFP30292

DATE ORIGINATED

	·	04/25/13
PROJECT:		
SITE:	CISSY	
DAY NEEDED:		
DELIVER TO:	Address	
REQUESTED BY:		
PHONE:		
APPROVED BY:		
PHONE:		

OLIANITITY.	IZEAC "	1.5		
UANTITY	ITEM #	UNIT	ITEM DESCRIPTION	UNIT PRICE
17	1	FT	PIPE - 20", 0.500" WT, ERW/DSAW, BE, API 5L PSL-2, X60, BARE	
19	2	FT	PIPE - 16", 0.500" WT, ERW/DSAW, BE, API 5L PSL-2, X52, BARE	
17	3	FT	PIPE - 12", 0.375" WT, ERW/SMLS, BE, API 5L PSL-2, X52, BARE	
113	4	FT	PIPE - 12", 0.375" WT, ERW/SMLS, BE, API 5L PSL-2, F52, COATED	
29	7	FT	PIPE - 10", 0.365" WT, ERW/SMLS, BE, API 5L PSL-2, X52, BARE	
35	6	FT	PIPE - 8", 0.322" WT, ERW/SMLS, BE, API 5L PSL-2, X42, BARE	
6	5	FT	PIPE - 8", 0.322" WT, ERW/SMLS, BE, API 5L PSL-2, X42, COATED	
3	8	FT	PIPE - 6", 0.280" WT, ERW/SMLS, BE, API 5L PSL-2, GRB, BARED	
29	9	FT	PIPE - 6", 0.280" WT, ERW/SMLS, BE, API 5L PSL-2, GRB, COATED	
13	10	FT	PIPE - 4", 0.237" WT, ERW/SMLS, BE, API 5L PSL-2, GRB, BARE	
4	11	FT	PIPE - 2", 0.218" WT, ERW/SMLS, BE, API 5L PSL-1, GRB, BARE	
14	12	FT	PIPE - 1 1/2", 0.200" WT, SMLS, BE, ASTM A106, GRB, BARE	
1	13	FT	PIPE - 1", 0.179" WT, SMLS, BE, ASTM A106, GRB, BARE	
1	14	FT	PIPE - 3/4", 0.154" WT, SMLS, BE, ASTM A106, GRB, BARE	
1	15	FT	PIPE - 1/2", 0.147" WT, SMLS, BE, ASTM A106, GRB, BARE	
2	16	EA	CLOSURE, HORIZONTAL - 20.000" OD, ANSI 600, TWT (NOMWT) WT, (NOMGR) PIPE, YALE OR EQUIV.	
1	17	EA	CLOSURE, HORIZONTAL - 12.750" OD, ANSI 600, TWT (NOMWT) WT, (NOMGR) PIPE, YALE OR EQUIV.	
1	18	EA	CLOSURE, HORIZONTAL - 4.500" OD, ANSI 600, TWT (NOMWT) WT, (NOMGR) PIPE, YALE OR EQUIV.	
2	19	EA	CLOSURE, HORIZONTAL - 2.375" OD, ANSI 600, TWT {NOMWT} WT, {NOMGR} PIPE, YALE OR EQUIV.	
2	20	EA	WELDOLET - 2" ON 20", BW, MSS-SP-75, F60, BONNEY FORGE OR EQUAL, PER MSS SP-97, -20°F TO 250°F	
1	21	EA	WELDOLET - 2" ON 12", BW, MSS-SP-75, F52, BONNEY FORGE OR EQUAL, PER MSS SP-97, -20°F TO 250°F	
2	22	EA	WELDOLET - 1 1/2" ON 20", BW, MSS-SP-75, F60, BONNEY FORGE OR EQUAL, PER MSS SP-97, -20°F TO 250°F	
2	23	EA	WELDOLET - 1 1/2" ON 16", BW, MSS-SP-75, F52, BONNEY FORGE OR EQUAL, PER MSS SP-97, -20°F TO 250°F	
2	24	EA	THREDOLET - 24" - 14" x 1-1/2", CLASS 3000, FNPT ASTM A105, BONNEY FORGE OR EQUAL, PER MSS SP-97, -20°F TO 250°F	
4	25	EA	THREDOLET - 12" - 8" x 1-1/2", CLASS 3000, FNPT ASTM A105, BONNEY FORGE OR EQUAL, PER MSS SP-97, -20°F TO 250°F	
2	26	EA	SADDLE, WELD 6" ON 20", 5/8" THK, HDR EDGE TAPERED TO 0.280", W/VENT HOLE, MSS-SP-75, Y65, PER FLEETLINE	
			CATALOG SFI-105 & ASME B31.8 SADDLE, WELD 4" ON 12", 5/8" THK, HDR EDGE TAPERED TO 0.237", W/VENT HOLE, MSS-SP-75, Y52, PER FLEETLINE	
1	27	EA	CATALOG SFI-105 & ASME B31.8	
1	28	EA	SADDLE, WELD 4" ON 10", 5/8" THK, HDR EDGE TAPERED TO 0.237", W/VENT HOLE, MSS-SP-75, Y52, PER FLEETLINE CATALOG SFI-105 & ASME B31.8	
2	29	EA	SADDLE, WELD 2" ON 20", 5/8" THK, HDR EDGE TAPERED TO 0.218", W/VENT HOLE, MSS-SP-75, Y65, PER FLEETLINE CATALOG SFI-105 & ASME B31.8	
1	30	EA	TEE, STRAIGHT - 12", 0.375" WT, BW, MSS-SP-75, Y52, PER ASME B16.9	
1	31	EA	TEE, STRAIGHT - 10", 0.365" WT, BW, MSS-SP-75, Y52, PER ASME B16.9	
1	32	EA	TEE, REDUCING - 16", 0.500" WT x 12", 0.375" WT, BW, MSS-SP-75, Y52, PER ASME B16.9	
1	33	EA	TEE, REDUCING - 12", 0.375" WT x 6", 0.280" WT, BW, MSS-SP-75, Y52, PER ASME B16.9	
1	34	EA	TEE, REDUCING - 12", 0.375" WT x 4", 0.237" WT, BW, MSS-SP-75, Y52, PER ASME B16.9	
1	35	EA	TEE, REDUCING - 8", 0.322" WT x 6", 0.280" WT, BW, MSS-SP-75, Y42, PER ASME B16.9	
4	36	EA	FLANGE - 16", ANSI 600, RFWN, ASTM A694, F52, TWT 0.5" WT, X52 PIPE, PER MSS-SP-44	
2	37	EA	FLANGE - 12", ANSI 600, RFWN, ASTM A694, F52, TWT 0.375" WT, X52 PIPE, PER MSS-SP-44	
4	38	EA	FLANGE - 10", ANSI 600, RFWN, ASTM A694, F52, TWT 0.365" WT, X52 PIPE, PER MSS-SP-44	
1	39	EA	FLANGE - 8", ANSI 600, RFWN, ASTM A694, F42, TWT 0.322" WT, X42 PIPE, PER MSS-SP-44	
4	40	EA	FLANGE - 6", ANSI 600, RFWN, ASTM A105, GRB, TWT 0.28" WT, GRB PIPE, PER ASME B16.5	
3	41	EA	FLANGE - 4", ANSI 600, RFWN, ASTM A105, GRB, TWT 0.237" WT, GRB PIPE, PER ASME B16.5	
7	42	EA	FLANGE - 2", ANSI 600, RFWN, ASTM A105, GRB, TWT 0.218" WT, GRB PIPE, PER ASME B16.5	
6	43	EA	FLANGE - 2 , ANSI 600, RFWN, ASTM A105, GRB, TWT 0.218 WT, GRB PIPE, PER ASME B16.5	
3	43	EA	FLANGE, BLIND - 2", ANSI 600, RF, ASTM A105, GRB, PER ASME B16.5, CD&T FOR 1/2" NPT	
2		EA		
	45		ELL, 90 DEG - LR, 12", 0.375" WT, BW, MSS-SP-75, Y52, PER ASME B16.9	
2	46	EA	ELL, 90 DEG - LR, 10", 0.365" WT, BW, MSS-SP-75, Y52, PER ASME B16.9	
2	47	EA	ELL, 90 DEG - LR, 8", 0.322" WT, BW, MSS-SP-75, Y42, PER ASME B16.9	
4	48	EA	ELL, 90 DEG - LR, 6", 0.28" WT, BW, ASTM A234, WPB, PER ASME B16.9	
2	49	EA	ELL, 90 DEG - LR, 4", 0.237" WT, BW, ASTM A234, WPB, PER ASME B16.9	
3	50	EA	ELL, 90 DEG - LR, 2", 0.218" WT, BW, ASTM A234, WPB, PER ASME B16.9	
6	51	EA	ELL, 90 DEG - LR, 1 1/2", 0.200" WT, BW, ASTM A234, WPB, PER ASME B16.9	

				T
2	52	EA	ELL, 45 DEG - 3R, 10", 0.365" WT, BW, MSS-SP-75, Y52, PER ASME B16.9	
2	53	EA	REDUCER, CONC 20", 0.500" WT x 16", 0.375" WT, BW, MSS-SP-75, Y60, PER ASME B16.9	
1	54	EA	REDUCER, CONC 12", 0.375" WT x 10", 0.365" WT, BW, MSS-SP-75, Y52, PER ASME B16.9	
1	55	EA	REDUCER, CONC 12", 0.375" WT x 8", 0.322" WT, BW, MSS-SP-75, Y52, PER ASME B16.9	
1	56	EA	REDUCER, ECC 12", 0.375" WT x 10", 0.365" WT, BW, MSS-SP-75, Y52, PER ASME B16.9	
4	57	EA	GASKET, SPIRAL WOUND - 16", ANSI 600, RF, FLEXITALLIC, STYLE CGI OR EQUAL, 304 SS WINDING WITH GRAPHITE	
4	31	LA	FILLER, 304 SS OUTER & INNER RING, 1/8" THK, FOR MSS-SP-44 FLANGE	
2	58	EA	GASKET, SPIRAL WOUND - 12", ANSI 600, RF, FLEXITALLIC, STYLE CGI OR EQUAL, 304 SS WINDING WITH GRAPHITE FILLER, 304 SS OUTER & INNER RING, 1/8" THK, FOR MSS-SP-44 FLANGE	
4	59	EA	GASKET, SPIRAL WOUND - 10", ANSI 600, RF, FLEXITALLIC, STYLE CGI OR EQUAL, 304 SS WINDING WITH GRAPHITE FILLER, 304 SS OUTER & INNER RING, 1/8" THK, FOR MSS-SP-44 FLANGE	
1	60	EA	GASKET, SPIRAL WOUND - 8", ANSI 600, RF, FLEXITALLIC, STYLE CGI OR EQUAL, 304 SS WINDING WITH GRAPHITE FILLER, 304 SS OUTER & INNER RING, 1/8" THK, FOR MSS-SP-44 FLANGE	
4	61	EA	GASKET, SPIRAL WOUND - 6", ANSI 600, RF, FLEXITALLIC, STYLE CGI OR EQUAL, 304 SS WINDING WITH GRAPHITE FILLER, 304 SS OUTER & INNER RING, 1/8" THK, FOR ASME B16.5 FLANGE	
3	62	EA	GASKET, SPIRAL WOUND - 4", ANSI 600, RF, FLEXITALLIC, STYLE CGI OR EQUAL, 304 SS WINDING WITH GRAPHITE FILLER, 304 SS OUTER & INNER RING, 1/8" THK, FOR ASME B16.5 FLANGE	
10	63	EA	GASKET, SPIRAL WOUND - 2", ANSI 600, RF, FLEXITALLIC, STYLE CGI OR EQUAL, 304 SS WINDING WITH GRAPHITE FILLER, 304 SS OUTER & INNER RING, 1/8" THK, FOR ASME B16.5 FLANGE	
6	64	EA	GASKET, SPIRAL WOUND - 1 1/2", ANSI 600, RF, FLEXITALLIC, STYLE CGI OR EQUAL, 304 SS WINDING WITH GRAPHITE FILLER, 304 SS OUTER & INNER RING, 1/8" THK, FOR ASME B16.5 FLANGE	
2	65	EA	PLUG, HEXHEAD, 1", CLASS 3000, SE, MNPT, ASTM A105, PER ASME B16.11	
2	66	EA	PLUG. HEXHEAD. 3/4". CLASS 3000. SE. MNPT. ASTM A105. PER ASME B16.11	
3	67	EA	PLUG, HEXHEAD, 1/2", CLASS 3000, SE, MNPT, ASTM A105, PER ASME B16.11	
3	68	EA	VALVE, PLUG - 1 1/2", ANSI 600, RF, API 6D, ASTM A216 WCB, REGULAR PATTERN, FOR SWEET NATURAL GAS SERVICE, - 20°F TO 120°F, LEVER OPERATED C/W LOCKING DEVICE, CLEANED AND PAINTED W/ SHOP PRIMER	
1	69	EA	VALVE, BALL - 16", ANSI 600, RF, API 6D, FULL PORT, DOUBLE BLOCK & BLEED, FOR SWEET NATURAL GAS SERVICE, -20°F TO 120°F, LESS LEVER FOR MOUNTING VALVE OPERATOR, CLEANED AND PAINTED W/ SHOP PRIMER	
1	70	EA	VALVE, BALL - 12", ANSI 600, RF, API 6D, FULL PORT, DOUBLE BLOCK & BLEED, FOR SWEET NATURAL GAS SERVICE, -20°F TO 120°F, LESS LEVER FOR MOUNTING VALVE OPERATOR, CLEANED AND PAINTED W/ SHOP PRIMER	
2	71	EA	VALVE, BALL - 10", ANSI 600, RF, API 6D, FULL PORT, DOUBLE BLOCK & BLEED, FOR SWEET NATURAL GAS SERVICE, -20°F TO 120°F, LESS LEVER FOR MOUNTING VALVE OPERATOR, CLEANED AND PAINTED W/ SHOP PRIMER	
2	72	EA	VALVE, BALL - 6", ANSI 600, RF, API 6D, FULL PORT, DOUBLE BLOCK & BLEED, FOR SWEET NATURAL GAS SERVICE, -20°F TO 120°F, LEVER OPERATED, C/W LOCKING DEVICE, CLEANED AND PAINTED W/ SHOP PRIMER	
1	73	EA	VALVE, BALL - 4", ANSI 600, RF x WE, FULL PATTERN, API 6D, FULL PORT, LEVER OPERATED, C/W LOCKING DEVICE, TWT 4" OD, 0.237" WT, GRB PIPE	
1	74	EA	VALVE, BALL - 4", ANSI 600, RF, API 6D, FULL PORT, DOUBLE BLOCK & BLEED, FOR SWEET NATURAL GAS SERVICE, -20°F TO 120°F, LEVER OPERATED, C/W LOCKING DEVICE, CLEANED AND PAINTED W/ SHOP PRIMER	
5	75	EA	VALVE, BALL - 2", ANSI 600, RF, API 6D, FULL PORT, DOUBLE BLOCK & BLEED, FOR SWEET NATURAL GAS SERVICE, -20°F TO 120°F, LEVER OPERATED, C/W LOCKING DEVICE, CLEANED AND PAINTED W/ SHOP PRIMER	
2	76	EA	VALVE, BALL - 1", CLASS 3000, W.O.G., THRD, FNPT, C.S, SS TRIM, FULL PORT, NATURAL GAS SERVICE, C/W LEVER OPERATOR & LOCKING DEVICE	
2	77	EA	VALVE, BALL - 3/4", CLASS 3000, W.O.G., THRD, FNPT, C.S, SS TRIM, FULL PORT, NATURAL GAS SERVICE, C/W LEVER OPERATOR & LOCKING DEVICE	
3	78	EA	VALVE, BALL - 1/2", CLASS 3000, W.O.G., THRD, FNPT, C.S, SS TRIM, FULL PORT, NATURAL GAS SERVICE, C/W LEVER OPERATOR & LOCKING DEVICE	
	<u> </u>			·
1				