

Client Name	Energy Transfer
Project Name	This Meter Station
Revision	2013-06-17 - 09:38:56 AM
HMM Contact	Olin Valby - 281-598-9539

LEGEND

Changes made to this revision

Current Quantities Per Site										Material Requested					
Mark No.	Unit	Description	Uniontown	Site A	Parker	Fab AB	Consumables	Total Qty.	Quantity Left to Acquire	Total Inventory to Date	RQST12	BRDLAND	TST1234	RFRP1234	123258
											6/6/2013	6/6/2013	5/8/2013	5/1/2013	4/22/2013
1	FT	PIPE - 30", 0.500" WT, ERW/DSAW, BE, API 5L PSL-2, X65, BARE		2	5		0	7	0	7			2		
3	FT	PIPE - 24", 0.500" WT, ERW/DSAW, BE, API 5L PSL-2, X60, BARE	17				0	17	0	17			17		
4	FT	PIPE - 20", 0.500" WT, ERW/DSAW, BE, API 5L PSL-2, X60, BARE			18		0	18	1	17		17			
5	FT	PIPE - 16", 0.500" WT, ERW/DSAW, BE, API 5L PSL-2, X52, BARE	19	21	19		0	59	0	59		19	19	21	
7	FT	PIPE - 12", 0.375" WT, ERW/SMLS, BE, API 5L PSL-2, X52, BARE	15	25	17		2	59	0	59		17	17	25	
8	FT	PIPE - 12", 0.375" WT, ERW/SMLS, BE, API 5L PSL-2, X52, COATED	113		113		0	226	0	226		111	115		
9	FT	PIPE - 10", 0.365" WT, ERW/SMLS, BE, API 5L PSL-2, X52, BARE	29		29		0	58	58	0					
11	FT	PIPE - 10", 0.322" WT, ERW/SMLS, BE, API 5L PSL-2, X42, COATED				80	0	80	12	68					60
12	FT	PIPE - 8", 0.322" WT, ERW/SMLS, BE, API 5L PSL-2, X42, BARE	1	5	1		0	7	(37)	44				5	39
13	FT	PIPE - 8", 0.322" WT, ERW/SMLS, BE, API 5L PSL-2, X42, COATED	6		6		0	12	0	12	6	6			
14	FT	PIPE - 6", 0.280" WT, ERW/SMLS, BE, API 5L PSL-2, GRB, BARE	3		3		0	6	0	6		3	3		
15	FT	PIPE - 6", 0.280" WT, ERW/SMLS, BE, API 5L PSL-2, GRB, COATED	29		29		0	58	0	58		29	29		
16	FT	PIPE - 4", 0.237" WT, ERW/SMLS, BE, API 5L PSL-2, GRB, BARE	13	84	13		0	110	(10)	120		13	13	84	
17	FT	PIPE - 4", 0.237" WT, ERW/SMLS, BE, API 5L PSL-2, GRB, COATED		17			0	17	(17)	34				17	17
18	FT	PIPE - 2", 0.218" WT, ERW/SMLS, BE, API 5L PSL-1, GRB, BARE	4	51	4		0	59	0	59		4	4	51	
19	FT	PIPE - 1 1/2", 0.200" WT, SMLS, BE, ASTM A106, GRB, BARE	14		14		0	28	0	28		14	14		
20	FT	PIPE - 1", 0.179" WT, SMLS, BE, ASTM A106, GRB, BARE	1		1		0	2	0	2		1	1		
21	FT	PIPE - 3/4", 0.154" WT, SMLS, BE, ASTM A106, GRB, BARE	1		1		0	2	0	2		1	1		
22	FT	PIPE - 1/2", 0.147" WT, SMLS, BE, ASTM A106, GRB, BARE	1		1		0	2	0	2		1	1		
45	EA	FLANGE - 16", ANSI 600, RFWN, ASTM A694, F52, TWT 0.500" WT, X52 PIPE, PER MSS-SP-44	4		4		0	8	0	8			4	4	
46	EA	FLANGE - 12", ANSI 600, RFWN, ASTM A694, F52, TWT 0.375" WT, X52 PIPE, PER MSS-SP-44	2		2		0	4	0	4			2	2	
47	EA	FLANGE - 10", ANSI 600, RFWN, ASTM A694, F52, TWT 0.365" WT, X52 PIPE, PER MSS-SP-44	4		4		0	8	0	8			4	4	
48	EA	FLANGE - 8", ANSI 600, RFWN, ASTM A694, F42, TWT 0.322" WT, X42 PIPE, PER MSS-SP-44	1		1		0	2	0	2			1	1	
49	EA	FLANGE - 6", ANSI 600, RFWN, ASTM A105, GR B, TWT 0.280" WT, GR B PIPE, PER ASME B16.5	4		4		0	8	0	8			4	4	
50	EA	FLANGE - 4", ANSI 600, RFWN, ASTM A105, GR B, TWT 0.237" WT, GR B PIPE, PER ASME B16.5	3		3		0	6	0	6			3	3	
51	EA	FLANGE - 2", ANSI 600, RFWN, ASTM A105, GR B, TWT 0.218" WT, GR B PIPE, PER ASME B16.5	7		7		0	14	0	14			7	7	
52	EA	FLANGE - 1 1/2", ANSI 600, RFWN, ASTM A105, GR B, TWT 0.200" WT, GR B PIPE, PER ASME B16.5	6		6		0	12	0	12			6	6	
53	EA	FLANGE, BLIND - 8", ANSI 600, RF, ASTM A694, F52, MSS SP-44, CD&T FOR 1" NPT		5			0	5	5	0					
54	EA	FLANGE, BLIND - 2", ANSI 600, RF, ASTM A105, GR B, PER ASME B16.5, CD&T FOR 1/2" NPT	3		3		0	6	0	6			3	3	
23	EA	TEE, STRAIGHT - 12", 0.375" WT, BW, MSS-SP-75, Y52, PER ASME B16.9	1		1		0	2	0	2		1	1		
CLIENT SUMMARY This Meter Station 2013-Jun-20 rev31.xlsx															
6/20															

24	EA	TEE, STRAIGHT - 10", 0.365" WT, BW, MSS-SP-75, Y52, PER ASME B16.9	1		1		0	2	0	2		1	1		
26	EA	TEE, REDUCING - 16", 0.500" WT x 12", 0.375" WT, BW, MSS-SP-75, Y52, PER ASME B16.9	1		1		0	2	0	2		1	1		
27	EA	TEE, REDUCING - 12", 0.375" WT x 6", 0.280" WT, BW, MSS-SP-75, Y52, PER ASME B16.9	1		1		0	2	1	1			1		
28	EA	TEE, REDUCING - 12", 0.375" WT x 4", 0.237" WT, BW, MSS-SP-75, Y52, PER ASME B16.9	1		1		0	2	0	2		1	1		
29	EA	TEE, REDUCING - 8", 0.322" WT x 6", 0.280" WT, BW, MSS-SP-75, Y42, PER ASME B16.9	1		1		0	2	0	2			1	1	
39	EA	REDUCER, CONC. - 20", 0.500" WT x 16", 0.375" WT, BW, MSS-SP-75, Y60, PER ASME B16.9	2		2		0	4	0	4			2	2	
40	EA	REDUCER, CONC. - 12", 0.375" WT x 10", 0.365" WT, BW, MSS-SP-75, Y52, PER ASME B16.9	1		1		0	2	0	2			1	1	
41	EA	REDUCER, CONC. - 12", 0.375" WT x 8", 0.322" WT, BW, MSS-SP-75, Y52, PER ASME B16.9	1		1		0	2	0	2			1	1	
43	EA	REDUCER, CONC. - 6", 0.280" WT x 4", 0.237" WT, BW, ASTM A234, WPB, PER ASME B16.9					0	0	(3)	3			3		
44	EA	REDUCER, ECC. - 12", 0.375" WT x 10", 0.365" WT, BW, MSS-SP-75, Y52, PER ASME B16.9	1		1		0	2	0	2			1	1	
30	EA	ELL, 90 DEG - LR, 12", 0.375" WT, BW, MSS-SP-75, Y52, PER ASME B16.9	2		2		0	4	0	4			2	2	
31	EA	ELL, 90 DEG - LR, 10", 0.365" WT, BW, MSS-SP-75, Y52, PER ASME B16.9	2		2		0	4	0	4			2	2	
32	EA	ELL, 90 DEG - LR, 8", 0.322" WT, BW, MSS-SP-75, Y42, PER ASME B16.9	2		2		0	4	0	4			2	2	
33	EA	ELL, 90 DEG - LR, 6", 0.28" WT, BW, ASTM A234, WPB, PER ASME B16.9	4		4		0	8	0	8			4	4	
34	EA	ELL, 90 DEG - LR, 4", 0.237" WT, BW, ASTM A234, WPB, PER ASME B16.9	2		2		0	4	0	4			2	2	
35	EA	ELL, 90 DEG - LR, 2", 0.218" WT, BW, ASTM A234, WPB, PER ASME B16.9	3		3		0	6	0	6			3	3	
36	EA	ELL, 90 DEG - LR, 1 1/2", 0.200" WT, BW, ASTM A234, WPB, PER ASME B16.9	6		6		0	12	0	12			6	6	
37	EA	ELL, 45 DEG - 3R, 10", 0.365" WT, BW, MSS-SP-75, Y52, PER ASME B16.9	2		2		0	4	0	4			2	2	
74	EA	VALVE, PLUG - 1 1/2", ANSI 600, RF, API 6D, ASTM A216 WCB, REGULAR PATTERN, FOR SWEET NATURAL GAS SERVICE, -20°F TO 120°F, LEVER OPERATED C/W LOCKING DEVICE, CLEANED AND PAINTED W/ SHOP PRIMER	3		3		0	6	0	6			3	3	
75	EA	VALVE, BALL - 16", ANSI 600, RF, API 6D, FULL PORT, DOUBLE BLOCK & BLEED, FOR SWEET NATURAL GAS SERVICE, -20°F TO 120°F, LESS LEVER FOR MOUNTING VALVE OPERATOR, CLEANED AND PAINTED W/ SHOP PRIMER	1		1		0	2	0	2			1	1	
76	EA	VALVE, BALL - 12", ANSI 600, RF, API 6D, FULL PORT, DOUBLE BLOCK & BLEED, FOR SWEET NATURAL GAS SERVICE, -20°F TO 120°F, LESS LEVER FOR MOUNTING VALVE OPERATOR, CLEANED AND PAINTED W/ SHOP PRIMER	1		1		0	2	0	2			1	1	
77	EA	VALVE, BALL - 10", ANSI 600, RF, API 6D, FULL PORT, DOUBLE BLOCK & BLEED, FOR SWEET NATURAL GAS SERVICE, -20°F TO 120°F, LESS LEVER FOR MOUNTING VALVE OPERATOR, CLEANED AND PAINTED W/ SHOP PRIMER	2		2		0	4	0	4			2	2	
78	EA	VALVE, BALL - 6", ANSI 600, RF, API 6D, FULL PORT, DOUBLE BLOCK & BLEED, FOR SWEET NATURAL GAS SERVICE, -20°F TO 120°F, LEVER OPERATED, C/W LOCKING DEVICE, CLEANED AND PAINTED W/ SHOP PRIMER	2		2		0	4	0	4			2	2	
79	EA	VALVE, BALL - 4", ANSI 600, RF x WE, FULL PATTERN, API 6D, FULL PORT, LEVER OPERATED, C/W LOCKING DEVICE, TWT 4" OD, 0.237" WT, GRB PIPE	1		1		0	2	0	2			1	1	

80	EA	VALVE, BALL - 4", ANSI 600, RF, API 6D, FULL PORT, DOUBLE BLOCK & BLEED, FOR SWEET NATURAL GAS SERVICE, -20°F TO 120°F, LEVER OPERATED, C/W LOCKING DEVICE, CLEANED AND PAINTED W/ SHOP PRIMER	1		1		0	2	0	2			1	1	
81	EA	VALVE, BALL - 2", ANSI 600, RF, API 6D, FULL PORT, DOUBLE BLOCK & BLEED, FOR SWEET NATURAL GAS SERVICE, -20°F TO 120°F, LEVER OPERATED, C/W LOCKING DEVICE, CLEANED AND PAINTED W/ SHOP PRIMER	5		5		0	10	0	10			5	5	
82	EA	VALVE, BALL - 1", CLASS 3000, W.O.G., THRD, FNPT, C.S, SS TRIM, FULL PORT, NATURAL GAS SERVICE, C/W LEVER OPERATOR & LOCKING DEVICE	2		2		0	4	0	4			2	2	
83	EA	VALVE, BALL - 3/4", CLASS 3000, W.O.G., THRD, FNPT, C.S, SS TRIM, FULL PORT, NATURAL GAS SERVICE, C/W LEVER OPERATOR & LOCKING DEVICE	2		2		0	4	0	4			2	2	
84	EA	VALVE, BALL - 1/2", CLASS 3000, W.O.G., THRD, FNPT, C.S, SS TRIM, FULL PORT, NATURAL GAS SERVICE, C/W LEVER OPERATOR & LOCKING DEVICE	3		3		0	6	0	6			3	3	
85	FT	VALVE, BALL - 1/4" BLAH BLAH		4			0	4	0	0					
56	EA	WELDOLET - 2" ON 20", BW, MSS-SP-75, F60, BONNEY FORGE OR EQUAL, PER MSS SP-97, -20°F TO 250°F	2		2		0	4	0	4		2	2		
57	EA	WELDOLET - 2" ON 12", BW, MSS-SP-75, F52, BONNEY FORGE OR EQUAL, PER MSS SP-97, -20°F TO 250°F	1		1		0	2	0	2		1	1		
58	EA	WELDOLET - 1 1/2" ON 20", BW, MSS-SP-75, F60, BONNEY FORGE OR EQUAL, PER MSS SP-97, -20°F TO 250°F	2		2		0	4	0	4		2	2		
59	EA	WELDOLET - 1 1/2" ON 16", BW, MSS-SP-75, F52, BONNEY FORGE OR EQUAL, PER MSS SP-97, -20°F TO 250°F	2		2		0	4	0	4		2	2		
60	EA	THREDOLET - 24" - 14" x 1-1/2", CLASS 3000, FNPT ASTM A105, BONNEY FORGE OR EQUAL, PER MSS SP-97, -20°F TO 250°F	2		2		0	4	0	4		2	2		
61	EA	THREDOLET - 12" - 8" x 1-1/2", CLASS 3000, FNPT ASTM A105, BONNEY FORGE OR EQUAL, PER MSS SP-97, -20°F TO 250°F	4		4		0	8	0	8		4	4		
67	EA	SADDLE, WELD 6" ON 20", 5/8" THK, HDR EDGE TAPERED TO 0.280", W/VENT HOLE, MSS-SP-75, Y65, PER FLEETLINE CATALOG SFI-105 & ASME B31.8	2		2		0	4	0	4		2	2		
68	EA	SADDLE, WELD 4" ON 12", 5/8" THK, HDR EDGE TAPERED TO 0.237", W/VENT HOLE, MSS-SP-75, Y52, PER FLEETLINE CATALOG SFI-105 & ASME B31.8	1		1		0	2	0	2		1	1		
69	EA	SADDLE, WELD 4" ON 10", 5/8" THK, HDR EDGE TAPERED TO 0.237", W/VENT HOLE, MSS-SP-75, Y52, PER FLEETLINE CATALOG SFI-105 & ASME B31.8	1		1		0	2	0	2		1	1		
70	EA	SADDLE, WELD 2" ON 20", 5/8" THK, HDR EDGE TAPERED TO 0.218", W/VENT HOLE, MSS-SP-75, Y65, PER FLEETLINE CATALOG SFI-105 & ASME B31.8	2		2		0	4	0	4		2	2		
63	EA	CLOSURE, HORIZONTAL - 20.000" OD, ANSI 600, TWT 0.500" WT, X60 PIPE, YALE OR EQUIV.	2		2		0	4	0	4		2	2		
64	EA	CLOSURE, HORIZONTAL - 12.750" OD, ANSI 600, TWT 0.375" WT, X52 PIPE, YALE OR EQUIV.	1		1		0	2	0	2		1	1		
65	EA	CLOSURE, HORIZONTAL - 4.500" OD, ANSI 600, TWT 0.237" WT, GR B PIPE, YALE OR EQUIV.	1		1		0	2	0	2		1	1		
66	EA	CLOSURE, HORIZONTAL - 2.375" OD, ANSI 600, TWT 0.218" WT, GR B PIPE, YALE OR EQUIV.	2		2		0	4	0	4		2	2		
71	EA	PLUG, HEXHEAD, 1", 3000#, MNPT, ASTM A105, PER ASME B16.11	2		2		2	6	2	4			2	2	
72	EA	PLUG, HEXHEAD, 3/4", 3000#, MNPT, ASTM A105, PER ASME B16.11	2		2		2	6	2	4			2	2	
73	EA	PLUG, HEXHEAD, 1/2", 3000#, MNPT, ASTM A105, PER ASME B16.11	3		3		2	8	2	6			3	3	
86	EA	GASKET, SPIRAL WOUND - 24", ANSI 600, RF, FLEXITALLIC, STYLE CGI OR EQUAL, 304 SS WINDING WITH GRAPHITE FILLER, 304 SS OUTER & INNER RING, 1/8" THK, FOR MSS-SP-44 FLANGE		6			1	7	7	0					

87	EA	GASKET, SPIRAL WOUND - 16", ANSI 600, RF, FLEXITALLIC, STYLE CGI OR EQUAL, 304 SS WINDING WITH GRAPHITE FILLER, 304 SS OUTER & INNER RING, 1/8" THK. FOR MSS-SP-44 FLANGE	4		4		1	9	1	8			4	4	
88	EA	GASKET, SPIRAL WOUND - 12", ANSI 600, RF, FLEXITALLIC, STYLE CGI OR EQUAL, 304 SS WINDING WITH GRAPHITE FILLER, 304 SS OUTER & INNER RING, 1/8" THK. FOR MSS-SP-44 FLANGE	2		2		1	5	1	4			2	2	
89	EA	GASKET, SPIRAL WOUND - 10", ANSI 600, RF, FLEXITALLIC, STYLE CGI OR EQUAL, 304 SS WINDING WITH GRAPHITE FILLER, 304 SS OUTER & INNER RING, 1/8" THK. FOR MSS-SP-44 FLANGE	4		4		1	9	1	8			4	4	
90	EA	GASKET, SPIRAL WOUND - 8", ANSI 600, RF, FLEXITALLIC, STYLE CGI OR EQUAL, 304 SS WINDING WITH GRAPHITE FILLER, 304 SS OUTER & INNER RING, 1/8" THK. FOR MSS-SP-44 FLANGE	1		1		1	3	1	2			1	1	
91	EA	GASKET, SPIRAL WOUND - 6", ANSI 600, RF, FLEXITALLIC, STYLE CGI OR EQUAL, 304 SS WINDING WITH GRAPHITE FILLER, 304 SS OUTER & INNER RING, 1/8" THK. FOR ASME B16.5 FLANGE	4		4		1	9	1	8			4	4	
92	EA	GASKET, SPIRAL WOUND - 4", ANSI 600, RF, FLEXITALLIC, STYLE CGI OR EQUAL, 304 SS WINDING WITH GRAPHITE FILLER, 304 SS OUTER & INNER RING, 1/8" THK. FOR ASME B16.5 FLANGE	3		3		1	7	1	6			3	3	
93	EA	GASKET, SPIRAL WOUND - 2", ANSI 600, RF, FLEXITALLIC, STYLE CGI OR EQUAL, 304 SS WINDING WITH GRAPHITE FILLER, 304 SS OUTER & INNER RING, 1/8" THK. FOR ASME B16.5 FLANGE	10		10		1	21	1	20			10	10	
94	EA	GASKET, SPIRAL WOUND - 1 1/2", ANSI 600, RF, FLEXITALLIC, STYLE CGI OR EQUAL, 304 SS WINDING WITH GRAPHITE FILLER, 304 SS OUTER & INNER RING, 1/8" THK. FOR ASME B16.5 FLANGE	6		6		1	13	1	12			6	6	