

Client Name	erg
Project Name	erg
Revision	2013-06-12 - 10:40:35 AM
HMM Contact	Olin Valby - 281-598-9539

LEGEND

Changes made to this revision

Current Quantities Per Site								Quantities Requested						
Mark No.	Unit	Description	Birdland	Site A	Parker	Total Qty.	Quantity Left to Acquire	Current Inventory	PRKR12	RQST12	BRDLAND	TST1234	RFRP1234	123258
									6/11/2013	6/6/2013	6/6/2013	5/8/2013	5/1/2013	4/22/2013
1	FT	PIPE - 24", 0.500" WT, ERW/DSAW, BE, API 5L PSL-2, X60, BARE	17			17	0	17				17		
88	FT	PIPE - 20", 0.500" WT, ERW/DSAW, BE, API 5L PSL-2, X60, BARE			18	18	1	17	1		17			
2	FT	PIPE - 16", 0.500" WT, ERW/DSAW, BE, API 5L PSL-2, X52, BARE	19	21	19	59	0	59			19	19	21	
3	FT	PIPE - 12", 0.375" WT, ERW/SMLS, BE, API 5L PSL-2, X52, BARE	17	25	17	59	0	59			17	17	25	
4	FT	PIPE - 12", 0.375" WT, ERW/SMLS, BE, API 5L PSL-2, X52, COATED	113		113	226	0	226			111	115		
90	FT	PIPE - 10", 0.365" WT, ERW/SMLS, BE, API 5L PSL-2, X52, BARE TESTING	29		29	58	0	0						
80	FT	PIPE - 10", 0.322" WT, ERW/SMLS, BE, API 5L PSL-2, X42, COATED				0	-60	60						60
6	FT	PIPE - 8", 0.322" WT, ERW/SMLS, BE, API 5L PSL-2, X42, BARE	1	5	1	7	-37	44					5	39
5	FT	PIPE - 8", 0.322" WT, ERW/SMLS, BE, API 5L PSL-2, X42, COATED	6		6	12	0	12		6	6			
8	FT	PIPE - 6", 0.280" WT, ERW/SMLS, BE, API 5L PSL-2, GRB, BARE	3		3	6	0	6			3	3		
9	FT	PIPE - 6", 0.280" WT, ERW/SMLS, BE, API 5L PSL-2, GRB, COATED	29		29	58	0	58			29	29		
10	FT	PIPE - 4", 0.237" WT, ERW/SMLS, BE, API 5L PSL-2, GRB, BARE	13	84	13	110	0	110			13	13	84	
79	FT	PIPE - 4", 0.237" WT, ERW/SMLS, BE, API 5L PSL-2, GRB, COATED		17		17	-17	34					17	17
11	FT	PIPE - 2", 0.218" WT, ERW/SMLS, BE, API 5L PSL-1, GRB, BARE	4	51	4	59	0	59			4	4	51	
12	FT	PIPE - 1 1/2", 0.200" WT, SMLS, BE, ASTM A106, GRB, BARE	14		14	28	0	28			14	14		
13	FT	PIPE - 1", 0.179" WT, SMLS, BE, ASTM A106, GRB, BARE	1		1	2	0	2			1	1		
14	FT	PIPE - 3/4", 0.154" WT, SMLS, BE, ASTM A106, GRB, BARE	1		1	2	0	2			1	1		
15	FT	PIPE - 1/2", 0.147" WT, SMLS, BE, ASTM A106, GRB, BARE	1		1	2	0	2			1	1		
30	EA	TEE, STRAIGHT - 12", 0.375" WT, BW, MSS-SP-75, Y52, PER ASME B16.9	1		1	2	0	2			1	1		
31	EA	TEE, STRAIGHT - 10", 0.365" WT, BW, MSS-SP-75, Y52, PER ASME B16.9	1		1	2	0	2			1	1		
32	EA	TEE, REDUCING - 16", 0.500" WT x 12", 0.375" WT, BW, MSS-SP-75, Y52, PER ASME B16.9	1		1	2	0	2			1	1		
33	EA	TEE, REDUCING - 12", 0.375" WT x 6", 0.280" WT, BW, MSS-SP-75, Y52, PER ASME B16.9	1		1	2	1	1	1			1		
34	EA	TEE, REDUCING - 12", 0.375" WT x 4", 0.237" WT, BW, MSS-SP-75, Y52, PER ASME B16.9	1		1	2	0	2			1	1		
35	EA	TEE, REDUCING - 8", 0.322" WT x 6", 0.280" WT, BW, MSS-SP-75, Y42, PER ASME B16.9	1		1	2	0	2				1	1	
45	EA	ELL, 90 DEG - LR, 12", 0.375" WT, BW, MSS-SP-75, Y52, PER ASME B16.9	2		2	4	0	4				2	2	
46	EA	ELL, 90 DEG - LR, 10", 0.365" WT, BW, MSS-SP-75, Y52, PER ASME B16.9	2		2	4	0	4				2	2	
47	EA	ELL, 90 DEG - LR, 8", 0.322" WT, BW, MSS-SP-75, Y42, PER ASME B16.9	2		2	4	0	4				2	2	
48	EA	ELL, 90 DEG - LR, 6", 0.28" WT, BW, ASTM A234, WPB, PER ASME B16.9	4		4	8	0	8				4	4	
49	EA	ELL, 90 DEG - LR, 4", 0.237" WT, BW, ASTM A234, WPB, PER ASME B16.9	2		2	4	0	4				2	2	

50	EA	ELL, 90 DEG - LR, 2", 0.218" WT, BW, ASTM A234, WPB, PER ASME B16.9	3		3	6	0	6					3	3	
51	EA	ELL, 90 DEG - LR, 1 1/2", 0.200" WT, BW, ASTM A234, WPB, PER ASME B16.9	6		6	12	0	12					6	6	
52	EA	ELL, 45 DEG - 3R, 10", 0.365" WT, BW, MSS-SP-75, Y52, PER ASME B16.9	2		2	4	0	4					2	2	
53	EA	REDUCER, CONC. - 20", 0.500" WT x 16", 0.375" WT, BW, MSS-SP-75, Y60, PER ASME B16.9	2		2	4	0	4					2	2	
54	EA	REDUCER, CONC. - 12", 0.375" WT x 10", 0.365" WT, BW, MSS-SP-75, Y52, PER ASME B16.9	1		1	2	0	2					1	1	
55	EA	REDUCER, CONC. - 12", 0.375" WT x 8", 0.322" WT, BW, MSS-SP-75, Y52, PER ASME B16.9	1		1	2	0	2					1	1	
85	EA	REDUCER, CONC. - 6", 0.280" WT x 4", 0.237" WT, BW, ASTM A234, WPB, PER ASME B16.9				0	-3	3					3		
56	EA	REDUCER, ECC. - 12", 0.375" WT x 10", 0.365" WT, BW, MSS-SP-75, Y52, PER ASME B16.9	1		1	2	0	2					1	1	
36	EA	FLANGE - 16", ANSI 600, RFWN, ASTM A694, F52, TWT 0.500" WT, X52 PIPE, PER MSS-SP-44	4		4	8	0	8					4	4	
37	EA	FLANGE - 12", ANSI 600, RFWN, ASTM A694, F52, TWT 0.375" WT, X52 PIPE, PER MSS-SP-44	2		2	4	0	4					2	2	
38	EA	FLANGE - 10", ANSI 600, RFWN, ASTM A694, F52, TWT 0.365" WT, X52 PIPE, PER MSS-SP-44	4		4	8	0	8					4	4	
39	EA	FLANGE - 8", ANSI 600, RFWN, ASTM A694, F42, TWT 0.322" WT, X42 PIPE, PER MSS-SP-44	1		1	2	0	2					1	1	
40	EA	FLANGE - 6", ANSI 600, RFWN, ASTM A105, GR B, TWT 0.280" WT, GR B PIPE, PER ASME B16.5	4		4	8	0	8					4	4	
41	EA	FLANGE - 4", ANSI 600, RFWN, ASTM A105, GR B, TWT 0.237" WT, GR B PIPE, PER ASME B16.5	3		3	6	0	6					3	3	
42	EA	FLANGE - 2", ANSI 600, RFWN, ASTM A105, GR B, TWT 0.218" WT, GR B PIPE, PER ASME B16.5	7		7	14	0	14					7	7	
43	EA	FLANGE - 1 1/2", ANSI 600, RFWN, ASTM A105, GR B, TWT 0.200" WT, GR B PIPE, PER ASME B16.5	6		6	12	0	12					6	6	
95	EA	FLANGE, BLIND - 8", ANSI 600, RF, ASTM A694, F52, MSS SP-44, CD&T FOR 1" NPT		5		5	5	0							
44	EA	FLANGE, BLIND - 2", ANSI 600, RF, ASTM A105, GR B, PER ASME B16.5, CD&T FOR 1/2" NPT	3		3	6	0	6					3	3	
20	EA	WELDOLET - 2" ON 20", BW, MSS-SP-75, F60, BONNEY FORGE OR EQUAL, PER MSS SP-97, -20°F TO 250°F	2		2	4	0	4			2	2			
21	EA	WELDOLET - 2" ON 12", BW, MSS-SP-75, F52, BONNEY FORGE OR EQUAL, PER MSS SP-97, -20°F TO 250°F	1		1	2	0	2			1	1			
22	EA	WELDOLET - 1 1/2" ON 20", BW, MSS-SP-75, F60, BONNEY FORGE OR EQUAL, PER MSS SP-97, -20°F TO 250°F	2		2	4	0	4			2	2			
23	EA	WELDOLET - 1 1/2" ON 16", BW, MSS-SP-75, F52, BONNEY FORGE OR EQUAL, PER MSS SP-97, -20°F TO 250°F	2		2	4	0	4			2	2			
24	EA	THREDOLET - 24" - 14" x 1-1/2", CLASS 3000, FNPT ASTM A105, BONNEY FORGE OR EQUAL, PER MSS SP-97, -20°F TO 250°F	2		2	4	0	4			2	2			
25	EA	THREDOLET - 12" - 8" x 1-1/2", CLASS 3000, FNPT ASTM A105, BONNEY FORGE OR EQUAL, PER MSS SP-97, -20°F TO 250°F	4		4	8	0	8			4	4			
16	EA	CLOSURE, HORIZONTAL - 20.000" OD, ANSI 600, TWT 0.500" WT, X60 PIPE, YALE OR EQUIV.	2		2	4	0	4			2	2			
17	EA	CLOSURE, HORIZONTAL - 12.750" OD, ANSI 600, TWT 0.375" WT, X52 PIPE, YALE OR EQUIV.	1		1	2	0	2			1	1			
18	EA	CLOSURE, HORIZONTAL - 4.500" OD, ANSI 600, TWT 0.237" WT, GR B PIPE, YALE OR EQUIV.	1		1	2	0	2			1	1			
19	EA	CLOSURE, HORIZONTAL - 2.375" OD, ANSI 600, TWT 0.218" WT, GR B PIPE, YALE OR EQUIV.	2		2	4	0	4			2	2			
26	EA	SADDLE, WELD 6" ON 20", 5/8" THK, HDR EDGE TAPERED TO 0.280", W/VENT HOLE, MSS-SP-75, Y65, PER FLEETLINE CATALOG SFI-105 & ASME B31.8	2		2	4	0	4			2	2			

27	EA	SADDLE, WELD 4" ON 12", 5/8" THK, HDR EDGE TAPERED TO 0.237", W/VENT HOLE, MSS-SP-75, Y52, PER FLEETLINE CATALOG SFI-105 & ASME B31.8	1		1	2	0	2			1	1		
28	EA	SADDLE, WELD 4" ON 10", 5/8" THK, HDR EDGE TAPERED TO 0.237", W/VENT HOLE, MSS-SP-75, Y52, PER FLEETLINE CATALOG SFI-105 & ASME B31.8	1		1	2	0	2			1	1		
29	EA	SADDLE, WELD 2" ON 20", 5/8" THK, HDR EDGE TAPERED TO 0.218", W/VENT HOLE, MSS-SP-75, Y65, PER FLEETLINE CATALOG SFI-105 & ASME B31.8	2		2	4	0	4			2	2		
65	EA	PLUG, HEXHEAD, 1", 3000#, MNPT, ASTM A105, PER ASME B16.11	2		2	4	0	4				2	2	
66	EA	PLUG, HEXHEAD, 3/4", 3000#, MNPT, ASTM A105, PER ASME B16.11	2		2	4	0	4				2	2	
67	EA	PLUG, HEXHEAD, 1/2", 3000#, MNPT, ASTM A105, PER ASME B16.11	3		3	6	0	6				3	3	
68	EA	VALVE, PLUG - 1 1/2", ANSI 600, RF, API 6D, ASTM A216 WCB, REGULAR PATTERN, FOR SWEET NATURAL GAS SERVICE, -20°F TO 120°F, LEVER OPERATED C/W LOCKING DEVICE, CLEANED AND PAINTED W/ SHOP PRIMER	3		3	6	0	6				3	3	
69	EA	VALVE, BALL - 16", ANSI 600, RF, API 6D, FULL PORT, DOUBLE BLOCK & BLEED, FOR SWEET NATURAL GAS SERVICE, -20°F TO 120°F, LESS LEVER FOR MOUNTING VALVE OPERATOR, CLEANED AND PAINTED W/ SHOP PRIMER	1		1	2	0	2				1	1	
70	EA	VALVE, BALL - 12", ANSI 600, RF, API 6D, FULL PORT, DOUBLE BLOCK & BLEED, FOR SWEET NATURAL GAS SERVICE, -20°F TO 120°F, LESS LEVER FOR MOUNTING VALVE OPERATOR, CLEANED AND PAINTED W/ SHOP PRIMER	1		1	2	0	2				1	1	
71	EA	VALVE, BALL - 10", ANSI 600, RF, API 6D, FULL PORT, DOUBLE BLOCK & BLEED, FOR SWEET NATURAL GAS SERVICE, -20°F TO 120°F, LESS LEVER FOR MOUNTING VALVE OPERATOR, CLEANED AND PAINTED W/ SHOP PRIMER	2		2	4	0	4				2	2	
72	EA	VALVE, BALL - 6", ANSI 600, RF, API 6D, FULL PORT, DOUBLE BLOCK & BLEED, FOR SWEET NATURAL GAS SERVICE, -20°F TO 120°F, LEVER OPERATED, C/W LOCKING DEVICE, CLEANED AND PAINTED W/ SHOP PRIMER	2		2	4	0	4				2	2	
73	EA	VALVE, BALL - 4", ANSI 600, RF x WE, FULL PATTERN, API 6D, FULL PORT, LEVER OPERATED, C/W LOCKING DEVICE, TWT 4" OD, 0.237" WT, GRB PIPE	1		1	2	0	2				1	1	
74	EA	VALVE, BALL - 4", ANSI 600, RF, API 6D, FULL PORT, DOUBLE BLOCK & BLEED, FOR SWEET NATURAL GAS SERVICE, -20°F TO 120°F, LEVER OPERATED, C/W LOCKING DEVICE, CLEANED AND PAINTED W/ SHOP PRIMER	1		1	2	0	2				1	1	
75	EA	VALVE, BALL - 2", ANSI 600, RF, API 6D, FULL PORT, DOUBLE BLOCK & BLEED, FOR SWEET NATURAL GAS SERVICE, -20°F TO 120°F, LEVER OPERATED, C/W LOCKING DEVICE, CLEANED AND PAINTED W/ SHOP PRIMER	5		5	10	0	10				5	5	
76	EA	VALVE, BALL - 1", CLASS 3000, W.O.G., THRD, FNPT, C.S, SS TRIM, FULL PORT, NATURAL GAS SERVICE, C/W LEVER OPERATOR & LOCKING DEVICE	2		2	4	0	4				2	2	
77	EA	VALVE, BALL - 3/4", CLASS 3000, W.O.G., THRD, FNPT, C.S, SS TRIM, FULL PORT, NATURAL GAS SERVICE, C/W LEVER OPERATOR & LOCKING DEVICE	2		2	4	0	4				2	2	
78	EA	VALVE, BALL - 1/2", CLASS 3000, W.O.G., THRD, FNPT, C.S, SS TRIM, FULL PORT, NATURAL GAS SERVICE, C/W LEVER OPERATOR & LOCKING DEVICE	3		3	6	0	6				3	3	
92	FT	VALVE, BALL - 1/4" BLAH BLAH		4		4	0	0						
86	EA	GASKET, SPIRAL WOUND - 24", ANSI 600, RF, FLEXITALLIC, STYLE CGI OR EQUAL, 304 SS WINDING WITH GRAPHITE FILLER, 304 SS OUTER & INNER RING, 1/8" THK. FOR MSS-SP-44 FLANGE		6		6	6	0						

57	EA	GASKET, SPIRAL WOUND - 16", ANSI 600, RF, FLEXITALLIC, STYLE CGI OR EQUAL, 304 SS WINDING WITH GRAPHITE FILLER, 304 SS OUTER & INNER RING, 1/8" THK. FOR MSS-SP-44 FLANGE	4		4	8	0	8				4	4	
58	EA	GASKET, SPIRAL WOUND - 12", ANSI 600, RF, FLEXITALLIC, STYLE CGI OR EQUAL, 304 SS WINDING WITH GRAPHITE FILLER, 304 SS OUTER & INNER RING, 1/8" THK. FOR MSS-SP-44 FLANGE	2		2	4	0	4				2	2	
59	EA	GASKET, SPIRAL WOUND - 10", ANSI 600, RF, FLEXITALLIC, STYLE CGI OR EQUAL, 304 SS WINDING WITH GRAPHITE FILLER, 304 SS OUTER & INNER RING, 1/8" THK. FOR MSS-SP-44 FLANGE	4		4	8	0	8				4	4	
60	EA	GASKET, SPIRAL WOUND - 8", ANSI 600, RF, FLEXITALLIC, STYLE CGI OR EQUAL, 304 SS WINDING WITH GRAPHITE FILLER, 304 SS OUTER & INNER RING, 1/8" THK. FOR MSS-SP-44 FLANGE	1		1	2	0	2				1	1	
61	EA	GASKET, SPIRAL WOUND - 6", ANSI 600, RF, FLEXITALLIC, STYLE CGI OR EQUAL, 304 SS WINDING WITH GRAPHITE FILLER, 304 SS OUTER & INNER RING, 1/8" THK. FOR ASME B16.5 FLANGE	4		4	8	0	8				4	4	
62	EA	GASKET, SPIRAL WOUND - 4", ANSI 600, RF, FLEXITALLIC, STYLE CGI OR EQUAL, 304 SS WINDING WITH GRAPHITE FILLER, 304 SS OUTER & INNER RING, 1/8" THK. FOR ASME B16.5 FLANGE	3		3	6	0	6				3	3	
63	EA	GASKET, SPIRAL WOUND - 2", ANSI 600, RF, FLEXITALLIC, STYLE CGI OR EQUAL, 304 SS WINDING WITH GRAPHITE FILLER, 304 SS OUTER & INNER RING, 1/8" THK. FOR ASME B16.5 FLANGE	10		10	20	0	20				10	10	
64	EA	GASKET, SPIRAL WOUND - 1 1/2", ANSI 600, RF, FLEXITALLIC, STYLE CGI OR EQUAL, 304 SS WINDING WITH GRAPHITE FILLER, 304 SS OUTER & INNER RING, 1/8" THK. FOR ASME B16.5 FLANGE	6		6	12	0	12				6	6	