Quantities Check Sheet

Mark No.	Model Total	Unit	Long Description	Current Model Quantities				Checked Quantities				
	I Otal			Uniontown	Site A	Area 0	Fab AB	Uniontown	Site A	Area 0	Fab AB	
1	7	FT	PIPE - 30", 0.500" WT, ERW/DSAW, BE, API 5L PSL-2, X65, BARE		2	5						
2	0	FT	PIPE - 24", 0.625" WT, ERW/DSAW, BE, API 5L PSL-2, X60, BARE									
3	17	FT	PIPE - 24", 0.500" WT, ERW/DSAW, BE, API 5L PSL-2, X60, BARE	17								
4	18	FT	PIPE - 20", 0.500" WT, ERW/DSAW, BE, API SL PSL-2, X60, BARE			18				18		
100	0	FT	PIPE - 20", 0.500" WT, ERW/DSAW, BE, API 5L PSL-2, X60, COATED									
5	59	FT	PIPE - 16", 0.500" WT, ERW/DSAW, BE, API 5L PSL-2, X52, BARE	19	21	19		19	21			
6	0	FT	PIPE - 16", 0.500" WT, DSAW, BE, API 5L PSL2, X52, COATED WITH 14 - 16 MILS FBE									
7	71	FT	PIPE - 12", 0.375" WT, ERW/SMLS, BE, API 5L PSL-2, X52, BARE	15	25	17	14	17	25			
8	262	FT	PIPE - 12", 0.375" WT, ERW/SMLS, BE, API 5L PSL-2, X52, COATED	113		113	36	113				
9	58	FT	PIPE - 10", 0.365" WT, ERW/SMLS, BE, API 5L PSL-2, X52, BARE	29		29						
10	0	FT	PIPE - 10", 0.322" WT, ERW/SMLS, BE, API 5L PSL-2, X42, BARE									
97	0	FT	PIPE - 10", 0.134" WT, SMLS, PE, ASTM A523, GR B, BARE, COMPLETE WITH CERTIFIED MILL TEST REPORTS									
12	7	FT	PIPE - 8", 0.322" WT, ERW/SMLS, BE, API 5L PSL-2, X42, BARE	1	5	1		1	5			
13	12	FT	PIPE - 8", 0.322" WT, ERW/SMLS, BE, API 5L PSL-2, X42, COATED	6		6		6				
14	36	FT	PIPE - 6", 0.280" WT, ERW/SMLS, BE, API 5L PSL-2, GRB, BARE	3		3	30	3				
15	76	FT	PIPE - 6", 0.280" WT, ERW/SMLS, BE, API 5L PSL-2, GRB, COATED	29		29	18	29				
16	111	FT	PIPE - 4", 0.237" WT, ERW/SMLS, BE, API 5L PSL-2, GRB, BARE	13	84	13	1	13	84			
17	38	FT	PIPE - 4", 0.237" WT, ERW/SMLS, BE, API SL PSL-2, GRB, COATED		17		21		17			
18	59	FT	PIPE - 2", 0.218" WT, ERW/SMLS, BE, API 5L PSL-1, GRB, BARE	4	51	4		4	51			
19	28	FT	PIPE - 1 1/2", 0.200" WT, SMLS, BE, ASTM A106, GRB, BARE	14		14		14				
20	3	FT	PIPE - 1", 0.179" WT, SMLS, BE, ASTM A106, GRB, BARE	1		1	1	1				
21	3	FT	PIPE - 3/4", 0.154" WT, SMLS, BE, ASTM A106, GRB, BARE	1		1	1	1				
22	3	FT	PIPE - 1/2", 0.147" WT, SMLS, BE, ASTM A106, GRB, BARE	1		1	1	1				
98	0	EA	FLANGE - 18", ANSI 600, FFWN, ASTM A694, F52, TWT 0.312" WT, X52 PIPE, MSS SP-44									
45	8	EA	FLANGE - 16", ANSI 600, RFWN, ASTM A694, F52, TWT 0.500" WT, X52 PIPE, PER MSS-SP-44	4		4		4				
46	12	EA	FLANGE - 12", ANSI 600, RFWN, ASTM A694, F52, TWT 0.375" WT, X52 PIPE, PER MSS-SP-44	2		2	8	2				
47	8	EA	FLANGE - 10", ANSI 600, RFWN, ASTM A694, F52, TWT 0.365" WT, X52 PIPE, PER MSS-SP-44	4		4		4				
48	2	EA	FLANGE - 8", ANSI 600, RFWN, ASTM A694, F42, TWT 0.322" WT, X42 PIPE, PER MSS-SP-44	1		1		1				
49	23	EA	FLANGE - 6", ANSI 600, RFWN, ASTM A105, GR B, TWT 0.280" WT, GR B PIPE, PER ASME B16.5	4		4	15	4				
50	11	EA	FLANGE - 4", ANSI 600, RFWN, ASTM A105, GR B, TWT 0.237" WT, GR B PIPE, PER ASME B16.5	3		3	5	3				
51	14	EA	FLANGE - 2", ANSI 600, RFWN, ASTM A105, GR B, TWT 0.218" WT, GR B PIPE, PER ASME B16.5	7		7		7				
52	12	EA	FLANGE - 1 1/2", ANSI 600, RFWN, ASTM A105, GR B, TWT 0.200" WT, GR B PIPE, PER ASME B16.5	6		6		6				
53	5	EA	FLANGE, BLIND - 8", ANSI 600, RF, ASTM A694, F52, MSS SP-44, CD&T FOR 1" NPT		5				5			
54	6	EA	FLANGE, BLIND - 2", ANSI 600, RF, ASTM A105, GR B, PER ASME B16.5, CD&T FOR 1/2" NPT	3		3		3				
55	0	EA	FLANGE, BLIND - 2", ANSI 600, FF, ASTM A105, GR B, ASME B16.5, CD&T FOR 1" NPT									

Mark No.	Model Total	Unit	Long Description	Cu	urrent Mod	el Quantities					
	Total			Uniontown	Site A	Area 0	Fab AB	Uniontown	Site A	Area 0	Fab AB
23	4	EA	TEE, STRAIGHT - 12", 0.375" WT, BW, MSS-SP-75, Y52, PER ASME B16.9	1		1	2	1			
24	2	EA	TEE, STRAIGHT - 10", 0.365" WT, BW, MSS-SP-75, Y52, PER ASME B16.9	1		1		1			
25	0	EA	TEE, STRAIGHT - 8", 0.250" WT, BW, MSS SP-75, Y42, WITH BARRED BRANCH								
110	1	EA	TEE, STRAIGHT - 6", 0.280" WT, BW, ASTM A234, WPB, PER ASME B16.9 (BARRED)				1				
99	0	EA	TEE, REDUCING - 24", 0.688" WT x 12", 0.500" WT, BW, MSS SP- 75, Y60								
26	2	EA	TEE, REDUCING - 16", 0.500" WT x 12", 0.375" WT, BW, MSS-SP- 75, Y52, PER ASME B16.9	1		1		1			
27	3	EA	TEE, REDUCING - 12", 0.375" WT x 6", 0.280" WT, BW, MSS-SP-75, Y52, PER ASME B16.9	1		1	1	1			
28	2	EA	TEE, REDUCING - 12", 0.375" WT x 4", 0.237" WT, BW, MSS-SP- 75, Y52, PER ASME B16.9	1		1		1			
29	2	EA	TEE, REDUCING - 8", 0.322" WT x 6", 0.280" WT, BW, MSS-SP-75, Y42, PER ASME B16.9	1		1		1			
109	1	EA	TEE, REDUCING - 3/4" x 1/2", CLASS 3000, THRD, FS, FNPT, ASTM A105, PER ASME B16.11				1				
39	4	EA	REDUCER, CONC 20", 0.500" WT x 16", 0.375" WT, BW, MSS- SP-75, Y60, PER ASME B16.9	2		2		2			
40	2	EA	REDUCER, CONC 12", 0.375" WT x 10", 0.365" WT, BW, MSS- SP-75, Y52, PER ASME B16.9	1		1		1			
41	2	EA	REDUCER, CONC 12", 0.375" WT x 8", 0.322" WT, BW, MSS-SP- 75, Y52, PER ASME B16.9	1		1		1			
42	1	EA	REDUCER, CONC 12", 0.375" WT x 6", 0.322" WT, BW, MSS-SP- 75, Y52, PER ASME B16.9				1				
119	0	EA	REDUCER, CONC 12", 0.375" WT x 6", 0.280" WT, BW, MSS-SP- 75, Y52, PER ASME B16.9								
43	2	EA	REDUCER, CONC 6", 0.280" WT x 4", 0.237" WT, BW, ASTM A234, WPB, PER ASME B16.9				2				
44	2	EA	REDUCER, ECC 12", 0.375" WT x 10", 0.365" WT, BW, MSS-SP- 75, Y52, PER ASME B16.9	1		1		1			
96	0	EA	REDUCER, ECC 6", 0.280" WT x 4", 0.237" WT, BW, ASTM A234, WPB, PER ASME B16.9, F.S.D.								
30	5	EA	ELL, 90 DEG - LR, 12", 0.375" WT, BW, MSS-SP-75, Y52, PER ASME B16.9	2		2	1	2			
31	4	EA	ELL, 90 DEG - LR, 10", 0.365" WT, BW, MSS-SP-75, Y52, PER ASME B16.9	2		2		2			
32	4	EA	ELL, 90 DEG - LR, 8", 0.322" WT, BW, MSS-SP-75, Y42, PER ASME B16.9	2		2		2			
33	14	EA	ELL, 90 DEG - LR, 6", 0.28" WT, BW, ASTM A234, WPB, PER ASME B16.9	4		4	6	4			
34	9	EA	ELL, 90 DEG - LR, 4", 0.237" WT, BW, ASTM A234, WPB, PER ASME B16.9	2		2	5	2			
35	6	EA	ELL, 90 DEG - LR, 2", 0.218" WT, BW, ASTM A234, WPB, PER ASME B16.9	3		3		3			
36	12	EA	ELL, 90 DEG - LR, 1 1/2", 0.200" WT, BW, ASTM A234, WPB, PER ASME B16.9	6		6		6			
107	1	EA	ELL, 90 DEG - 3R, 12", 0.375" WT, BW, MSS-SP-75, Y52, PER ASME B16.9				1				
113	1	EA	ELL, 90 DEG - 3R, 6", 0.280" WT, BW, ASTM A234, WPB, PER ASME B16.9, TRIMMED				1				
106	1	EA	ELL, 45 DEG - 3R, 12", 0.375" WT, BW, MSS-SP-75, Y52, PER ASME B16.9				1				
37	4	EA	ELL, 45 DEG - 3R, 10", 0.365" WT, BW, MSS-SP-75, Y52, PER ASME B16.9	2		2		2			
38	4	EA	ELL, 45 DEG - 3R, 6", 0.280" WT, BW, ASTM A234, WPB, PER ASME B16.9				4				
56	4	EA	WELDOLET - 2" ON 20", BW, MSS-SP-75, F60, BONNEY FORGE OR EQUAL, PER MSS SP-97, -20°F TO 250°F	2		2		2			
57	2	EA	WELDOLET - 2" ON 12", BW, MSS-SP-75, F52, BONNEY FORGE OR EQUAL, PER MSS SP-97, -20°F TO 250°F	1		1		1			
58	4	EA	WELDOLET - 1 1/2" ON 20", BW, MSS-SP-75, F60, BONNEY FORGE OR EQUAL, PER MSS SP-97, -20°F TO 250°F	2		2		2			
59	4	EA	WELDOLET - 1 1/2" ON 16", BW, MSS-SP-75, F52, BONNEY FORGE OR EQUAL, PER MSS SP-97, -20°F TO 250°F	2		2		2			

Mark No.	Model Total	Unit	Long Description Current Model Quantities Check							d Quantities		
	Jotal			Uniontown	Site A	Area 0	Fab AB	Uniontown	Site A	Area 0	Fab AB	
121	0	EA	WELDOLET - 3/4" ON 12", BW, MSS-SP-75, F52, BONNEY FORGE									
60	4	Γ.	OR EQUAL, PER MSS SP-97, -20°F TO 250°F	2		2		2				
60	4	EA	THREDOLET - 24" - 14" x 1-1/2", CLASS 3000, FNPT ASTM A105, BONNEY FORGE OR EQUAL, PER MSS SP-97, -20°F TO 250°F	2		2		2				
61	9	EA	THREDOLET - 12" - 8" x 1-1/2", CLASS 3000, FNPT ASTM A105, BONNEY FORGE OR EQUAL, PER MSS SP-97, -20°F TO 250°F	4		4	1	4				
111	1	EA	THREDOLET - "12"" - 6"" x 3/4""", CLASS 3000, FNPT ASTM A105, BONNEY FORGE OR EQUAL, PER MSS SP-97, -20°F TO 250°F				1					
112	2	EA	THREDOLET - "6"" - 5"" x 1-1/2"", CLASS 3000, FNPT ASTM A105, BONNEY FORGE OR EQUAL, PER MSS SP-97, -20°F TO 250°F				2					
116	1	EA	VALVE, SWING CHECK - 6", ANSI 600, RF, API 6D, ASTM A216 WCB, FULL PORT, BOLTED BONNET W/ "O" RING GASKET AND 1/2" PLUG, FOR SWEET NATURAL GAS SERVICE, -20°F TO 120°F, CLEANED AND PAINTED W/ SHOP PRIMER				1					
115	1	EA	VALVE, PLUG - 6", ANSI 600, RF, API 6D, ASTM A216 WCB, REGULAR PATTERN, FOR SWEET NATURAL GAS SERVICE, -20°F TO 120°F, MANUAL GEAR OPERATOR & HANDWHEEL, CLEANED AND PAINTED W/ SHOP PRIMER				1					
114	1	EA	VALVE, PLUG - 4", ANSI 600, RF, API 6D, ASTM A216 WCB, REGULAR PATTERN, FOR SWEET NATURAL GAS SERVICE, -20°F TO 120°F, MANUAL GEAR OPERATOR & HANDWHEEL, CLEANED AND PAINTED W/ SHOP PRIMER				1					
74	6	EA	VALVE, PLUG - 1 1/2", ANSI 600, RF, API 6D, ASTM A216 WCB, REGULAR PATTERN, FOR SWEET NATURAL GAS SERVICE, -20°F TO 120°F, LEVER OPERATED C/W LOCKING DEVICE, CLEANED AND PAINTED W/ SHOP PRIMER	3		3		3				
75	2	EA	VALVE, BALL - 16", ANSI 600, RF, API 6D, FULL PORT, DOUBLE BLOCK & BLEED, FOR SWEET NATURAL GAS SERVICE, -20°F TO 120°F, LESS LEVER FOR MOUNTING VALVE OPERATOR, CLEANED AND PAINTED W/ SHOP PRIMER	1		1		1				
120	0	EA	VALVE, BALL - 12", ANSI 600, RF, API 6D, FULL PORT, DOUBLE BLOCK & BLEED, FOR SWEET NATURAL GAS SERVICE, -20°F TO 120°F, MANUAL GEAR VALVE OPERATOR, CLEANED AND PAINTED W/ SHOP PRIMER									
76	6	EA	VALVE, BALL - 12", ANSI 600, RF, API 6D, FULL PORT, DOUBLE BLOCK & BLEED, FOR SWEET NATURAL GAS SERVICE, -20°F TO 120°F, LESS LEVER FOR MOUNTING VALVE OPERATOR, CLEANED AND PAINTED W/ SHOP PRIMER	1		1	4	1				
77	4	EA	VALVE, BALL - 10", ANSI 600, RF, API 6D, FULL PORT, DOUBLE BLOCK & BLEED, FOR SWEET NATURAL GAS SERVICE, -20°F TO 120°F, LESS LEVER FOR MOUNTING VALVE OPERATOR, CLEANED AND PAINTED W/ SHOP PRIMER	2		2		2				
78	6	EA	VALVE, BALL - 6", ANSI 600, RF, API 6D, FULL PORT, DOUBLE BLOCK & BLEED, FOR SWEET NATURAL GAS SERVICE, -20°F TO 120°F, LEVER OPERATED, C/W LOCKING DEVICE, CLEANED AND PAINTED W/ SHOP PRIMER	2		2	2	2				
79	2	EA	VALVE, BALL - 4", ANSI 600, RF x WE, FULL PATTERN, API 6D, FULL PORT, LEVER OPERATED, C/W LOCKING DEVICE, TWT 4" OD, 0.237" WT, GRB PIPE	1		1		1				
80	2	EA	VALVE, BALL - 4", ANSI 600, RF, API 6D, FULL PORT, DOUBLE BLOCK & BLEED, FOR SWEET NATURAL GAS SERVICE, -20°F TO 120°F, LEVER OPERATED, C/W LOCKING DEVICE, CLEANED AND PAINTED W/ SHOP PRIMER	1		1		1				
81	10	EA	VALVE, BALL - 2", ANSI 600, RF, API 6D, FULL PORT, DOUBLE BLOCK & BLEED, FOR SWEET NATURAL GAS SERVICE, -20°F TO 120°F, LEVER OPERATED, C/W LOCKING DEVICE, CLEANED AND PAINTED W/ SHOP PRIMER	5		5		5				
82	6	EA	VALVE, BALL - 1", CLASS 3000, W.O.G., THRD, FNPT, C.S, SS TRIM, FULL PORT, NATURAL GAS SERVICE, C/W LEVER OPERATOR & LOCKING DEVICE	2		2	2	2				

Mark No.	Model Total	Unit	Long Description	Cu	Current Model Quantities				Checked Quantities				
	Juli			Uniontown	Site A	Area 0	Fab AB	Uniontown	Site A	Area 0	Fab AB		
83	6	EA	VALVE, BALL - 3/4", CLASS 3000, W.O.G., THRD, FNPT, C.S, SS TRIM, FULL PORT, NATURAL GAS SERVICE, C/W LEVER OPERATOR & LOCKING DEVICE	2		2	2	2					
84	7	EA	VALVE, BALL - 1/2", CLASS 3000, W.O.G., THRD, FNPT, C.S, SS TRIM, FULL PORT, NATURAL GAS SERVICE, C/W LEVER OPERATOR & LOCKING DEVICE	3		3	1	3					
105	1	EA	CLOSURE, VERTICAL - 6.625" OD, ANSI 600, TWT {NOMWT} WT, {NOMGR} PIPE, YALE OR EQUIV.				1						
62	0	EA	CLOSURE, HORIZONTAL - 24.000" OD, ANSI 600, TWT 0.500" WT, X60 PIPE, YALE OR EQUIV.										
63	4	EA	CLOSURE, HORIZONTAL - 20.000" OD, ANSI 600, TWT 0.500" WT, X60 PIPE, YALE OR EQUIV.	2		2		2					
64	2	EA	CLOSURE, HORIZONTAL - 12.750" OD, ANSI 600, TWT 0.375" WT, X52 PIPE, YALE OR EQUIV.	1		1		1					
65	2	EA	CLOSURE, HORIZONTAL - 4.500" OD, ANSI 600, TWT 0.237" WT, GR B PIPE, YALE OR EQUIV.	1		1		1					
66	4	EA	CLOSURE, HORIZONTAL - 2.375" OD, ANSI 600, TWT 0.218" WT, GR B PIPE, YALE OR EQUIV.	2		2		2					
67	4	EA	SADDLE, WELD 6" ON 20", 5/8" THK, HDR EDGE TAPERED TO 0.280", W/VENT HOLE, MSS-SP-75, Y65, PER FLEETLINE CATALOG SFI-105 & ASME B31.8	2		2		2					
68	3	EA	SADDLE, WELD 4" ON 12", 5/8" THK, HDR EDGE TAPERED TO 0.237", W/VENT HOLE, MSS-SP-75, Y52, PER FLEETLINE CATALOG SFI-105 & ASME B31.8	1		1	1	1					
69	2	EA	SADDLE, WELD 4" ON 10", 5/8" THK, HDR EDGE TAPERED TO 0.237", W/VENT HOLE, MSS-SP-75, Y52, PER FLEETLINE CATALOG SFI-105 & ASME B31.8	1		1		1					
70	4	EA	SADDLE, WELD 2" ON 20", 5/8" THK, HDR EDGE TAPERED TO 0.218", W/VENT HOLE, MSS-SP-75, Y65, PER FLEETLINE CATALOG SFI-105 & ASME B31.8	2		2		2					
104	4	EA	CAP - 6", 0.280" WT, BW, ASTM A234, WPB, PER ASME B16.9				4						
122	0	EA	CAP - 1/2", 3000#, FNPT, ASTM A105, GR B, PER ASME B16.11										
108	1	EA	NIPPLE, PIPE - 3/4" NOM., x 3" LG, 0.219" WT, SCH. 160, TBE, MNPT, SMLS, CS, ASTM A106, GRB, FOR SWEET NATURAL GAS SERVICE				1						
71	6	EA	PLUG, HEXHEAD, 1", 3000#, MNPT, ASTM A105, PER ASME B16.11	2		2	2	2					
72	6	EA	PLUG, HEXHEAD, 3/4", 3000#, MNPT, ASTM A105, PER ASME B16.11	2		2	2	2					
73	7	EA	PLUG, HEXHEAD, 1/2", 3000#, MNPT, ASTM A105, PER ASME B16.11	3		3	1	3					
86	6	EA	GASKET, SPIRAL WOUND - 24", ANSI 600, RF, FLEXITALLIC, STYLE CGI OR EQUAL, 304 SS WINDING WITH GRAPHITE FILLER, 304 SS OUTER & INNER RING, 1/8" THK, FOR MSS-SP-44 FLANGE		6				6				
87	8	EA	GASKET, SPIRAL WOUND - 16", ANSI 600, RF, FLEXITALLIC, STYLE CGI OR EQUAL, 304 SS WINDING WITH GRAPHITE FILLER, 304 SS OUTER & INNER RING, 1/8" THK, FOR MSS-SP-44 FLANGE	4		4		4					
88	7	EA	GASKET, SPIRAL WOUND - 12", ANSI 600, RF, FLEXITALLIC, STYLE CGI OR EQUAL, 304 SS WINDING WITH GRAPHITE FILLER, 304 SS OUTER & INNER RING, 1/8" THK, FOR MSS-SP-44 FLANGE	2		2	3	2					
89	8	EA	GASKET, SPIRAL WOUND - 10", ANSI 600, RF, FLEXITALLIC, STYLE CGI OR EQUAL, 304 SS WINDING WITH GRAPHITE FILLER, 304 SS OUTER & INNER RING, 1/8" THK, FOR MSS-SP-44 FLANGE	4		4		4					
90	2	EA	GASKET, SPIRAL WOUND - 8", ANSI 600, RF, FLEXITALLIC, STYLE CGI OR EQUAL, 304 SS WINDING WITH GRAPHITE FILLER, 304 SS OUTER & INNER RING, 1/8" THK, FOR MSS-SP-44 FLANGE	1		1		1					
91	21	EA	GASKET, SPIRAL WOUND - 6", ANSI 600, RF, FLEXITALLIC, STYLE CGI OR EQUAL, 304 SS WINDING WITH GRAPHITE FILLER, 304 SS OUTER & INNER RING, 1/8" THK, FOR ASME B16.5 FLANGE	4		4	13	4					

92 93 94 95	20	EA EA	GASKET, SPIRAL WOUND - 4", ANSI 600, RF, FLEXITALLIC, STYLE CGI OR EQUAL, 304 SS WINDING WITH GRAPHITE FILLER, 304 SS OUTER & INNER RING, 1/8" THK, FOR ASME B16.5 FLANGE GASKET, SPIRAL WOUND - 2", ANSI 600, RF, FLEXITALLIC, STYLE CGI OR EQUAL, 304 SS WINDING WITH GRAPHITE FILLER, 304 SS OUTER & INNER RING, 1/8" THK, FOR ASME B16.5 FLANGE GASKET, SPIRAL WOUND - 1 1/2", ANSI 600, RF, FLEXITALLIC, STYLE CGI OR EQUAL, 304 SS WINDING WITH GRAPHITE FILLER,	3 10 6	Site A	3 10	Fab AB	3 10	Site A	Area 0	Fab AB
93	20	EA	CGI OR EQUAL, 304 SS WINDING WITH GRAPHITE FILLER, 304 SS OUTER & INNER RING, 1/8" THK, FOR ASME B16.5 FLANGE GASKET, SPIRAL WOUND - 2", ANSI 600, RF, FLEXITALLIC, STYLE CGI OR EQUAL, 304 SS WINDING WITH GRAPHITE FILLER, 304 SS OUTER & INNER RING, 1/8" THK, FOR ASME B16.5 FLANGE GASKET, SPIRAL WOUND - 1 1/2", ANSI 600, RF, FLEXITALLIC, STYLE CGI OR EQUAL, 304 SS WINDING WITH GRAPHITE FILLER,	10			3	-			
94	12		CGI OR EQUAL, 304 SS WINDING WITH GRAPHITE FILLER, 304 SS OUTER & INNER RING, 1/8" THK, FOR ASME B16.5 FLANGE GASKET, SPIRAL WOUND - 1 1/2", ANSI 600, RF, FLEXITALLIC, STYLE CGI OR EQUAL, 304 SS WINDING WITH GRAPHITE FILLER,			10		10			
		EA	STYLE CGI OR EQUAL, 304 SS WINDING WITH GRAPHITE FILLER,	6							
95	0		304 SS OUTER & INNER RING, 1/8" THK, FOR ASME B16.5 FLANGE			6		6			
55	Ü	EA	BOLT, STUD - 1 3/8" DIA. x 10 1/4" LG., THREAD TO THREAD, ALLOY STEEL, ASTM A193, GRB7, CLASS 2A, RTAHT, W/ 2 HH NUTS EACH, ASTM A194, CLASS 2B, GR 2H, FOR 14", ANSI 600, RF FLANGE (20 BOLTS PER SET) (INSULATING SET), TEFLON COATED								
102	9	EA	BOLT, STUD - 1 1/4" DIA. x 8 3/4" LG., THREAD TO THREAD, ALLOY STEEL, ASTM A193, GR B7 , CLASS 2A, RTAHT, W/ 2 HH NUTS EACH, ASTM A194, CLASS 2B, GR 2H, FOR 12", ANSI 600, RF FLANGE (20 BOLTS PER SET), TEFLON COATED				9				
101	16	EA	BOLT, STUD - 1" DIA. x 6 3/4" LG., THREAD TO THREAD, ALLOY STEEL, ASTM A193, GR B7 , CLASS 2A, RTAHT, W/ 2 HH NUTS EACH, ASTM A194, CLASS 2B, GR 2H, FOR 6", ANSI 600, RF FLANGE (12 BOLTS PER SET), TEFLON COATED				16				
103	5	EA	BOLT, STUD - 7/8" DIA. x 5 3/4" LG., THREAD TO THREAD, ALLOY STEEL, ASTM A193, GR B7 , CLASS 2A, RTAHT, W/ 2 HH NUTS EACH, ASTM A194, CLASS 2B, GR 2H, FOR 4", ANSI 600, RF FLANGE (8 BOLTS PER SET), TEFLON COATED				5				
117	0	EA EA	BOLT, STUD - 5/8" DIA. x 4 1/4" LG., THREAD TO THREAD, ALLOY STEEL, ASTM A193, GR B7, CLASS 2A, RTAHT, W/ 2 HH NUTS EACH, ASTM A194, CLASS 2B, GR 2H, FOR 2", ANSI 600, RF FLANGE (8 BOLTS PER SET), TEFLON COATED PRESSURE INDICATOR - GENERIC								