Minimizing weighted makespan in a two-machine flow shop

Author One[a,*], Author Two[b]

[a]Institution One, Location, Country

[b]Institution Two, Location, Country

Abstract

Motivated by the scheduling of perishable lots in process industries, this paper studies the two-machine flow shop problem with the maximum weighted completion time objective, also known as the weighted makespan. We establish binary NP-hardness even with two distinct weights and strong NP-hardness when the number of distinct weights is arbitrary. We further prove that an optimal schedule has a block structure, with one block per distinct weight, blocks arranged in non-increasing order of weight, and jobs within each block sequenced according to Johnson's rule. Exploiting this structure, we develop an exact dynamic programming algorithm that is pseudo-polynomial for a fixed number of distinct weights, a fully polynomial-time approximation scheme for a fixed number of distinct weights, and a polynomial-time approximation scheme when the ratio of the largest to the smallest weight is bounded. We also propose a near-linear-time two-approximation algorithm and adapt the NEH heuristic and a weight-block genetic algorithm (WBGA) for larger instances. Computational experiments on 440 small-scale and 640 large-scale instances are conducted using a mixed-integer programming model and a lower bound as benchmarks. The results show that the two-approximation algorithm is the fastest method and remains closest to the lower bound on large instances. NEH offers the best quality-cost trade-off on small instances, whereas WBGA achieves the best solution quality on large instances at a substantially higher computational cost.

Keywords: Scheduling; Two-machine flow shop; Dynamic programming; Weighted makespan;

*Corresponding author. E-mail address: author@email.com

1 Introduction

Consider a manufacturing environment in which every batch must pass through two processing stages in the same order before leaving the factory. Typical examples include mixing followed by drying, coating followed by curing, and formulation followed by sterilization. Since the first stage is typically faster, batches accumulate in the buffer between the two stages, where they continue to deteriorate in quality: enzymes remain active, microorganisms continue to grow, and thermal budgets are progressively consumed. Production scheduling models have taken this deterioration into account, either by tracking the quality of each batch as it waits (Steinbacher et al., 2023) or by trading quality against distribution decisions (Jafari Nozar and Behnamian, 2021). In these models quality enters the schedule as a constraint on which batches may wait, not as a charge on the time at which each batch completes.

The rate of quality deterioration varies across batches. A batch with ten times the sensitivity incurs ten times the quality loss under the same exposure time. Accordingly, the loss associated with a batch depends on both its sensitivity and its time in the system, rather than on time alone. The manufacturer, however, is not primarily concerned with the total quality loss across all batches. Once the loss of an individual batch exceeds an acceptable threshold, the entire batch may have to be scrapped or recalled. The resulting loss from a single batch can outweigh the cumulative losses of all other batches. Therefore, the critical concern is the batch with the largest weighted completion time, and the scheduling objective is to minimize the maximum weighted completion time.

The same structure arises beyond the food and pharmaceutical industries. In the maintenance of high-value equipment, the two stages may correspond to disassembly and inspection, with the weight representing the cost per unit of equipment downtime. In hospital diagnostics, they may correspond to medical imaging and treatment, with the weight reflecting the severity of a patient's condition. In these settings, each job incurs a cost proportional to its weight and completion time, and the objective is to minimize the maximum individual cost rather than the total cost. These applications motivate the study of the two-machine flow shop scheduling problem with the maximum weighted completion time objective.

Research on the maximum weighted completion time objective has primarily focused on single-machine and parallel-machine environments. For single-machine scheduling, approximation algorithms and polynomial-time approximation schemes have been developed in two-agent settings (Nong et al., 2011). Online variants have also received considerable attention, with competitive algorithms established for both preemptive and non-preemptive settings (Li, 2015), followed by online algorithms with best-possible competitive guarantees (Chai et al., 2018). Subsequent studies have extended these settings to incorporate no-delayed-processing constraints (Li and Liu, 2023), unexpected machine breakdowns (Guo et al., 2024), and a single restart of the jobs (Liang et al., 2024). Further research has considered

release dates, preemption, and multiple objectives in multi-agent scheduling (Yuan et al., 2020), as well as lot scheduling with the maximum weighted tardiness objective (Mosheiov and Sarig, 2023) and identical parallel machines (Sun, 2024). More recent contributions have addressed order acceptance and rejection decisions (Lu et al., 2025), lot scheduling under the same objective (Zheng et al., 2025), online scheduling on an unbounded parallel-batch machine (Zhang et al., 2025), online settings under (dis)agreeability conditions (Fan et al., 2026), and scheduling with restricted rate- or weight-modifying activities (Zuo et al., 2026a,b). Despite these advances, the maximum weighted completion time objective has received limited attention in flow shop environments, particularly in the two-machine setting. This gap motivates our investigation of the two-machine flow shop scheduling problem with the objective of minimizing the maximum weighted completion time.

The two-machine flow shop has been extensively studied since Johnson established his rule for makespan minimization (Johnson, 1954). Subsequent research has developed constructive heuristics for various flow shop settings (Shao et al., 2021), while the corresponding three-machine problem remains strongly $\mathcal{NP}$-hard (Pinedo, 2022). Other studies have investigated disruptions (Hnaien and Arbaoui, 2023), branch-and-bound algorithms (Liu and Urgo, 2024a), reentrant production (Liu and Urgo, 2024b), alternative objective functions (Shabtay and Gerstl, 2024), and distributed manufacturing environments (Tristan Becker, 2025). Meanwhile, refinements of Johnson's rule continue to attract research interest (Della Croce and Schau, 2026).

The rest of the paper is organized as follows. Section 2 fixes the notation, states the completion-time recurrence and gives the mixed integer programming formulation. Section 3 establishes the complexity of the problem. Section 4 proves the structural properties, develops the exact dynamic program, and presents the approximation schemes. Section 5 describes the 2-approximation and the two heuristics. Section 6 reports the computational study, and Section 7 concludes.

2 Problem description

Consider a set $\mathcal{J} = \{J_1, J_2, \ldots, J_n\}$ of n independent and non-preemptive jobs to be scheduled in a two-machine flow shop with machines M_1 and M_2. All jobs are released at time zero and follow the same route, $M_1 \to M_2$. For $j = 1, 2, \ldots, n$, job J_j is represented by a triple $\Phi_j = (a_j, b_j, w_j)$, where a_j and b_j are its nonnegative integer processing times on M_1 and M_2, respectively, and w_j is a positive weight reflecting its importance. Let K be the number of distinct weights. For a feasible schedule π, let $C_j^1(\pi)$ and $C_j^2(\pi)$ denote the completion times of J_j on M_1 and M_2, respectively; thus $C_j(\pi) = C_j^2(\pi)$ is its completion time. The makespan and the weighted makespan (i.e., the maximum weighted completion

time) in π are given by

$$C_{\max}(\pi) = \max_{1\le j\le n}\{C_j(\pi)\} \quad \text{and} \quad C^w_{\max}(\pi) = \max_{1\le j\le n}\{w_j C_j(\pi)\},$$

respectively. The objective is to minimize the weighted makespan $C^w_{\max}$. Using the standard 3-field scheduling notation (Pinedo, 2022), this problem is denoted by $F2 \,||\, C^w_{\max}$.

In a two-machine flow shop, a schedule is called a *permutation* schedule if the jobs are processed in the same order on both machines. Johnson (1954) showed that an optimal permutation schedule exists for $F2 \,||\, C_{\max}$. By a similar argument, an optimal permutation schedule also exists for $F2 \,||\, C^w_{\max}$. Hence, we restrict attention to permutation schedules. Let $\pi = (\pi(1), \pi(2), \ldots, \pi(n))$ denote a feasible permutation schedule for $F2 \,||\, C^w_{\max}$, where $J_{\pi(j)}$ is the j-th job in π. By simple calculation, it follows that

$$C_{\pi(j)} = \max_{1\le i\le j}\Big\{\sum_{h=1}^{i} a_{\pi(h)} + \sum_{h=i}^{j} b_{\pi(h)}\Big\}, \quad j = 1, 2, \ldots, n. \tag{1}$$

Then, the weighted makespan of π is given by

$$C^w_{\max}(\pi) = \max_{1\le j\le n}\{w_{\pi(j)} C_{\pi(j)}\}. \tag{2}$$

To formulate the problem as a mixed integer linear program (MILP), we introduce the following decision variables:

- $x_{jk} = 1$ if job J_j is the k-th job, and 0 otherwise;
- $C^1_{[k]}$ is the completion time of the k-th job on M_1;
- $C^2_{[k]}$ is the completion time of the k-th job on M_2;
- C_j is the completion time of job J_j;
- M is a sufficiently large constant (e.g., $M = \sum_{j=1}^{n}(a_j + b_j)$).

The MILP model can be formulated as follows:

$$\min \quad C^w_{\max} \tag{3}$$

$$\text{s.t.} \quad \sum_{k=1}^{n} x_{jk} = 1, \quad j = 1, 2, \ldots, n \tag{4}$$

$$\sum_{j=1}^{n} x_{jk} = 1, \quad k = 1, 2, \ldots, n \tag{5}$$

$$C^1_{[1]} = \sum_{j=1}^{n} a_j x_{j1} \tag{6}$$

$$C^1_{[k]} = C^1_{[k-1]} + \sum_{j=1}^{n} a_j x_{jk}, \quad k = 2, 3, \ldots, n \tag{7}$$

$$C^2_{[1]} = C^1_{[1]} + \sum_{j=1}^{n} b_j x_{j1} \tag{8}$$

$$C^2_{[k]} \geq C^1_{[k]} + \sum_{j=1}^{n} b_j x_{jk}, \quad k = 2, 3, \ldots, n \tag{9}$$

$$C^2_{[k]} \geq C^2_{[k-1]} + \sum_{j=1}^{n} b_j x_{jk}, \quad k = 2, 3, \ldots, n \tag{10}$$

$$C_j \geq C^2_{[k]} - M(1 - x_{jk}), \quad j = 1, 2, \ldots, n; \quad k = 1, 2, \ldots, n \tag{11}$$

$$C^w_{\max} \geq w_j C_j, \quad j = 1, 2, \ldots, n \tag{12}$$

$$x_{jk} \in \{0, 1\}, \quad j = 1, 2, \ldots, n; \quad k = 1, 2, \ldots, n \tag{13}$$

$$C_j, C^1_{[k]}, C^2_{[k]} \geq 0 \quad j = 1, 2, \ldots, n; \quad k = 1, 2, \ldots, n \tag{14}$$

The objective is to minimize $C^w_{\max}$, as expressed in (3). Constraints (4) and (5) assign each job to exactly one position and each position to exactly one job. Constraints (6) and (7) determine the completion times on M_1, and (8) through (10) determine those those on M_2. In particular, for $k \geq 2$, the job in position k can start on M_2 only after it has completed M_1 and the preceding job has finished on M_2. Constraint (11) relates the position-based completion times to the job-based ones via a big-M formulation. Note that when $x_{jk} = 1$ (i.e., J_j is assigned to the k-th position), it requires $C_j \geq C^2_{[k]}$; when $x_{jk} = 0$, it is inactive, since $C^2_{[k]} - M \leq 0$ and $C_j \geq 0$. Constraint (12) imposes $WC_{\max} \geq w_j C_j$ for each job, so minimizing $C^w_{\max}$ yields the optimal objective value of (2). Constraints (13) and (14) require the decision variables x_{jk} to be binary and the completion times nonnegative.

3 Computational complexity

When $K = 1$ (i.e., all jobs have equal weights), $F2 \mid\mid C^w_{\max}$ reduces to $F2 \mid\mid C_{\max}$, which is solvable in $O(n \log n)$ time (Johnson, 1954). In contrast, We show that $F2 \mid\mid C^w_{\max}$ is binary $\mathcal{NP}$-hard even with only two distinct weights and strongly $\mathcal{NP}$-hard when K is arbitrary.

Theorem 3.1. *$F2 \mid\mid C^w_{\max}$ is binary $\mathcal{NP}$-hard even with only two distinct weights.*

Proof. To establish the result, we give a polynomial-time reduction from Partition, which is $\mathcal{NP}$-complete in the ordinary sense (Garey and Johnson, 1979).

Partition: Given r positive integers $x_1, x_2, \ldots, x_r$ and an integer X with $\sum_{i=1}^{r} x_i = 2X$, does there exist a partition of $\{1, 2, \ldots, r\}$ into two disjoint subsets $\mathcal{X}_1$ and $\mathcal{X}_2$ such that $\sum_{i \in \mathcal{X}_1} x_i = \sum_{i \in \mathcal{X}_2} x_i = X$?

Given an arbitrary instance $(x_1, x_2, \ldots, x_r; X)$ of Partition, we construct an instance of $F2 \mid\mid C^w_{\max}$ with $n = r + 1$ jobs. For $j = 1, 2, \ldots, n-1$, job J_j has $a_j = 1$, $b_j = rx_j$, and $w_j = X + 1$; job J_n has $a_n = rX$, $b_n = 1$, and $w_n = 2X + 1$. Set the threshold to $Y = r(X + 1)(2X + 1)$. The question is whether there exists a schedule with $C^w_{\max} \leq Y$.

We demonstrate that $F2 \mid\mid WC_{\max}$ has a feasible schedule π with $C^w_{\max}(\pi) \leq Y$ if and only if PARTITION has a solution.

Suppose that PARTITION admits a solution $(\mathcal{X}_1, \mathcal{X}_2)$ with $\sum_{j\in\mathcal{X}_1} x_j = \sum_{j\in\mathcal{X}_2} x_j = X$. Define $\mathcal{J}_1 = \{J_j : j \in \mathcal{X}_1\}$ and $\mathcal{J}_2 = \{J_{r+j} : j \in \mathcal{X}_2\}$. We build a feasible permutation schedule π in which both machines process the jobs in the order $\mathcal{J}_1 \to J_n \to \mathcal{J}_2$, with the jobs in $\mathcal{J}_1$ and $\mathcal{J}_2$ processed in arbitrary order (see Figure 1).




Figure 1: A feasible permutation scheule π

Since $a_j \leq b_j$ for each $j = 1, 2, \ldots, r$ and $|\mathcal{X}_1| \leq r-1$, it can be easily verified that $C_n(\pi) = rX + |\mathcal{X}_1| + 1 \leq r(X+1)$ and $C_{\max}(\pi) = 2rX + |\mathcal{X}_1| + 1 \leq r(2X+1)$. Hence, $C^w_{\max}(\pi) \leq r(X+1)(2X+1) = Y$.

Conversely, suppose that $F2 \mid\mid C^w_{\max}$ admits a feasible schedule π with $C^w_{\max}(\pi) \leq Y$. Let $\mathcal{J}_1 = \{J_j : C_j(\pi) < C_n(\pi)\}$ and $\mathcal{J}_2 = \{J_j : C_j(\pi) > C_n(\pi)\}$ be the sets of jobs completed before and after J_n in π, respectively, and let $\mathcal{X}_1 = \{j : J_j \in \mathcal{J}_1\}$ and $\mathcal{X}_2 = \{j : J_j \in \mathcal{J}_2\}$. By (1), we have

$$C_n(\pi) \geq \sum_{j\in\mathcal{X}_1} a_j + a_n + 1 = |\mathcal{X}_1| + rX + 1 \tag{15}$$

and

$$C_n(\pi) \geq a_{\pi(1)} + \sum_{j\in\mathcal{X}_1} b_j + b_n = r\sum_{j\in\mathcal{X}_1} x_j + 2. \tag{16}$$

Case 1. If $\sum_{j\in\mathcal{X}_1} x_j > X$, then $\sum_{j\in\mathcal{X}_1} x_j \geq X+1$ because the x_j are integers. By (16), $WC_{\max}(\pi) \geq w_n C_n(\pi) \geq (2X+1)(r(X+1)+2) > r(X+1)(2X+1) = Y$, contradicting the assumption that $C^w_{\max}(\pi) \leq Y$.

Case 2. If $\sum_{j\in\mathcal{X}_1} x_j < X$, then $\sum_{j\in\mathcal{X}_1} x_j \leq X-1$ because the x_j are integers. Since $(\mathcal{X}_1, \mathcal{X}_2)$ is a partition of $\{1, 2, \ldots, r\}$, we have

$$\sum_{j\in\mathcal{X}_2} x_j = 2X - \sum_{j\in\mathcal{X}_1} x_j \geq X+1. \tag{17}$$

By (1), (15), and (17), we have

$$C_{\pi(n)}(\pi) = C_{\max}(\pi) \geq C_n(\pi) + \sum_{j\in\mathcal{X}_2} b_j \geq |\mathcal{X}_1| + rX + 1 + r\sum_{j\in\mathcal{X}_2} x_j \geq r(2X+1) + 1. \tag{18}$$

Using $w_{\pi(n)} = 1$, (18) yields

$$C^w_{\max}(\pi) \geq w_{\pi(n)} C_{\pi(n)}(\pi) \geq (X+1)(r(2X+1)+1) > r(X+1)(2X+1) = Y,$$

This contradicts the assumption that $C^w_{\max}(\pi) \leq Y$.

Combining the above two cases, we obtain that $\sum_{j\in\mathcal{X}_1} x_j = \sum_{j\in\mathcal{X}_2} x_j = X$. Therefore, $(\mathcal{X}_1, \mathcal{X}_2)$ is a solution to PARTITION. □

Theorem 3.2. *$F2 \,||\, C^w_{\max}$ is strongly $\mathcal{NP}$-hard when K is arbitrary.*

Proof. To establish the result, we give a polynomial-time reduction from 3-PARTITION, which is strongly $\mathcal{NP}$-complete (Garey and Johnson, 1979).

3-PARTITION: Given $3r$ positive integers $x_1, x_2, \ldots, x_{3r}$ and an integer X with $\sum_{i=1}^{3r} x_i = rX$ and $\frac{X}{4} < x_j < \frac{X}{2}$ for each $j = 1, 2, \ldots, 3r$, does there exist a partition of $\{1, 2, \ldots, 3r\}$ into m disjoint subsets $\mathcal{X}_1, \mathcal{X}_2, \ldots, \mathcal{X}_r$ such that $\sum_{j\in\mathcal{X}_i} x_j = X$ for $i = 1, 2, \ldots, r$?

Given an arbitrary instance $(x_1, x_2, \ldots, x_{3r}; X)$ of 3-PARTITION, we construct an instance of $F2 \,||\, C^w_{\max}$ consisting of r separating jobs and $3r$ basic jobs. For $j = 1, 2, \ldots, r$, separating job J_j has $a_j = 4X$, $b_j = X$, and $w_j = \frac{5r+4}{5j}$; for $j = r+1, r+2, \ldots, 4r$, basic job J_j has $a_j = x_{j-r}$, $b_j = 4x_{j-r}$, and $w_j = 1$. Set the threshold to $Y = (5r+4)X$. The question is whether there exists a schedule with $WC_{\max} \leq Y$.

We demonstrate that $F2 \,||\, C^w_{\max}$ has a feasible schedule π with $C^w_{\max}(\pi) \leq Y$ if and only if 3-PARTITION has a solution.

Suppose that 3-PARTITION admits a solution $(\mathcal{X}_1, \mathcal{X}_2, \ldots, \mathcal{X}_r)$, so that $\sum_{j\in\mathcal{X}_i} x_j = X$ and $|\mathcal{X}_i| = 3$ for all i. Let $\mathcal{J}_i = \{J_{r+j} : j \in \mathcal{X}_i\}$ for $i = 1, 2, \ldots, r$. We build a feasible permutation schedule π in which both machines process the jobs in the order

$$J_1 \to \mathcal{J}_1 \to J_2 \to \mathcal{J}_2 \to \cdots \to J_r \to \mathcal{J}_r,$$

with the jobs in each $\mathcal{J}_i$ processed in arbitrary order (see Figure 2).




Figure 2: A feasible permutation scheule π

According to Figure 2, it can be easily verified that $C_j(\pi) = 5jX$ for $j = 1, 2, \ldots, r$, and $C_j(\pi) \leq C_{\max}(\pi) = (5r+4)X$ for $j = r+1, r+2, \ldots, 4r$. Then $w_j C_j(\pi) = (5r+4)X = Y$

for $j = 1, 2, \ldots, r$, and $w_j C_j(\pi) \le w_j C_{\max}(\pi) = (5r+4)X = Y$ for $j = r+1, r+2, \ldots, 4r$. Hence, $C^w_{\max}(\pi) \le Y$.

Conversely, suppose that $F2 \mid\mid C^w_{\max}$ admits a feasible schedule π with $C^w_{\max}(\pi) \le Y$. Because all separating jobs have the same processing time on M_1 and M_2 and weights $w_1 > w_2 > \cdots > w_r$, a standard interchange argument lets us assume they appear in π in decreasing order of weight.

Claim 1. $C_{\max}(\pi) \le Y = (5r+4)X$.

Proof of Claim 1. Since $w_j \ge 1$ for all $1 \le j \le 4r$, we have $C_{\max}(\pi) \le C^w_{\max}(\pi) \le Y = (5r+4)X$. ■

Claim 2. J_1 is the first job scheduled in π.

Proof of Claim 2. Since $C^w_{\max}(\pi) \le Y = (5r+4)X$ and $w_1 = \frac{5r+4}{5}$, we have $a_1 + b_1 \le C_1(\pi) \le \frac{C^w_{\max}(\pi)}{w_1} \le 5X = a_1 + b_1$. This means that J_1 is the first job scheduled in π. ■

For $i = 1, 2, \ldots, r-1$, let $\mathcal{B}_i = \{J_j : C_i(\pi) < C_j(\pi) < C_{i+1}(\pi)\}$ be the set of basic jobs scheduled between J_i and J_{i+1} in π, and let $\mathcal{B}_r = \{J_j : C_j(\pi) > C_r(\pi)\}$ be the set of basic jobs scheduled after J_r. For $i = 1, 2, \ldots, r$, define $\mathcal{X}_i = \{j - r : J_j \in \mathcal{B}_i\}$. Then, by Claim 2, π can be written as

$$\pi = (J_1 \to \mathcal{B}_1 \to J_2 \to \mathcal{B}_2 \to \cdots \to J_r \to \mathcal{B}_r). \tag{19}$$

Since $(\mathcal{X}_1, \mathcal{X}_2, \ldots, \mathcal{X}_r)$ is a partition of $\{1, 2, \ldots, 3r\}$, we have

$$\sum_{i=1}^{r} \sum_{j \in \mathcal{X}_i} x_j = \sum_{j=1}^{3r} x_j = rX. \tag{20}$$

Claim 3. For $k = 1, 2, \ldots, r-1$, $\sum_{i=1}^{k} \sum_{j \in \mathcal{X}_i} x_j \le kX$.

Proof of Claim 3. Suppose to the contrary that there exists some m $(1 \le m \le r-1)$ with $\sum_{i=1}^{m} \sum_{j \in \mathcal{X}_i} x_j > mX$. Since the x_j are integers, this implies

$$\sum_{i=1}^{m} \sum_{j \in \mathcal{X}_i} x_j \ge mX + 1. \tag{21}$$

Because $a_j = 4X$ and $b_j = X$ for $1 \le j \le r$, and $a_j = x_{j-r}$ for $r+1 \le j \le 4r$, (1), (19), and (21) give

$$C_{m+1}(\pi) \ge \sum_{j=1}^{m+1} a_j + \sum_{i=1}^{m} \sum_{j \in \mathcal{B}_i} a_j + b_{m+1} = 4(m+1)X + \sum_{i=1}^{m} \sum_{j \in \mathcal{X}_i} x_j + X \ge 5(m+1)X + 1. \tag{22}$$

Using $w_{m+1} = \frac{5r+4}{5(m+1)}$, (22) yields

$$C^w_{\max}(\pi) \ge w_{m+1} C_{m+1}(\pi) \ge \frac{5r+4}{5(m+1)}(5(m+1)X + 1) > (5r+4)X = Y, \tag{23}$$

which contradicts the assumption that $C^w_{\max}(\pi) \le Y$. Hence, Claim 3 holds. ■

Claim 4. For $k = 1, 2, \ldots, r-1$, $\sum_{i=1}^{k} \sum_{j \in \mathcal{X}_i} x_j \ge kX$.

Proof of Claim 4. Suppose to the contrary that there exists some m $(1 \le m \le r-1)$ with $\sum_{i=1}^{m} \sum_{j \in \mathcal{X}_i} x_j < mX$. By (20) and the x_j are integers, we have

$$\sum_{i=m+1}^{r} \sum_{j \in \mathcal{X}_i} x_j = rX - \sum_{i=1}^{m} \sum_{j \in \mathcal{X}_i} x_j \ge (r-m)X + 1. \tag{24}$$

Because $a_j = 4X$ and $b_j = X$ for $1 \le j \le r$, and $a_j = x_{j-r}$ and $b_j = 4x_{j-r}$ for $r+1 \le j \le 4r$, (1), (19), (20), and (24) give

$$\begin{aligned}
C_{\max}(\pi) &\ge \sum_{j=1}^{m+1} a_j + \sum_{i=1}^{m} \sum_{j \in \mathcal{B}_i} a_j + \sum_{j=m+1}^{r} b_j + \sum_{i=m+1}^{r} \sum_{j \in \mathcal{B}_i} b_j \\
&= 4(m+1)X + \sum_{i=1}^{m} \sum_{j \in \mathcal{X}_i} x_j + (r-m)X + \sum_{i=m+1}^{r} \sum_{j \in \mathcal{X}_i} 4x_j \\
&= 4(m+1)X + (r-m)X + rX + 3 \sum_{i=m+1}^{r} \sum_{j \in \mathcal{X}_i} x_j \\
&\ge 4(m+1)X + (r-m)X + rX + 3((r-m)X + 1) \\
&= (5r+4)X + 3 > (5r+4)X = Y.
\end{aligned}$$

which contradicts Claim 1. Hence, Claim 4 holds. ■

Combining Claims 3 and 4 with (20), we obtain that $\sum_{j \in \mathcal{X}_i} x_j = X$ for $i = 1, 2, \ldots, r$. Since $X/4 < x_j < X/2$ for each j, a sum equal to X must contain exactly three elements; hence $|\mathcal{X}_i| = 3$ for each i. Therefore, $(\mathcal{X}_1, \mathcal{X}_2, \ldots, \mathcal{X}_r)$ is a solution to 3-PARTITION. □

4 Fixed number of weights

In this section, we focus on the case where the number of weights K is fixed, i.e., $K = O(1)$. For $K = 1$, the problem is exactly $F2 \,||\, C_{\max}$, which Johnson's rule solves in $O(n \log n)$ time (Johnson, 1954); the rule is summarized in Algorithm 1. For $K = 2$, the problem $F2 \,||\, C^w_{\max}$ is already binary $\mathcal{NP}$-hard (Theorem 3.1). For fixed K, we develop an exact DP algorithm running in pseudo-polynomial time and derive an FPTAS from it.

Algorithm 1: Johnson's rule for $F2 \,||\, C_{\max}$

Input: Job set $\mathcal{J}$; job parameters a_j and b_j for $j = 1, 2, \ldots, n$.

1 **Step 1.** Partition $\mathcal{J}$ into two sets $\mathcal{J}^1 = \{J_j : a_j \le b_j\}$ and $\mathcal{J}^2 = \{J_j : a_j > b_j\}$.

2 **Step 2.** Order the jobs in $\mathcal{J}^1$ in nondecreasing order of a_j, followed by those in $\mathcal{J}^2$ in nondecreasing order of b_j.

3 **Step 3.** Process the jobs in this order on M_1 and then on M_2, yielding the permutation schedule π.

Output: The resulting schedule π.

Let $W_1 > W_2 > \cdots > W_K$ denote the distinct weights of the n jobs, and let $\mathcal{G}_k = \{J_j \in \mathcal{J} : w_j = W_k\}$ be set of jobs having weight W_k, $k = 1, 2, \ldots, K$.

4.1 Block structure of an optimal schedule

To establish the key structural lemma, we first introduce some notation for partitioning a permutation schedule into blocks.

Definition 4.1. ***(Block partition)*** *Let $\pi = (\pi(1), \pi(2), \ldots, \pi(n))$ be a permutation schedule. Set $\ell_0 = 0$ and $\mathcal{R}_1 = \mathcal{J}$. For $k = 1, 2, \ldots, K$, if $\mathcal{R}_k \cap \mathcal{G}_k \neq \emptyset$, define $\ell_k = \max\{j : J_{\pi(j)} \in \mathcal{R}_k \cap \mathcal{G}_k\}$, $\mathcal{B}_k^\pi = \{J_{\pi(\ell_{k-1}+1)}, J_{\pi(\ell_{k-1}+2)}, \ldots, J_{\pi(\ell_k)}\}$, and $\mathcal{R}_{k+1} = \mathcal{J} \setminus \bigcup_{i=1}^{k} \mathcal{B}_i^\pi$. Otherwise, set $\ell_k = \ell_{k-1}$, $\mathcal{B}_k^\pi = \emptyset$, and $\mathcal{R}_{k+1} = \mathcal{R}_k$. Then we call $\mathcal{B}(\pi) = (\mathcal{B}_1^\pi, \mathcal{B}_2^\pi, \ldots, \mathcal{B}_K^\pi)$ the block partition of π.*

Thus, ℓ_k is the position of the last job in $\mathcal{R}_k$ of weight W_k, $\mathcal{B}_k^\pi$ is the k-th block (possibly empty), and $\mathcal{R}_k$ is the set of jobs left after removing the first $k-1$ blocks. By construction, every nonempty block $\mathcal{B}_k^\pi$ ends with a job of weight W_k (i.e., $w_{\pi(\ell_k)} = W_k$), and all jobs in the block have weight at most W_k, i.e., $w_{\pi(j)} \leq W_k$ for all $\ell_{k-1} + 1 \leq j \leq \ell_k$. This means that

$$W_k C_{\pi(\ell_k)}(\pi) = \max\{w_{\pi(j)} C_{\pi(j)}(\pi) : \ell_{k-1} + 1 \leq j \leq \ell_k\}. \tag{25}$$

Consequently, (2) can be reformulated as

$$C_{\max}^w(\pi) = \max_{1 \leq k \leq K} \{W_k C_{\pi(\ell_k)(\pi)}\}. \tag{26}$$

Definition 4.2. ***(Regular block and regular permutation schedule)*** *Let $\pi = (\pi(1), \pi(2), \ldots, \pi(n))$ be a permutation schedule with block partition $\mathcal{B}(\pi) = (\mathcal{B}_1^\pi, \mathcal{B}_2^\pi, \ldots, \mathcal{B}_K^\pi)$. A block $\mathcal{B}_k^\pi$ is called regular if it is empty or if the sequence of its jobs in π matches the sequence obtained by applying Johnson's rule to that block. The schedule π is called regular if all blocks $\mathcal{B}_1^\pi, \mathcal{B}_2^\pi, \ldots, \mathcal{B}_K^\pi$ are regular.*

To illustrate the block partition, we give a small numerical example for $F2 \mid\mid C_{\max}^w$.

Example 4.1. *Consider a six-job instance of $F2 \mid\mid C_{\max}^w$ whose job data are given in Table 1, and let $\pi = (1, 2, \ldots, 6)$ be a permutation schedule.*

Table 1: Job data for Example 4.1

	J_1	J_2	J_3	J_4	J_5	J_6
a_j	2	5	6	8	2	3
b_j	5	3	9	4	3	3
w_j	2	3	5	2	3	2

In Example 4.1, we have $K = 3$, $\mathcal{G}_1 = \{J_3\}$, $\mathcal{G}_2 = \{J_2, J_5\}$, and $\mathcal{G}_3 = \{J_1, J_4, J_6\}$. The resulting blocks are $\mathcal{B}_1^\pi = \{J_1, J_2, J_3\}$, $\mathcal{B}_2^\pi = \{J_4, J_5\}$, and $\mathcal{B}_3^\pi = \{J_6\}$ (see Figure 3). By (26), the weighted makespan of π is $C_{\max}^w(\pi) = \max\{5 \times 22, 3 \times 29, 2 \times 32\} = 110$.




Figure 3: A block partition of π

Given a permutation schedule $\pi = (\pi(1), \pi(2), \ldots, \pi(n))$, for $1 \le g \le h \le n$, define

$$C_{\max}^w(\pi)[g:h] = \max_{g \le j \le h} \{w_{\pi(j)} C_{\pi(j)}(\pi)\}$$

as the maximum weighted completion time over the jobs $J_{\pi(g)}, J_{\pi(g+1)}, \ldots, J_{\pi(h)}$.

The following lemma shows that if the jobs in each block of π are rescheduled in accordance with Johnson's rule, the resulting permutation schedule π' has objective value no larger than that of π, i.e., $C_{\max}^w(\pi') \le C_{\max}^w(\pi)$.

Lemma 4.1. *Given a permutation schedule π and its block partition $\mathcal{B}(\pi) = (\mathcal{B}_1^\pi, \mathcal{B}_2^\pi, \ldots, \mathcal{B}_K^\pi)$, let π_k be the permutation of $\mathcal{B}_k^\pi$ obtained by Johnson's rule for $k = 1, 2, \ldots, K$. Then the schedule π' formed by concatenating $\pi_1, \pi_2, \ldots, \pi_K$ satisfies $C_{\max}^w(\pi') \le C_{\max}^w(\pi)$.*

Proof. First, if $\mathcal{B}_k^\pi \neq \emptyset$, then rescheduling the jobs in $\mathcal{B}_k^\pi$ according to Johnson's rule does not change the set of jobs assigned to positions $\ell_{k-1} + 1, \ell_{k-1} + 2, \ldots, \ell_k$, i.e.,

$$\mathcal{B}_k^\pi = \{J_{\pi(\ell_{k-1}+1)}, J_{\pi(\ell_{k-1}+2)}, \ldots, J_{\pi(\ell_k)}\} = \{J_{\pi'(\ell_{k-1}+1)}, J_{\pi'(\ell_{k-1}+2)}, \ldots, J_{\pi'(\ell_k)}\}. \tag{27}$$

Thus, in π', the jobs in $\mathcal{B}_k^\pi$ still occupy this same index interval. By (25), we have

$$C_{\max}^w(\pi)[\ell_{k-1} + 1 : \ell_k] = W_k C_{\pi(\ell_k)}(\pi) = w_{\pi(\ell_k)} C_{\pi(\ell_k)}(\pi), k = 1, 2, \ldots, K. \tag{28}$$

Moreover, by (27), for $k = 1, 2, \ldots, K$, $\mathcal{B}_k^\pi$ has the same completion time on M_1 under π and π', i.e., $C_{\pi'(\ell_k)}^1(\pi') = C_{\pi(\ell_k)}^1(\pi) = \sum_{j=1}^{\ell_k} a_{\pi(j)}$.

Second, we prove by induction on k that, for all $k = 1, 2, \ldots, K$,

$$C_{\pi'(\ell_k)}(\pi') \le C_{\pi(\ell_k)}(\pi) \text{ and } C_{\max}^w(\pi')[\ell_{k-1} + 1 : \ell_k] \le C_{\max}^w(\pi)[\ell_{k-1} + 1 : \ell_k]. \tag{29}$$

For the base case $i = 1$, both machines are available at time zero. Rescheduling the jobs in $\mathcal{B}_1^\pi$ according to Johnson's rule gives $C_{\pi'(\ell_1)}(\pi') \le C_{\pi(\ell_1)}(\pi)$. Since π' only permutes the

jobs in $\mathcal{B}_1^\pi$, we have $w_{\pi'(j)} \le W_1$ for $j = 1, 2, \ldots, \ell_1$. Hence, we have

$$C^w_{\max}(\pi')[1:\ell_1] = \max_{1\le j\le \ell_1}\{w_{\pi'(j)}C_{\pi'(j)}(\pi')\} \le W_1 C_{\pi'(\ell_1)}(\pi') \le W_1 C_{\pi(\ell_1)}(\pi) = C^w_{\max}(\pi)[1:\ell_1],$$

where the last equality follows from (28)

Assume that (29) holds for all $i = 1, 2, \ldots, k$. We now prove the $(k+1)$-block. If $\mathcal{B}_{k+1}^\pi = \emptyset$, the assertion is immediate. It remains to consider $\mathcal{B}_{k+1}^\pi \neq \emptyset$. In this case, in π', by the inductive hypothesis, M_1 becomes available at time $C^1_{\pi'(\ell_k)}(\pi') = C^1_{\pi(\ell_k)}(\pi)$, and M_2 is available at time $C_{\pi'(\ell_k)}(\pi') \le C_{\pi(\ell_k)}(\pi)$. We introduce a dummy job J_0 with processing times $a_0 = 0$ and $b_0 = C_{\pi'(\ell_k)}(\pi') - C^1_{\pi'(\ell_k)}(\pi')$, and apply Johnson's rule to schedule the jobs in $\mathcal{B}_{k+1}^\pi \cup \{J_0\}$, with both machines available from time $C^1_{\pi'(\ell_k)}(\pi')$. Because $a_0 = 0$, J_0 is scheduled in the first position according to Johnson's rule, and it completes at time $C_{\pi'(\ell_k)}(\pi')$. By positioning the dummy job in this way, the jobs in $\mathcal{B}_{k+1}^\pi$ can be scheduled on M_2 without overlapping with the previously scheduled jobs in $\mathcal{B}_1^\pi \cup \mathcal{B}_2^\pi \cup \cdots \cup \mathcal{B}_k^\pi$. Since the jobs in $\mathcal{B}_{k+1}$ are scheduled according to Johnson's rule, it follows that $C_{\pi'(\ell_{k+1})}(\pi') \le C_{\pi(\ell_{k+1})}(\pi)$. Moreover, since π' only permutes the jobs in $\mathcal{B}_{k+1}^\pi$, we have $w_{\pi'(j)} \le W_{k+1}$ for $j = \ell_k + 1, \ell_k + 2, \ldots, \ell_{k+1}$. Hence,

$$\begin{aligned} C^w_{\max}(\pi')[\ell_k+1:\ell_{k+1}] &= \max_{\ell_k+1\le j\le \ell_{k+1}}\{w_{\pi'(j)}C_{\pi'(j)}(\pi')\} \le W_{k+1}C_{\pi'(\ell_{k+1})}(\pi') \\ &\le W_{k+1}C_{\pi(\ell_{k+1})}(\pi) = C^w_{\max}(\pi)[\ell_k+1:\ell_{k+1}], \end{aligned}$$

where the last equality follows from (28). This completes the inductive step.

Note that $C^w_{\max}(\pi') = \max_{1\le k\le K}\{C^w_{\max}(\pi')[\ell_{k-1}+1:\ell_k]\}$ and $C^w_{\max}(\pi) = \max_{1\le k\le K}\{C^w_{\max}(\pi)[\ell_{k-1}+1:\ell_k]\}$. Hence, (29) yields $C^w_{\max}(\pi') \le C^w_{\max}(\pi)$. □

To illustrate Lemma 4.1, consider Example 4.1. Given π and its block partition $\mathcal{B}(\pi) = (\mathcal{B}_1^\pi, \mathcal{B}_2^\pi, \mathcal{B}_3^\pi)$, we apply Johnson's rule independently within each block $\mathcal{B}_k^\pi$, $k = 1, 2, 3$, obtaining a permutation π_k of the jobs in that block. Concatenating π_1, π_2, π_3 gives $\pi' = (1, 3, 2, 5, 4, 6)$, with blocks $\mathcal{B}_1^{\pi'} = \{J_1, J_3\}$, $\mathcal{B}_2^{\pi'} = \{J_2, J_5\}$, and $\mathcal{B}_3^{\pi'} = \{J_4, J_6\}$ (see Figure 4). By (26), the weighted makespan of π' is $C^w_{\max}(\pi') = \max\{5\times 17, 3\times 23, 2\times 30\} = 85$.




Figure 4: An applicaiton of Lemma 4.1 to π

Lemma 4.2. *For $F2 \,||\, C^w_{\max}$, there exists an optimal permutation schedule that is regular.*

Proof. Let π be an optimal permutation schedule for $F2 \mid\mid C^w_{\max}$. If π is regular, the lemma follows. Otherwise, let $\mathcal{B}(\pi) = (\mathcal{B}^\pi_1, \mathcal{B}^\pi_2, \ldots, \mathcal{B}^\pi_K)$ be its block partition. Apply Johnson's rule within each block $\mathcal{B}^\pi_k$ $(k = 1, 2, \ldots, K)$ to obtain a permutation π_k, and concatenate $\pi_1, \pi_2, \ldots, \pi_K$ to form a permutation schedule π'. By Lemma 4.1, $C^w_{\max}(\pi') \leq C^w_{\max}(\pi)$. Since π is optimal, π' is optimal as well.

If π' is regular, the lemma follows. Otherwise, repeat the above procedure with π' in place of π. For termination, suppose the first i blocks of the current schedule are already regular (initially $i = 0$). By definition, applying Johnson's rule to a regular block leaves its job sequence unchanged. Hence, the first i blocks remain unchanged. The $(i+1)$-th block in the resulting schedule may contain a different job set, but it satisfies Johnson's rule. Thus the first $i+1$ blocks are regular, so every application increases the number of leading regular blocks by at least one. Since there are at most K nonempty blocks in each schedule, the procedure terminates after at most K iterations and yields an optimal regular schedule. □

Let π be a regular permutation schedule for $F2 \mid\mid C^w_{\max}$ with block partition $\mathcal{B}(\pi) = (\mathcal{B}^\pi_1, \mathcal{B}^\pi_2, \ldots, \mathcal{B}^\pi_K)$. For each $k = 1, 2, \ldots, K$, let π_k denote the schedule obtained by processing the jobs in $\mathcal{B}^\pi_k$ consecutively from time zero in accordance with Johnson's rule. Note that π coincides with the schedule obtained by concatenating $\pi_1, \pi_2, \ldots, \pi_K$. This representation allows us to compute $C_{\max}(\pi)$ and $C^w_{\max}(\pi)$ from parameters defined for each π_k. Specifically, for each k, let $A_k = A(\pi_k)$ and $B_k = B(\pi_k)$ denote the total processing times of the jobs in π_k on M_1 and M_2, respectively, and let $C_k = C(\pi_k)$ denote the makespan of π_k. Given these parameters, we describe an procedure for computing $C_{\max}(\pi)$ and $C^w_{\max}(\pi)$. The procedure starts with π_1 and successively appends $\pi_2, \pi_3, \ldots, \pi_K$ in that order. For $k = 1, 2, \ldots, K$, let $\pi[1:k]$ denote the schedule obtained by concatenating $\pi_1, \pi_2, \ldots, \pi_k$; thus $\pi = \pi[1:K]$. The makespan and weighted makespan of $\pi[1:k]$ are computed recursively. For convenience, set $C_{\max}(\pi[1:0]) = C^w_{\max}(\pi[1:0]) = 0$. For $k = 1, 2, \ldots, K$, by direct calculation and induction on k, we have

$$\begin{aligned} C_{\max}(\pi[1:k]) &= \max\Big\{ \sum_{i=1}^{k-1} A_i + C_k, C_{\max}(\pi[1:k-1]) + B_k \Big\} \\ &= \max_{0 \leq h \leq k-1} \Big\{ \sum_{i=1}^{h} A_i + C_{h+1} + \sum_{i=h+2}^{k} B_i \Big\} \end{aligned} \tag{30}$$

and

$$\begin{aligned} C^w_{\max}(\pi[1:k]) &= \max\{C^w_{\max}(\pi[1:k-1]), W_k C_{\max}(\pi[1:k])\} \\ &= \max_{1 \leq h \leq k} \{W_h C_{\max}(\pi[1:h])\}. \end{aligned} \tag{31}$$

Hence, $C^w_{\max}(\pi) = C^w_{\max}(\pi[1:K])$.

4.2 An exact DP algorithm

Recall that $W_1 > W_2 > \cdots W_K$. For each job J_j $(j = 1, 2, \ldots, n)$, let $g_j \in \{1, 2, \ldots, K\}$ be the index such that $w_j = W_{g_j}$, i.e., $J_j \in \mathcal{G}_{g_j}$. Assume that the jobs in $\mathcal{J}$ are indexed in accordance with Johnson's rule.

Building on the preceding discussion in Section 4.1, we develop an exact DP algorithm for $F2 \mid\mid C^w_{\max}$. It generates a sequence of sets $\mathcal{H}_0, \mathcal{H}_1, \ldots, \mathcal{H}_n$. Each $\mathcal{H}_j$ consists of K-tuples $(X_1, X_2, \ldots, X_K)$, where $X_k = (A_k, B_k, C_k, L_k)$ for $k = 1, 2, \ldots, K$. A tuple in $\mathcal{H}_j$ $(j = 1, 2, \ldots, n)$ encodes an assignment of jobs $J_1, J_2, \ldots, J_j$ to K schedules (i.e., blocks) $\pi_1(j), \pi_2(j), \ldots, \pi_K(j)$, with jobs in each schedule processed from time zero in increasing order of their indices. For each schedule $\pi_k(j)$, A_k and B_k are the total processing times on M_1 and M_2, respectively, and C_k and L_k are the makespan of $\pi_k(j)$ and the weight of its last job.

Initially, $\mathcal{H}_0$ consists of a single tuple, all of whose $4K$ entries are zero, i.e., $\mathcal{H}_0 = \{\big(\underbrace{(0,0,0,0),\ldots,(0,0,0,0)}_{K \text{ copies}}\big)\}$. In the j-th iteration $(j = 1, 2, \ldots, n)$, $\mathcal{H}_j$ is constructed from $\mathcal{H}_{j-1}$. For each tuple $(X_1, X_2, \ldots, X_K) \in \mathcal{H}_{j-1}$, with $X_k = (A_k, B_k, C_k, L_k)$ for $k = 1, 2, \ldots, K$, the definition of g_j and Lemma 4.2 together imply that this tuple generates g_j new tuples in $\mathcal{H}_j$. If $k \le g_j$, appending J_j to $\pi_k(j-1)$ yields the new tuple $(X_1, \ldots, X_{k-1}, X'_k, X_{k+1}, \ldots, X_K)$ into $\mathcal{H}_j$, where $X'_k = (A'_k, B'_k, C'_k, L'_k)$ is given by

$$A'_k = A_k + a_j,\ B'_k = B_k + b_j,\ C'_k = \max\{C_k, A_k + a_j\} + b_j,\ L'_k = w_j. \tag{32}$$

The following lemma will be used to remove dominated tuples during the tuple generation, which can be easily verified.

Lemma 4.3. *Let $X = (X_1, X_2, \ldots, X_K)$ and $X' = (X'_1, X'_2, \ldots, X'_K)$ be two tuples in $\mathcal{H}_j$, with $X_k = (A_k, B_k, C_k, L_k)$ and $X'_k = (A'_k, B'_k, C'_k, L'_k)$ for $k = 1, 2, \ldots, K$. If*

$$A_k = A'_k,\ B_k = B'_k,\ C_k = C'_k,\ L_k = L'_k\ (k = 1, 2, \ldots, K-1),$$

$L_K = L'_K$, and $C_K \le C'_K$, then X' is dominated by X and can therefore be deleted from $\mathcal{H}_j$.

By Lemma 4.2, it suffices to consider regular permutation schedules. Therefore, once $\mathcal{H}_n$ has been generated, we discard every tuple $(X_1, X_2, \ldots, X_K)$ with $L_k \notin \{0, W_k\}$ for some k, since concatenating the schedules corresponding to $X_1, X_2, \ldots, X_K$ cannot yield a regular schedule. This does not affect our search for the optimal solution. Then, for each retained tuple in $\mathcal{H}_n$, we compute the makespan and weighted makespan according to (30) and (31), respectively.

Summarizing the above analysis and utilizing Lemma 4.2 and Lemma 4.3, the following algorithm is developed to solve $F2 \mid\mid C^w_{\max}$.

Algorithm 2: An exact DP algorithm for $F2 \mid\mid C^w_{\max}$

Input: Job set $\mathcal{J}$; job parameters a_j, b_j, w_j, and g_j for $j = 1, 2, \ldots, n$, K distinct weights with $W_1 > W_2 > \cdots > W_K$.

Step 1. [Preprocessing] Renumber jobs in $\mathcal{J}$ according to Johnson' rule (Algorithm 1).

Step 2. [Initialization] Set $\mathcal{H}_0 = \{\big(\underbrace{(0,0,0,0),\ldots,(0,0,0,0)}_{K \text{ copies}}\big)\}$, and $\mathcal{H}_j = \emptyset$ for $j = 1, 2, \ldots, n$.

Step 3. [Generation of sets $\mathcal{H}_1, \mathcal{H}_2, \ldots, \mathcal{H}_n$]

for $j = 1$ **to** n **do**

  for *each* $(X_1, X_2, \ldots, X_K) \in \mathcal{H}_{j-1}$ *with* $X_k = (A_k, B_k, C_k, L_k)$, $k = 1, 2, \ldots, K$ **do**

    for $k = 1$ **to** g_j **do**

      $A'_k = A_k + a_j$, $B'_k = B_k + b_j$, $C'_k = \max\{C_{k-1}, A_{k-1} + a_j\} + b_j$, $L'_k = w_j$.

      $X'_k = (A'_k, B'_k, C'_k, L'_k)$.

      Add the tuple $(X_1, \ldots, X_{k-1}, X'_k, X_{k+1}, \ldots, X_K)$ to $\mathcal{H}_j$.

    end

  end

  [Elimination] Among all tuples in $\mathcal{H}_j$ with the same $X_1, X_2, \ldots, X_{K-1}$ and the same L_K, retain only the tuple with the smallest C_K (by Lemma 4.3).

end

Step 4. [Computation of objective values for the tuples in $\mathcal{H}_n$]

for *each* $X = (X_1, X_2, \ldots, X_K) \in \mathcal{H}_n$ *with* $X_k = (A_k, B_k, C_k, L_k)$, $k = 1, 2, \ldots, K$ **do**

  if $L_k \in \{0, W_k\}$ *for each* $k = 1, 2, \ldots, K$ **then**

    Set $T^1_0 = 0$, $T^2_0 = 0$, $Z_0 = 0$.

    for $k = 1$ **to** K **do**

      $T^1_k = T^1_{k-1} + A_k$, $T^2_k = \max\{T^1_{k-1} + C_k,\ T^2_{k-1} + B_k\}$.

      $Z_k = \max\{Z_{k-1}, L_k \cdot T^2_k\}$.

    end

    $C^w_{\max}(X) = Z_K$.

  else

    $C^w_{\max}(X) = +\infty$.

  end

end

Step 5. [Result] Compute $C^w_{\max}(X_{\text{opt}}) = \min\{C^w_{\max}(X) : X \in \mathcal{H}_n\}$ and recover the corresponding optimal schedule π_{opt} from X_{opt} by backtracking.

Output: The optimal schedule π_{opt}.

Theorem 4.1. *Algorithm 2 solves* $F2 \mid\mid C^w_{\max}$ *in* $O(nK(K+1)!2^{K-1}P^{3K-3})$ *time, where* $P = \max\{\sum_{j=1}^n a_j, \sum_{j=1}^n b_j\}$. *For fixed* K, *it runs in* $O(nP^{3K-3})$ *time and is therefore pseudo-polynomial.*

Proof. The correctness follows from three facts: (i) the algorithm enumerates all tuples corresponding to regular schedules, as characterized by Definition 4.2 and Lemma 4.2; (ii)

the elimination operation deletes only dominated tuples, as guaranteed by Lemma 4.3; and (iii) the weighted makespan of a regular schedule is computed using (31).

Step 1 sorts in $O(n \log n)$ time, and Step 2 initializes in $O(n)$ time. For each $j = 1, 2, \ldots, n$ and each tuple $(X_1, X_2, \ldots, X_K) \in \mathcal{H}_j$, write $X_k = (A_k, B_k, C_k, L_k)$, $k = 1, 2, \ldots, K$. The components satisfy $A_k \le \sum_{i=1}^{j} a_i \le P$, $B_k \le \sum_{i=1}^{j} b_i \le P$, $C_k \le \sum_{i=1}^{j} a_i + \sum_{i=1}^{j} b_i \le 2P$, $L_k \in \{0, W_k, W_{k+1}, \ldots, W_K\}$ for $k = 1, 2, \ldots, K$. Because $\sum_{k=1}^{K} A_k = \sum_{i=1}^{j} a_i$ and $\sum_{k=1}^{K} B_k = \sum_{i=1}^{j} b_i$, only $K-1$ of the A_k and $K-1$ of the B_k are independent. After elimination, the number of distinct tuples in $\mathcal{H}_j$ is at most $O((K+1)!P^{2K-2}(2P)^{K-1}) = O((K+1)!2^{K-1}P^{3K-3})$. In addition, each tuple in $\mathcal{H}_{j-1}$ generates $g_j \le K$ new tuples in $\mathcal{H}_j$. Thus, $\mathcal{H}_j$ can be generated in $O(K(K+1)!2^{K-1}P^{3K-3})$ time. Summing the cost of Step 3 over its n iterations gives $O(nK(K+1)!2^{K-1}P^{3K-3})$ time. Step 4 computes the objective value of each tuple in $\mathcal{H}_n$ in $O(K)$ time and thus requires $O(K(K+1)!2^{K-1}P^{3K-3})$ time. Step 5 requires $O((K+1)!2^{K-1}P^{3K-3})$ time. Consequently, the algorithm runs in $O(nK(K+1)!2^{K-1}P^{3K-3})$ time. □

Applying Algorithm 2 to Example 4.1, we obtain an optimal schedule $\pi^* = (3, 5, 6, 2, 1, 4)$, with blocks $\mathcal{B}_1^{\pi^*} = \{J_3\}$, $\mathcal{B}_2^{\pi^*} = \{J_5, J_6, J_2\}$, and $\mathcal{B}_3^{\pi^*} = \{J_1, J_4\}$ (see Figure 5). The weighted makespan of π^* is $C_{\max}^{w}(\pi^*) = \max\{5 \times 15, 3 \times 24, 2 \times 33\} = 75$.




Figure 5: An optimal scheule π^*

4.3 An FPTAS for fixed number of weights

Let $0 < \epsilon \le 1$ be real, and let $\delta = 1 + \epsilon/(2n)$. Define the function $\Delta(\cdot)$ on $[0, +\infty)$ by

$$\Delta(z) = \lfloor \log_\delta z \rfloor \quad (z \ge 1), \qquad \Delta(0) = -1. \tag{33}$$

Equivalently, if k is an integer that satisfies $\delta^k \le z < \delta^{k+1}$, then $\Delta(z) = k$.

For fixed K, we apply the geometric rounding technique to transform Algorithm 2 into an FPTAS (which we call Algorithm 3). In contrast to Algorithm 2, the proposed algorithm may remove some non-dominated states in the tuple set generation procedure. Let $\mathcal{H}_j^{\epsilon}$ be the set of tuples generated by Algorithm 3 in the j-th iteration. For each tuple $(X_1, X_2, \ldots, X_K) \in \mathcal{H}_j^{\epsilon}$, define its label to be $(Y_1, Y_2, \ldots, Y_K)$, where $X_k = (A_k, B_k, C_k, L_k)$ for $k = 1, 2, \ldots, K$; the first $K-1$ labels are

$$Y_k = (\Delta(A_k), \Delta(B_k), \Delta(C_k), L_k), \quad 1 \le k \le K-1,$$

while the last label is

$$Y_K = (\Delta(A_K), \Delta(B_K), L_K).$$

By construction, for each $1 \le k \le K$ with $A_k \ge 1$, the rounded value $\delta^{\Delta(A_k)}$ approximates A_k up to a small multiplicative error; likewise, $\delta^{\Delta(B_k)}$ and $\delta^{\Delta(C_k)}$ approximate B_k and C_k, respectively. Hence, whenever two tuples share a label, one of them is eliminated during tuple elimination procedure. A formal description of Algorithm 3 is given below.

Algorithm 3: An FPTAS for $F2 \,||\, C^w_{\max}$

Input: Job set $\mathcal{J}$; error parameter ϵ; job parameters a_j, b_j, w_j, and g_j for $j = 1, 2, \ldots, n$; K distinct weights with $W_1 > W_2 > \cdots > W_K$.

Step 1. [Preprocessing] Renumber jobs in $\mathcal{J}$ according to Johnson' rule (Algorithm 1).

Step 2. [Initialization] Set $\delta = 1 + \epsilon/(2n)$. Let $S_0 = \Big(\underbrace{(0,0,0,0),\ldots,(0,0,0,0)}_{K \text{ copies}}\Big)$, and let $R_0 = \Big(\underbrace{(-1,-1,-1,0),\ldots,(-1,-1,-1,0)}_{K-1 \text{ copies}},(-1,-1,0)\Big)$ be its label. Initialize $\mathcal{H}^\epsilon_0 = \{S_0\}$ and $\mathcal{H}^\epsilon_j = \emptyset$ for $j = 1, 2, \ldots, n$.

Step 3. [Generation of sets $\mathcal{H}^\epsilon_1, \mathcal{H}^\epsilon_2, \ldots, \mathcal{H}^\epsilon_n$]

for $j = 1$ **to** n **do**

  for *each* $(X_1, X_2, \ldots, X_K) \in \mathcal{H}^\epsilon_{j-1}$ *with* $X_k = (A_k, B_k, C_k, L_k)$, $k = 1, 2, \ldots, K$ **do**

    for $k = 1$ **to** g_j **do**

      $A'_k = A_k + a_j$, $B'_k = B_k + b_j$, $C'_k = \max\{C_{k-1}, A_{k-1} + a_j\} + b_j$, $L'_k = w_j$.

      $X'_k = (A'_k, B'_k, C'_k, L'_k)$.

      if $k \le K - 1$ **then**

        $Y'_k = (\Delta(A'_k), \Delta(B'_k), \Delta(C'_k), L'_k)$.

      else

        $Y'_K = (\Delta(A'_K), \Delta(B'_K), L'_K)$.

      end

      Add the tuple $(X_1, \ldots, X_{k-1}, X'_k, X_{k+1}, \ldots, X_K)$ to $\mathcal{H}^\epsilon_j$ and attach the associated label $(Y_1, \ldots, Y_{k-1}, Y'_k, Y_{k+1}, \ldots, Y_K)$ to it.

    end

  end

  [Elimination] Among tuples in $\mathcal{H}^\epsilon_j$ sharing identical labels, retain only the one with the smallest C_K.

end

Step 4. [Computation of objective values for the tuples in $\mathcal{H}^\epsilon_n$]

for *each* $X = (X_1, X_2, \ldots, X_K) \in \mathcal{H}^\epsilon_n$ *with* $X_k = (A_k, B_k, C_k, L_k)$, $k = 1, 2, \ldots, K$ **do**

  Perform the same operations as in Step 4 of Algorithm 2.

end

Step 5. [Result] Compute $C^w_{\max}(X') = \min\{C^w_{\max}(X) : X \in \mathcal{H}^\epsilon_n\}$ and recover the corresponding approximate schedule π' from X' by backtracking.

Output: The approximate schedule π'.

In Algorithm 3, the box-elimination operation considers coordinate values that increase

geometrically. Multiplicative errors can occur if, during tuple elimination, each label is represented by the smallest C_X coordinates inside its box rather than by its exact value. Nevertheless, the lemma below demonstrates that the tuples left after elimination form a good approximation to those produced by Algorithm 2.

Lemma 4.4. *Given any tuple $(X_1, X_2, \ldots, X_K) \in \mathcal{H}_j$ generated by Algorithm 2, where $X_k = (A_k, B_k, C_k, L_k)$ for $k = 1, 2, \ldots, K$, Algorithm 3 returns a tuple $(\widetilde{X_1}, \widetilde{X_2}, \ldots, \widetilde{X_K}) \in \mathcal{H}_j^\epsilon$, with $\widetilde{X_k} = (\widetilde{A_k}, \widetilde{B_k}, \widetilde{C_k}, L_k)$, such that*

$$\widetilde{A_k} \le \delta^j A_k, \quad \widetilde{B_k} \le \delta^j B_k, \quad \widetilde{C_k} \le \delta^j C_k, \quad k = 1, 2, \ldots, K. \tag{34}$$

Proof. We prove the result by induction on $j = 1, 2, \ldots, n$. For the base case $j = 1$, J_1 can be assigned to each of the g_1 schedules (each induced by a block) in Algorithm 2 and Algorithm 3. Since these g_1 tuples receive distinct labels in Algorithm 3, it follows that $\mathcal{H}_1^\epsilon = \mathcal{H}_1$, so (34) holds for $j = 1$.

Assume that (34) holds for $j - 1$ (the induction hypothesis), where $j \ge 2$. Let $(X_1, X_2, \ldots, X_K) \in \mathcal{H}_j$ be a tuple obtained from Algorithm 2 for the first j jobs, where $X_k = (A_k, B_k, C_k, L_k)$ for $k = 1, 2, \ldots, K$. When implementing Algorithm 2, the tuple $(X_1, X_2, \ldots, X_K)$ is constructed from a tuple $(X'_1, X'_2, \ldots, X'_K) \in \mathcal{H}_{j-1}$, where $X'_k = (A'_k, B'_k, C'_k, L'_k)$ for $k = 1, 2, \ldots, K$. Specifically, J_j is assigned to one of the g_j schedules corresponding to $(X'_1, X'_2, \ldots, X'_K)$ for the first $j-1$ jobs. Based on the induction hypothesis, there exists a tuple $(\widetilde{X'_1}, \widetilde{X'_2}, \ldots, \widetilde{X'_K}) \in \mathcal{H}_{j-1}^\epsilon$, where $\widetilde{X'_k} = (\widetilde{A'_k}, \widetilde{B'_k}, \widetilde{C'_k}, L'_k)$, such that

$$\widetilde{A'_k} \le \delta^{j-1} A'_k, \quad \widetilde{B'_k} \le \delta^{j-1} B'_k, \quad \widetilde{C'_k} \le \delta^{j-1} C'_k, \quad k = 1, 2, \ldots, K. \tag{35}$$

To prove that (34) holds for j, consider the g_j possible cases in which J_j is assigned to one of these schedules.

Let J_j be assigned to the h-th schedule in Algorithm 2 for some $h \in \{1, 2, \ldots, g_j\}$. Then

$$\begin{aligned} &A_k = A'_k, \quad B_k = B'_k \ , C_k = C'_k \ , L_k = L'_k, \quad k \in \{1, 2, \ldots, K\} \setminus \{h\}; \\ &A_h = A'_h + a_j, \quad B_h = B'_h + b_j, \quad C_h = \max\{C'_h, A'_h + a_j\} + b_j, \quad L_h = w_j. \end{aligned} \tag{36}$$

Since $(\widetilde{X'_1}, \widetilde{X'_2}, \ldots, \widetilde{X'_K}) \in \mathcal{H}_{j-1}^\epsilon$, the tuple $(\widetilde{X'_1}, \widetilde{X'_2}, \ldots, \widetilde{X'_{h-1}}, \overline{X'_h}, \widetilde{X'_{h+1}}, \ldots, \widetilde{X'_K})$ is added to $\mathcal{H}_j^\epsilon$ in Algorithm 3, where $\overline{X'_h} = (\overline{A'_h}, \overline{B'_h}, \overline{C'_h}, \overline{L'_h})$ is defined by

$$\overline{A'_h} = \widetilde{A'_h} + a_j, \quad \overline{B'_h} = \widetilde{B'_h} + b_j, \quad \overline{C'_h} = \max\{\widetilde{C'_h}, \widetilde{A'_h} + a_j\} + b_j, \quad \overline{L'_h} = w_j. \tag{37}$$

Because two tuples can share a label, $(\widetilde{X'_1}, \widetilde{X'_2}, \ldots, \widetilde{X'_{h-1}}, \overline{X'_h}, \widetilde{X'_{h+1}}, \ldots, \widetilde{X'_K})$ may be discarded in Algorithm 3 in favor of another tuple $(\widetilde{X_1}, \widetilde{X_2}, \ldots, \widetilde{X_K}) \in \mathcal{H}_j^\epsilon$, where $\widetilde{X_k} = (\widetilde{A_k}, \widetilde{B_k}, \widetilde{C_k}, \widetilde{L_k})$ for $k = 1, 2, \ldots, K$. For this tuple, by (35)–(37) and the construction in Algorithm 3, we have

$$\begin{cases} \widetilde{A_k} \le \delta \widetilde{A'_k} \le \delta^j A'_k = \delta^j A_k \\ \widetilde{B_k} \le \delta \widetilde{B'_k} \le \delta^j B'_k = \delta^j B_k \\ \widetilde{L_k} = \overline{L'_k} = L'_k = L_k \end{cases} \quad \text{if} \quad k \in \{1, 2, \ldots, K\} \setminus \{h\}; \tag{38}$$

$$\begin{cases} \widetilde{A_h} \le \delta\overline{A'_h} = \delta(\widetilde{A'_h} + a_j) \le \delta(\delta^{j-1}A'_h + a_j) \le \delta^j(A'_h + a_j) = \delta^j A_h \\ \widetilde{B_h} \le \delta\overline{B'_h} = \delta(\widetilde{B'_h} + b_j) \le \delta(\delta^{j-1}B'_h + b_j) \le \delta^j(B'_h + b_j) = \delta^j B_h \\ \widetilde{L_h} = \overline{L'_h} = w_j = L_h \end{cases}; \tag{39}$$

$$\begin{cases} \widetilde{C_k} \le \delta\widetilde{C'_k} \le \delta^j C'_k = \delta^j C_k & \text{if } \ k \in \{1,2,\ldots,K-1\} \setminus \{h\} \\ \widetilde{C_K} \le \widetilde{C'_K} \le \delta^{j-1}C'_K \le \delta^j C_K & \text{if } \ K \ne h \end{cases}; \tag{40}$$

$$\begin{cases} \widetilde{C_h} \le \delta\overline{C'_h} = \delta(\max\{\widetilde{C'_h}, \widetilde{A'_h} + a_j\} + b_j) \\ \qquad \le \delta(\max\{\delta^{j-1}C'_h, \delta^{j-1}A'_h + a_j\} + b_j) & \text{if } \ h \ne K \\ \qquad \le \delta^j(\max\{C'_h, A'_h + a_j\} + b_j) = \delta^j C_h \\ \widetilde{C_K} \le \overline{C'_K} = \max\{\widetilde{C'_K}\widetilde{A'_K} + a_j\} + b_j \\ \qquad \le \max\{\delta^{j-1}C'_K, \delta^{j-1}A'_K + a_j\} + b_j & \text{if } \ h = K \\ \qquad \le \delta^{j-1}(\max\{C'_K, A'_K + a_j\} + b_j) \le \delta^j C_K \end{cases}. \tag{41}$$

By (38)-(41), (34) holds for j when J_j is assigned to the h-th schedule. Since h is arbitrary, this covers every possible assignment of J_j. Thus, the induction step is established for j. □

To analyze the approximation error and time complexity of Algorithm 3, we use the following two well-known inequalities. The first follows because $f(x) = x\ln x - (x-1)$ is increasing on $[1, +\infty)$ and $f(1) = 0$. The second follows because $g(x) = (1 + \frac{x}{n})^n - (1 + 2x)$ is convex on $[0, 1]$, with $g(0) = 0$ and $g(1) \le 0$.

Lemma 4.5. *For any real $x \ge 1$, $\ln x \ge (x-1)/x$.*

Lemma 4.6. *For any real $0 < x \le 1$, $(1 + x/n)^n \le 1 + 2x$.*

Theorem 4.2. *For fixed K, Algorithm 3 is an FPTAS for $F2 \ || \ C^w_{\max}$ with $O((n^{3K}/\epsilon^{3K-1})(\log P)^{3K-1})$ running time.*

Proof. We first bound the approximation error of the algorithm. Let π' be the approximate schedule returned by algorithm 3, and let π_{opt} be the optimal schedule returned by Algorithm 2. Denote by $(X^*_1, X^*_2, \ldots, X^*_K) \in \mathcal{H}_n$ the tuple corresponding to π_{opt}, where $X^*_k = (A^*_k, B^*_k, C^*_k, L^*_k)$ for $k = 1, 2, \ldots, K$. By (30) and (31), we have

$$C^w_{\max}(\pi_{\text{opt}}) = \max_{1\le k\le K}\Big\{W_k \max_{0\le h\le k-1}\Big(\sum_{i=1}^{h} A^*_i + C^*_{h+1} + \sum_{i=h+2}^{k} B^*_i\Big)\Big\}. \tag{42}$$

By Lemma 4.4, there exists a tuple $(\widetilde{X^*_1}, \widetilde{X^*_2}, \ldots, \widetilde{X^*_K}) \in \mathcal{H}^\epsilon_n$ generated by Algorithm 3, with $\widetilde{X^*_k} = (\widetilde{A^*_k}, \widetilde{B^*_k}, \widetilde{C^*_k}, L^*_k)$, such that

$$\widetilde{A^*_k} \le \delta^n A^*_k, \quad \widetilde{B^*_k} \le \delta^n B^*_k, \quad \widetilde{C^*_k} \le \delta^n C^*_k, \quad k = 1, 2, \ldots, K. \tag{43}$$

Let $\widetilde{\pi_{\text{opt}}}$ be the schedule corresponding to $(\widetilde{X_1^*}, \widetilde{X_2^*}, \ldots, \widetilde{X_K^*})$. Again by (30) and (31), we have

$$C_{\max}^w(\widetilde{\pi_{\text{opt}}}) = \max_{1\le k\le K}\Big\{W_k \max_{0\le h\le k-1}\Big(\sum_{i=1}^{h}\widetilde{A_i^*} + \widetilde{C_{h+1}^*} + \sum_{i=h+2}^{k}\widetilde{B_i^*}\Big)\Big\}. \tag{44}$$

Recall that $0 < \epsilon \le 1$ and $\delta = 1 + \epsilon/(2n)$. Then by Lemma 4.6 and (42)–(44), we have

$$\begin{aligned} C_{\max}^w(\widetilde{\pi_{\text{opt}}}) &\le \max_{1\le k\le K}\Big\{W_k \max_{0\le h\le k-1}\Big(\sum_{i=1}^{h}\delta^n A_i^* + \delta^n C_{h+1}^* + \sum_{i=h+2}^{k}\delta^n B_i^*\Big)\Big\} \\ &= \delta^n \max_{1\le k\le K}\Big\{W_k \max_{0\le h\le k-1}\Big(\sum_{i=1}^{h} A_i^* + C_{h+1}^* + \sum_{i=h+2}^{k} B_i^*\Big)\Big\} \\ &\le (1+\epsilon) C_{\max}^w(\pi_{\text{opt}}). \end{aligned}$$

Thus, from the execution of Algorithm 3, it returns an approximate schedule π' with $C_{\max}^w(\pi') \le C_{\max}^w(\widetilde{\pi_{\text{opt}}}) \le (1+\epsilon) C_{\max}^w(\pi_{\text{opt}})$.

We next bound the time complexity of the algorithm. Step 1 sorts in $O(n \log n)$ time, and Step 2 initializes in $O(n)$ time. In Step 3, at most one tuple is retained per label after elimination. For each $(X_1, X_2, \ldots, X_K) \in \mathcal{H}_j^\epsilon$ $(j = 1, 2, \ldots, n)$, the corresponding label is $(Y_1, Y_2, \ldots, Y_K)$, where $X_k = (A_k, B_k, C_k, L_k)$ for $k = 1, 2, \ldots, K$, $Y_k = (\Delta(A_k), \Delta(B_k), \Delta(C_k), L_k)$ for $1 \le k \le K-1$, and $Y_K = (\Delta(A_K), \Delta(B_K), L_K)$. Note that $A_k \le P$, $B_k \le P$, $C_k \le 2P$, and $L_k \in \{0, W_k, W_{k+1}, \ldots, W_K\}$ for $k = 1, 2, \ldots, K$. By Lemma 4.5, the number of distinct values attained by $\Delta(A_k)$ is upper bounded by $1 + \lfloor \log_\delta P \rfloor = 1 + \lfloor \ln P / \ln \delta \rfloor \le 1 + \lfloor (1 + 2n/\epsilon) \ln P \rfloor = O((n/\epsilon) \log P)$. Analogously, the number of distinct values attained by $\Delta(B_k)$ and $\Delta(C_k)$ are also upper bounded by $O((n/\epsilon) \log P)$. Because each tuple yields at most K new tuples, after elimination, the number of retained tuples in $\mathcal{H}_j^\epsilon$ is upper bounded by $O((n^{3K-1}/\epsilon^{3K-1})(\log P)^{3K-1})$. Summing the cost of Step 3 over its n iterations gives $O((n^{3K}/\epsilon^{3K-1}) \log P)$ time. Step 4 computes the objective value of each tuple in $\mathcal{H}_n^\epsilon$ in $O(K)$ time, and thus requires $O((n^{3K-1}/\epsilon^{3K-1})(\log P)^{3K-1})$ time in total. Step 5 has the same time complexity. Consequently, the algorithm runs in $O((n^{3K}/\epsilon^{3K-1})(\log P)^{3K-1})$ time. □

4.4 The bounded max-to-min weight ratio

Consider the bounded max-to-min ratio weight case where $w_{\max}/w_{\min} \le C$ for some constant C. Here, $w_{\max} = \max_{1\le j\le n}\{w_j\}$ is the maximum weight of the n jobs, and $w_{\min} = \min_{1\le j\le n}\{w_j\}$ is the minimum weight. The proof of Theorem 3.1 demonstrates that the problem remains $\mathcal{NP}$-hard even when $C = 2$.

Let $0 < \epsilon \le 1$ be a real number. For $j = 1, 2, \ldots, n$, we round each weight w_j down to the nearest value of the form $w_{\min}(1+\epsilon/2)^k$, i.e., $\overline{w_j} = w_{\min}(1+\epsilon/2)^{\theta_j}$, where θ_j is the unique integer satisfying

$$w_{\min}(1+\epsilon/2)^{\theta_j} \le w_j < w_{\min}(1+\epsilon/2)^{\theta_j+1}. \tag{45}$$

By combining job-weight rounding with the FPTAS in Section 4.3, a PTAS for the bounded max-to-min ratio weight case is given as follows.

Algorithm 4: A PTAS for $F2 \,||\, C^w_{\max}$ with bounded max-to-min weight ratio

Input: Job set $\mathcal{J}$; error parameter ϵ; job parameters a_j, b_j, and w_j for $j = 1, 2, \ldots, n$.

1 **Step 1.** Construct the rounded instance $\mathcal{I}'$ from the original instance $\mathcal{I}$: replace each job J_j by J'_j with $w'_j = w_{\min}(1+\epsilon/2)^{\theta_j}$, where θ_j is the integer given by (45); keep all other job parameters unchanged.

2 **Step 2.** Let $W_1 > W_2 > \cdots > W_K$ be the ordered sequence of distinct rounded weights in $\mathcal{I}'$. Run Algorithm 3 on $\mathcal{I}'$ to obtain a $(1+\epsilon/3)$-approximation schedule π_ϵ.

Output: The approximate schedule π_ϵ.

For a schedule π, let $C^w_{\max}(\pi, \mathcal{I}) = \max_{1\le j\le n}\{w_{\pi(j)}C_{\pi(j)}(\pi, \mathcal{I})\}$ and $C^w_{\max}(\pi, \mathcal{I}') = \max_{1\le j\le n}\{w'_{\pi(j)}C_{\pi(j)}(\pi, \mathcal{I}')\}$ denote its weighted makespan on instances $\mathcal{I}$ and $\overline{\mathcal{I}}$, respectively. Here, $C_{\pi(j)}(\pi, \mathcal{I})$ and $C_{\pi(j)}(\pi, \mathcal{I}')$ are the completion times of $J_{\pi(j)}$ under π on $\mathcal{I}$ and $\mathcal{I}'$, respectively.

Theorem 4.3. *When $w_{\max}/w_{\min} \le C$, Algorithm 4 is a PTAS for $F2 \,||\, C^w_{\max}$ with $O((n^{O(1/\epsilon)}/\epsilon^{O(1/\epsilon)})(\log P)^{O(1/\epsilon)})$ running time.*

Proof. Let π_{opt} be an optimal schedule for $\mathcal{I}$, and let π'_{opt} be an optimal schedule for $\mathcal{I}'$. Because $\mathcal{I}$ and $\mathcal{I}'$ differ only in their job weights, a fixed schedule π yields the same job completion times on both instances, i.e., $C_{\pi(j)}(\pi, \mathcal{I}) = C_{\pi(j)}(\pi, \mathcal{I}')$. Thus, from the fact that $w'_j \le w_j < (1+\epsilon/2)w'_j$, $j = 1, 2, \ldots, n$, we have

$$C^w_{\max}(\pi_\epsilon, \mathcal{I}) < (1+\epsilon/2)C^w_{\max}(\pi_\epsilon, \mathcal{I}') \tag{46}$$

and

$$C^w_{\max}(\pi'_{\text{opt}}, \mathcal{I}') \le C^w_{\max}(\pi_{\text{opt}}, \mathcal{I}') \le C^w_{\max}(\pi_{\text{opt}}, \mathcal{I}). \tag{47}$$

Since π_ϵ is a $(1+\epsilon/3)$-approximation schedule for $\mathcal{I}'$, we have

$$C^w_{\max}(\pi_\epsilon, \mathcal{I}') \le (1+\epsilon/3)C^w_{\max}(\pi'_{\text{opt}}, \mathcal{I}'). \tag{48}$$

Then, (46)–(48) imply that

$$C^w_{\max}(\pi_\epsilon, \mathcal{I}) \le (1+\epsilon/2)(1+\epsilon/3)C^w_{\max}(\pi'_{\text{opt}}, \mathcal{I}') \le (1+\epsilon)C^w_{\max}(\pi_{\text{opt}}, \mathcal{I}).$$

Let $\mathcal{W} = \{\overline{w_j} : 1 \le j \le n\}$ be the set of distinct rounded job weights in $\mathcal{I}'$, and let $K = |\mathcal{W}|$. Since $w_{\max}/w_{\min} \le C$ and C is a constant, we have $K \le 1 + \lfloor \log_{1+\epsilon/2} C \rfloor = O(1/\epsilon)$. The running time is dominated by Step 2. By Theorem 4.2, it requires $O((n^{3K}/\epsilon^{3K-1})(\log P)^{3K-1}) = O((n^{O(1/\epsilon)}/\epsilon^{O(1/\epsilon)})(\log P)^{O(1/\epsilon)})$ time. Consequently, the overall running time is $O((n^{O(1/\epsilon)}/\epsilon^{O(1/\epsilon)})(\log P)^{O(1/\epsilon)})$. □

5 Heuristic algorithms

This section presents two heuristic methods for instances that are too large to be solved efficiently by the exact methods: an adaptation of the NEH heuristic, which constructs a schedule through sequential job insertion, and a genetic algorithm, which searches the space of job permutations.

5.1 The LW algorithm

Sun (2024) proved that the LW-based greedy algorithm is a $(2-1/m)$-approximation for $Pm \mid\mid C^w_{\max}$. For $F2 \mid\mid C^w_{\max}$, we describe the analogous LW-based algorithm and show that its worst-case approximation ratio is 2.

Algorithm 5: LW's rule for $F2 \mid\mid C^w_{\max}$

Input: Job set $\mathcal{J}$; job parameters a_j, b_j, and w_j for $j = 1, 2, \ldots, n$.

1 **Step 1.** Renumber the jobs in nonincreasing order of their weights (i.e., the LW order), so that $w_1 \geq w_2 \geq \cdots \geq w_n$.

2 **Step 2.** Process the jobs in this order on M_1 and then on M_2, yielding the permutation schedule π_{lw}.

Output: The resulting schedule π_{lw}.

Theorem 5.1. *For $F2 \mid\mid C^w_{\max}$, Algorithm 5 has a worst-case approximation ratio of 2, which is tight, and runs in $O(n \log n)$ time.*

Proof. Since $1 \mid\mid C^w_{\max}$ can be solved in $O(n \log n)$ time by the LW rule (Nong et al., 2011), we have

$$C^w_{\max}(\pi_{\mathrm{opt}}) \geq LB = \max\left\{ \max_{1\leq j\leq n}\left\{w_j \sum_{i=1}^{j} a_i\right\}, \max_{1\leq j\leq n}\left\{w_j \sum_{i=1}^{j} b_i\right\}, \max_{1\leq j\leq n}\left\{w_j(a_j+b_j)\right\}\right\}, \quad (49)$$

where the first two terms are machine-based lower bounds and the last is a job-based lower bound.

By construction, Algorithm 5 yields $\pi_{\mathrm{lw}}(j) = j$ for $j = 1, 2, \ldots, n$. Combining (1) with (2), the weighted makespan of π_{lw} can be written as

$$C^w_{\max}(\pi_{\mathrm{lw}}) = \max_{1\leq j\leq n}\left\{w_{\pi_{\mathrm{lw}}(j)} C_{\pi_{\mathrm{lw}}(j)}\right\} = \max_{1\leq j\leq n}\left\{w_j \max_{1\leq i\leq j}\left(\sum_{h=1}^{i} a_h + \sum_{h=i}^{j} b_h\right)\right\}. \quad (50)$$

By (49) and (50), we have

$$\begin{aligned} C^w_{\max}(\pi_{\mathrm{lw}}) &\le \max_{1\le j\le n}\left\{w_j\sum_{h=1}^{j}a_h + w_j\sum_{h=1}^{j}b_h\right\} \\ &\le \max_{1\le j\le n}\left\{w_j\sum_{h=1}^{j}a_h\right\} + \max_{1\le j\le n}\left\{w_j\sum_{h=1}^{j}b_h\right\} \\ &\le 2C^w_{\max}(\pi_{\mathrm{opt}}). \end{aligned} \tag{51}$$

To show that the bound is tight, consider an instance with two jobs: J_1 has $a_1 = 1+\epsilon$, $b_1 = \epsilon$, and $w_1 = 1+\epsilon$, and J_2 has $a_2 = \epsilon$, $b_2 = 1+\epsilon$, and $w_2 = 1$, where $\epsilon > 0$ is arbitrarily small. Algorithm 5 yields the schedule $\pi_{\mathrm{lw}} = (1,2)$ with $C^w_{\max}(\pi_{\mathrm{lw}}) = 2+\epsilon$, while the optimal schedule is $\pi_{\mathrm{opt}} = (2,1)$ with $C^w_{\max}(\pi_{\mathrm{opt}}) = (1+\epsilon)(1+2\epsilon)$. Hence, $C^w_{\max}(\pi_{\mathrm{lw}})/C^w_{\max}(\pi_{\mathrm{opt}}) \to 2$ as $\epsilon \to 0$. □

5.2 The NEH algorithm

The NEH heuristic is a classical insertion-based constructive method for the permutation flow-shop scheduling problem. In the formulation of Nawaz et al. Nawaz et al. (1983), jobs are placed sequentially: at each iteration, an unassigned job is examined at every feasible position in the current partial schedule, and the position with the smallest resulting makespan is retained. This procedure has proven competitive in diverse scheduling settings. In addition, NEH has recently been used in scheduling research as a construction to be refined (Puka et al., 2024), as a rule for assigning jobs in distributed lot-streaming and cascaded flow shops (Shao et al., 2023; Wang et al., 2024b), and as the core of composite heuristics for a constrained distributed group scheduling problem (Wang et al., 2024a). For the $C^w_{\max}$ objective, two properties are relevant. First, jobs with large total processing time a_j+b_j tend to lengthen the schedule and should be scheduled early to avoid delaying other jobs. Second, for a fixed makespan, jobs with larger weight w_j benefit more from earlier positions, since this reduces the objective value. Accordingly, we prioritize jobs by nonincreasing a_j+b_j, breaking ties by nonincreasing w_j, and insert each job into the position yielding the smallest objective value. The detailed procedure is presented in Algorithm 6. At iteration k, evaluating all k insertion positions requires $O(k^2)$ time, so the overall running time is $O(n^3)$.

Algorithm 6: NEH heuristic for $F2 \mid\mid C^w_{\max}$

Input: Job set $\mathcal{J}$; job parameters a_j, b_j, and w_j for $j = 1, 2, \ldots, n$.

Step 1. [Preprocessing] Renumber the jobs in $\mathcal{J}$ by nonincreasing $a_j + b_j$, and the ties are broken by nonincreasing w_j.

Step 2. [Initialization] $\pi \leftarrow (J_1)$.

Step 3. [Insertion] **for** $k = 2$ **to** n **do**

  $\pi \leftarrow$ insert J_k into π at a position that minimizes $C^w_{\max}$.

end

Output: The resulting schedule π.

5.3 The genetic algorithm

Genetic algorithms (GAs) are commonly applied in scheduling, where operators are tailored to problem structure. Recent flow-shop studies have developed genetic operators for blocking constraints (de Athayde Prata and Fuchigami, 2024), sequence-independent setup times and non-interruption requirements (Qiao et al., 2022), and energy consumption under variable machine speeds (Wang et al., 2023). For the $C^w_{\max}$ objective, an optimal schedule consists of weight-based blocks, and jobs within each block follow Johnson's order (Lemma 4.1). Using this structural property, we design a weight-block genetic algorithm (which we call Algorithm 7) with a weight-class-based mutation operator as its core component.

Each chromosome encodes a job permutation. The initial population contains the schedule constructed from Johnson's rule and $N - 1$ adjacent-swap variants, where N is the population size. Johnson's rule ignores job weights, but it provides a structured, makespan-minimizing schedule as a starting point for the weight-aware search. Parents are selected by fitness-based binary tournament. Partially mapped crossover is applied with probability p_c and mutation with probability p_m. Elitist selection keeps the N best individuals from the combined parent and offspring pools, preserving the best solution across generations.

The distinctive component of Algorithm 7 is its weight-class mutation operator. Rather than moving individual jobs, it removes a whole weight class, keeps the relative order of its jobs, and reinserts the class as a block at the position yielding the smallest $C^w_{\max}$. The class is chosen with equal probability either from classes containing a job that attains the current $C^w_{\max}$ or uniformly at random. Repositioning all jobs of a class at once makes use of the block structure. A forward move can delay the jobs passed over, so the move is not guaranteed to improve the schedule; its retention is left to the subsequent selection. To improve schedule quality, a local search sequentially relocates the k jobs with the largest $w_j C_j$ values to the position minimizing $C^w_{\max}$. It stops when a round produces no improvement in $C^w_{\max}$ or after G rounds.

Algorithm 7: The weight-block genetic algorithm (WBGA) for $F2 \mid\mid C^w_{\max}$

Input: Job set $\mathcal{J}$; number of distinct weights K; population size N; generations G; offspring λ; probabilities p_c, p_m; reinsertion count k.

Step 1. [Initialization] $P_0 \leftarrow$ Johnson's schedule and $N-1$ adjacent-swap variants; evaluate.
Step 2. [Evolution] **for** $g = 1$ **to** G **do**
  Selection $M_g \leftarrow$ binary tournament on P_{g-1}.
  Crossover while $|O_g| < \lambda$ **do**
    Draw π_1, π_2 from M_g; with probability p_c obtain two children by block crossover, otherwise copy the parents; add them to O_g.
  end
  Mutation Apply block mutation to each child with probability p_m; evaluate.
  Survival $P_g \leftarrow$ the N best of $P_{g-1} \cup O_g$ by $C^w_{\max}$.
end
$\pi^* \leftarrow$ the best of P_G.
Step 3. [Local search] **repeat**
  $J_1, \ldots, J_k \leftarrow$ the k jobs of π^* with the largest $w_j C_j$.
  $\pi' \leftarrow$ best schedule from removing one J_i and reinserting it at one position.
  if $C^w_{\max}(\pi') < C^w_{\max}(\pi^*)$ **then**
    $\pi^* \leftarrow \pi'$
  end
until *no reinsertion lowers* $C^w_{\max}(\pi^*)$*, or* G *rounds have been reached*
Output: π^*.

6 Numerical experiments

All algorithms were implemented in Python 3.13 and run on a computer equipped with an Intel Core Ultra 5 230F processor and 16 GB of RAM, running Windows 11. The MILP model was solved using Gurobi 13.0 with a single thread.

6.1 Experimental setup

Three groups of test instances are considered.Each configuration contains 20 independently generated instances. Each instance is subject to a time limit of 600 s. The processing times are independently drawn from $\mathcal{U} \sim (1, p_{\max})$, where $p_{\max} = 40$ or 80.

Group 1 evaluates the performance of DP with $n \in \{40, 60, 80, 100\}$, and weights $\in \{1, 10\}$ or $\in \{1, 10, 100\}$.

Group 2 compares small-scale instances of the MILP model with LW, NEH, and GA for $n \in \{10, 15, \ldots, 60\}$, and weights $\in \{1, 2, \ldots, 30\}$ or weights $\in \{1, 2, \ldots, 100\}$.

Group 3 compares large-scale instances of LW, NEH, and GA for $n \in \{100, 15, \ldots, 400\}$, and weights $\in \{1, 2, \ldots, 30\}$ or weights $\in \{1, 2, \ldots, 100\}$.

For GA, the population size is set to $N = \min\{20, \max\{6, \lceil n/2 \rceil\}\}$. The number of generations is set to $G = \max\{1, \lfloor (n-5)/5 \rfloor\}$ for small instances and $G = 1 + \lfloor (n-100)/50 \rfloor$ for large instances. The number of offspring per generation is set to $\lambda = \max\{1, \lfloor \max\{0, n-20\}^2/20 \rfloor\}$ for small instances and $\lambda = \max\{3, \lfloor 3n^3/10^6 \rfloor\}$ for large instances. These parameter settings are designed to balance solution quality and computational time.

Algorithmic performance is evaluated using the relative percentage gap:

$$\text{gap}_A = \frac{z_A - z_{\text{base}}}{z_{\text{base}}} \times 100\%, \tag{52}$$

where z_A is the objective value obtained by method A $(\text{DP}, \text{LW}, \text{NEH}, \text{GA})$, and z_{base} is the reference value. For the small-scale instances, z_{base} is the MILP optimum whenever optimality is proven by the solver. For the large-scale instances, it is the lower bound LB of (49), the maximum of the two machine-based bounds and the job-based bound. Thus, large-scale gaps measure the distance from a common lower bound rather than from competing heuristic solutions. This bound is tight only when the heaviest jobs also appear earliest.

6.2 Computational results

The five methods exhibit different trade-offs between solution quality, computational cost and generality, with none dominating across all instances.

6.2.1 The DP

The DP is the only exact method considered and guarantees optimality whenever it terminates. It solves the instances in almost all configurations, with mean running times of 1.47 s and 4.98 s for forty-job instances under $[1, 40]$ and $[1, 80]$, respectively (Table 2). However, its running time increases rapidly with instance size. Under $[1, 40]$, the mean running time rises from 1.47 s for forty jobs to 89.59 s for one hundred jobs, a 61-fold increase, while the mean objective value increases by only a factor of 2.5. Expanding the processing-time range to $[1, 80]$ further increases the mean running time by factors of 2.9–3.7. For one hundred-job instances under $[1, 80]$, some instances reach the 600 s time limit, and the remaining ones require an average of 329.01 s. Moreover, the DP cannot handle a third weight class due to memory limitations, restricting its applicability to $K = 2$. These results indicate that the DP is effective for relatively small instances with few distinct weights but has limited scalability.

Table 2: DP, weights $\in \{1, 10\}$

n	$a_j, b_j \in [1, 40]$			$a_j, b_j \in [1, 80]$		
	time (s)		opt.	time (s)		opt.
	avg	max		avg	max	
20	0.01	0.11	20/20	0.01	0.08	20/20
40	2.41	7.02	20/20	7.95	32.37	20/20
50	11.80	24.25	20/20	28.90	63.55	20/20
60	25.05	58.58	20/20	78.55	176.76	20/20
120	269.83	600.00	19/20	565.30	600.00	2/20
140	405.57	600.00	16/20	−−	−−	−−

Table 3: DP, weights $\in \{1, 10, 100\}$

n	$a_j, b_j \in [1, 40]$			$a_j, b_j \in [1, 80]$		
	time (s)		opt.	time (s)		opt.
	avg	max		avg	max	
10	0.00	0.01	20/20	0.00	0.00	20/20
20	1.09	4.21	20/20	1.59	6.56	20/20
30	58.67	417.68	20/20	91.51	600.00	19/20
40	−−	−−	−−	−−	−−	−−

6.2.2 Small-scale instances

Tables 4 to 5 report the running times of the four methods and the gaps of the three heuristics under $[1, 40]$ and $[1, 80]$, respectively.

The MILP model solves almost all instances to optimality, providing reference values. Under $[1, 40]$, its mean running time increases from 7.0e1 ms for ten jobs to 1.6e5 ms for sixty jobs, with a few instances at the largest size reaching the time limit. The wider processing-time range roughly doubles the objective values but has no consistent effect on running time.

NEH outperforms LW in every configuration: its mean gap is 3.4% against 7.3% for LW at ten jobs and 4.3% against 4.7% at sixty jobs, with worst individual-instance gaps of 24.9% and 21.5%, respectively. This improvement comes at a higher computational cost: at ten jobs NEH takes 7.3e−2 ms against 8.8e−3 ms for LW, and at sixty jobs 8.0e0 ms against 2.5e−2 ms, reflecting its sequential evaluation of insertion positions versus the latter's single-pass construction. Thus, LW is preferable when computational efficiency outweighs solution quality.

The GA shows the opposite trend, with its mean gap decreasing from 12.6% to 1.7% under $[1, 40]$ and from 14.3% to 3.9% under $[1, 80]$ as the number of jobs increases from ten to sixty. It outperforms both constructive methods at sixty jobs. Nevertheless, its gap is the largest at the smaller sizes, and its performance is non-monotonic, with a worst individual-instance gap of 57.5% at twenty-five jobs. This may reflect the limited search budget at smaller sizes, where six individuals, one generation and a single offspring for ten jobs provide insufficient opportunities to establish the block structure. Its mean running time rises from 6.4e−1 ms to 1.7e3 ms, remaining well below that of the MILP model. At sixty jobs, however, the mean gaps of the three heuristics differ by about three percentage points.

Overall, the small-scale results distinguish the methods primarily by computational cost. The MILP model alone certifies optimality but becomes increasingly expensive as the instance size grows. Among the heuristics, NEH offers the best quality-cost trade-off, LW sacrifices some solution quality for substantially lower running times, while GA performs worst in solution quality and incurs the highest computational cost (Figure 6). Hence, NEH is the preferred heuristic for small instances unless optimality certification is required. The effectiveness of the additional search effort invested in GA on larger instances is examined next.

Table 4: Small scale, $p_{\max} = 40$, weights $\in \{1, \ldots, 30\}$

n	MILP		LW				NEH				GA			
	time (ms)		gap		time (ms)		gap		time (ms)		gap		time (ms)	
	avg	max	avg	max	avg	max	avg	max	avg	max	avg	max	avg	max
10	7.0e1	1.2e2	7.3	17.2	8.8e−3	2.5e−2	**3.4**	24.9	7.3e−2	7.9e−2	12.6	30.6	6.4e−1	7.2e−1
15	1.9e2	4.7e2	6.8	16.9	9.9e−3	1.9e−2	**2.1**	8.5	1.9e−1	2.0e−1	18.2	49.5	2.6e0	2.9e0
20	5.6e2	1.9e3	6.2	19.9	1.3e−2	2.3e−2	**2.7**	11.7	3.8e−1	4.1e−1	12.1	33.0	1.0e1	1.1e1
25	1.5e3	5.7e3	5.6	21.5	1.4e−2	2.5e−2	**3.7**	17.5	7.0e−1	7.4e−1	15.3	57.5	2.8e1	3.3e1
30	2.8e3	1.0e4	5.6	14.9	1.4e−2	2.6e−2	**3.9**	10.8	1.1e0	1.2e0	11.6	26.7	6.2e1	7.0e1
35	8.4e3	3.6e4	5.7	12.2	1.4e−2	2.4e−2	**3.2**	13.8	1.8e0	1.8e0	12.8	38.7	1.2e2	1.3e2
40	2.1e4	1.2e5	4.9	10.6	1.7e−2	3.0e−2	**2.4**	6.2	2.5e0	2.6e0	7.0	17.5	2.4e2	2.5e2
45	3.1e4	2.5e5	6.0	19.0	1.8e−2	3.8e−2	**3.7**	10.3	3.5e0	3.7e0	8.8	24.7	4.1e2	4.5e2
50	8.4e4	5.1e5	4.5	13.0	1.8e−2	3.1e−2	**3.6**	8.4	4.8e0	4.9e0	6.5	22.9	6.7e2	7.3e2
55	1.1e5	5.2e5	4.7	10.9	2.7e−2	4.7e−2	**3.1**	11.9	6.2e0	6.4e0	4.2	14.6	1.0e3	1.2e3
60	1.6e5	6.0e5	4.7	11.7	2.5e−2	4.2e−2	4.3	8.8	8.0e0	8.2e0	**1.7**	8.2	1.7e3	1.9e3

Table 5: Small scale, $p_{\max} = 80$, weights $\in \{1, \ldots, 30\}$

n	MILP		LW				NEH				GA			
	time (ms)		gap		time (ms)		gap		time (ms)		gap		time (ms)	
	avg	max	avg	max	avg	max	avg	max	avg	max	avg	max	avg	max
10	5.1e1	1.0e2	8.1	17.5	8.5e−3	1.8e−2	**0.8**	5.7	7.2e−2	7.8e−2	14.3	47.5	6.1e−1	6.8e−1
15	2.9e2	1.8e3	7.7	19.7	9.5e−3	2.0e−2	**2.4**	14.5	1.9e−1	2.1e−1	15.9	37.5	2.6e0	2.9e0
20	4.5e2	1.8e3	4.5	11.8	1.2e−2	2.9e−2	**2.6**	9.6	3.8e−1	4.1e−1	16.3	39.1	1.0e1	1.2e1
25	1.6e3	4.6e3	4.7	16.2	1.2e−2	2.1e−2	**2.1**	7.9	7.0e−1	7.4e−1	15.7	37.6	2.8e1	3.0e1
30	3.2e3	9.5e3	5.6	11.7	1.5e−2	2.9e−2	**2.6**	13.6	1.2e0	1.2e0	14.4	34.2	6.1e1	6.6e1
35	8.7e3	4.1e4	7.0	18.1	1.8e−2	3.1e−2	**4.3**	7.9	1.8e0	1.8e0	11.5	27.5	1.2e2	1.3e2
40	2.4e4	1.5e5	6.3	20.8	1.8e−2	3.1e−2	**2.4**	7.6	2.5e0	2.6e0	5.5	15.9	2.5e2	2.7e2
45	6.8e4	3.8e5	4.8	12.3	1.6e−2	1.9e−2	**2.8**	11.9	3.5e0	3.7e0	5.3	13.1	4.2e2	4.5e2
50	7.7e4	4.8e5	6.2	12.4	1.9e−2	3.0e−2	**3.8**	11.1	4.7e0	4.8e0	4.2	12.0	6.6e2	7.4e2
55	1.4e5	4.7e5	5.0	11.4	2.2e−2	3.9e−2	5.0	16.2	6.2e0	6.5e0	**3.5**	14.7	1.1e3	1.2e3
60	1.9e5	6.0e5	5.0	13.5	2.8e−2	4.4e−2	4.4	15.4	8.0e0	8.2e0	**3.9**	20.8	1.7e3	1.8e3




Figure 6: Small scale: LW, NEH, GA against the optimum.

6.2.3 Large-scale instances

Tables 6 to 7 report the gaps and running times of the three heuristics under $[1, 40]$ and $[1, 80]$, respectively.

On the large scale, the ranking varies with instance size. The LW achieves the smaller mean gap at every size: 4.4% against 5.2% for NEH at one hundred jobs and 2.0% against 3.9% at four hundred, with worst individual-instance gaps of 12.9% and 10.8%, respectively. By contrast, the GA improves substantially with instance size: its mean gap decreases from 18.3% to 0.6% under $[1, 40]$ and from 16.0% to 0.8% under $[1, 80]$ between one hundred and four hundred jobs. It overtakes NEH at 220 jobs under both ranges and LW at 220 and 240 jobs, respectively.

For sufficiently large instances, the GA achieves the best solution quality at a higher

computational cost. At four hundred jobs, its mean gap is 0.6% against 2.0% for LW and 3.9% for NEH, while its mean running time is 1.28e5 ms, against 1.46e−1 ms and 2.18e3 ms, respectively. Unlike the DP, it also handles instances with 30 distinct weight classes. The processing-time range has little effect on the ranking: at four hundred jobs under $[1, 80]$, the mean gaps are 1.7% for LW, 5.8% for NEH and 0.8% for GA. The bound LB is tight only when the heaviest jobs appear earliest; the gaps therefore measure deviations from LB rather than true optimality gaps.

Overall, the large-scale results highlight the trade-off between solution quality and computational time. The LW is the fastest method and achieves the smallest overall mean gap, while NEH offers intermediate performance at negligible computational cost. The GA achieves the best solutions on sufficiently large instances but requires substantially more time (Figure 7). The choice therefore depends on whether computational speed or solution quality is the priority.

Table 6: Large scale, $p_{\max} = 40$, weights $\in \{1, \ldots, 30\}$

n	LW				NEH				GA			
	gap		time (ms)		gap		time (ms)		gap		time (ms)	
	avg	max	avg	max	avg	max	avg	max	avg	max	avg	max
100	**4.4**	10.0	3.36e−2	6.16e−2	5.2	9.7	3.73e1	6.30e1	18.3	29.2	9.67e2	1.10e3
120	**3.5**	6.5	4.82e−2	1.05e−1	4.8	10.0	6.08e1	6.32e1	13.8	32.1	1.78e3	1.85e3
140	**3.0**	6.6	5.76e−2	1.19e−1	5.3	8.5	9.66e1	1.03e2	9.3	20.6	3.11e3	3.20e3
160	**3.4**	7.5	6.72e−2	1.28e−1	4.2	7.4	1.42e2	1.47e2	6.5	14.4	5.12e3	5.29e3
180	**2.6**	7.8	7.09e−2	9.77e−2	4.9	7.6	2.04e2	2.15e2	5.3	13.8	8.04e3	8.37e3
200	**2.6**	5.6	7.51e−2	1.17e−1	4.4	7.6	2.74e2	2.89e2	4.5	15.7	1.22e4	1.26e4
220	3.4	8.6	8.67e−2	1.05e−1	5.0	8.2	3.64e2	3.76e2	**3.0**	11.7	1.76e4	1.84e4
240	**2.8**	5.9	8.52e−2	1.11e−1	4.7	7.3	4.86e2	5.08e2	2.8	7.4	2.59e4	2.69e4
260	2.6	6.0	9.98e−2	1.48e−1	5.4	8.7	5.69e2	5.84e2	**1.6**	4.7	3.24e4	3.29e4
280	2.5	7.8	9.67e−2	1.20e−1	5.1	7.7	7.22e2	7.39e2	**0.8**	3.9	4.31e4	4.37e4
300	2.0	4.9	1.11e−1	1.79e−1	4.9	8.6	8.99e2	9.12e2	**0.9**	5.0	5.34e4	5.45e4
320	3.0	7.6	1.13e−1	1.23e−1	4.4	7.4	1.10e3	1.12e3	**1.2**	6.3	6.50e4	6.59e4
340	1.5	3.7	1.27e−1	2.41e−1	4.7	7.1	1.32e3	1.35e3	**1.2**	8.0	7.78e4	7.89e4
360	2.2	5.5	1.31e−1	1.58e−1	4.7	7.0	1.58e3	1.63e3	**0.9**	7.1	9.28e4	9.61e4
380	2.3	6.2	1.36e−1	1.50e−1	4.5	8.7	1.87e3	1.92e3	**0.3**	1.5	1.09e5	1.11e5
400	2.0	5.9	1.46e−1	1.69e−1	3.9	8.0	2.18e3	2.22e3	**0.6**	2.7	1.28e5	1.30e5

Table 7: Large scale, $p_{\max} = 80$, weights $\in \{1, \ldots, 30\}$

n	LW				NEH				GA			
	gap		time (ms)		gap		time (ms)		gap		time (ms)	
	avg	max	avg	max	avg	max	avg	max	avg	max	avg	max
100	**3.6**	8.9	4.09e−2	1.25e−1	4.6	10.8	3.63e1	4.12e1	16.0	30.1	9.64e2	1.02e3
120	**4.4**	12.9	4.30e−2	7.13e−2	5.4	9.3	6.09e1	6.21e1	17.1	38.5	1.79e3	1.85e3
140	**3.5**	10.7	5.21e−2	9.38e−2	4.4	7.7	9.61e1	9.95e1	12.6	25.3	3.10e3	3.24e3
160	**3.2**	11.4	6.84e−2	1.12e−1	5.8	9.9	1.42e2	1.51e2	8.1	25.8	5.10e3	5.23e3
180	**3.0**	7.3	6.74e−2	9.56e−2	5.3	9.0	2.08e2	2.50e2	5.9	14.3	8.27e3	8.55e3
200	**2.7**	8.6	9.31e−2	2.55e−1	4.7	7.2	2.75e2	2.88e2	4.9	10.1	1.22e4	1.26e4
220	**2.9**	8.0	7.99e−2	1.12e−1	4.8	8.7	3.75e2	3.97e2	3.6	9.0	1.83e4	1.93e4
240	2.9	6.4	8.86e−2	1.17e−1	6.0	8.9	4.55e2	4.80e2	**1.9**	6.5	2.40e4	2.54e4
260	1.8	5.3	9.07e−2	1.07e−1	5.2	9.3	5.71e2	5.82e2	**1.6**	8.0	3.24e4	3.32e4
280	2.3	4.8	1.02e−1	1.27e−1	5.5	9.2	7.22e2	7.31e2	**0.8**	4.3	4.31e4	4.38e4
300	2.8	6.3	1.03e−1	1.23e−1	5.4	7.5	8.98e2	9.13e2	**2.0**	11.8	5.32e4	5.41e4
320	1.9	4.7	1.21e−1	2.31e−1	5.7	8.5	1.10e3	1.12e3	**1.4**	6.1	6.47e4	6.62e4
340	1.4	3.0	1.19e−1	1.33e−1	5.6	8.6	1.33e3	1.36e3	**0.8**	3.3	7.80e4	7.97e4
360	1.7	3.2	1.27e−1	1.51e−1	5.8	8.2	1.58e3	1.63e3	**1.1**	7.3	9.26e4	9.39e4
380	1.8	4.0	1.37e−1	1.56e−1	5.9	9.1	1.87e3	1.94e3	**0.8**	2.9	1.09e5	1.13e5
400	1.7	4.6	1.48e−1	2.07e−1	5.8	9.1	2.19e3	2.26e3	**0.8**	2.9	1.27e5	1.29e5




Figure 7: Large scale: LW, NEH, GA against LB.

7 Conclusion

This paper studies the two-machine flow shop scheduling problem with the maximum weighted completion time objective. The problem is strongly NP-hard, and its optimal

schedules exhibit a weight-based block structure, with Johnson's order within each block and blocks arranged in non-increasing order of weight. Exploiting this structure, we develop the DP, an FPTAS for a fixed number of weight classes, and three heuristics the LW rule, NEH and the GA.

Several directions for future research remain. First, the problem can be extended to more than two machines. Although the existing MILP formulation provides a starting point, the single-permutation property established for two machines does not generally hold for $m > 2$. The extended model must therefore account for machine-specific sequencing decisions and precedence constraints between operations. Investigating the structural properties of optimal schedules in this setting may also provide a basis for developing more efficient exact and approximation algorithms.

Second, for instances with more distinct weight classes, branch-and-bound offers a promising alternative to the DP, whose computational requirements increase rapidly with K. The weight-based block structure can guide branching decisions, while the lower bounds can be used to evaluate partial schedules and prune unpromising nodes. Further improvements may be obtained by combining these bounds with dominance rules and heuristic solutions to establish strong upper bounds at early stages of the search.

Third, the proposed heuristics can be extended to distributed flow shops, where job assignment to production shops and job sequencing must be optimized jointly. The NEH algorithm can be adapted to evaluate job insertions across candidate shops, accounting for both assignment and sequencing decisions. For the GA, the chromosome can be extended to encode shop assignments together with job sequences, while the weight-block mutation can be retained or modified to preserve the structural advantages identified in this study. These extensions may provide effective solution approaches for larger and more complex production environments.

References

Chai, X., Lu, L., Li, W., and Zhang, L. (2018). Best-possible online algorithms for single machine scheduling to minimize the maximum weighted completion time. *Asia-Pacific Journal of Operational Research*, 35(6):1850048.

de Athayde Prata, B. and Fuchigami, H. Y. (2024). A genetic iterated greedy algorithm for the blocking flowshop to minimize total earliness and tardiness. *Journal of Intelligent Manufacturing*, 35(5):2161–2174.

Della Croce, F. and Schau, Q. (2026). Revisiting Johnson's rule for minimizing makespan in the two-machine flow shop scheduling problem. *Operations Research Letters*, 69:107514.

Fan, B., Lu, L., and Shi, Z. (2026). On-line single-machine scheduling to minimize the

weighted makespan under (dis)agreeability conditions. *Journal of Industrial and Management Optimization*, 22(8):4138–4150.

Garey, M. R. and Johnson, D. S. (1979). *Computers and Intractability: A Guide to the Theory of $\mathcal{NP}$-Completeness*. W. H. Freeman and Company, San Francisco, CA.

Guo, S., Chen, Y., Mao, Y., and Zhang, X. (2024). Online single-processor scheduling with an unexpected breakdown. *Asia-Pacific Journal of Operational Research*, 41(1):2350005.

Hnaien, F. and Arbaoui, T. (2023). Minimizing the makespan for the two-machine flow shop scheduling problem with random breakdown. *Annals of Operations Research*, 328(2):1437–1460.

Jafari Nozar, F. and Behnamian, J. (2021). Hyper-heuristic for integrated due-window scheduling and vehicle routing problem for perishable products considering production quality. *Engineering Optimization*, 53(11):1902–1921.

Johnson, S. M. (1954). Optimal two- and three-stage production schedules with setup times included. *Naval Research Logistics Quarterly*, 1(1):61–68.

Li, W. (2015). A best possible online algorithm for the parallel-machine scheduling to minimize the maximum weighted completion time. *Asia-Pacific Journal of Operational Research*, 32(04):1550030.

Li, W. and Liu, H. (2023). Online NDP-constraint scheduling of jobs with delivery times or weights. *Optimization Letters*, 17(3):591–612.

Liang, X., Lu, L., Sun, X., Yu, X., and Zuo, L. (2024). Online scheduling on a single machine with one restart for all jobs to minimize the weighted makespan. *AIMS Mathematics*, 9(1):2518–2529.

Liu, L. and Urgo, M. (2024a). A branch-and-bound approach to minimise the value-at-risk of the makespan in a stochastic two-machine flow shop. *International Journal of Production Research*, 62(6):2107–2123.

Liu, L. and Urgo, M. (2024b). Robust scheduling in a two-machine re-entrant flow shop to minimise the value-at-risk of the makespan: branch-and-bound and heuristic algorithms based on Markovian activity networks and phase-type distributions. *Annals of Operations Research*, 338(1):741–764.

Lu, L., Zuo, L., Zhang, L., and Ou, J. (2025). Order acceptance and scheduling with weighted makespan. *4OR*, 23(3):247–267.

Mosheiov, G. and Sarig, A. (2023). A note on lot scheduling on a single machine to minimize maximum weighted tardiness. *Journal of Combinatorial Optimization*, 45(5):128.

Nawaz, M., Enscore, E. E., and Ham, I. (1983). A heuristic algorithm for the m-machine, n-job flow-shop sequencing problem. *Omega*, 11(1):91–95.

Nong, Q. Q., Cheng, T. C. E., and Ng, C. T. (2011). Two-agent scheduling to minimize the total cost. *European Journal of Operational Research*, 215(1):39–44.

Pinedo, M. L. (2022). *Scheduling: Theory, Algorithms, and Systems*. Springer, Cham, Switzerland, 6 edition.

Puka, R., Skalna, I., Duda, J., and Stawowy, A. (2024). Deterministic constructive vN-NEH+ algorithm to solve permutation flow shop scheduling problem with makespan criterion. *Computers & Operations Research*, 162:106473.

Qiao, Y., Wu, N., He, Y., Li, Z., and Chen, T. (2022). Adaptive genetic algorithm for two-stage hybrid flow-shop scheduling with sequence-independent setup time and no-interruption requirement. *Expert Systems with Applications*, 208:118068.

Shabtay, D. and Gerstl, E. (2024). Coordinating scheduling and rejection decisions in a two-machine flow shop scheduling problem. *European Journal of Operational Research*, 316(3):887–898.

Shao, W., Shao, Z., and Pi, D. (2021). Effective constructive heuristics for distributed no-wait flexible flow shop scheduling problem. *Computers & Operations Research*, 136:105482.

Shao, W., Shao, Z., and Pi, D. (2023). Modelling and optimization of distributed heterogeneous hybrid flow shop lot-streaming scheduling problem. *Expert Systems with Applications*, 214:119151.

Steinbacher, L. M., Rippel, D., Schulze, P., Rohde, A.-K., and Freitag, M. (2023). Quality-based scheduling for a flexible job shop. *Journal of Manufacturing Systems*, 70:202–216.

Sun, R. (2024). Randomized approximation schemes for minimizing the weighted makespan on identical parallel machines. *Journal of Combinatorial Optimization*, 47:34.

Tristan Becker, Janis Neufeld, U. B. (2025). The distributed flow shop scheduling problem with inter-factory transportation. *European Journal of Operational Research*, 322(1):39–55.

Wang, B.-T., Pan, Q.-K., Gao, L., and Li, W. (2024a). The paradoxes, accelerations and heuristics for a constrained distributed flowshop group scheduling problem. *Computers & Industrial Engineering*, 196:110465.

Wang, C., Pan, Q.-K., and Sang, H.-Y. (2024b). The cascaded flowshop joint scheduling problem: A mathematical model and population-based iterated greedy algorithm to minimize total tardiness. *Robotics and Computer-Integrated Manufacturing*, 88:102747.

Wang, Y.-J., Wang, G.-G., Tian, F.-M., Gong, D.-W., and Pedrycz, W. (2023). Solving energy-efficient fuzzy hybrid flow-shop scheduling problem at a variable machine speed using an extended NSGA-II. *Engineering Applications of Artificial Intelligence*, 121:105977.

Yuan, J., Ng, C. T., and Cheng, T. C. E. (2020). Scheduling with release dates and preemption to minimize multiple max-form objective functions. *European Journal of Operational Research*, 280(3):860–875.

Zhang, H., Lu, L., and Yuan, J. (2025). Online scheduling on an unbounded parallel-batch machine to minimize the weighted makespan. *Journal of Combinatorial Optimization*, 49(1):6.

Zheng, F., Li, N., Liu, M., and Xu, Y. (2025). Single machine lot scheduling to minimize maximum weighted completion time. *Journal of Combinatorial Optimization*, 50(1):1.

Zuo, L., Lu, L., and Zhang, L. (2026a). Single machine scheduling with a restricted weight-modifying activity to minimize the weighted makespan. *International Journal of Foundations of Computer Science*, 37(5):693–707.

Zuo, L., Zhang, J., Shi, Z., and Fan, B. (2026b). Single machine scheduling with a restricted rate-modifying activity to minimize the weighted makespan. *Discrete Applied Mathematics*, 380:89–100.