UM6P | College of Computing

Machine Learning for Shock-Capturing Numerical Schemes

Learning reconstruction decisions for
1D hyperbolic conservation laws


WENO-NN / NN-TENO5 / DIFFERENTIABLE CFD

Yasser Baouzil

Supervisor: Radouan Boukharfane

UM6P · College of Computing


PHYSICS × NUMERICS × LEARNING



Capturing sharp fronts without spurious oscillations

$$\frac{\partial u}{\partial t} + \frac{\partial f(u)}{\partial x} = 0$$

Learning inside a classical shock-capturing solver



My technical work · scientific-ML internship

$$\partial_t U + \partial_x F(U) = 0$$

Modular ENO baseline + WENO/TENO 3, 5, 7
Convergence checks; Sod / Shu–Osher benchmarks
Characteristic Euler + neural stencil decisions
Differentiable JAX rollouts; classical/NN blending
Controlled investigation of numerical failures

Original WENO-NN
Coefficient corrections

NN-TENO / oracle
Candidate selection

JAX / unrolled
Rollout loss + blending

Later V2
Classical gate + NN

Objective: improve solution accuracy while retaining numerical reliability.

Project scope: src/schemes/ · src/core/ · scripts/legacy_imitation_training/ · scripts/unrolled_physics_loss/

Where the network enters the Euler solver

$$U = (\rho, m, E)^{\mathsf{T}}, \quad F(U) = \begin{pmatrix} m \\ m^2/\rho + p \\ m(E+p)/\rho \end{pmatrix}$$

Conservative forward-Euler building block

$$\bar{U}_i^{n+1} = \bar{U}_i^n - \frac{\Delta t}{\Delta x}\left(\widehat{F}_{i+1/2} - \widehat{F}_{i-1/2}\right)$$

Conserved state U → Roe basis L and R → LF split fluxes → **TENO / NN reconstruction** (LEARNED DECISION) → Shared-face flux → SSPRK3 stages

Default path: reconstruct characteristic split fluxes, not physical left/right interface states.

$$\mathcal{R}_{V2} = \mathcal{R}_T + G\lambda\left(\mathcal{R}_{NN} - \mathcal{R}_T\right)$$

Later V2
G: classical TENO trouble gate
λ: controlled correction strength

Implemented: euler_jax.py:166–254 · gated_teno5_jax.py:19–67. SSPRK3 reevaluates reconstruction at every stage.

Conservation does not ensure positive Euler states

$$p = (\gamma - 1)\left(E - \frac{m^2}{2\rho}\right) \qquad \rho > 0, \qquad p > 0$$

$$\boxed{\delta p \approx (\gamma - 1)\left(\delta E - v\,\delta m + \tfrac{1}{2}v^2\delta\rho\right)}$$

v = m/ρ · linearization about an admissible reference state

Oracle NN-TENO5 · Sod, N=120	**Non-positive density · step 6**
V2 soft/.75 · Riemann, N=128	**Negative pressure · step 13, stage 1**
V2 soft/.25 · same short IVP	**15 steps · all raw stages admissible**

Neural flux → Euler update → possible negative internal energy → invalid pressure

Smaller corrections / repair remain empirical.
Weights and SSPRK3 alone do not ensure positivity.
Invalid p can break sound speeds and the Roe basis.


Established · not implemented

Conservative flux limiter + admissible low-order baseline + stage CFL.

Observed: audit §§3.1/3.3. Theory: Hu–Adams–Shu (2013); Zhang–Shu (2012); Gottlieb–Shu–Tadmor (2001).

The dissipation sweep did not isolate the cause

LF multiplier increased · timestep fixed



×: next non-finite step. 1.5× ends finite but enormous.

The experiment was confounded: dissipation, effective timestep restriction, and neural inputs changed simultaneously.

$$F^{\pm}(U) = \frac{1}{2}\left(F(U) \pm \alpha U\right)$$

$$\mathrm{CFL}_{LF} \sim \frac{\alpha \Delta t}{\Delta x}$$

Fixed Δt confounds the stability scale

Neural inputs changed too. Earlier divergence does not show that dissipation itself is harmful.

Roe conditioning remains a hypothesis

No trace establishes it as the initiating cause.

Next: matched CFL + classical TENO5

First-invalid RK stages and cond(R) tracing.

Data: models/euler_instability_trace.csv. Test: EulerInstability_TraceCapture.py:66–114. No unique cause established.

Direct state repair breaks the conservative budget

$$\bar{U}_i^{n+1} = \bar{U}_i^n - \frac{\Delta t}{\Delta x}\left(\widehat{F}_{i+1/2} - \widehat{F}_{i-1/2}\right)$$

$$\Delta M_{\text{repair}} = \Delta x \sum_i \left(\rho_i^{\text{after}} - \rho_i^{\text{before}}\right)$$

Implemented · post-update repair

Flux update → Invalid stage → Overwrite cell

One repaired stage · final RK-weighted source

Δmass ≈ +0.001611 · Δenergy ≈ +0.000889

Post-repair penalties once hid violations.
Guarded training ≠ unguarded validation.

Established · flux limiting (not tested)

NN flux → Limit face flux → Update cells


Shared face flux preserves the discrete budget.
Needs an admissible baseline, factors and CFL.

Not implemented or validated
in this neural solver.

> A finite repaired trajectory does not certify the unguarded learned solver.


Measured: results/repair/repair.json, soft/.75, one repaired stage row. Conservative remedy: Hu–Adams–Shu (2013).

Validation gains did not imply universal transfer



0.94794

Validation macro L^1 ratio
307 short Euler IVPs · no invalid stages



Sod N=192: 4.3% lower L^1, but TV rises and density undershoot ≈ 3.51×10^{-4}.

Woodward–Colella blast · N=128, 256

FAILED — no accuracy score

V2 non-finite; classical TENO5 completed both.


Possible contributors · not isolated causes

Shock strength, interactions, reflective walls.
State feedback; training / deployment mismatch.

Short-horizon validation did not guarantee stability under stronger out-of-distribution Euler dynamics.

Frozen V2 only. Data: full-validation/summary.json · independent/benchmark.json · wall-closure/benchmark.json.

The classical FV pipeline also limited accuracy



$$\overline{F(U)} \neq F(\bar{U})$$

Nonlinear flux evaluation and cell averaging do not commute.

Historical FV path: order ≈ 2.01
State + Rusanov: order ≈ 5.00

Experimental remedy
Consistent FV state reconstruction.
Shock/positivity behavior unvalidated.

This limitation affects classical TENO5 too; it is not a neural-only failure.

Data: nonlinear_euler.json; semidiscrete exact-average divergence. WENO7 details → Backup B. Wall correction ≠ blast robustness.

Learn within verifiable numerical constraints

Observed limitations

Negative stages · repair sources
Transfer gaps · accuracy/oscillations

Established techniques

Flux limiting · invariant domains
Moments · conditional SSP

Open research

Admissible learned corrections
DG/SIAC moments · residual checks

Shared-face limited flux

$$\widehat{F}^{limited} = \widehat{F}^{LO} + \theta\left(\widehat{F}^{NN} - \widehat{F}^{LO}\right)$$

Independent space–time residual

$$\mathscr{R} = \partial_t \widehat{U} + \partial_x F(\widehat{U})$$

θ in [0,1] alone does not ensure positivity. A residual alone does not certify an error bound.

Giesselmann, Kwon & Krumscheid (2026) · RKDG + SIAC

Begin with checkable smooth-state, moment and stability assumptions; then test near shocks.
The convection–diffusion RKDG–SIAC paper does not certify this neural Euler solver.

> Can learned high-order reconstruction improve numerical accuracy while retaining provable structural constraints and independently verifiable error control?

Hu–Adams–Shu (2013) · Guermond et al. (2018) · Gottlieb et al. (2001) · arXiv:2604.01200. Discussion; backups follow.